

FCC SAR Exclusion Report

Product name : Sentien Audio
Applicant : Sentien HQ s.r.o.
FCC ID : 2A5DB-SA11

Test report No. : P000055333 002 Ver 1.0



Report number: P000055333 002 Ver 1.0

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

The Industry Canada company number for Telefication is: 4173A.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Kiwa Telefication BV
Test Site location	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +31 88998 3393
Test Site FCC	NL0001
CABID	NL0001

Revision History

Version	Date	Remarks	By
V0.5	10-05-2022	Draft	PvW
V1.0	28-07-2022	Initial release	PvW

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT).....	4
1.4 Applicable standards.....	4
1.5 Conclusions	5
2 SAR exclusion Evaluation	6
2.1 Transmitter specifications.....	6
2.2 Evaluation calculations.....	7
2.3 Conclusion.....	7



Report number: P000055333 002 Ver 1.0

1 General Description

1.1 Applicant

Client name: Sentien HQ s.r.o.
Address: Jankovcova 1522 / 53; 170 00 Prague; Czech Republic
Telephone: +420 606 895 278
E-mail: support@sentrinhq.com
Contact name: Imrich Valach

1.2 Manufacturer

Client name: Sentien HQ s.r.o.
Address: Jankovcova 1522 / 53; 170 00 Prague; Czech Republic
Telephone: +420 606 895 278
E-mail: support@sentrinhq.com
Contact name: Imrich Valach

1.3 Tested Equipment Under Test (EUT)

Product name: Sentien Audio
Brand name: Sentien Audio
FCC ID: 2A5DB-SA11
Product type: Wireless headset
Model(s): SA-1
Batch and/or serial No. --
Software version: 1.1
Hardware version: SA-5
Date of receipt: 03-03-2022

1.4 Applicable standards

47 CFR § 1.1307 (b)(1)(i)(A)

1.5 Conclusions

The sample of the product showed **NO NON-COMPLIANCES** to the specifications stated in paragraph 1.4 of this report.

The results of the test as stated in this report, are exclusively applicable to the product items as identified in this report. Telefication accepts no responsibility for any properties of product items in this test report, which are not supported by the tests as specified in paragraph 1.4 "*Applicable standards*".

Assessment is performed by:

Name : P. van Wanrooij, BSc

Review of assessment methods and report by:

Name : R. Tolud

The above conclusions have been verified by the following signatory:

Date : 29-07-2022

Name : Koray Korcum, Msc

Function : Test Engineer

Signature :

A blue ink signature of the name 'Koray' with a small 'K' and 'R' preceding it, enclosed within a stylized oval.

2 SAR exclusion Evaluation

2.1 Transmitter specifications

BLE

Variable (unit)	Value	Symbol
Conducted time-averaged output power (mW)	2.60	P
Time-averaged output power ERP (mW)	3.16	P_{ERP}
Operating frequency range (MHz)	2402-2480	f
Separation distance (cm)	0.5	d
Separation distance (m)	0.005	R

BT/BT EDR

Variable (unit)	Value	Symbol
Conducted time-averaged output power (mW)	2.09	P
Time-averaged output power ERP (mW)	--	P_{ERP}
Operating frequency range (MHz)	2402-2480	f
Separation distance (cm)	0.5	D
Separation distance (m)	0.005	R

BLE and BT/BT EDR can not transmit simultaneously so each transmitter is evaluated separately.

2.2 Evaluation calculations

BLE

BLE is evaluated according to method B of KDB 447498 D04 v01

Method B:

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm} \right)^x & d \leq 20 \text{ cm} \\ ERP_{20cm} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} * \sqrt{f}} \right)$$

$$ERP_{20cm}(mW) = \begin{cases} 2040 * f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6.0 \text{ GHz} \end{cases}$$

Filling in the values of d (cm) and f (GHz) as reported in clause 2.1 in the equations above gives the result:

$P_{th} = 2.79 \text{ mW}$

$P = 2.6 \text{ mW}$ which is less than the calculated P_{th} so the EUT complies with the SAR based exemption requirement.

BT/BT EDR

BT/BT EDR is evaluated according to method B of KDB 447498 D04 v01

Method B:

$$P_{th}(mW) = \begin{cases} ERP_{20cm} \left(\frac{d}{20cm} \right)^x & d \leq 20 \text{ cm} \\ ERP_{20cm} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where:

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} * \sqrt{f}} \right)$$

$$ERP_{20cm}(mW) = \begin{cases} 2040 * f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6.0 \text{ GHz} \end{cases}$$

Filling in the values of d (cm) and f (GHz) as reported in clause 2.1 in the equations above gives the result:

$P_{th} = 2.79 \text{ mW}$

P or $P_{ERP} = 2.09 \text{ mW}$ which is less than the calculated P_{th} so the EUT complies with the SAR based exemption requirement.

2.3 Conclusion

Since the EUT does not cause exposure in excess of the general population limit, no additional mitigation actions are required.