

FCC ID: 2A5DUYCC-SW4002

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHZ})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHZ})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	3.35	2.16	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	3.785	2.39	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	3.011	2.00	4±1	5.00	3.16	<5	0.99599	3.00	YES
π/4DQPSK	2.402	3.199	2.09	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	3.319	2.15	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	2.568	1.81	3±1	4.00	2.51	<5	0.79114	3.00	YES
8DPSK	2.402	3.43	2.20	4±1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	3.552	2.27	4±1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	2.822	1.92	3±1	4.00	2.51	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.99599\text{W/Kg} \leq \text{FCC Limit } 3.0$ for 1g SAR.