

FCC RADIO TEST REPORT

FCC ID:2A5EI-PENGUIN

Product: 7inch tablet

Trade Mark: EGOTEK

Model No.: Penguin

Family Model: GTABKIDS, GTABPND

Report No.: S22030403413002

Issue Date: Mar. 17, 2022

Prepared for

Shenzhen Yigao Electronic Technology Co., Limited
4F-5F, C1 Building, Tongfuyu Xinqiao Industrial Park Shajing, Baoan,
Shenzhen Guangdong, PR China 518104

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320
0090 Website: <http://www.ntek.org.cn>

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION.....	3
2 SUMMARY OF TEST RESULTS.....	4
3 FACILITIES AND ACCREDITATIONS.....	5
3.1 FACILITIES.....	5
3.2 LABORATORY ACCREDITATIONS AND LISTINGS.....	5
3.3 MEASUREMENT UNCERTAINTY.....	5
4 GENERAL DESCRIPTION OF EUT.....	6
5 DESCRIPTION OF TEST MODES.....	8
6 SETUP OF EQUIPMENT UNDER TEST.....	10
6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	10
6.2 SUPPORT EQUIPMENT.....	11
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS.....	12
7 TEST REQUIREMENTS.....	14
7.1 CONDUCTED EMISSIONS TEST.....	14
7.2 RADIATED SPURIOUS EMISSION.....	17
7.3 6DB BANDWIDTH.....	26
7.4 DUTY CYCLE.....	28
7.5 MAXIMUM OUTPUT POWER.....	29
7.6 POWER SPECTRAL DENSITY.....	31
7.7 CONDUCTED BAND EDGE MEASUREMENT.....	33
7.8 SPURIOUS RF CONDUCTED EMISSIONS.....	35
7.9 ANTENNA APPLICATION.....	37
8 TEST RESULTS.....	38
8.1 MAXIMUM CONDUCTED OUTPUT POWER.....	38
8.2 OCCUPIED CHANNEL BANDWIDTH.....	39
8.3 MAXIMUM POWER SPECTRAL DENSITY LEVEL.....	48
8.4 BAND EDGE.....	51
8.5 CONDUCTED RF SPURIOUS EMISSION.....	53
9 TEST SETUP PHOTOS OF THE EUT.....	59
10 PHOTOS OF THE EUT.....	60

1 TEST RESULT CERTIFICATION

Applicant's name.....:	Shenzhen Yigao Electronic Technology Co., Limited
Address.....:	4F-5F, C1 Building, Tongfuyu Xinqiao Industrial Park Shajing, Baoan, Shenzhen Guangdong, PR China 518104
Manufacturer's Name.....:	Shenzhen Ego Devices Co., Limited
Address.....:	4F-5F ,C1 Building, Jidali Industrial Park, Shajing, Baoan District, Shenzhen, PR China, 518104
Product description	
Product name.....:	7inch tablet
Model and/or type reference	Penguin
Family Model.....:	GTABKIDS, GTABPND

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : Jan. 20, 2022 ~Mar. 17, 2022

Testing Engineer : Mukzi Lee
(Mukzi Lee)

Authorized Signatory : Alex
(Alex Li)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Maximum Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District Shenzhen, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District Shenzhen, Guangdong, China

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	7inch tablet
Trade Mark	EGOTEK
FCC ID	2AMKM-oliostream1
Model No.	Penguin
Family Model	GTABKIDS, GTABPND
Model Difference	All the model are the same circuit and RF module,except the exterior is difference.
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20); 2422-2452MHz for 802.1111n(HT40);
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Number of Channels	11 channels for 802.11b/g/11n(HT20); 7 channels for 802.11b/g/11n(HT20);
Antenna Type	PIFA Antenna
Antenna Gain	0 dBi
Power supply	DC 5.0V from USB Port or DC 3.7V from battery.
Adapter	Model: JK050200-S04USA Input: AC 100-240Vac, 50/60Hz 0.5A Output: DC 5.0V---2000mA
HW Version	N/A
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20/HT40):

Channel	Frequency(MHz)
1	2412
2	2417
...	...
5	2432
6	2437
...	...
10	2457
11	2462

Note: $f_c = 2412\text{MHz} + (k-1) \times 5\text{MHz}$ $k=1$ to 11
 EUT built-in battery-powered, the battery is fully-charged.


Test Mode:

Test Items	Mode	Data Rate	Channel	Ant
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	13.5Mbps	3/6/9	1
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	13.5Mbps	3/6/9	1
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	13.5Mbps	3/6/9	1
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	13.5Mbps	3/6/9	1
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
	11n HT40	13.5Mbps	3/6/9	1


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	JK050200-S04USA	N/A	Peripherals
AE-2	7inch tablet	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Type-c Cable	NO	NO	1.0m
C-2	Power Cable	NO	NO	1.0m
C-3	RF Cable	YES	NO	0.1m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation & Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2021.04.27	2022.04.26	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2021.04.27	2022.04.26	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2021.04.27	2022.04.26	1 year
4	Test Receiver	R&S	ESPI7	101318	2021.04.27	2022.04.26	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2021.03.29	2022.03.28	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11	2023.05.10	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2021.03.29	2022.03.28	1 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2021.11.19	2022.11.18	1 year
9	Amplifier	EMC	EMC051835SE	980246	2021.07.01	2022.06.30	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2021.11.19	2022.11.18	1 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2021.11.19	2022.11.18	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2019.08.06	2022.08.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2019.08.06	2022.08.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2019.06.28	2022.06.27	3 year
15	Filter	TRILTHIC	2400MHz	29	2021.11.19	2022.11.18	1 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2021.04.27	2022.04.26	1 year
2	LISN	R&S	ENV216	101313	2021.04.27	2022.04.26	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2021.04.27	2022.04.26	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2020.05.11	2023.05.10	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2020.05.11	2023.05.10	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2020.05.11	2023.05.10	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2020.05.11	2023.05.10	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit


Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


7.1.6 Test Results

EUT:	7inch tablet	Model Name :	Penguin
Temperature:	22 °C	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5.0V from Adapter AC 120V/60Hz	Test Mode:	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1824	31.42	10.38	41.80	64.37	-22.57	QP
0.1804	23.64	10.38	34.02	54.46	-20.44	AVG
0.3392	31.08	10.42	41.50	59.22	-17.72	QP
0.3392	21.81	10.42	32.23	49.22	-16.99	AVG
1.0620	31.15	10.45	41.60	56.00	-14.40	QP
1.0620	22.90	10.45	33.35	46.00	-12.65	AVG
4.4298	23.94	10.66	34.60	56.00	-21.40	QP
4.4378	16.00	10.66	26.66	46.00	-19.34	AVG
12.1455	31.49	10.71	42.20	60.00	-17.80	QP
12.1455	21.63	10.71	32.34	50.00	-17.66	AVG
28.0335	25.77	10.61	36.38	60.00	-23.62	QP
28.0335	14.28	10.61	24.89	50.00	-25.11	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	7inch tablet	Model Name :	Penguin
Temperature:	22°C	Relative Humidity:	57%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5.0V from Adapter AC 120V/60Hz	Test Mode:	Normal Link

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2230	32.46	10.44	42.90	62.70	-19.80	QP
0.2230	20.44	10.44	30.88	52.70	-21.82	AVG
0.5977	19.50	10.40	29.90	56.00	-26.10	QP
0.6018	4.84	10.40	15.24	46.00	-30.76	AVG
1.8140	21.88	10.42	32.30	56.00	-23.70	QP
1.8140	8.72	10.42	19.14	46.00	-26.86	AVG
4.7019	17.16	10.64	27.80	56.00	-28.20	QP
4.7019	3.58	10.64	14.22	46.00	-31.78	AVG
8.4817	14.93	10.67	25.60	60.00	-34.40	QP
8.4817	0.52	10.67	11.19	50.00	-38.81	AVG
18.5699	19.31	10.73	30.04	60.00	-29.96	QP
18.6296	7.78	10.73	18.51	50.00	-31.49	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


- Remark : 1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. For Frequency 9kHz~30MHz:
 Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
 Limit line=Specific limits(dBuV) + distance extrapolation factor.
 For Frequency above 30MHz:
 Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
 Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22. This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz and frequencies above 1GHz,
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

For peak measurement:

Set RBW=120 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;

Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz

For average measurement:

$VBW = 10$ Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20)	Test By:	Mukzi Lee

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


- Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT:	7inch tablet	Model Name :	Penguin
Temperature:	25 °C	Relative Humidity:	55%
Pressure:	1010hPa	Test Mode:	Normal Link
Test Voltage :	DC 5V		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	35.6240	12.63	15.37	28.00	40.00	-12.00	QP
V	62.6507	25.47	5.23	30.70	40.00	-9.30	QP
V	124.1329	19.52	11.88	31.40	43.50	-12.10	QP
V	181.2834	23.91	9.59	33.50	43.50	-10.00	QP
V	293.0842	20.99	14.21	35.20	46.00	-10.80	QP
V	550.9479	12.13	23.27	35.40	46.00	-10.60	QP

Remark:


Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	50.2324	23.63	8.07	31.70	40.00	-8.30	QP
H	74.1350	25.29	6.61	31.90	40.00	-8.10	QP
H	115.7256	19.60	11.70	31.30	43.50	-12.20	QP
H	159.7844	23.52	10.68	34.20	43.50	-9.30	QP
H	280.0237	22.85	13.35	36.20	46.00	-9.80	QP
H	750.1082	14.12	24.28	38.40	46.00	-7.60	QP

Remark:

Emission Level = Meter Reading+ Factor, Margin= Emission Level- Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n(HT20)	Test By:	Mukzi Lee

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2412 MHz)(802.11b)--Above 1G									
4824.069	67.45	21.52	3.52	33.12	59.37	74	-14.63	Pk	Vertical
4824.069	50.12	23.65	4.56	33.08	45.25	54	-8.75	AV	Vertical
7236.154	66.45	25.58	6.15	33.57	64.61	74	-9.39	Pk	Vertical
7236.154	48.69	27.68	6.98	33.26	50.09	54	-3.91	AV	Vertical
4824.103	67.48	21.52	3.52	33.12	59.4	74	-14.6	Pk	Horizontal
4824.103	48.79	23.65	4.56	33.08	43.92	54	-10.08	AV	Horizontal
7236.146	66.42	25.58	6.15	33.57	64.58	74	-9.42	Pk	Horizontal
7236.146	44.35	27.68	6.98	33.26	45.75	54	-8.25	AV	Horizontal
Middle Channel (2437 MHz)(802.11b)--Above 1G									
4874.135	66.15	21.78	3.58	33.27	58.24	74	-15.76	Pk	Vertical
4874.135	47.26	24.15	4.57	33.87	42.11	54	-11.89	AV	Vertical
7311.271	65.42	26.04	6.24	33.19	64.51	74	-9.49	Pk	Vertical
7311.271	45.26	27.98	7.18	33.68	46.74	54	-7.26	AV	Vertical
4874.089	65.12	21.78	3.58	33.27	57.21	74	-16.79	Pk	Horizontal
4874.089	45.56	24.15	4.57	33.87	40.41	54	-13.59	AV	Horizontal
7311.192	64.25	26.04	6.24	33.19	63.34	74	-10.66	Pk	Horizontal
7311.192	47.36	27.98	7.18	33.68	48.84	54	-5.16	AV	Horizontal
High Channel (2462 MHz)(802.11b)--Above 1G									
4924.055	65.25	22.56	4.17	33.75	58.23	74	-15.77	Pk	Vertical
4924.055	45.36	24.78	5.36	33.17	42.33	54	-11.67	AV	Vertical
7386.215	64.12	27.14	6.97	33.62	64.61	74	-9.39	Pk	Vertical
7386.215	44.26	28.16	7.65	33.58	46.49	54	-7.51	AV	Vertical
4924.183	64.25	22.56	4.17	33.75	57.23	74	-16.77	Pk	Horizontal
4924.183	44.25	24.78	5.36	33.17	41.22	54	-12.78	AV	Horizontal
7386.144	63.46	27.14	6.97	33.62	63.95	74	-10.05	Pk	Horizontal
7386.144	43.25	28.16	7.65	33.58	45.48	54	-8.52	AV	Horizontal

Note:

- (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
- (2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.
- (3)"802.11b" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

■ Spurious Emission in Restricted Band 2310MHz -18000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Meter Reading	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	dB/m	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
802.11b									
2310.00	65.25	21.52	3.52	33.12	57.17	74	-16.83	Pk	Horizontal
2310.00	45.36	23.65	4.56	33.08	40.49	54	-13.51	AV	Horizontal
2310.00	64.24	25.58	6.15	33.57	62.4	74	-11.6	Pk	Vertical
2310.00	44.25	27.68	6.98	33.26	45.65	54	-8.35	AV	Vertical
2390.00	64.26	21.52	3.52	33.12	56.18	74	-17.82	Pk	Vertical
2390.00	44.85	23.65	4.56	33.08	39.98	54	-14.02	AV	Vertical
2390.00	63.25	25.58	6.15	33.57	61.41	74	-12.59	Pk	Horizontal
2390.00	43.26	27.68	6.98	33.26	44.66	54	-9.34	AV	Horizontal
2483.50	64.75	21.52	3.52	33.12	56.67	74	-17.33	Pk	Vertical
2483.50	45.63	23.65	4.56	33.08	40.76	54	-13.24	AV	Vertical
2483.50	63.25	25.58	6.15	33.57	61.41	74	-12.59	Pk	Horizontal
2483.50	44.25	27.68	6.98	33.26	45.65	54	-8.35	AV	Horizontal
802.11g									
2310.00	66.48	21.52	3.52	33.12	58.4	74	-15.6	Pk	Horizontal
2310.00	45.53	23.65	4.56	33.08	40.66	54	-13.34	AV	Horizontal
2310.00	65.56	25.58	6.15	33.57	63.72	74	-10.28	Pk	Vertical
2310.00	43.25	27.68	6.98	33.26	44.65	54	-9.35	AV	Vertical
2390.00	68.45	21.78	3.58	33.27	60.54	74	-13.46	Pk	Vertical
2390.00	44.65	24.15	4.57	33.87	39.5	54	-14.5	AV	Vertical
2390.00	64.25	26.04	6.24	33.19	63.34	74	-10.66	Pk	Horizontal
2390.00	43.26	27.98	7.18	33.68	44.74	54	-9.26	AV	Horizontal
2483.50	67.46	21.78	3.58	33.27	59.55	74	-14.45	Pk	Vertical
2483.50	46.35	24.15	4.57	33.87	41.2	54	-12.8	AV	Vertical
2483.50	66.25	26.04	6.24	33.19	65.34	74	-8.66	Pk	Horizontal
2483.50	45.36	27.98	7.18	33.68	46.84	54	-7.16	AV	Horizontal
802.11n20									
2310.00	70.21	22.56	4.17	33.75	63.19	74	-10.81	Pk	Horizontal
2310.00	50.12	24.78	5.36	33.17	47.09	54	-6.91	AV	Horizontal
2310.00	68.56	27.14	6.97	33.62	69.05	74	-4.95	Pk	Vertical
2310.00	47.63	28.16	7.65	33.58	49.86	54	-4.14	AV	Vertical
2390.00	68.59	22.56	4.17	33.75	61.57	74	-12.43	Pk	Vertical
2390.00	45.63	24.78	5.36	33.17	42.6	54	-11.4	AV	Vertical
2390.00	66.35	27.14	6.97	33.62	66.84	74	-7.16	Pk	Horizontal
2390.00	44.26	28.16	7.65	33.58	46.49	54	-7.51	AV	Horizontal
2483.50	67.36	22.56	4.17	33.75	60.34	74	-13.66	Pk	Vertical
2483.50	45.35	24.78	5.36	33.17	42.32	54	-11.68	AV	Vertical
2483.50	65.56	27.14	6.97	33.62	66.05	74	-7.95	Pk	Horizontal
2483.50	44.63	28.16	7.65	33.58	46.86	54	-7.14	AV	Horizontal

Spurious Emission in Restricted Bands 3260MHz- 18000MHz

All the modulation modes have been tested, the worst result was report as below:

Frequency	Reading Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	dB/m	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	68.69	22.56	4.17	33.75	61.67	74	-12.33	Pk	Vertical
3260	46.34	24.78	5.36	33.17	43.31	54	-10.69	AV	Vertical
3260	67.45	27.14	6.97	33.62	67.94	74	-6.06	Pk	Horizontal
3260	46.36	28.16	7.65	33.58	48.59	54	-5.41	AV	Horizontal
3332	66.85	21.52	3.52	33.12	58.77	74	-15.23	Pk	Vertical
3332	46.58	23.65	4.56	33.08	41.71	54	-12.29	AV	Vertical
3332	65.36	25.58	6.15	33.57	63.52	74	-10.48	Pk	Horizontal
3332	45.25	27.68	6.98	33.26	46.65	54	-7.35	AV	Horizontal
17797	67.85	21.52	3.52	33.12	59.77	74	-14.23	Pk	Vertical
17797	45.53	23.65	4.56	33.08	40.66	54	-13.34	AV	Vertical
17788	66.25	25.58	6.15	33.57	64.41	74	-9.59	Pk	Horizontal
17788	44.25	27.68	6.98	33.26	45.65	54	-8.35	AV	Horizontal

“802.11b” mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

VBW \geq 3*RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Test data reference attachment.

7.4 DUTY CYCLE

7.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance v05r02 Section 6.

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value.
- 3) Set VBW \geq RBW. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

Measure T_{total} and T_{on}

Calculate Duty Cycle = T_{on} / T_{total}

7.4.6 Test Results

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Note: Not applicable

7.5 MAXIMUM OUTPUT POWER

7.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.2.3.

7.5.2 Conformance Limit


The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.5.3 Measuring Instruments

The following table is the setting of the power meter.

Power meter parameter	Setting
Detector	PK

7.5.4 Test Setup



7.5.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.9.1.3 of ANSI C63.10

7.5.6 EUT operation during Test

The EUT was programmed to be in continuously transmitting mode.

7.5.7 Test Results

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Test data reference attachment.

7.6 POWER SPECTRAL DENSITY

7.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

7.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 * \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.6 Test Results

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Test data reference attachment.

7.7 CONDUCTED BAND EDGE MEASUREMENT

7.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

7.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

7.7.6 Test Results

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Test data reference attachment.

7.8 SPURIOUS RF CONDUCTED EMISSIONS

7.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.3 Test Setup

Please refer to Section 6.1 of this test report.

7.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 26.5GHz.

7.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

EUT:	7inch tablet	Model No.:	Penguin
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	802.11b/g/n20	Test By:	Mukzi Lee

Test data reference attachment.

7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The EUT antenna is permanent attached PIFA Antenna (Gain: 0 dBi). It comply with the standard requirement.

8 TEST RESULTS

8.1 MAXIMUM CONDUCTED OUTPUT POWER

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	9.17	30.00	Pass
	06	9.36		
	11	9.24		
802.11g	01	8.24	30.00	Pass
	06	8.88		
	11	8.42		
802.11n(HT20)	01	8.66	30.00	Pass
	06	7.84		
	11	7.87		
802.11n(HT40)	03	7.54	30.00	Pass
	06	8.02		
	09	7.98		

Note:

1. Measured output power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss.
3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;

8.2 OCCUPIED CHANNEL BANDWIDTH

Test Mode	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
802.11b	2412	13.934	2405.063	2418.997	---	PASS
	2437	13.937	2430.060	2443.997	---	PASS
	2462	13.904	2455.037	2468.941	---	PASS
802.11g	2412	16.541	2403.736	2420.277	---	PASS
	2437	16.513	2428.756	2445.269	---	PASS
	2462	16.504	2453.750	2470.254	---	PASS
802.11N20	2412	17.672	2403.201	2420.873	---	PASS
	2437	17.677	2428.214	2445.891	---	PASS
	2462	17.577	2453.211	2470.788	---	PASS
802.11N40	2422	35.543	2404.338	2439.881	---	PASS
	2437	35.602	2419.319	2454.921	---	PASS
	2452	35.466	2434.361	2469.827	---	PASS

802.11b 2412MHz



802.11b 2437MHz Ant1



802.11b 2462MHz



802.11g 2412MHz



802.11g 2437MHz



802.11g 2462MHz



802.11n(HT20) 2412MHz



802.11n(HT20) 2437MHz



802.11n(HT20) 2462MHz



802.11n(HT40) 2422MHz



802.11n(HT40) 2437MHz



802.11n(HT40) 2452MHz




DTS Bandwidth

Test Mode	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
802.11b	2412	10.080	2406.960	2417.040	0.5	PASS
	2437	10.080	2431.960	2442.040	0.5	PASS
	2462	10.120	2456.920	2467.040	0.5	PASS
802.11g	2412	15.680	2404.240	2419.920	0.5	PASS
	2437	15.920	2429.040	2444.960	0.5	PASS
	2462	15.680	2454.240	2469.920	0.5	PASS
802.11n(HT20)	2412	16.280	2404.120	2420.400	0.5	PASS
	2437	16.320	2429.080	2445.400	0.5	PASS
	2462	15.400	2454.120	2469.520	0.5	PASS
802.11n(HT40)	2422	31.520	2406.960	2438.480	0.5	PASS
	2437	33.920	2420.360	2454.280	0.5	PASS
	2452	29.440	2437.360	2466.800	0.5	PASS

802.11b

802.11g


Lowest channel



Middle channel





Highest channel




802.11n20

801.11n40


Lowest channel



Middle channel



Highest channel





8.3 MAXIMUM POWER SPECTRAL DENSITY LEVEL

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-20.27	8.00	Pass
	06	-20.29		
	11	-20.21		
802.11g	01	-21.80	8.00	Pass
	06	-21.31		
	11	-20.81		
802.11n(HT20)	01	-21.99	8.00	Pass
	06	-21.01		
	11	-20.65		
802.11n(HT40)	03	-23.04	8.00	Pass
	06	-22.53		
	09	-21.93		

Note:

1. Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
 2. Test results including cable loss;
 3. Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40;
- Please refer to following plots;






8.4 BAND EDGE


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	802.11b	2412	Ant 1	-49.53	-20	Pass
NVNT	802.11b	2462	Ant 1	-48.39	-20	Pass
NVNT	802.11g	2412	Ant 1	-49.60	-20	Pass
NVNT	802.11g	2462	Ant 1	-48.48	-20	Pass
NVNT	802.11n(HT20)	2412	Ant 1	-50.11	-20	Pass
NVNT	802.11n(HT20)	2462	Ant 1	-49.04	-20	Pass
NVNT	802.11n(HT40)	2422	Ant 1	-50.06	-20	Pass
NVNT	802.11n(HT40)	2452	Ant 1	-48.86	-20	Pass

Test mode:

802.11b




Lowest channel




Highest channel

Test mode:

802.11g




Lowest channel




Highest channel

Test mode:

802.11n(HT20)



Lowest channel



Highest channel

Test mode:

802.11n(HT40)



Lowest channel



Highest channel

8.5 CONDUCTED RF SPURIOUS EMISSION

Test Mode	Frequency [MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
802.11b	2412	Reference	-0.28	-0.28	---	PASS
		30~1000	-0.28	-55.63	≤-20.28	PASS
		1000~26500	-0.28	-43.18	≤-20.28	PASS
	2437	Reference	-0.26	-0.26	---	PASS
		30~1000	-0.26	-56.67	≤-20.26	PASS
		1000~26500	-0.26	-42.84	≤-20.26	PASS
	2462	Reference	-0.20	-0.20	---	PASS
		30~1000	-0.20	-57.44	≤-20.2	PASS
		1000~26500	-0.20	-42.04	≤-20.2	PASS
802.11g	2412	Reference	-7.89	-7.89	---	PASS
		30~1000	-7.89	-57.65	≤-27.89	PASS
		1000~26500	-7.89	-43.71	≤-27.89	PASS
	2437	Reference	-7.44	-7.44	---	PASS
		30~1000	-7.44	-58.06	≤-27.44	PASS
		1000~26500	-7.44	-42.97	≤-27.44	PASS
	2462	Reference	-6.89	-6.89	---	PASS
		30~1000	-6.89	-58.18	≤-26.89	PASS
		1000~26500	-6.89	-43.21	≤-26.89	PASS
802.11n(HT20)	2412	Reference	-7.79	-7.79	---	PASS
		30~1000	-7.79	-56.94	≤-27.79	PASS
		1000~26500	-7.79	-43.3	≤-27.79	PASS
	2437	Reference	-7.15	-7.15	---	PASS
		30~1000	-7.15	-58.17	≤-27.15	PASS
		1000~26500	-7.15	-43.49	≤-27.15	PASS
	2462	Reference	-6.58	-6.58	---	PASS
		30~1000	-6.58	-58.16	≤-26.58	PASS
		1000~26500	-6.58	-43.2	≤-26.58	PASS
802.11n(HT40)	2422	Reference	-10.76	-10.76	---	PASS
		30~1000	-10.76	-57.95	≤-30.76	PASS
		1000~26500	-10.76	-43.29	≤-30.76	PASS
	2437	Reference	-10.58	-10.58	---	PASS
		30~1000	-10.58	-58.35	≤-30.58	PASS
		1000~26500	-10.58	-43.42	≤-30.58	PASS
	2452	Reference	-9.97	-9.97	---	PASS
		30~1000	-9.97	-58.06	≤-29.97	PASS
		1000~26500	-9.97	-43	≤-29.97	PASS


802.11b




Reference
CH01




Reference
CH06




30MHz-1GHz




30MHz-1GHz



1GHz -26.5GHz



1GHz -26.5GHz





802.11g





Reference
CH06

Reference
CH11



30MHz-1GHz


30MHz-1GHz



1GHz -26.5GHz

1GHz -26.5GHz


802.11n20




Reference
CH01




Reference
CH06




30MHz-1GHz



30MHz-1GHz




1GHz-26.5GHz



1GHz-26.5GHz


802.11n40




Reference
CH06



Reference
CH09




30MHz-1GHz



30MHz-1GHz



1GHz -26.5GHz



1GHz -26.5GHz

9 TEST SETUP PHOTOS OF THE EUT




10 PHOTOS OF THE EUT


















END OF REPORT