

**FCC ID: 2A5FB-HB030BX13**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot \sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
EDR mode (GFSK)	2.402	-1.443	0.72	-1±1	0.00	1.00	<5	0.30997	3.00	YES
	2.441	-1.363	0.73	-1±1	0.00	1.00	<5	0.31247	3.00	YES
	2.480	-1.58	0.70	-1±1	0.00	1.00	<5	0.31496	3.00	YES
EDR mode ( $\pi$ /4DQPSK)	2.402	-0.593	0.87	-0±1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	-0.519	0.89	-0±1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	-0.718	0.85	-0±1	1.00	1.26	<5	0.39651	3.00	YES
EDR mode (8DPSK)	2.402	-0.233	0.95	-0±1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	-0.122	0.97	-0±1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	-0.451	0.90	-0±1	1.00	1.26	<5	0.39651	3.00	YES

**Conclusion:**

For the max result :  $0.39651\text{W/Kg} \leq \text{FCC Limit } 3.0 \text{ for } 1\text{g SAR.}$