

# FCC MPE TEST REPORT

**FCC ID: 2A5K5-MWCS7S1**

**Sample :** Mooas Crystal Lamp 3 in1 Magsafe Stand

**Trade Mark :** N/A

**Main Model :** MWCS7S1

**Additional Model :** N/A

**Report No. :** UNIA24052814ER-62

## Prepared for

Mooas Inc.

C-819-822, Munjeong Hyundai Knowledge Industry Center, 7,  
Beobwon-ro 11-gil, Songpa- gu, Seoul, Korea, South Korea 05836

## Prepared by

Shenzhen United Testing Technology Co., Ltd.

D101&D401, No. 107, Kaicheng High-Tech Park, Taoyuan Community,  
Dalang Sub-District, Longhua District, Shenzhen, Guangdong, China

## TEST RESULT CERTIFICATION

**Applicant**.....: Mooas Inc.

**Address**.....: C-819-822, Munjeong Hyundai Knowledge Industry Center, 7,  
Beobwon-ro 11-gil, Songpa- gu, Seoul, Korea, South Korea 05836

**Manufacturer** .....: Shenzhen Sunrise Industry Co., LTD

**Address**.....: Floor 4,Building E,HuaChuangDa,No.42 District Baoan,  
Shenzhen City,Guangdong Province,P.R.China.

### Product description

**Product** .....: Mooas Crystal Lamp 3 in1 Magsafe Stand

**Trade Mark**.....: N/A

**Model Name**.....: MWCS7S1

**Standards** .....: FCC KDB680106 D01 Wireless Power Transfer v04

This device described above has been tested by Shenzhen United Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of UNI, this document may be altered or revised by Shenzhen United Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

### Date of Test

**Date (s) of performance of tests** .....: May 29, 2024 ~ Jun. 05, 2024

**Date of Issue** .....: Jun. 06, 2024


**Test Result** .....: Pass

Prepared by:



Jason Ye/Editor

Reviewer:



Kelly Cheng/Supervisor

Approved & Authorized Signer:



Liuze/Manager

Table of Contents	Pages
1 TEST SUMMARY	4
1.1 TEST PROCEDURES AND RESULTS	4
1.2 TEST FACILITY	5
1.3 MEASUREMENT UNCERTAINTY	6
1.4 ENVIRONMENTAL CONDITIONS	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 CARRIER FREQUENCY OF CHANNELS	8
2.3 TEST MODE	8
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	9
2.5 TEST INSTRUMENTS	9
3 MAXIMUM PERMISSIBLE EXPOSURE	10
3.1 MAXIMUM PERMISSIBLE EXPOSURE	10
3.2 TEST PROCEDURE	11
3.3 TEST SETUP	11
3.4 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE	12
3.5 TEST PHOTO	13

## 1 TEST SUMMARY

### 1.1 TEST PROCEDURES AND RESULTS

FCC KDB680106 D01 Wireless Power Transfer v04

FCC CFR 47			
Standard Section	Test Item	Result	Remark
FCC CFR 47 part1, 1.1310 KDB680106 D01 v04	Electric Field Strength (E) (V/m)	N/A	--
	Magnetic Field Strength (H) (A/m)	PASS	--

Note: "N/A" denotes test is not applicable in this Test Report.

Compliant with FCC KDB680106 D01 Wireless Power Transfer v04 section 5.2:

- 1) The power transfer frequency is below 1MHz.  
Yes, the working frequency is: 110-205kHz and 326.5kHz.
- 2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.  
Yes, the maximum output power is 15 watts.
- 3) A client device providing the maximum permitted load is placed in physical contact with the transmitter(i.e. , the surfaces of the transmitter and client device enclosures need to be in physical contact)  
Yes, the maximum permitted load is placed in physical contact with the transmitter.
- 4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).  
Yes, this provision does not cover § 2.1093-Portable exposure conditions.
- 5) The H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios(i.e. , the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.  
Yes, The H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit ; coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.



6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.

Yes, For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.

## 1.2 TEST FACILITY

Test Firm : Shenzhen United Testing Technology Co., Ltd.  
Address : D101&D401, No. 107, Kaicheng High-Tech Park, Taoyuan Community, Dalang Sub-District, Longhua District, Shenzhen, Guangdong, China

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

A2LA Certificate Number: 4747.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 674885

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 31584

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

### 1.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Radiated Measurement (9KHz-30MHz)	$\pm 2.50\text{dB}$
2	Temperature	$\pm 0.5^\circ\text{C}$
3	Humidity	$\pm 2\%$

### 1.4 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 °C
Relative Humidity:	30~60 %
Air Pressure:	950~1050 hPa

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>Product:</b>	Mooas Crystal Lamp 3 in1 Magsafe Stand
<b>Trade Mark:</b>	N/A
<b>Main Model:</b>	MWCS7S1
<b>Additional Model:</b>	N/A
<b>Model Difference:</b>	N/A
<b>FCC ID:</b>	2A5K5-MWCS7S1
<b>Operation Frequency:</b>	Phone: 110-205kHz Earphone: 110-205kHz Watch: 326.5kHz
<b>Modulation Type:</b>	ASK
<b>Wireless Charging Output Power:</b>	5W/7.5W/10W/15W(MAX)
<b>Antenna Type:</b>	Coil Antenna
<b>Antenna Gain:</b>	0dBi
<b>Battery:</b>	N/A
<b>Adapter:</b>	N/A
<b>Power Source:</b>	DC 5V or 9V by adapter

## 2.2 CARRIER FREQUENCY OF CHANNELS

Test Channel					
ANT	Frequency (kHz)	ANT	Frequency (kHz)	ANT	Frequency (kHz)
01	132.9	02	156.1	03	326.5

## 2.3 TEST MODE

NO.	TEST MODE DESCRIPTION
1	ANT 1(PHONE COIL) + Full load
2	ANT 1(PHONE COIL) + Half load
3	ANT 1(PHONE COIL) + Null load
7	ANT 2(EARPHONE COIL) + Full load
8	ANT 2(EARPHONE COIL) + Half load
9	ANT 2(EARPHONE COIL) + Null load
10	ANT 3(WATCH COIL) + Full load
11	ANT 3(WATCH COIL) + Half load
12	ANT 3(WATCH COIL) + Null load
13	ANT 1(PHONE COIL) + ANT 2(EARPHONE COIL) + ANT 3(WATCH COIL) + Full load
14	ANT 1(PHONE COIL) + ANT 2(EARPHONE COIL) + ANT 3(WATCH COIL) + Half load
15	ANT 1(PHONE COIL) + ANT 2(EARPHONE COIL) + ANT 3(WATCH COIL) + Null load
Note:	
The mode 13 was the worst case and only the data of the worst case record in this report.	



## 2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Mooas Crystal Lamp 3 in1 Magsafe Stand	N/A	MWCS7S1	EUT
E-2	Adapter	Xiaomi	MDY-11-EX	AE
E-3	WPT Station (15W/10W/7.5W/5W)	N/A	N/A	AE
E-4	Earphone	APPLE	AirPods Pro2	AE
E-5	Watch	Samsung	Watch5Pro	AE

Note:

1. The support equipment was authorized by Declaration of Confirmation.
2. All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

## 2.5 TEST INSTRUMENTS

Description	Brand	Model No.	Frequency Range	Calibrated Until
Broadband Field Meter	NARDA	NBM-550	—	Jan. 01, 2025
Magnetic Field Meter	NARDA	ELT-400	1–400kHz	Jan. 01, 2025
Magnetic Probe	NARDA	HF-3061	300kHz–30MHz	Jan. 01, 2025
Magnetic Probe	NARDA	HF-0191	27–1000MHz	Jan. 01, 2025
Broadband Field Meter	NARDA	NBM-550	—	Jan. 01, 2025
Electric Field Meter	COMBINOVA	EFM 200	5Hz–400kHz	Jan. 01, 2025
E-Field Probe	NARDA	EF-0391	100kHz–3GHz	Jan. 01, 2025
E-Field Probe	NARDA	EF-6091	100MHz–60GHz	Jan. 01, 2025

NOTE: The calibration interval of the above test instruments is 12 month.

### 3 MAXIMUM PERMISSIBLE EXPOSURE

#### 3.1 MAXIMUM PERMISSIBLE EXPOSURE

Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; \*Plane-wave equivalent power density.


2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v04.

3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

### 3.2 TEST PROCEDURE

For devices designed for typical desktop applications, such as wireless charging pads, RF exposure evaluation should be at 20 cm surrounding the device and 20 cm above the top surface. H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair at 20 cm surrounding the device and 20 cm above the top surface.

### 3.3 TEST SETUP



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT(20 cm measure distance)

### 3.4 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

For ANT 1(Phone coil) + ANT 2(Earphone coil) + ANT 3(Watch coil) + Full load mode:

H-Filed Strength at 20 cm surrounding the device and 20 cm above the top surface (A/m)

Filed Strength	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
uT	0.16	0.18	0.17	0.19	0.20	/	/
A/m	0.13	0.14	0.14	0.15	0.16	0.815	1.63

Note: Calculation:  $A/m = uT/1.25$

For ANT 1(Phone coil) + ANT 2(Earphone coil) + ANT 3(Watch coil) + Half load mode:

H-Filed Strength at 20 cm surrounding the device and 20 cm above the top surface (A/m)

Filed Strength	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
uT	0.18	0.19	0.17	0.16	0.19	/	/
A/m	0.14	0.15	0.14	0.13	0.15	0.815	1.63

Note: Calculation:  $A/m = uT/1.25$

For ANT 1(Phone coil) + ANT 2(Earphone coil) + ANT 3(Watch coil) + No load mode:


H-Filed Strength at 20 cm surrounding the device and 20 cm above the top surface (A/m)



Filed Strength	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
uT	0.17	0.20	0.16	0.19	0.20	/	/
A/m	0.14	0.16	0.13	0.15	0.16	0.815	1.63

Note: 1. Calculation:  $A/m = uT/1.25$




### 3.5 TEST PHOTO









\*\*\*End of Report\*\*