W9 PRO说明书 50700-0017-06 300g铜版纸双面印刷 70*70mm

正面

反面

For iwatch

Magnetic Charging Cable

W9_{PRO}



iWatch Magentic Charger Manual

Technical parameters

Length of Wire: 120CM External Material Quality: ABS+TPE Input Voltage & Current: 5V1A Output Voltage & Current: 5V0.4A

Output power :2W

Effective transformation distance: 2mm

working frequency: 300-350KHz

Charging way: electromagnetic induction

Charging speed: Offer a fast charging speed about 2. 5 hours.

Features

Compatible with APPLE Watch SE\7\6\5\4\3\2\1 generation of the latest system, realize the one-to-one wireless charging function hardware architecture design is simple, easy to operate



NOTE: To better protect from getting too hot, we advise to charger without i-watch case. Use 5V /2A adaptor or Apple Watch original Adapter, otherwise it will affect the charging effect.

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -- Consult the dealer or an experienced radio/TV technic ian for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body: Use only the supplied antenna.