

承 认 书

SPECIFICATION FOR APPROVAL

客 户:
CUSTOMER:

客 户 料 号:
CUST P/N:

煜 耀 料 号:
YUYAO P/N:

产 品 型 号:
D E S T: Ø14.25*0.08*24P*14TS-8.2UH-3200GS-25MM

日 期:
DATE: 2023.03.14

版 本:
VERSION: V0

制 定 PREPARED BY	审 核 CHECKED BY	批 准 APPROVED BY	客 户 承 认 CUSTOMER APPROVE
郑少东	姚振东	曹前程	



东莞市煜耀电子科技有限公司

DONGGUAN YUYAO ELECTRONIC TECHNOLOGY CO.,LTD

Factory address: 21 Building, New Sun City Industrial City, No. 1 Xinyang Road, L Lin Village, Tangxia Town, Dongguan







TEL: 0769-82866410

FAX: 0769-82866409

Version Change History

[illegible]

SPECIFICATION APPROVAL

产品型号: D E S T:	Ø14.25*0.08*24P*14TS- 8.2UH-3200GS-25MM	版 本: VERSION:	V0	客 户: CUSTOMER:	喜中喜	
				客 户 料 号: CUST P/N:		
				煜 耀 料 号: YUYAO P/N:		
一、尺寸 DIMENSION:(mm) 磁铁  隔磁片  线圈 					A	7.65±0.1
					B	2±0.1
					C	8±0.5
					D	13.5±0.3
					E	21±0.3
					F	23.5±0.3
					G	25±0.3
					H	2.7±0.1
					I	14.25±0.2
					J	20.5±0.5
					K	25±1
L	3±1					
制定/日期 PREPARED BY/DATE		审核/日期 CHECKED BY/DATE				
郑少东/2023.03.06		姚振东/2023.03.06				

SPECIFICATION APPROVAL

产品型号: D E S T:	Ø14.25*0.08*24P*14TS- 8.2UH-3200GS-25MM	版 本: VERSION:	V0	客 户: CUSTOMER:	喜中喜
				客 户 料 号: CUST P/N:	
				煜 耀 料 号: YUYAO P/N:	

二、原理图 SCHEMATIC DIAGRAM:



三、绕线参数 WINDING SPECIFICATION:

序号 NO	端子 TERMINAL		线径 WIRE	圈数 TURNS	绕线方向 WINDING DIRECTION
1	S	F	0.08*24P	14TS	逆时针

四、电气特性 ELECTRICAL CHARACTERISTICS:

温度 TEMPERATURE:25℃±10℃,湿度 RELATIVE HUMIDITY:65±20%

序号 NO	项目 ITEM	端子 TERMINAL	标准 SPECIFICATION	测试条件 TEST FREQUENCY	测试仪器 TEST EQUIPMENTS
1	IND	S-F	4.7UH±5%单线圈	100KHZ/1V	LCZ METER1062B
2	IND	S-F	8.2UH±5%带磁片	100KHZ/1V	LCZ METER1062B
3	DCR	S-F	130mΩMAX	1KHZ/1V	TH2810
4	Q值	S-F	27MIN	100KHZ/1V	LCZ METER1062B

制定/日期 PREPARED BY/DATE		审核/日期 CHECKED BY/DATE	
郑少东/2023.03.06		姚振东/2023.03.06	