



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20201200043EX-03
Applicant: Shenzhen Yuweida Electronics Technology Co., Ltd.
Address of Applicant: 5F, 6Building, Second industrial district, Zhu five ancient stone, Longgang district, Shenzhen,China
Manufacturer: Shenzhen Yuweida Electronics Technology Co., Ltd.
Address of Manufacturer: 5F, 6Building, Second industrial district, Zhu five ancient stone, Longgang district, Shenzhen,China
Factory: Shenzhen Yuweida Electronics Technology Co., Ltd.
Address of Factory: 5F, 6Building, Second industrial district, Zhu five ancient stone, Longgang district, Shenzhen,China

Equipment Under Test (EUT):

Product: HD Wireless Monitor with CarPlay and Recording Function
Model No.: T86F,A3007, A3008 , A3016
Brand Name: N/A
FCC ID: 2A5TW-T86
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2022.05.05-2022.05.13

Date of Issue: 2022-05-14

Test Result : **PASS***

Tested By:

Tom Chen

(Tom chen)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200200089E-03	Rev.01	Initial report	2022-05-14

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 SAR EVALUATION.....	4
3.1 RF EXPOSURE COMPLIANCE REQUIREMENT	4
3.1.1 <i>Limits</i>	4
3.1.2 <i>Test Procedure</i>	4
3.1.3 <i>EUT RF Exposure</i>	5

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure

1) For 2.4G BT

Ant gain=0dBi

Ant numeric gain= 1

Field strength = 88.84 dBuV/m@3m

$P = \{ [10^{(88.84/20)} / 10^6 * 3]^2 / (30 * 1) \} * 1000 \text{mW} = 0.00284 \text{mW}$

$P_d = (30 * 0.003 * 1) / (377 * 20^2) = 0.0000006 < 1$

Remark:

The Max Conducted Average Output Power data refer to report Report No.: 90332-22-72-22-PP001

The Maximum power is less than the limit, complies with the exemption requirements, SAR is exempted.