



TEST REPORT

FCC ID: 2A5UI-BM7IIDS

Product: LCD monitors

Model No.: BM7IIDS

Additional Model No.: BM7DS ,LH6W,LH6X,LH6P,LS7P ,RECKEY II BT II ,BTIII
WRX ,WTX,LH5X,Keygrip J,Keygrip N,Pico Mini,LINKEY Mini,LINKEY
CTRL,LH5PIII,WRV7

Trade Mark: **PortKeys**

Report No.: WSCT-A2LA-R&E240600028A-LE

Issued Date: 22 July 2024

Issued for:

SHENZHEN PORTKEYS ELECTRONIC TECHNOLOGY CO.,LTD
Room 201, Building 1 , No. 101, ShangWei Road, ShangWei Village,
ZhangKengJing Community, GuanHu Street, LongHua District, ShenZhen

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B, Baoshi Science & Technology Park, Baoshi Road,
Bao'an District, Shenzhen, Guangdong, China

TEL: +86-755-26996192

FAX: +86-755-86376605



Note: The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. This report must not be used by the client to claim product certification, approval, or any agency of the U.S. Government.





TABLE OF CONTENTS

- 1. Test Certification..... 3
- 2. Test Result Summary 4
- 3. EUT Description..... 5
- 4. Genera Information..... 6
 - 4.1. TEST ENVIRONMENT AND MODE..... 6
 - 4.2. DESCRIPTION OF SUPPORT UNITS 6
- 5. Facilities and Accreditations 7
 - 5.1. FACILITIES 7
 - 5.2. ACCREDITATIONS 7
 - 5.3. MEASUREMENT UNCERTAINTY 8
 - 5.4. MEASUREMENT INSTRUMENTS 9
- 6. Test Results and Measurement Data 10
 - 6.1. ANTENNA REQUIREMENT..... 10
 - 6.2. CONDUCTED EMISSION 11
 - 6.3. CONDUCTED OUTPUT POWER 14
 - 6.4. EMISSION BANDWIDTH..... 16
 - 6.5. POWER SPECTRAL DENSITY 20
 - 6.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT 24
 - 6.7. RADIATED SPURIOUS EMISSION MEASUREMENT 30





Report No. WSCT-A2LA-R&E240600028A-LE

Certificate #5768.01

For Question, Please Contact with WSCT www.wsct-cert.com

1. Test Certification

Product: LCD monitors

Model No.: BM7IIDS

Additional Model: BM7DS ,LH6W,LH6X,LH6P,LS7P ,RECKEY II BT II ,BTIII WRX ,WTX,LH5X,Keygrip J,Keygrip N,Pico Mini,LINKEY Mini,LINKEY CTRL,LH5PIII,WRV7

Trade Mark: **PortKeys**

Applicant: SHENZHEN PORTKEYS ELECTRONIC TECHNOLOGY CO.,LTD

Address: Room 201, Building 1 , No. 101, ShangWei Road, ShangWei Village, ZhangKengJing Community, GuanHu Street, LongHua District, ShenZhen

Manufacturer: SHENZHEN PORTKEYS ELECTRONIC TECHNOLOGY CO.,LTD

Address: Room 201, Building 1 , No. 101, ShangWei Road, ShangWei Village, ZhangKengJing Community, GuanHu Street, LongHua District, ShenZhen

Date of Test: 11 June 2024 to 22 July 2024

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen)Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wang Xiang
(Wang Xiang)

Checked By: Chen Xu
(Chen Xu)

Approved By: Liu Fuxin
(Liu Fuxin)

Date: 22 July 2024





2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	1§5.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.





3. EUT Description

Product:	LCD monitors
Model No.:	BM7IIDS
Additional Model:	BM7DS ,LH6W,LH6X,LH6P,LS7P ,RECKEY II BT II ,BTIII WRX ,WTX,LH5X,Keygrip J,Keygrip N,Pico Mini,LINKEY Mini,LINKEY CTRL,LH5PIII,WRV7
Trade Mark:	PortKeys
Operation Frequency:	2402MHz~2480MHz
Channel Separation:	1MHz
Number of Channel:	40
Modulation Technology:	GFSK
Antenna Type:	RP-SMA Antenna
Antenna Gain:	3.0dBi
Power Supply	DC 12V
Remark:	N/A.

Models difference:

BM7IIDS, BM7DS ,LH6W,LH6X,LH6P,LS7P ,RECKEYII BTII,BTIII WRX ,WTX,LH5X,Keygrip J,Keygrip N,Pico Mini,LINKEY Mini,LINKEY CTRL,LH5PIII,WRV7 are series models, only the appearance size is different,the main test is BM7IIDS.

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
...
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Remark: Channel 0, 19 & 39 have been tested.





4. Genera Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Adapter	60-12-3-B	/	/	TECNO
Laptop	/	/	/	HP

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.





5. Facilities and Accreditations

5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group(Shenzhen) CO., LTD**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 32. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

CNAS - Registration Number: L3732

China National Accreditation Service for Conformity Assessment, The test firm Registration Number: L3732

FCC - Designation Number: CN1303

World Standardization Certification & Testing Group(Shenzhen) CO., LTD. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Designation Number: CN1303.

A2LA - Certificate Number: 5768.01

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number: 5768.01



5.3.Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
5	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2.0\%$





5.4.MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
Test software	--	EZ-EMC	CON-03A	-	-
Test software	--	MTS8310	-	-	-
EMI Test Receiver	R&S	ESCI	100005	11/05/2023	11/04/2024
LISN	AFJ	LS16	16010222119	11/05/2023	11/04/2024
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2023	11/04/2024
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	11/05/2023	11/04/2024
Coaxial cable	Megalon	LMR400	N/A	11/05/2023	11/04/2024
GPIOB cable	Megalon	GPIOB	N/A	11/05/2023	11/04/2024
Spectrum Analyzer	R&S	FSU	100114	11/05/2023	11/04/2024
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2023	11/04/2024
Pre-Amplifier	CDSI	PAP-1G18-38	--	11/05/2023	11/04/2024
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	11/05/2023	11/04/2024
9*6*6 Anechoic	--	--	--	11/05/2023	11/04/2024
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	11/05/2023	11/04/2024
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	11/05/2023	11/04/2024
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	11/05/2023	11/04/2024
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	11/05/2023	11/04/2024
Loop Antenna	EMCO	6502	00042960	11/05/2023	11/04/2024
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	11/05/2023	11/04/2024
Power meter	Anritsu	ML2487A	6K00003613	11/05/2023	11/04/2024
Power sensor	Anritsu	MX248XD	--	11/05/2023	11/04/2024
Spectrum Analyzer	Keysight	N9010B	MY60241089	11/05/2023	11/04/2024



6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
E.U.T Antenna:	The Bluetooth antenna is a RP-SMA Antenna. it meets the standards, and the best case gain of the antenna is 3.0dBi.





6.2. Conducted Emission


6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2014														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
	Frequency range (MHz)		Limit (dBuV)												
		Quasi-peak	Average												
	0.15-0.5	66 to 56*	56 to 46*												
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> 1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2014 on conducted measurement. 														
Test Result:	PASS														



6.2.2. Test data (worst case)

The worst mode is BLE High channel
Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	2.77	20.73	23.50	66.00	-42.50	QP
2	0.1635	-15.06	20.72	5.66	55.28	-49.62	AVG
3	0.1815	-2.70	20.70	18.00	64.42	-46.42	QP
4	0.3030	-7.07	20.63	13.56	60.16	-46.60	QP
5	0.3930	-7.00	20.57	13.57	58.00	-44.43	QP
6	0.3930	-19.56	20.57	1.01	48.00	-46.99	AVG
7	0.6045	-13.84	20.53	6.69	46.00	-39.31	AVG
8 *	0.6134	-3.76	20.53	16.77	56.00	-39.23	QP
9	0.7215	-10.51	20.55	10.04	56.00	-45.96	QP
10	0.7845	-23.90	20.58	-3.32	46.00	-49.32	AVG
11	1.9590	-25.45	20.61	-4.84	46.00	-50.84	AVG
12	3.1335	-26.01	20.59	-5.42	46.00	-51.42	AVG






Report No.: WSCT-A2LA-R&E240600028A-LE

Certificate # 5768.01

For Question, Please Contact with WSCT
www.wsct-cert.com

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	22.19	0.00	22.19	66.00	-43.81	QP
2	0.1725	4.65	0.00	4.65	54.84	-50.19	AVG
3	0.1860	18.52	0.00	18.52	64.21	-45.69	QP
4	0.2580	14.40	0.00	14.40	61.50	-47.10	QP
5	0.3345	13.22	0.00	13.22	59.34	-46.12	QP
6	0.3930	0.96	0.00	0.96	48.00	-47.04	AVG
7	0.6045	16.56	0.00	16.56	56.00	-39.44	QP
8 *	0.6090	6.58	0.00	6.58	46.00	-39.42	AVG
9	0.7080	10.80	0.00	10.80	56.00	-45.20	QP
10	0.7845	-4.04	0.00	-4.04	46.00	-50.04	AVG
11	1.9590	-5.36	0.00	-5.36	46.00	-51.36	AVG
12	3.1335	-5.94	0.00	-5.94	46.00	-51.94	AVG

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)

Q.P. =Quasi-Peak AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.





6.3.2. Test Data

BLE 1M			
Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	6.45	30.00	PASS
Middle	9.55	30.00	PASS
Highest	10.07	30.00	PASS


Test plots as follows:





6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074
Limit:	>500kHz
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 4.1
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS





6.4.2. Test data

BLE 1M


Test channel	6dB Emission Bandwidth (kHz)		
	BT LE mode	Limit	Result
Lowest	0.668	>500k	PASS
Middle	0.637	>500k	
Highest	0.637	>500k	

Test plots as follows:






BLE 1M Lowest channel



Middle channel






Highest channel





6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 4.1
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth $\text{VBW} \geq 3 \times \text{RBW}$. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW) 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 04, 2024
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Nov. 04, 2024
Antenna Connector	TCT	RFC-01	N/A	Nov. 04, 2024

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



6.5.3. Test data


Test channel	Power Spectral Density (dBm/3kHz)		
	BLE 1M	Limit	Result
Lowest	-8.80	8 dBm/3kHz	PASS
Middle	-5.76	8 dBm/3kHz	
Highest	-5.44	8 dBm/3kHz	

Test plots as follows:






BLE 1M
Lowest channel




Middle channel






Highest channel





6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification



Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
Test Mode:	Refer to item 4.1
Test Procedure:	<ol style="list-style-type: none"> 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS







6.6.2. Test Data

Band Edge










Report No.: WSCT-A2LA-R&E240600028A-LE



Certificate #5768.01

For Question, Please Contact with WSCT
www.wsct-cert.com

Conducted RF Spurious Emission










6.7. Radiated Spurious Emission Measurement


6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2014				
Frequency Range:	9 kHz to 25 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Refer to item 4.1				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)		
	0.009-0.490	2400/F(KHz)	300		
	0.490-1.705	24000/F(KHz)	30		
	1.705-30	30	30		
	30-88	100	3		
	88-216	150	3		
	Above 960	500	3		
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	
	Above 1GHz	500	3	Average	
		5000	3	Peak	
Test setup:	For radiated emissions below 30MHz				
	30MHz to 1GHz				






Above 1GHz



Test Procedure:

- For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.1 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.





	<p>2. Corrected Reading: Antenna Factor + Cable Loss Read Level - Preamp Factor = Level</p> <p>3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \leq 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
<p>Test mode:</p>	<p>Refer to section 4.1 for details</p>
<p>Test results:</p>	<p>PASS</p>


Note: Freq. = Emission frequency in MHz
 Reading level (dB μ V) = Receiver reading
 Corr. Factor (dB) = Attenuation factor + Cable loss
 Level (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)
 Limit (dB μ V) = Limit stated in standard
 Margin (dB) = Level (dB μ V) – Limits (dB μ V)





6.7.2. Test Data(worst case)

Please refer to following diagram for individual
The worst mode is BLE High channel
Below 1GHz
Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		37.0248	34.39	-1.87	32.52	40.00	-7.48	QP
2	!	191.7450	43.89	-5.60	38.29	43.50	-5.21	QP
3	*	275.1570	46.17	-3.19	42.98	46.00	-3.02	QP
4	!	323.3204	42.79	-1.82	40.97	46.00	-5.03	QP
5		477.1694	32.48	1.43	33.91	46.00	-12.09	QP
6		979.1804	26.51	8.36	34.87	54.00	-19.13	QP






Report No.: WSCT-A2LA-R&E240600028A-LE

Certificate # 5768.01

For Question, Please Contact with WSCT
www.wsct-cert.com

Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	37.9450	34.45	-1.72	32.73	40.00	-7.27	QP
2		190.4050	37.29	-5.39	31.90	43.50	-11.60	QP
3		229.2931	36.18	-4.40	31.78	46.00	-14.22	QP
4		273.2341	34.43	-3.23	31.20	46.00	-14.80	QP
5		327.8873	35.18	-1.79	33.39	46.00	-12.61	QP
6		996.4996	25.72	8.53	34.25	54.00	-19.75	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)






Above 1GHz

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

Low channel: 2402MHz

Horizontal:



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1941.2500	42.34	2	40.34	74	-31.66	150.6	Horizontal	PK	Pass
1	1941.2500	32.32	2	30.32	54	-21.68	150.6	Horizontal	AV	Pass
2	2440.0000	46.97	7.71	39.26	74	-27.03	153	Horizontal	PK	Pass
2	2440.0000	38.19	7.71	30.48	54	-15.81	153	Horizontal	AV	Pass
3	5674.3750	57.68	21.16	36.52	74	-16.32	198.4	Horizontal	PK	Pass
3	5674.3750	47.84	21.16	26.68	54	-6.16	198.4	Horizontal	AV	Pass
4	8593.5000	38.94	37.24	1.7	74	-35.06	1.4	Horizontal	PK	Pass
4	8593.5000	31.16	37.24	-6.08	54	-22.84	1.4	Horizontal	AV	Pass
5	11628.0000	45.99	38.93	7.06	74	-28.01	360.1	Horizontal	PK	Pass
5	11628.0000	37.71	38.93	-1.22	54	-16.29	360.1	Horizontal	AV	Pass
6	15172.5000	49.96	39.67	10.29	74	-24.04	53.1	Horizontal	PK	Pass
6	15172.5000	42.33	39.67	2.66	54	-11.67	53.1	Horizontal	AV	Pass






Report No.: WSCT-A2LA-R&E240600028A-LE
Vertical:

Certificate # 5768.01

For Question, Please Contact with WSCT
ct-cert.com



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1453.1250	23.55	25.05	-1.5	74	-50.45	322.5	Vertical	PK	Pass
1	1453.1250	14.42	25.05	-10.63	54	-39.58	322.5	Vertical	AV	Pass
2	2489.3750	33.91	27.56	6.35	74	-40.09	-0.1	Vertical	PK	Pass
2	2489.3750	25.74	27.56	-1.82	54	-28.26	-0.1	Vertical	AV	Pass
3	3199.3750	36.51	28.32	8.19	74	-37.49	1.9	Vertical	PK	Pass
3	3199.3750	27.14	28.32	-1.18	54	-26.86	1.9	Vertical	AV	Pass
4	6954.0000	34.33	6.21	28.12	74	-39.67	134.3	Vertical	PK	Pass
4	6954.0000	27.4	6.21	21.19	54	-26.6	134.3	Vertical	AV	Pass
5	9463.5000	39.25	11.05	28.2	74	-34.75	108.1	Vertical	PK	Pass
5	9463.5000	32.11	11.05	21.06	54	-21.89	108.1	Vertical	AV	Pass
6	11824.5000	45.22	16.29	28.93	74	-28.78	41.1	Vertical	PK	Pass
6	11824.5000	38.32	16.29	22.03	54	-15.68	41.1	Vertical	AV	Pass






Report No.: WSCT-A2LA-R&E240600028A-LE
 Middle channel: 2440MHz
 Horizontal:

Certificate # 5768.01

For Question,
 Please Contact with WSCT
www.wsct-cert.com



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1744.3750	43.4	0.55	42.85	74	-30.6	0	Horizontal	PK	Pass
1	1744.3750	31.08	0.55	30.53	54	-22.92	0	Horizontal	AV	Pass
2	2459.3750	48.11	7.77	40.34	74	-25.89	0	Horizontal	PK	Pass
2	2459.3750	37.51	7.77	29.74	54	-16.49	0	Horizontal	AV	Pass
3	5589.3750	56.4	20.74	35.66	74	-17.6	0	Horizontal	PK	Pass
3	5589.3750	47.37	20.74	26.63	54	-6.63	0	Horizontal	AV	Pass
4	8455.5000	39.17	37.18	1.99	74	-34.83	59	Horizontal	PK	Pass
4	8455.5000	31.21	37.18	-5.97	54	-22.79	59	Horizontal	AV	Pass
5	11997.0000	47	38.6	8.4	74	-27	12.1	Horizontal	PK	Pass
5	11997.0000	38.1	38.6	-0.5	54	-15.9	12.1	Horizontal	AV	Pass
6	17952.0000	53.22	46.18	7.04	74	-20.78	121.3	Horizontal	PK	Pass
6	17952.0000	46.2	46.18	0.02	54	-7.8	121.3	Horizontal	AV	Pass






Report No.: WSCT-A2LA-R&E240600028A-LE
Vertical:

Certificate # 5768.01

For Question, Please Contact with WSCT
ct-cert.com



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1941.8750	47.6	2	45.6	74	-26.4	321.3	Vertical	PK	Pass
1	1941.8750	32.3	2	30.3	54	-21.7	321.3	Vertical	AV	Pass
2	2724.3750	45.85	6.68	39.17	74	-28.15	-0.1	Vertical	PK	Pass
2	2724.3750	36.38	6.68	29.7	54	-17.62	-0.1	Vertical	AV	Pass
3	5936.8750	57.16	22.03	35.13	74	-16.84	274.6	Vertical	PK	Pass
3	5936.8750	48.58	22.03	26.55	54	-5.42	274.6	Vertical	AV	Pass
4	8962.5000	39.13	37.38	1.75	74	-34.87	65	Vertical	PK	Pass
4	8962.5000	32.31	37.38	-5.07	54	-21.69	65	Vertical	AV	Pass
5	11562.0000	44.95	38.99	5.96	74	-29.05	20	Vertical	PK	Pass
5	11562.0000	37.95	38.99	-1.04	54	-16.05	20	Vertical	AV	Pass
6	14020.5000	49.96	41.47	8.49	74	-24.04	232.4	Vertical	PK	Pass
6	14020.5000	42.12	41.47	0.65	54	-11.88	232.4	Vertical	AV	Pass






Report No.: WSCT-A2LA-R&E240600028A-LE
 High channel: 2480MHz
 Horizontal:

Certificate #5768.01

For Question,
 Please Contact with WSCT
 www.wsct-cert.com



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1958.7500	48.9	2.1	46.8	74	-25.1	359.5	Horizontal	PK	Pass
1	1958.7500	32.76	2.1	30.66	54	-21.24	359.5	Horizontal	AV	Pass
2	2458.1250	46.84	7.77	39.07	74	-27.16	59.8	Horizontal	PK	Pass
2	2458.1250	37.59	7.77	29.82	54	-16.41	59.8	Horizontal	AV	Pass
3	5661.8750	56.84	21.1	35.74	74	-17.16	127.9	Horizontal	PK	Pass
3	5661.8750	48.05	21.1	26.95	54	-5.95	127.9	Horizontal	AV	Pass
4	8881.5000	39.42	37.35	2.07	74	-34.58	141.5	Horizontal	PK	Pass
4	8881.5000	31.64	37.35	-5.71	54	-22.36	141.5	Horizontal	AV	Pass
5	12181.5000	45.57	38.65	6.92	74	-28.43	270.6	Horizontal	PK	Pass
5	12181.5000	37.84	38.65	-0.81	54	-16.16	270.6	Horizontal	AV	Pass
6	17715.0000	51.81	44.59	7.22	74	-22.19	179.8	Horizontal	PK	Pass
6	17715.0000	44.53	44.59	-0.06	54	-9.47	179.8	Horizontal	AV	Pass






Report No.: WSCT-A2LA-R&E240600028A-LE
Vertical:

Certificate #5768.01

For Question, Please Contact with WSCT
ct-cert.com



Susputed Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1752.5000	40.32	0.62	39.7	74	-33.68	207.7	Vertical	PK	Pass
1	1752.5000	31.34	0.62	30.72	54	-22.66	207.7	Vertical	AV	Pass
2	2461.8750	53.16	7.78	45.38	74	-20.84	45.1	Vertical	PK	Pass
2	2461.8750	37.33	7.78	29.55	54	-16.67	45.1	Vertical	AV	Pass
3	5655.0000	57.31	21.07	36.24	74	-16.69	268.6	Vertical	PK	Pass
3	5655.0000	48.03	21.07	26.96	54	-5.97	268.6	Vertical	AV	Pass
4	8451.0000	39.7	37.18	2.52	74	-34.3	358.6	Vertical	PK	Pass
4	8451.0000	31.16	37.18	-6.02	54	-22.84	358.6	Vertical	AV	Pass
5	11745.0000	46.29	38.83	7.46	74	-27.71	181.4	Vertical	PK	Pass
5	11745.0000	40.41	38.83	1.58	54	-13.59	181.4	Vertical	AV	Pass
6	17766.0000	52.15	44.93	7.22	74	-21.85	314.2	Vertical	PK	Pass
6	17766.0000	45.22	44.93	0.29	54	-8.78	314.2	Vertical	AV	Pass

Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level+Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

*******END OF REPORT*******

