

FCC RF Exposure

FCC ID:2A5UL-RC03RF

EUT Description: 2.4GHz RF Remote Controller

Model No.:RC03RF

Series Model:RC01RF,RC01RFB,RC02RF,RC02RFB,RC03RFB,RC04RF,RC04RFB,RC05RF,RC05RFB,RC06RF,RC06RFB,WR01RF,WR02RF,WR03RF,WR04RF,LM091,LM096,LM087,LM007,GW01W,GW01Z,GW02Z

Equipment type: Portable Device

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numeric simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0$ for 1-g SAR, and < 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{E}_{\text{Meas}} + 20 \log(d_{\text{meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

E_{Meas} in dBm is the field strength of the emission at the measurement distance, in dB u V/m

d_{meas} is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
89.20	-6	0.2511	2408	5	0.0779	3.0
89.48	-5.72	0.2679	2440	5	0.0836	3.0
92.79	-2.41	0.5741	2474	5	0.1805	3.0

Conclusion: No SAR is required