





Channel 144-1





IEEE 802.11a

IEEE 802.11n-HT20


Channel 144-2




Channel 149



Channel 157




Channel 165





IEEE 802.11n-HT40


Channel 38



Channel 46







TEST REPORT

Appendix E

Test Results of Radiated Emissions


Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):


Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.639	26.41	-4.90	21.51	40.00	-18.49	QP
2	52.634	37.02	-15.97	21.05	40.00	-18.95	QP
3	300.699	34.42	-6.41	28.01	46.00	-17.99	QP
4	401.105	28.23	-3.61	24.62	46.00	-21.38	QP
5	550.290	32.29	-1.00	31.29	46.00	-14.71	QP
6	754.963	26.88	2.48	29.36	46.00	-16.64	QP

Vertical



No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	40.584	34.73	-8.29	26.44	40.00	-13.56	QP
2	51.536	41.00	-15.30	25.70	40.00	-14.30	QP
3	163.162	47.20	-12.92	34.28	43.50	-9.22	QP
4	190.441	45.26	-10.33	34.93	43.50	-8.57	QP
5	550.290	42.03	-1.00	41.03	46.00	-4.97	QP
6	602.929	33.39	0.45	33.84	46.00	-12.16	QP

TEST REPORT

Radiated Emission Test Data (Above 1GHz):

IEEE 802.11a_Channel 36

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360	34.0	7.2	41.1	68.2	-27.1	Peak	Horizontal
2	10360	21.9	7.2	29.0	54	-25.0	Average	Horizontal
3	15540	30.3	12.2	42.6	74	-31.4	Peak	Horizontal
4	15540	17.4	12.2	29.7	54	-24.3	Average	Horizontal
5	10360	36.7	7.2	43.9	68.2	-24.3	Peak	Vertical
6	10360	23.0	7.2	30.2	54	-23.8	Average	Vertical
7	15540	30.8	12.2	43.0	74	-31.0	Peak	Vertical
8	15540	17.7	12.2	29.9	54	-24.1	Average	Vertical

IEEE 802.11a_Channel 44

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440	34.3	7.3	41.6	68.2	-26.6	Peak	Horizontal
2	10440	20.8	7.3	28.1	54	-25.9	Average	Horizontal
3	15660	31.2	12.3	43.5	74	-30.5	Peak	Horizontal
4	15660	18.3	12.3	30.6	54	-23.4	Average	Horizontal
5	10440	34.8	7.3	42.1	68.2	-26.1	Peak	Vertical
6	10440	21.4	7.3	28.7	54	-25.3	Average	Vertical
7	15660	31.3	12.3	43.6	74	-30.4	Peak	Vertical
8	15660	18.4	12.3	30.7	54	-23.3	Average	Vertical

IEEE 802.11a_Channel 48

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480	31.1	7.3	38.4	68.2	-29.8	Peak	Horizontal
2	10480	19.3	7.3	26.6	54	-27.4	Average	Horizontal
3	15720	32.1	12.3	44.4	74	-29.6	Peak	Horizontal
4	15720	18.8	12.3	31.1	54	-22.9	Average	Horizontal
5	10480	33.3	7.3	40.6	68.2	-27.6	Peak	Vertical
6	10480	19.0	7.3	26.3	54	-27.7	Average	Vertical
7	15720	31.9	12.3	44.2	74	-29.8	Peak	Vertical
8	15720	19.1	12.3	31.4	54	-22.6	Average	Vertical

TEST REPORT

IEEE 802.11a_Channel 52

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520	32.3	7.4	39.7	68.2	-28.5	Peak	Horizontal
2	10520	18.9	7.4	26.3	54	-27.7	Average	Horizontal
3	15780	32.3	12.3	44.6	74	-29.4	Peak	Horizontal
4	15780	19.0	12.3	31.4	54	-22.6	Average	Horizontal
5	10520	32.3	7.4	39.7	68.2	-28.5	Peak	Vertical
6	10520	18.9	7.4	26.3	54	-27.7	Average	Vertical
7	15780	33.3	12.3	45.7	74	-28.3	Peak	Vertical
8	15780	19.2	12.3	31.6	54	-22.4	Average	Vertical

IEEE 802.11a_Channel 60

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600	34.5	7.6	42.1	74	-31.9	Peak	Horizontal
2	10600	19.7	7.6	27.4	54	-26.7	Average	Horizontal
3	15900	30.8	12.4	43.2	74	-30.8	Peak	Horizontal
4	15900	18.6	12.4	31.0	54	-23.0	Average	Horizontal
5	10600	34.2	7.6	41.8	74	-32.2	Peak	Vertical
6	10600	19.9	7.6	27.5	54	-26.5	Average	Vertical
7	15900	31.2	12.4	43.6	74	-30.4	Peak	Vertical
8	15900	18.9	12.4	31.3	54	-22.8	Average	Vertical

IEEE 802.11a_Channel 64

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640	33.5	7.7	41.3	74	-32.7	Peak	Horizontal
2	10640	19.7	7.7	27.5	54	-26.5	Average	Horizontal
3	15960	31.0	12.4	43.4	74	-30.6	Peak	Horizontal
4	15960	18.6	12.4	31.0	54	-23.0	Average	Horizontal
5	10640	33.9	7.7	41.7	74	-32.3	Peak	Vertical
6	10640	19.7	7.7	27.4	54	-26.6	Average	Vertical
7	15960	30.9	12.4	43.3	74	-30.7	Peak	Vertical
8	15960	18.8	12.4	31.2	54	-22.8	Average	Vertical

TEST REPORT

IEEE 802.11a_Channel 100

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000	35.2	8.7	43.9	74	-30.1	Peak	Horizontal
2	11000	21.7	8.7	30.4	54	-23.6	Average	Horizontal
3	16500	31.3	14.1	45.3	68.2	-22.9	Peak	Horizontal
4	16500	19.2	14.1	33.2	54	-20.8	Average	Horizontal
5	11000	36.1	8.7	44.9	74	-29.1	Peak	Vertical
6	11000	21.6	8.7	30.4	54	-23.6	Average	Vertical
7	16500	31.2	14.1	45.2	68.2	-23.0	Peak	Vertical
8	16500	19.5	14.1	33.5	54	-20.5	Average	Vertical

IEEE 802.11a_Channel 120

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11200	39.0	7.4	46.3	74	-27.7	Peak	Horizontal
2	11200	25.6	7.4	32.9	54	-21.1	Average	Horizontal
3	16800	34.7	12.5	47.2	68.2	-21.0	Peak	Horizontal
4	16800	22.5	12.5	35.0	54	-19.0	Average	Horizontal
5	11200	37.3	7.4	44.6	74	-29.4	Peak	Vertical
6	11200	25.1	7.4	32.5	54	-21.5	Average	Vertical
7	16800	34.7	12.5	47.2	68.2	-21.0	Peak	Vertical
8	16800	22.7	12.5	35.1	54	-18.9	Average	Vertical

IEEE 802.11a_Channel 140

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400	32.6	8.0	40.6	74	-33.4	Peak	Horizontal
2	11400	19.1	8.0	27.0	54	-27.0	Average	Horizontal
3	17100	30.2	14.1	44.3	68.2	-23.9	Peak	Horizontal
4	17100	18.5	14.1	32.6	54	-21.4	Average	Horizontal
5	11400	32.4	8.0	40.4	74	-33.6	Peak	Vertical
6	11400	18.7	8.0	26.7	54	-27.3	Average	Vertical
7	17100	30.4	14.1	44.6	68.2	-23.6	Peak	Vertical
8	17100	18.7	14.1	32.8	54	-21.2	Average	Vertical

TEST REPORT

IEEE 802.11a_Channel 144

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11440	37.3	7.8	45.0	74	-29.0	Peak	Horizontal
2	11440	23.9	7.8	31.6	54	-22.4	Average	Horizontal
3	17160	35.7	13.4	49.2	68.2	-19.0	Peak	Horizontal
4	17160	23.9	13.4	37.3	54	-16.7	Average	Horizontal
5	11440	36.9	7.8	44.7	74	-29.4	Peak	Vertical
6	11440	24.0	7.8	31.7	54	-22.3	Average	Vertical
7	17160	35.4	13.4	48.8	68.2	-19.4	Peak	Vertical
8	17160	24.0	13.4	37.4	54	-16.6	Average	Vertical

IEEE 802.11a_Channel 149

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490	32.1	7.8	39.9	74	-34.1	Peak	Horizontal
2	11490	17.7	7.8	25.5	54	-28.5	Average	Horizontal
3	17235	30.4	14.5	44.9	68.2	-23.3	Peak	Horizontal
4	17235	18.7	14.5	33.2	54	-20.8	Average	Horizontal
5	11490	33.0	7.8	40.8	74	-33.2	Peak	Vertical
6	11490	17.6	7.8	25.4	54	-28.6	Average	Vertical
7	17235	30.2	14.5	44.6	68.2	-23.6	Peak	Vertical
8	17235	18.9	14.5	33.4	54	-20.6	Average	Vertical

IEEE 802.11a_Channel 157

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570	33.1	7.8	40.9	74	-33.1	Peak	Horizontal
2	11570	18.9	7.8	26.6	54	-27.4	Average	Horizontal
3	17355	30.3	14.7	45.0	68.2	-23.2	Peak	Horizontal
4	17355	17.4	14.7	32.2	54	-21.8	Average	Horizontal
5	11570	33.1	7.8	40.9	74	-33.1	Peak	Vertical
6	11570	19.1	7.8	26.8	54	-27.2	Average	Vertical
7	17355	30.3	14.7	45.1	68.2	-23.1	Peak	Vertical
8	17355	18.2	14.7	32.9	54	-21.1	Average	Vertical

TEST REPORT

IEEE 802.11a_Channel 165

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650	33.3	7.8	41.1	74	-32.9	Peak	Horizontal
2	11650	18.6	7.8	26.4	54	-27.6	Average	Horizontal
3	17475	29.9	15.0	44.9	68.2	-23.3	Peak	Horizontal
4	17475	17.8	15.0	32.8	54	-21.2	Average	Horizontal
5	11650	33.2	7.8	41.0	74	-33.0	Peak	Vertical
6	11650	18.7	7.8	26.5	54	-27.5	Average	Vertical
7	17475	30.6	15.0	45.6	68.2	-22.6	Peak	Vertical
8	17475	17.6	15.0	32.6	54	-21.4	Average	Vertical

IEEE 802.11n-HT20_Channel 36

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10360	33.4	7.2	40.5	68.2	-27.7	Peak	Horizontal
2	10360	20.6	7.2	27.7	54	-26.3	Average	Horizontal
3	15540	31.7	12.2	43.9	74	-30.1	Peak	Horizontal
4	15540	16.8	12.2	29.0	54	-25.0	Average	Horizontal
5	10360	34.6	7.2	41.8	68.2	-26.4	Peak	Vertical
6	10360	21.0	7.2	28.2	54	-25.8	Average	Vertical
7	15540	31.0	12.2	43.3	74	-30.7	Peak	Vertical
8	15540	17.2	12.2	29.4	54	-24.6	Average	Vertical

IEEE 802.11n-HT20_Channel 44

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10440	34.3	7.3	41.6	68.2	-26.6	Peak	Horizontal
2	10440	20.8	7.3	28.1	54	-25.9	Average	Horizontal
3	15660	31.2	12.3	43.5	74	-30.5	Peak	Horizontal
4	15660	18.3	12.3	30.6	54	-23.4	Average	Horizontal
5	10440	34.7	7.3	42.0	68.2	-26.2	Peak	Vertical
6	10440	21.3	7.3	28.6	54	-25.4	Average	Vertical
7	15660	31.6	12.3	43.9	74	-30.1	Peak	Vertical
8	15660	18.4	12.3	30.7	54	-23.3	Average	Vertical

TEST REPORT

IEEE 802.11n-HT20_Channel 48

No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Antenna Polaxis
1	10480	32.7	7.3	40.0	68.2	-28.2	Peak	Horizontal
2	10480	19.0	7.3	26.3	54	-27.7	Average	Horizontal
3	15720	31.3	12.3	43.6	74	-30.4	Peak	Horizontal
4	15720	19.1	12.3	31.4	54	-22.6	Average	Horizontal
5	10480	31.6	7.3	38.9	68.2	-29.3	Peak	Vertical
6	10480	19.0	7.3	26.3	54	-27.7	Average	Vertical
7	15720	32.8	12.3	45.1	74	-28.9	Peak	Vertical
8	15720	19.2	12.3	31.5	54	-22.5	Average	Vertical

IEEE 802.11n-HT20_Channel 52

No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Antenna Polaxis
1	10520	32.2	7.4	39.6	68.2	-28.6	Peak	Horizontal
2	10520	18.7	7.4	26.1	54	-27.9	Average	Horizontal
3	15780	31.5	12.3	43.9	74	-30.1	Peak	Horizontal
4	15780	19.0	12.3	31.3	54	-22.7	Average	Horizontal
5	10520	32.0	7.4	39.4	68.2	-28.8	Peak	Vertical
6	10520	18.9	7.4	26.3	54	-27.7	Average	Vertical
7	15780	31.8	12.3	44.2	74	-29.8	Peak	Vertical
8	15780	19.0	12.3	31.3	54	-22.7	Average	Vertical

IEEE 802.11n-HT20_Channel 60

No.	Frequency (MHz)	Reading (dB μ V/m)	Correction factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	Antenna Polaxis
1	10600	35.1	7.6	42.7	74	-31.3	Peak	Horizontal
2	10600	19.7	7.6	27.3	54	-26.7	Average	Horizontal
3	15900	30.8	12.4	43.2	74	-30.8	Peak	Horizontal
4	15900	18.7	12.4	31.1	54	-23.0	Average	Horizontal
5	10600	34.8	7.6	42.4	74	-31.6	Peak	Vertical
6	10600	19.8	7.6	27.4	54	-26.6	Average	Vertical
7	15900	30.7	12.4	43.1	74	-30.9	Peak	Vertical
8	15900	18.7	12.4	31.1	54	-22.9	Average	Vertical

TEST REPORT

IEEE 802.11n-HT20_Channel 64

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10640	33.5	7.7	41.2	74	-32.8	Peak	Horizontal
2	10640	19.5	7.7	27.4	54	-26.6	Average	Horizontal
3	15960	32.0	12.4	44.4	74	-29.6	Peak	Horizontal
4	15960	18.7	12.4	31.1	54	-22.9	Average	Horizontal
5	10640	34.5	7.7	42.2	74	-31.8	Peak	Vertical
6	10640	19.9	7.7	27.7	54	-26.4	Average	Vertical
7	15960	30.6	12.4	43.0	74	-31.0	Peak	Vertical
8	15960	18.7	12.4	31.1	54	-22.9	Average	Vertical

IEEE 802.11n-HT20_Channel 100

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11000	35.2	8.7	44.0	74	-30.0	Peak	Horizontal
2	11000	21.6	8.7	30.3	54	-23.7	Average	Horizontal
3	16500	31.9	14.1	46.0	68.2	-22.2	Peak	Horizontal
4	16500	19.3	14.1	33.4	54	-20.6	Average	Horizontal
5	11000	34.7	8.7	43.4	74	-30.6	Peak	Vertical
6	11000	21.9	8.7	30.6	54	-23.4	Average	Vertical
7	16500	31.9	14.1	45.9	68.2	-22.3	Peak	Vertical
8	16500	19.2	14.1	33.3	54	-20.7	Average	Vertical

IEEE 802.11n-HT20_Channel 120

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11200	38.0	6.5	45.4	74	-28.6	Peak	Horizontal
2	11200	23.4	6.5	30.8	54	-23.2	Average	Horizontal
3	16800	34.7	11.8	47.2	68.2	-21.0	Peak	Horizontal
4	16800	23.3	11.8	35.8	54	-18.2	Average	Horizontal
5	11200	37.9	6.5	45.2	74	-28.8	Peak	Vertical
6	11200	23.6	6.5	31.0	54	-23.0	Average	Vertical
7	16800	35.7	11.8	48.2	68.2	-20.0	Peak	Vertical
8	16800	23.2	11.8	35.7	54	-18.3	Average	Vertical

IEEE 802.11n-HT20_Channel 140

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11400	32.5	8.0	40.5	74	-33.5	Peak	Horizontal
2	11400	18.9	8.0	26.9	54	-27.1	Average	Horizontal
3	17100	29.9	14.1	44.0	68.2	-24.2	Peak	Horizontal
4	17100	18.6	14.1	32.7	54	-21.3	Average	Horizontal
5	11400	31.8	8.0	39.8	74	-34.2	Peak	Vertical
6	11400	18.9	8.0	26.8	54	-27.2	Average	Vertical
7	17100	30.5	14.1	44.6	68.2	-23.6	Peak	Vertical
8	17100	18.6	14.1	32.7	54	-21.3	Average	Vertical

IEEE 802.11n-HT20_Channel 144

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11440	37.6	7.8	45.4	74	-28.6	Peak	Horizontal
2	11440	24.2	7.8	32.0	54	-22.0	Average	Horizontal
3	17160	35.9	13.4	49.4	68.2	-18.9	Peak	Horizontal
4	17160	24.2	13.4	37.7	54	-16.3	Average	Horizontal
5	11440	37.4	7.8	45.1	74	-28.9	Peak	Vertical
6	11440	24.2	7.8	32.0	54	-22.0	Average	Vertical
7	17160	35.6	13.4	49.0	68.2	-19.2	Peak	Vertical
8	17160	24.2	13.4	37.7	54	-16.3	Average	Vertical

IEEE 802.11n-HT20_Channel 149

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11490	31.8	7.8	39.6	74	-34.4	Peak	Horizontal
2	11490	17.6	7.8	25.4	54	-28.6	Average	Horizontal
3	17235	31.1	14.5	45.6	68.2	-22.6	Peak	Horizontal
4	17235	18.5	14.5	32.9	54	-21.1	Average	Horizontal
5	11490	31.9	7.8	39.7	74	-34.3	Peak	Vertical
6	11490	17.9	7.8	25.7	54	-28.3	Average	Vertical
7	17235	30.6	14.5	45.1	68.2	-23.1	Peak	Vertical
8	17235	18.8	14.5	33.3	54	-20.7	Average	Vertical

IEEE 802.11n-HT20_Channel 157

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11570	35.9	7.8	43.7	74	-30.3	Peak	Horizontal
2	11570	19.6	7.8	27.4	54	-26.6	Average	Horizontal
3	17355	28.9	14.7	43.6	68.2	-24.6	Peak	Horizontal
4	17355	17.2	14.7	31.9	54	-22.1	Average	Horizontal
5	11570	32.9	7.8	40.7	74	-33.3	Peak	Vertical
6	11570	20.0	7.8	27.8	54	-26.2	Average	Vertical
7	17355	30.7	14.7	45.5	68.2	-22.7	Peak	Vertical
8	17355	17.5	14.7	32.2	54	-21.8	Average	Vertical

IEEE 802.11n-HT20_Channel 165

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11650	32.9	7.8	40.7	74	-33.3	Peak	Horizontal
2	11650	18.4	7.8	26.2	54	-27.8	Average	Horizontal
3	17475	29.2	15.0	44.2	68.2	-24.0	Peak	Horizontal
4	17475	17.0	15.0	32.1	54	-21.9	Average	Horizontal
5	11650	32.9	7.8	40.7	74	-33.3	Peak	Vertical
6	11650	18.9	7.8	26.7	54	-27.3	Average	Vertical
7	17475	29.3	15.0	44.4	68.2	-23.8	Peak	Vertical
8	17475	17.2	15.0	32.2	54	-21.8	Average	Vertical

IEEE 802.11n-HT40_Channel 38

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10380	33.2	7.2	40.4	68.2	-27.8	Peak	Horizontal
2	10380	21.8	7.2	29.0	54	-25.0	Average	Horizontal
3	15570	29.9	12.2	42.2	74	-31.8	Peak	Horizontal
4	15570	16.5	12.2	28.7	54	-25.3	Average	Horizontal
5	10380	34.8	7.2	42.0	68.2	-26.2	Peak	Vertical
6	10380	21.3	7.2	28.5	54	-25.5	Average	Vertical
7	15570	30.8	12.2	43.0	74	-31.0	Peak	Vertical
8	15570	16.9	12.2	29.1	54	-24.9	Average	Vertical

IEEE 802.11n-HT40_Channel 46

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10460	32.9	7.3	40.2	68.2	-28.0	Peak	Horizontal
2	10460	20.4	7.3	27.7	54	-26.3	Average	Horizontal
3	15690	30.3	12.3	42.5	74	-31.5	Peak	Horizontal
4	15690	17.6	12.3	29.9	54	-24.1	Average	Horizontal
5	10460	33.4	7.3	40.7	68.2	-27.5	Peak	Vertical
6	10460	20.7	7.3	28.0	54	-26.0	Average	Vertical
7	15690	32.1	12.3	44.4	74	-29.6	Peak	Vertical
8	15690	17.8	12.3	30.1	54	-23.9	Average	Vertical

IEEE 802.11n-HT40_Channel 54

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10540	29.1	7.5	36.5	68.2	-31.7	Peak	Horizontal
2	10540	15.7	7.5	23.1	54	-30.9	Average	Horizontal
3	15810	31.3	12.4	43.6	74	-30.4	Peak	Horizontal
4	15810	18.5	12.4	30.9	54	-23.1	Average	Horizontal
5	10540	29.7	7.5	37.1	68.2	-31.1	Peak	Vertical
6	10540	16.2	7.5	23.7	54	-30.3	Average	Vertical
7	15810	31.4	12.4	43.7	74	-30.3	Peak	Vertical
8	15810	18.7	12.4	31.1	54	-22.9	Average	Vertical

IEEE 802.11n-HT40_Channel 62

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	10620	33.8	7.7	41.5	74	-32.5	Peak	Horizontal
2	10620	19.1	7.7	26.8	54	-27.2	Average	Horizontal
3	15930	29.7	12.4	42.1	74	-31.9	Peak	Horizontal
4	15930	17.6	12.4	30.0	54	-24.0	Average	Horizontal
5	10620	33.0	7.7	40.7	74	-33.3	Peak	Vertical
6	10620	19.3	7.7	27.0	54	-27.0	Average	Vertical
7	15930	30.2	12.4	42.6	74	-31.4	Peak	Vertical
8	15930	17.9	12.4	30.4	54	-23.7	Average	Vertical

TEST REPORT

IEEE 802.11n-HT40_Channel 102

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11020	33.8	8.7	42.5	74	-31.5	Peak	Horizontal
2	11020	21.1	8.7	29.8	54	-24.2	Average	Horizontal
3	16530	30.6	14.0	44.6	68.2	-23.6	Peak	Horizontal
4	16530	18.3	14.0	32.3	54	-21.7	Average	Horizontal
5	11020	34.4	8.7	43.0	74	-31.0	Peak	Vertical
6	11020	21.3	8.7	30.0	54	-24.0	Average	Vertical
7	16530	29.7	14.0	43.7	68.2	-24.5	Peak	Vertical
8	16530	18.4	14.0	32.4	54	-21.6	Average	Vertical

IEEE 802.11n-HT40_Channel 118

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11180	36.9	6.3	44.3	74	-29.7	Peak	Horizontal
2	11180	23.7	6.3	31.1	54	-22.9	Average	Horizontal
3	16770	35.0	11.6	47.5	68.2	-20.7	Peak	Horizontal
4	16770	23.2	11.6	35.7	54	-18.3	Average	Horizontal
5	11180	37.9	6.3	45.3	74	-28.7	Peak	Vertical
6	11180	24.0	6.3	31.3	54	-22.7	Average	Vertical
7	16770	35.5	11.6	48.0	68.2	-20.2	Peak	Vertical
8	16770	23.2	11.6	35.7	54	-18.3	Average	Vertical

IEEE 802.11n-HT40_Channel 134

No.	Frequency (MHz)	Reading (dBµV/m)	Correction factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11340	32.0	8.1	40.1	74	-33.9	Peak	Horizontal
2	11340	18.3	8.1	26.4	54	-27.6	Average	Horizontal
3	17010	30.0	13.9	43.9	68.2	-24.3	Peak	Horizontal
4	17010	17.9	13.9	31.8	54	-22.2	Average	Horizontal
5	11340	32.7	8.1	40.8	74	-33.2	Peak	Vertical
6	11340	18.5	8.1	26.6	54	-27.4	Average	Vertical
7	17010	28.9	13.9	42.9	68.2	-25.3	Peak	Vertical
8	17010	18.1	13.9	32.1	54	-21.9	Average	Vertical

IEEE 802.11n-HT40_Channel 142

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11420	37.6	7.8	45.4	74	-28.6	Peak	Horizontal
2	11420	23.5	7.8	31.3	54	-22.7	Average	Horizontal
3	17130	35.4	13.4	48.8	68.2	-19.4	Peak	Horizontal
4	17130	23.7	13.4	37.0	54	-17.0	Average	Horizontal
5	11420	37.1	7.8	44.9	74	-29.1	Peak	Vertical
6	11420	23.5	7.8	31.3	54	-22.7	Average	Vertical
7	17130	35.7	13.4	49.0	68.2	-19.2	Peak	Vertical
8	17130	23.7	13.4	37.0	54	-17.0	Average	Vertical

IEEE 802.11n-HT40_Channel 151

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11510	32.2	7.8	39.9	74	-34.1	Peak	Horizontal
2	11510	16.8	7.8	24.6	54	-29.4	Average	Horizontal
3	17265	28.8	14.5	43.4	68.2	-24.8	Peak	Horizontal
4	17265	17.1	14.5	31.6	54	-22.4	Average	Horizontal
5	11510	32.3	7.8	40.1	74	-33.9	Peak	Vertical
6	11510	17.3	7.8	25.1	54	-28.9	Average	Vertical
7	17265	29.3	14.5	43.8	68.2	-24.4	Peak	Vertical
8	17265	17.5	14.5	32.0	54	-22.0	Average	Vertical

IEEE 802.11n-HT40_Channel 159

No.	Frequency (MHz)	Reading (dBμV/m)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	11590	30.0	7.8	37.8	74	-36.2	Peak	Horizontal
2	11590	18.4	7.8	26.2	54	-27.8	Average	Horizontal
3	17385	25.7	14.8	40.5	68.2	-27.7	Peak	Horizontal
4	17385	16.6	14.8	31.4	54	-22.6	Average	Horizontal
5	11590	31.8	7.8	39.6	74	-34.4	Peak	Vertical
6	11590	17.9	7.8	25.7	54	-28.3	Average	Vertical
7	17385	28.3	14.8	43.1	68.2	-25.1	Peak	Vertical
8	17385	16.4	14.8	31.3	54	-22.7	Average	Vertical



Remark:



1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Limit- Result
4. The worst-case emission is reported however emission whose levels were not within 20dB of the respective limited were not reported

TEST REPORT



Band Edge Measurements (Radiated)

IEEE 802.11a









TEST REPORT







TEST REPORT







TEST REPORT









TEST REPORT







TEST REPORT

IEEE 802.11n-HT20















TEST REPORT







TEST REPORT





TEST REPORT





TEST REPORT



IEEE 802.11n-HT40





TEST REPORT





TEST REPORT







TEST REPORT





TEST REPORT







TEST REPORT




TEST REPORT

Appendix F

Mode: WIFI Link


Live Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.158	15.33	10.03	25.36	55.57	-30.21	Average
2	0.158	36.33	10.03	46.36	65.57	-19.21	QP
3	0.326	4.57	10.03	14.60	49.55	-34.95	Average
4	0.326	23.57	10.03	33.60	59.55	-25.95	QP
5	3.717	9.60	10.25	19.85	46.00	-26.15	Average
6	3.717	23.60	10.25	33.85	56.00	-22.15	QP
7	8.188	14.99	10.48	25.47	50.00	-24.53	Average
8	8.188	25.99	10.48	36.47	60.00	-23.53	QP
9	18.498	11.52	11.15	22.67	50.00	-27.33	Average
10	18.498	30.52	11.15	41.67	60.00	-18.33	QP
11	23.321	9.69	11.38	21.07	50.00	-28.93	Average
12	23.321	29.69	11.38	41.07	60.00	-18.93	QP

TEST REPORT

Neutral Line



No.	Frequency (MHz)	Reading (dB μ V)	Correction factor (dB)	Result (dB μ V)	Limit (dB μ V)	Margin (dB)	Detector
1	0.158	20.33	10.02	30.35	55.57	-25.22	Average
2	0.158	36.33	10.02	46.35	65.57	-19.22	QP
3	0.318	15.94	10.01	25.95	49.76	-23.81	Average
4	0.318	23.94	10.01	33.95	59.76	-25.81	QP
5	3.725	6.38	10.24	16.62	46.00	-29.38	Average
6	3.725	21.38	10.24	31.62	56.00	-24.38	QP
7	8.228	15.41	10.43	25.84	50.00	-24.16	Average
8	8.228	25.41	10.43	35.84	60.00	-24.16	QP
9	19.354	10.35	11.11	21.46	50.00	-28.54	Average
10	19.354	29.35	11.11	40.46	60.00	-19.54	QP
11	25.337	7.87	11.38	19.25	50.00	-30.75	Average
12	25.337	29.87	11.38	41.25	60.00	-18.75	QP

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Reading + Factor

3. Margin = Limit - Level

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.


Appendix G

Test Results of Dynamic frequency selection


BW / Channel	Test Item	Test Result	Limit	Pass/Fail
20 MHz / 5300 MHz	Channel Move Time	0.7181 s	< 10s	Pass
	Channel Closing Transmission Time	4.8 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
20 MHz / 5500 MHz	Channel Move Time	0.4868 s	< 10s	Pass
	Channel Closing Transmission Time	8.1 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
40 MHz / 5310 MHz	Channel Move Time	0.8176 s	< 10s	Pass
	Channel Closing Transmission Time	6.6 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass
40 MHz / 5510 MHz	Channel Move Time	0.7512 s	< 10s	Pass
	Channel Closing Transmission Time	6 ms	< 200+60ms	Pass
	Non-Occupancy Period	No transmission	30 minutes	Pass

Radars Waveform calibration Plot


Reference DFS test signal




Data Traffic Plot



Noise Floor (No transmission)




Channel Move Time & Channel Closing Transmission Time 802.11a_5300 MHz




Note:

- 1) Mark1 Time: 373.9 ms, Mark2 Time: 10373.9 ms, Ontime Points: 16
- 2) Dwell = $S/B = 12000\text{ms}/40000 = 0.3\text{ ms}$, $C = N \times \text{Dwell} = 16 \times 0.3 = 4.8\text{ms}$
 $\text{CMT} = 1.092\text{ s} - 0.3739\text{ s} = 0.7181\text{ s}$

Non-Occupancy Period_802.11a_CH60_5300 MHz




Channel Move Time & Channel Closing Transmission Time 802.11a_5500 MHz




Note:

- 1) Mark1 Time: 649.2 ms, Mark2 Time: 10649.2 ms, Ontime Points: 27
- 2) Dwell = $S/B = 12000\text{ms}/40000 = 0.3\text{ ms}$, $C = N \times \text{Dwell} = 27 \times 0.3 = 8.1\text{ms}$
 $\text{CMT} = 1.136\text{ s} - 0.6492\text{ s} = 0.4868\text{ s}$

Non-Occupancy Period_802.11a_CH100_5500 MHz




Channel Move Time & Channel Closing Transmission Time 802.11n40_5310 MHz




Note:

- 1) Mark1 Time: 350.4 ms, Mark2 Time: 10350.4 ms, Ontime Points: 22
- 2) Dwell = $S/B = 12000\text{ms}/40000 = 0.3\text{ ms}$, $C = N \times \text{Dwell} = 22 \times 0.3 = 6.6\text{ ms}$
 $\text{CMT} = 1.168\text{ s} - 0.3504\text{ s} = 0.8176\text{ s}$

Non-Occupancy Period_802.11n40_CH62_5310 MHz



Channel Move Time & Channel Closing Transmission Time 802.11n40_5510 MHz



Note:

- 1) Mark1 Time: 442.8 ms, Mark2 Time: 10442.8 ms, Ontime Points: 20
- 2) Dwell = S/B = 12000ms/40000 = 0.3 ms, C = N x Dwell = 20 x 0.3 = 6 ms
CMT = 1.194 s – 0.4428 s = 0.7512 s

Non-Occupancy Period_802.11n40_CH102_5510 MHz

