







## RF EXPOSURE REPORT

|   |   |
|---|---|
| <b>Applicant:</b>   | SOUND AROUND INC.   |
| <b>Address:</b>   | 1600 63 RD STREET BROOKLYN,NEW YORK,USA   |
| <b>Manufacturer:</b>  | Guangzhou Yuandong Smart Sports Technology Co, Ltd.                               |
| <b>Address:</b>   | No.192, Kezhu Road, Huangpu District, Guangzhou,China                             |
| <b>Product Description:</b>   | Travel APButton   |
| <b>Brand Name:</b>  | SQUATZ  |
| <b>Tested Model:</b>  | Travel APOLLO Button  |
| <b>FCC ID:</b>  | 2A5X5-APTRVLBTN22   |
| <b>Report No.:</b>  | JCF230725201-006  |
| <b>Received Date:</b>   | Jul. 25, 2023   |
| <b>Tested Date:</b>   | Jul. 25, 2023 - Sep. 04, 2023   |
| <b>Issued Date:</b>   | Sep. 04, 2023   |
| <b>Test Standards:</b>  | FCC Part 2(Section 2.1091)<br>447498 D04 Interim General RF Exposure Guidance v01 |
| <b>Test Result:</b>   | Pass  |
| <b>Prepared By:</b>   |   |
| <br><u>Roger Li/Engineer</u>     |   |
| <b>Date:</b> Sep. 04, 2023      |   |
| <b>Reviewed By:</b>   |   |
| <br><u>Kennys Zhang/Engineer</u> |   |
| <b>Date:</b> Sep. 04, 2023      |   |
| <b>Approved By:</b>   |   |
| <br><u>Talent Zhang/Engineer</u> |   |
| <b>Date:</b> Sep. 04, 2023      |   |

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

**Report Revise Record**

| Report Version | Revise Time | Issued Date   | Valid Version   | Notes |
|----------------|-------------|---------------|-----------------|-------|
| V1.0           | /           | Sep. 04, 2023 | Original Report | /     |

## Table of Contents

|  |           |
|--|-----------|
| <b>1. Test Report Declare .....</b>  | <b>4</b>  |
| <b>2. Equipment Under Test .....</b>   | <b>5</b>  |
| 2.1. Description of EUT .....  | 5         |
| 2.2. Description of Available Antennas .....   | 5         |
| <b>3. Test Laboratory .....</b>  | <b>6</b>  |
| <b>4. FCC Radio Frequency Radiation Exposure Limits .....</b>                          | <b>7</b>  |
| 4.1. Blanket 1 mW Blanket Exemption .....  | 7         |
| 4.2. MPE-based Exemption .....   | 7         |
| 4.3. SAR-based Exemption .....   | 8         |
| 4.4. Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions ..... | 9         |
| <b>5. RF Exposure Calculation .....</b>  | <b>11</b> |

## 1. Test Report Declare

|                                |   |
|--------------------------------|---|
| <b>Applicant:</b>              | SOUND AROUND INC.                                     |
| <b>Address:</b>                | 1600 63 RD STREET BROOKLYN,NEW YORK,USA               |
| <b>Manufacturer:</b>           | Guangzhou Yuandong Smart Sports Technology Co, Ltd.   |
| <b>Address:</b>                | No.192, Kezhu Road, Huangpu District, Guangzhou,China |
| <b>Product Name</b>            | Travel APButton                                       |
| <b>Brand Name:</b>             | SQUATZ  |
| <b>Model Name:</b>             | Travel APOLLO Button                                  |
| <b>Difference Description:</b> | N/A   |

### We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

## 2. Equipment Under Test

### 2.1. Description of EUT

|                                  |  |
|----------------------------------|--|
| <b>EUT* Name:</b>                | Travel APButton  |
| <b>Model Number:</b>             | Travel APOLLO Button   |
| <b>EUT Function Description:</b> | Please reference user's manual   |
| <b>Power Supply:</b>             | DC 3.3V  |
| <b>Hardware Version:</b>         | YD.SWITCH.2  |
| <b>Software Version:</b>         | TX_BK2535_a97730   |
| <b>Radio Specification:</b>      | Non-specific short range devices   |
| <b>Operation Frequency:</b>      | 2405MHz  |
| <b>Modulation:</b>               | GFSK   |
| <b>Data Rate:</b>                | 250kbps  |
| <b>Antenna Type:</b>             | PCB Antenna, MAX. Gain: -3.81 dBi  |
| <b>Product Type:</b>             | <input checked="" type="checkbox"/> Portable device <input type="checkbox"/> Mobile device <input type="checkbox"/> Fixed device |

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

### 2.2. Description of Available Antennas

| Test Mode | Transmit and Receive Mode               | Description                        |
|-----------|---|------------------------------------|
| GFSK      | <input checked="" type="checkbox"/> 1TX | ANT 1 can be used as transmitting. |

### **3. Test Laboratory**

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.192, Kezhu Road, Huangpu District, Guangzhou, Guangdong, China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.01

FCC Designation Number: CN1331. Test Firm Registration Number: 360543

IC Test Firm Registration Number: 28796

Conformity Assessment Body identifier: CN0138

## 4. FCC Radio Frequency Radiation Exposure Limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

### 4.1. Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

### 4.2. MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

| RF Source Frequency |   |           | Minimum Distance   |   |                    | Threshold ERP                |
|---------------------|---|-----------|--------------------|---|--------------------|------------------------------|
| $f_L$ MHz           |   | $f_H$ MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W                            |
| 0.3                 | – | 1.34      | 159 m              | – | 35.6 m             | 1,920 R <sup>2</sup>         |
| 1.34                | – | 30        | 35.6 m             | – | 1.6 m              | 3,450 R <sup>2</sup> / $f^2$ |
| 30                  | – | 300       | 1.6 m              | – | 159 mm             | 3.83 R <sup>2</sup>          |
| 300                 | – | 1,500     | 159 mm             | – | 31.8 mm            | 0.0128 R <sup>2</sup> / $f$  |
| 1,500               | – | 100,000   | 31.8 mm            | – | 0.5 mm             | 19.2R <sup>2</sup>           |

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

#### Limit calculation:

| Frequency range(GHz) | Frequency(GHz) | R( $\lambda/2\pi$ )(m) | P <sub>th</sub> /ERP <sub>20cm</sub> (mW) |
|----------------------|----------------|------------------------|---|
| 0.3~1.5              | NA             | NA                     | NA  |
| 1.5~6                | NA             | NA                     | NA  |

### 4.3. SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P<sub>th</sub> (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P<sub>th</sub> is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).

The example values shown in Table B.2 are for illustration only.



Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) |    |    |     |     |     |     |     |     |     |  |
|-----------------|---------------|----|----|-----|-----|-----|-----|-----|-----|-----|--|
|                 | 5             | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |  |
| 300             | 39            | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |  |
| 450             | 22            | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |  |
| 835             | 9             | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |  |
| 1900            | 3             | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |  |
| 2450            | 3             | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |  |
| 3600            | 2             | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |  |
| 5800            | 1             | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |  |

**Limit calculation:**

| Frquency range(GHz) | Frequency(GHz) | X    | Distance(cm) | P <sub>th</sub> (mW) |
|---------------------|----------------|------|--------------|----------------------|
| 0.3~1.5             | NA             | NA   | NA           | NA                   |
| 1.5~6               | 2.405          | 1.90 | 0.5          | 2.77                 |

Note:If RF exposure testing requirements for a specific device are covered in a KDB publication, those requirements must be satisfied before applying any SAR test exemption provisions. For example, this is the case for handheld PTT two-way radios, handsets, laptops, and tablets, etc.9

Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

#### 4.4. Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated<sub>k</sub> term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1 \quad (1)$$

**Remark:**

a: number of fixed, mobile, or portable RF sources claiming exemption using the § 1.1307(b)(3)(i)(B) formula for  $P_{th}$ , including existing exempt transmitters and those being added.

b: number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.

c: number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.

$P_i$ : the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ : the exemption threshold power ( $P_{th}$ ) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source  $i$ .

$ERP_j$ : the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$ : exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$ , according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

$Evaluated_k$ : the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation.

$Exposure\ Limit_k$ : either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

## 5. RF Exposure Calculation

We used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

| TEST MODE | CHANNEL FREQUENCY (MHz) | CONDUCTED POWER (dBm) | ANTENNA GAIN (dBi) | EIRP (mW) | CONDUCTED POWER (mW) | Exempt Limit (mW) | PASS/FAIL |
|-----------|-------------------------|-----------------------|--------------------|-----------|----------------------|-------------------|-----------|
| GFSK      | 2405                    | 3.68                  | -3.81              | 0.97      | 2.33                 | 2.77              | PASS      |

Conclusion of simultaneous transmitter

The sum of the ratios=2.77mW

Therefore the worst-case situation is to qualify for simultaneous transmission SAR test exemption, the exemption report is in lieu of the SAR report.

--END--