

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: [2A5X9-ZT307](#)

### EUT Specification

<b>EUT</b>	<b>luna</b>
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: BLE: 2402-2480MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	BLE: 3.33 dBm (0.0022W) WiFi2.4G: 15.29dBm (0.0338W)
<b>Antenna gain (Max)</b>	BLE: 0 dBi WiFi2.4G: 0 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	<b>F/300</b>	<b>6</b>
1500-100000	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	<b>F/1500</b>	<b>6</b>
1500-100000	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/ cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
BLE	2402	2.96	2.96 ± 1	3.96	0	0.0005	1
	2440	2.64	2.64 ± 1	3.64	0	0.0005	1
	2480	3.33	3.33 ± 1	4.33	0	0.0005	1
802.11b	2412	15.08	15.08 ± 1	16.08	0	0.0081	1
	2437	15.29	15.29 ± 1	16.29	0	0.0085	1
	2462	15.14	15.14 ± 1	16.14	0	0.0082	1
802.11g	2412	14.24	14.24 ± 1	15.24	0	0.0067	1
	2437	14.47	14.47 ± 1	15.47	0	0.0070	1
	2462	14.78	14.78 ± 1	15.78	0	0.0075	1
802.11n (HT20)	2412	14.31	14.31 ± 1	15.31	0	0.0068	1
	2437	14.58	14.58 ± 1	15.58	0	0.0072	1
	2462	14.87	14.87 ± 1	15.87	0	0.0077	1