

# RF EVALUATION TEST REPORT

Applicant..... : Dongguan Aiue Electronics Technology Co., LTD  
Address..... : Room 103, NO.42, Yanhedong Street, Ailingkan, Dalingshan Town, Dongguan,  
Guangdong, China  
Manufacturer..... : Dongguan Aiue Electronics Technology Co., LTD  
Address..... : Room 103, NO.42, Yanhedong Street, Ailingkan, Dalingshan Town, Dongguan,  
Guangdong, China  
Factory ..... : Dongguan Aiue Electronics Technology Co., LTD  
Address ..... : Room 103, NO.42, Yanhedong Street, Ailingkan, Dalingshan Town, Dongguan,  
Guangdong, China  
Product Name..... : SOUND TABLE SPEAKER  
Brand Name..... :   
Model No. .... : AT105, AT106, AT115, C11, C12, C13  
(For model difference refer to section 2.)  
FCC ID..... : 2A65MAU105B  
Measurement Standard..... : 47 CFR PART 2, Section 2.1091  
Receipt Date of Samples.... : March 15, 2024  
Date of Tested..... : March 15, 2024 to April 07, 2024  
Date of Report..... : April 10, 2024

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Rose Hu / Project Engineer



Iori Fan / Assistant Signatory


## Table of Contents

1. General Description of EUT .....	4
2. Test Facility and Location .....	6
3. Applicable Standards and References.....	7
4. Maximum Permissible Exposure Limit .....	8
5. RF Exposure Evaluation Results .....	11

Revision History

Report Number	Description	Issued Date
NTC2403412F01	Initial Issue	2024-04-10

## 1. General Description of EUT

Product Information	
Product name:	SOUND TABLE SPEAKER
Main Model Name:	AT105
Additional Model Name:	AT106, AT115, C11, C12, C13
Model Difference:	These models have the same circuit schematic, structure, PCB Layout and critical components. The difference is model number due to trading purpose.
S/N:	2403-1376
Brand Name:	
Hardware version:	VER01
Software version:	V01
Rating:	DC 5V 1000mA come from adapter
Typical Arrangement:	Floor-standing
I/O Port:	Refer to the user manual
Accessories Information	
Adapter:	Manufacturer: Dongguan Yunhe electronics Co., Ltd Model: YH12-0501000U Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V 1000mA
Cable:	DC line(adapter): 1.50m, unshielded, undetachable
Other:	N/A
Additional Information	
Note:	According to the model difference and manufacturer's requirements, all tests were performed on model AT105.
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification	
Bluetooth Version:	V5.0
Frequency Range:	2402-2480MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK
Number of Channel:	79 (refer to following channel list for details)
Channel Space:	1MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-0.58 dBi
Remark:	The manufacturer declared that the product does not support BLE feature.

## 2. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	<p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2024</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2025</p> <p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number: 907417</p> <p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number. Is 46405-9743A</p>
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

### 3. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

**Test Standards:**

47 CFR Part 1, 1.1307

47 CFR Part 2, 2.1091

KDB 447498 D04 v01

#### 4. Maximum Permissible Exposure Limit

According to 47 CFR Part 1, 1.1307, for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if: 47 CFR Part 1, 1.1307

(A) The available maximum time- averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time- averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where,

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

And,

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the minimum separation distance (cm) in any direction from any part of the device antenna(s) or radiating structure(s) to the body of the device user.

For multiple RF sources: Multiple RF sources are exempt if:



(A) The available maximum time- averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Where,

$a$  = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

$b$  = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

$c$  = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

---

*Evaluate<sub>k</sub>* = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

*Exposure Limit<sub>k</sub>* = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

## 5. RF Exposure Evaluation Results

Single RF Source								
Mode	Frequency (MHz)	Max. Conducted Power (dBm)	Antenna Gain (dBi)	Max. EIRP (dBm)	Max. ERP (dBm)	Max. ERP (mW)	Separation Distance (cm)	Part 1.1307 Option (B) P <sub>th</sub> (mW)
GFSK	2402	0.423	-0.58	-0.16	-2.31	0.59	20	3060
	2441	0.297	-0.58	-0.283	-2.433	0.57	20	3060
	2480	1.080	-0.58	0.5	-1.65	0.68	20	3060
Π4/-DQPSK	2402	1.155	-0.58	0.575	-1.575	0.70	20	3060
	2441	1.052	-0.58	0.472	-1.68	0.68	20	3060
	2480	1.888	-0.58	1.308	-0.842	0.82	20	3060

### Conclusion:

According to 47 CFR §1.1307 (b)(3)(i)(B), the RF exposure analysis concludes that the product is compliant with the FCC RF exposure requirements in mobile exposure condition.

---End---