





Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

NOTE: This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference and (2) this device must accept any interference received, including interference that may cause undesired operation

FCC Statement: This equipment has been tested and found to comply with the limits for a Class Bidgital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If his equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Recrient or relocate the receiving antenna.
 Increase the separation between the equipment and receiver.
- —Connect the equipment into an outlet on a circuit different from that to which the receiver is
- Consult the dealer or an experienced radio/TV technician for help.



Temperature: -10°C ~ 50°C (± 0.5°C) / 14°F ~ 122°F (± 32.9°F) Humidity: 20% ~ 99% RH (±5%)
Battery Spec: 1 × 3V Button Battery (CR2045)

Produce Size: 41 × 41 × 13 mm Packing List:

ET-301 x 1; Lanyard x 1; User Manual x 1

1) Do not expose the device to water, not place it in a high temperature environment exceeding 60°C, and keep it away from fire.

2) The device is a precision measuring instrument, and it is not allowed to disassemble it without authorization. 3) Do not place the device in an environment full of dust or corrosive gas for measurement.















