



3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix C.



3.9 Antenna Requirements

3.9.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.9.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.9.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Sep. 26, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Sep. 26, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Sep. 26, 2023	Jan. 04, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 10, 2023	Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz, MAX 30dB	Mar. 24, 2023	Oct. 12, 2023	Mar. 23, 2024	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	Apr. 09, 2023	Oct. 12, 2023	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Oct. 12, 2023	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Oct. 12, 2023	Jan. 07, 2024	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 06, 2023	Oct. 12, 2023	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2023	Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz~18Ghz	Oct. 10, 2023	Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz~18Ghz	Jan. 05, 2023	Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 12, 2023	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 12, 2023	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 12, 2023	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 0.46 dB
Conducted Emissions	± 2.26 dB
Occupied Channel Bandwidth	± 0.1 %

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.28dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.88dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.26dB
--	--------

----- THE END -----



Appendix A. Conducted Test Results

Bluetooth

Test Engineer:	Jacob Zhang	Temperature:	20~26	°C
Test Date:	2023/9/26	Relative Humidity:	40~51	%

TEST RESULTS DATA**20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (KHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	1.039	0.946	1306.800	0.6927	Pass
DH	1Mbps	1	39	2441	1.042	0.946	994.200	0.6947	Pass
DH	1Mbps	1	78	2480	1.039	0.946	1002.900	0.6927	Pass
2DH	2Mbps	1	0	2402	1.346	1.201	998.600	0.8973	Pass
2DH	2Mbps	1	39	2441	1.346	1.201	1007.200	0.8973	Pass
2DH	2Mbps	1	78	2480	1.346	1.201	1002.900	0.8973	Pass
3DH	3Mbps	1	0	2402	1.298	1.184	998.600	0.8654	Pass
3DH	3Mbps	1	39	2441	1.307	1.181	994.200	0.8712	Pass
3DH	3Mbps	1	78	2480	1.307	1.184	998.600	0.8712	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	0.07	20.97	Pass
	39	1	0.50	20.97	Pass
	78	1	1.25	20.97	Pass
2DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	2.61	20.97	Pass
	39	1	3.32	20.97	Pass
	78	1	3.74	20.97	Pass
3DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	2.78	20.97	Pass
	39	1	3.51	20.97	Pass
	78	1	3.98	20.97	Pass

TEST RESULTS DATA**Number of Hopping Frequency**

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	79	> 15	Pass

Appendix B. Radiated Spurious Emission

Test Engineer :	Chris Chen	Relative Humidity :	22~23℃
		Temperature :	41~42%



Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	SISO	Bluetooth BR_GFSK	00	2402	DH5	-	-
Mode 2	2400-2483.5	SISO	Bluetooth BR_GFSK	39	2441	DH5	-	-
Mode 3	2400-2483.5	SISO	Bluetooth BR_GFSK	78	2480	DH5	-	-



Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	00	2389.95	55.23	74.00	-18.77	H	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	00	4804.00	43.59	74.00	-30.41	V	PEAK	Pass	Harmonic
2	Bluetooth BR_GFSK	39	-	-	-	-	-	-	-	Band Edge
	Bluetooth BR_GFSK	39	7323.00	45.81	74.00	-28.19	V	PEAK	Pass	Harmonic
3	Bluetooth BR_GFSK	78	2484.19	57.52	74.00	-16.48	V	PEAK	Pass	Band Edge
	Bluetooth BR_GFSK	78	7440.00	45.49	74.00	-28.51	H	PEAK	Pass	Harmonic
3	Bluetooth BR_GFSK	78	480.08	39.89	46.00	-6.11	H	PEAK	Pass	LF





Mode	1																																																																																																																																
	Band Edge																																																																																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																																
ANT	siso																																																																																																																																
Pol.	Horizontal						Fundamental																																																																																																																										
Peak																																																																																																																																	
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>55.23</td><td>74.00</td><td>-18.77</td><td>43.43</td><td>32.06</td><td>6.60</td><td>32.06</td><td>6.00</td><td>188</td><td>67 PEAK</td></tr><tr><td>2</td><td>2389.95</td><td>30.47</td><td>54.00</td><td>-23.53</td><td>18.67</td><td>32.06</td><td>6.60</td><td>32.06</td><td>6.00</td><td>188</td><td>67 AVERAGE</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2389.95	55.23	74.00	-18.77	43.43	32.06	6.60	32.06	6.00	188	67 PEAK	2	2389.95	30.47	54.00	-23.53	18.67	32.06	6.60	32.06	6.00	188	67 AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>95.11</td><td>-----</td><td>-----</td><td>83.12</td><td>32.21</td><td>6.62</td><td>32.84</td><td>6.00</td><td>188</td><td>67 PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>70.35</td><td>-----</td><td>-----</td><td>58.36</td><td>32.21</td><td>6.62</td><td>32.84</td><td>6.00</td><td>188</td><td>67 AVERAGE</td></tr></table>							Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2402.00	95.11	-----	-----	83.12	32.21	6.62	32.84	6.00	188	67 PEAK	2	2402.00	70.35	-----	-----	58.36	32.21	6.62	32.84	6.00	188	67 AVERAGE
			Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	2389.95	55.23	74.00	-18.77	43.43	32.06	6.60	32.06	6.00	188	67 PEAK																																																																																																																						
2	2389.95	30.47	54.00	-23.53	18.67	32.06	6.60	32.06	6.00	188	67 AVERAGE																																																																																																																						
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	2402.00	95.11	-----	-----	83.12	32.21	6.62	32.84	6.00	188	67 PEAK																																																																																																																						
2	2402.00	70.35	-----	-----	58.36	32.21	6.62	32.84	6.00	188	67 AVERAGE																																																																																																																						





Mode	1																																																																																																																																	
	Band Edge																																																																																																																																	
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																																	
ANT	siso																																																																																																																																	
Pol.	Vertical						Fundamental																																																																																																																											
Peak																																																																																																																																		
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2320.79</td><td>54.44</td><td>74.00</td><td>-19.56</td><td>43.18</td><td>31.73</td><td>6.50</td><td>32.97</td><td>6.00</td><td>100</td><td>20 PEAK</td></tr><tr><td>2</td><td>2320.79</td><td>29.68</td><td>54.00</td><td>-24.32</td><td>18.42</td><td>31.73</td><td>6.50</td><td>32.97</td><td>6.00</td><td>100</td><td>20 AVERAGE</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2320.79	54.44	74.00	-19.56	43.18	31.73	6.50	32.97	6.00	100	20 PEAK	2	2320.79	29.68	54.00	-24.32	18.42	31.73	6.50	32.97	6.00	100	20 AVERAGE	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>99.76</td><td>-----</td><td>-----</td><td>87.77</td><td>32.21</td><td>6.62</td><td>32.84</td><td>6.00</td><td>100</td><td>20 PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>75.00</td><td>-----</td><td>-----</td><td>63.01</td><td>32.21</td><td>6.62</td><td>32.84</td><td>6.00</td><td>100</td><td>20 AVERAGE</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2402.00	99.76	-----	-----	87.77	32.21	6.62	32.84	6.00	100	20 PEAK	2	2402.00	75.00	-----	-----	63.01	32.21	6.62	32.84	6.00	100	20 AVERAGE
			Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																							
1	2320.79	54.44	74.00	-19.56	43.18	31.73	6.50	32.97	6.00	100	20 PEAK																																																																																																																							
2	2320.79	29.68	54.00	-24.32	18.42	31.73	6.50	32.97	6.00	100	20 AVERAGE																																																																																																																							
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																							
1	2402.00	99.76	-----	-----	87.77	32.21	6.62	32.84	6.00	100	20 PEAK																																																																																																																							
2	2402.00	75.00	-----	-----	63.01	32.21	6.62	32.84	6.00	100	20 AVERAGE																																																																																																																							



Mode	1																																																																																																											
	Harmonic																																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																											
ANT	siso																																																																																																											
Pol.	Horizontal						Vertical																																																																																																					
Peak Avg																																																																																																												
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>43.44</td><td>74.00</td><td>-30.56</td><td>60.72</td><td>34.20</td><td>9.44</td><td>60.92</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4804.00	43.44	74.00	-30.56	60.72	34.20	9.44	60.92	0.00	---	---	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4804.00</td><td>43.59</td><td>74.00</td><td>-30.41</td><td>60.87</td><td>34.20</td><td>9.44</td><td>60.92</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>								Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4804.00	43.59	74.00	-30.41	60.87	34.20	9.44	60.92	0.00	---	---	PEAK
			Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																		
1	4804.00	43.44	74.00	-30.56	60.72	34.20	9.44	60.92	0.00	---	---	PEAK																																																																																																
		Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																		
1	4804.00	43.59	74.00	-30.41	60.87	34.20	9.44	60.92	0.00	---	---	PEAK																																																																																																





Mode	2																																																																																																																																											
	Harmonic																																																																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																											
ANT	siso																																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																																					
Peak Avg																																																																																																																																												
	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4882.00</td><td>43.84</td><td>74.00</td><td>-30.16</td><td>60.97</td><td>34.20</td><td>9.53</td><td>60.86</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7323.00</td><td>45.76</td><td>74.00</td><td>-28.24</td><td>58.73</td><td>35.69</td><td>11.69</td><td>60.35</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4882.00	43.84	74.00	-30.16	60.97	34.20	9.53	60.86	0.00	---	---	PEAK	2	7323.00	45.76	74.00	-28.24	58.73	35.69	11.69	60.35	0.00	---	---	PEAK	<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4882.00</td><td>43.89</td><td>74.00</td><td>-30.11</td><td>61.02</td><td>34.20</td><td>9.53</td><td>60.86</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7323.00</td><td>45.81</td><td>74.00</td><td>-28.19</td><td>58.78</td><td>35.69</td><td>11.69</td><td>60.35</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	4882.00	43.89	74.00	-30.11	61.02	34.20	9.53	60.86	0.00	---	---	PEAK	2	7323.00	45.81	74.00	-28.19	58.78	35.69	11.69	60.35	0.00	---	---	PEAK
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	4882.00	43.84	74.00	-30.16	60.97	34.20	9.53	60.86	0.00	---	---	PEAK																																																																																																																																
2	7323.00	45.76	74.00	-28.24	58.73	35.69	11.69	60.35	0.00	---	---	PEAK																																																																																																																																
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																	
1	4882.00	43.89	74.00	-30.11	61.02	34.20	9.53	60.86	0.00	---	---	PEAK																																																																																																																																
2	7323.00	45.81	74.00	-28.19	58.78	35.69	11.69	60.35	0.00	---	---	PEAK																																																																																																																																



Mode	3																																																																																																																								
	Band Edge																																																																																																																								
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																								
ANT	siso																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak																																																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2492.51</td><td>56.13</td><td>74.00</td><td>-17.87</td><td>43.14</td><td>32.84</td><td>6.75</td><td>32.60</td><td>6.00</td><td>100</td><td>46 PEAK</td></tr><tr><td>2</td><td>2492.51</td><td>31.37</td><td>54.00</td><td>-22.63</td><td>18.38</td><td>32.84</td><td>6.75</td><td>32.60</td><td>6.00</td><td>100</td><td>46 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2492.51	56.13	74.00	-17.87	43.14	32.84	6.75	32.60	6.00	100	46 PEAK	2	2492.51	31.37	54.00	-22.63	18.38	32.84	6.75	32.60	6.00	100	46 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>96.76</td><td>-----</td><td>-----</td><td>83.92</td><td>32.74</td><td>6.73</td><td>32.63</td><td>6.00</td><td>100</td><td>46 PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>72.00</td><td>-----</td><td>-----</td><td>59.16</td><td>32.74</td><td>6.73</td><td>32.63</td><td>6.00</td><td>100</td><td>46 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	96.76	-----	-----	83.92	32.74	6.73	32.63	6.00	100	46 PEAK	2	2480.00	72.00	-----	-----	59.16	32.74	6.73	32.63	6.00	100	46 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2492.51	56.13	74.00	-17.87	43.14	32.84	6.75	32.60	6.00	100	46 PEAK																																																																																																														
2	2492.51	31.37	54.00	-22.63	18.38	32.84	6.75	32.60	6.00	100	46 AVERAGE																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2480.00	96.76	-----	-----	83.92	32.74	6.73	32.63	6.00	100	46 PEAK																																																																																																														
2	2480.00	72.00	-----	-----	59.16	32.74	6.73	32.63	6.00	100	46 AVERAGE																																																																																																														



Mode	3																																																																																																																									
	Band Edge																																																																																																																									
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																									
ANT	siso																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																			
Peak																																																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.19</td><td>57.52</td><td>74.00</td><td>-16.48</td><td>44.64</td><td>32.77</td><td>6.73</td><td>32.62</td><td>6.00</td><td>122</td><td>22 PEAK</td></tr><tr><td>2</td><td>2484.19</td><td>32.76</td><td>54.00</td><td>-21.24</td><td>19.88</td><td>32.77</td><td>6.73</td><td>32.62</td><td>6.00</td><td>122</td><td>22 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.19	57.52	74.00	-16.48	44.64	32.77	6.73	32.62	6.00	122	22 PEAK	2	2484.19	32.76	54.00	-21.24	19.88	32.77	6.73	32.62	6.00	122	22 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.45</td><td>-----</td><td>-----</td><td>89.61</td><td>32.74</td><td>6.73</td><td>32.63</td><td>6.00</td><td>122</td><td>22 PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>77.69</td><td>-----</td><td>-----</td><td>64.85</td><td>32.74</td><td>6.73</td><td>32.63</td><td>6.00</td><td>122</td><td>22 AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	102.45	-----	-----	89.61	32.74	6.73	32.63	6.00	122	22 PEAK	2	2480.00	77.69	-----	-----	64.85	32.74	6.73	32.63	6.00	122	22 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2484.19	57.52	74.00	-16.48	44.64	32.77	6.73	32.62	6.00	122	22 PEAK																																																																																																															
2	2484.19	32.76	54.00	-21.24	19.88	32.77	6.73	32.62	6.00	122	22 AVERAGE																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2480.00	102.45	-----	-----	89.61	32.74	6.73	32.63	6.00	122	22 PEAK																																																																																																															
2	2480.00	77.69	-----	-----	64.85	32.74	6.73	32.63	6.00	122	22 AVERAGE																																																																																																															




Mode	3																																																																																																																													
	Harmonic																																																																																																																													
	2400-2483.5 Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																													
ANT	siso																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																							
Peak Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>44.18</td><td>74.00</td><td>-29.82</td><td>61.19</td><td>34.18</td><td>9.61</td><td>60.80</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>45.49</td><td>74.00</td><td>-28.51</td><td>58.64</td><td>35.70</td><td>11.77</td><td>60.62</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	44.18	74.00	-29.82	61.19	34.18	9.61	60.80	0.00	---	---	PEAK	2	7440.00	45.49	74.00	-28.51	58.64	35.70	11.77	60.62	0.00	---	---	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>43.71</td><td>74.00</td><td>-30.29</td><td>60.72</td><td>34.18</td><td>9.61</td><td>60.80</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>45.25</td><td>74.00</td><td>-28.75</td><td>58.40</td><td>35.70</td><td>11.77</td><td>60.62</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4960.00	43.71	74.00	-30.29	60.72	34.18	9.61	60.80	0.00	---	---	PEAK	2	7440.00	45.25	74.00	-28.75	58.40	35.70	11.77	60.62	0.00	---	---	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4960.00	44.18	74.00	-29.82	61.19	34.18	9.61	60.80	0.00	---	---	PEAK																																																																																																																		
2	7440.00	45.49	74.00	-28.51	58.64	35.70	11.77	60.62	0.00	---	---	PEAK																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4960.00	43.71	74.00	-30.29	60.72	34.18	9.61	60.80	0.00	---	---	PEAK																																																																																																																		
2	7440.00	45.25	74.00	-28.75	58.40	35.70	11.77	60.62	0.00	---	---	PEAK																																																																																																																		
Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				




Mode	3																																																																																																																																																																	
	LF																																																																																																																																																																	
	2400-2483.5 Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																																																																	
ANT	siso																																																																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																																																																
Peak QP	Data: 3 Site : 03CH06-KS Condition : FCC PART 15C 3m LF 6111D SN44483 HORIZONTAL <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>186.17</td><td>22.59</td><td>-20.91</td><td>43.50</td><td>38.00</td><td>1.84</td><td>14.92</td><td>32.17</td><td>Peak</td></tr><tr><td>2</td><td>271.53</td><td>22.98</td><td>-23.02</td><td>46.00</td><td>33.33</td><td>2.22</td><td>19.60</td><td>32.17</td><td>Peak</td></tr><tr><td>3</td><td>480.08</td><td>39.89</td><td>-6.11</td><td>46.00</td><td>45.94</td><td>2.96</td><td>23.64</td><td>32.65</td><td>Peak</td></tr><tr><td>4</td><td>518.88</td><td>37.70</td><td>-8.30</td><td>46.00</td><td>42.67</td><td>3.07</td><td>24.52</td><td>32.56</td><td>Peak</td></tr><tr><td>5</td><td>764.29</td><td>32.58</td><td>-13.42</td><td>46.00</td><td>32.78</td><td>3.74</td><td>28.20</td><td>32.14</td><td>Peak</td></tr><tr><td>6</td><td>960.23</td><td>37.93</td><td>-16.07</td><td>54.00</td><td>33.71</td><td>4.18</td><td>30.92</td><td>30.88</td><td>Peak</td></tr></table>	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	186.17	22.59	-20.91	43.50	38.00	1.84	14.92	32.17	Peak	2	271.53	22.98	-23.02	46.00	33.33	2.22	19.60	32.17	Peak	3	480.08	39.89	-6.11	46.00	45.94	2.96	23.64	32.65	Peak	4	518.88	37.70	-8.30	46.00	42.67	3.07	24.52	32.56	Peak	5	764.29	32.58	-13.42	46.00	32.78	3.74	28.20	32.14	Peak	6	960.23	37.93	-16.07	54.00	33.71	4.18	30.92	30.88	Peak	Data: 4 Site : 03CH06-KS Condition : FCC PART 15C 3m LF 6111D SN44483 VERTICAL <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>Read</th><th>CableAntenna</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>42.61</td><td>32.25</td><td>-7.75</td><td>40.00</td><td>45.74</td><td>0.62</td><td>18.33</td><td>32.44</td><td>Peak</td></tr><tr><td>2</td><td>124.09</td><td>23.40</td><td>-20.10</td><td>43.50</td><td>36.49</td><td>1.48</td><td>17.60</td><td>32.17</td><td>Peak</td></tr><tr><td>3</td><td>445.16</td><td>39.48</td><td>-6.52</td><td>46.00</td><td>46.13</td><td>2.85</td><td>22.98</td><td>32.48</td><td>Peak</td></tr><tr><td>4</td><td>686.69</td><td>32.27</td><td>-13.73</td><td>46.00</td><td>34.35</td><td>3.55</td><td>26.65</td><td>32.28</td><td>Peak</td></tr><tr><td>5</td><td>815.70</td><td>33.66</td><td>-12.34</td><td>46.00</td><td>33.23</td><td>3.86</td><td>28.55</td><td>31.98</td><td>Peak</td></tr><tr><td>6</td><td>960.23</td><td>37.96</td><td>-16.04</td><td>54.00</td><td>33.74</td><td>4.18</td><td>30.92</td><td>30.88</td><td>Peak</td></tr></table>	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg	1	42.61	32.25	-7.75	40.00	45.74	0.62	18.33	32.44	Peak	2	124.09	23.40	-20.10	43.50	36.49	1.48	17.60	32.17	Peak	3	445.16	39.48	-6.52	46.00	46.13	2.85	22.98	32.48	Peak	4	686.69	32.27	-13.73	46.00	34.35	3.55	26.65	32.28	Peak	5	815.70	33.66	-12.34	46.00	33.23	3.86	28.55	31.98	Peak	6	960.23	37.96	-16.04	54.00	33.74	4.18	30.92	30.88	Peak
	Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																								
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																																																																																									
1	186.17	22.59	-20.91	43.50	38.00	1.84	14.92	32.17	Peak																																																																																																																																																									
2	271.53	22.98	-23.02	46.00	33.33	2.22	19.60	32.17	Peak																																																																																																																																																									
3	480.08	39.89	-6.11	46.00	45.94	2.96	23.64	32.65	Peak																																																																																																																																																									
4	518.88	37.70	-8.30	46.00	42.67	3.07	24.52	32.56	Peak																																																																																																																																																									
5	764.29	32.58	-13.42	46.00	32.78	3.74	28.20	32.14	Peak																																																																																																																																																									
6	960.23	37.93	-16.07	54.00	33.71	4.18	30.92	30.88	Peak																																																																																																																																																									
Freq	Level	Over	Limit	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB/m	dB	cm	deg																																																																																																																																																									
1	42.61	32.25	-7.75	40.00	45.74	0.62	18.33	32.44	Peak																																																																																																																																																									
2	124.09	23.40	-20.10	43.50	36.49	1.48	17.60	32.17	Peak																																																																																																																																																									
3	445.16	39.48	-6.52	46.00	46.13	2.85	22.98	32.48	Peak																																																																																																																																																									
4	686.69	32.27	-13.73	46.00	34.35	3.55	26.65	32.28	Peak																																																																																																																																																									
5	815.70	33.66	-12.34	46.00	33.23	3.86	28.55	31.98	Peak																																																																																																																																																									
6	960.23	37.96	-16.04	54.00	33.74	4.18	30.92	30.88	Peak																																																																																																																																																									

Appendix C. Duty Cycle Plots

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.