





<div> 雷宝电子 —ZYCOIL—</div>		Specification							Number	ZY9204-1001
									Version	A/0
									Page	1/1
Customer	ZY9204	Wire	Sample wire: 2USTC-INB/155 0.07*24P						Machine	
Item	Wireless charger coil	Spec	10x0.07x24px9.6uH+Ferrite						Direction	CW
1.Specification (Unit:mm)										
Item	Turns	L 120KHZ/1V	DCR 25℃	ID	OD	Coil thick	Total thick (Include lead)	Lead (From coil)	Tin	
Standard	18TS	9.6uH	200mΩ	10	26	0.9	1.75	20	2-4	
Tolerance	Fixed	+10%/-5%	±10%	±0.3	±1	MAX	MAX	±2		
Sample data	18TS	9.97	203	10.03	25.70	0.62	1.68	21	3	
2.Drawing										
<div><div><div></div><div><div>Before assembly, gently flatten the winding wire and then attach the magnetic sheet. The winding wire should be attached to the magnetic sheet downwards.</div><div></div></div></div></div>										
3. BOM										
Material		Specification				Unit	Usage	Suppliler	Mark	
WIRE		0.07*24P (USTC WIRE)				g	1.1			
Ferrite		OD30.1±0.2*ID7±0.2*thick0.2 (one piece 3M9448A tape)				pcs	1			
Glue		530				g	0.03			
OPP bag		90x55mm				pcs	2pcs/bag			
Version		Content				Date	Remark			
A/0						2023/12/9				
Approval										
Maek		Audit		Approval		Customer confirm				
尹艺										