



Report No.: ET-22040185E

TEST REPORT

Applicant: DONGGUAN YI RUI ELECTRONIC TECHNOLOGY CO.,LTD
Address of Applicant: ROOM NO. 202, BUILDING 2, NO.11, NIULING ROAD,CHANGPING TOWN, DONGGUAN CITY, CHINA
Manufacturer/Factory: DONGGUAN YI RUI ELECTRONIC TECHNOLOGY CO.,LTD
Address of Manufacturer/Factory: ROOM NO. 202, BUILDING 2, NO.11, NIULING ROAD,CHANGPING TOWN, DONGGUAN CITY, CHINA
Product Name: Wireless charger
Model No.: WXC-5W-02
Trade Mark: N/A
FCC ID: 2A6HU-WXC5W02
Applicable standards: FCC CFR Title 47 Part 1.1310
Date of Test: May.20,2022- May.28,2022
Date of report issued: Jun.06,2022
Test Result : PASS

Remark:

* In the configuration tested, the EUT complied with the standards specified above.

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Project Engineer

Reviewed by:

Project Manager

Approved by:



Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-22040185E	Original	Jun.06,2022

Contents

Page

1	TEST SUMMARY	4
2	GENERAL INFORMATION	5
2.1	GENERAL DESCRIPTION OF EUT	5
2.2	TEST MODE	6
2.3	DESCRIPTION OF SUPPORT UNITS	6
2.4	DEVIATION FROM STANDARDS	6
2.5	ABNORMALITIES FROM STANDARD CONDITIONS	6
2.6	TEST FACILITY	6
2.7	TEST LOCATION	6
2.8	ADDITIONAL INSTRUCTIONS	6
3	TEST INSTRUMENTS LIST	7
4	MAXIMUM PERMISSIBLE EXPOSURE	8
4.1	LIMIT	8
4.2	REQUIREMENTS	8
4.3	MEASURE PROCEDURES	9
4.4	MEASURE SETUP	9
4.5	MEASUREMENT DATA	9
5	TEST SETUP PHOTO	10

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Electric Field strength (E) (V/m)	KDB 680106 D01 RF Exposure Wireless Charging App v03r01	Pass	Yvan
Magnetic strength (H) (A/m)		Pass	Yvan

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-1000MHz	±4.30 dB	(1)
Radiated Emission	1GHz-18GHz	±4.35 dB	(1)
Radiated Emission	18GHz-40GHz	±4.59 dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.02 dB	(1)
Occupied Channel Bandwidth	/	±0.55%	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

2 General Information

2.1 General Description of EUT

Product Name:	Wireless charger
Model No.:	WXC-5W-02
Model of difference:	N/A
Test model:	WXC-5W-02
Sample(s) Status:	Engineer sample
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	115~205KHz
Channel numbers:	1
Modulation type:	ASK
Antenna Type:	Induction coil Antenna
Power supply:	Input: DC 5V from adapter Output: wireless DC 5V/5W

Operation channel list

Channel	Frequency
00	142.1 KHz
/	/
/	/

Test channel

Channel	Frequency
00	142.1 KHz
/	/
/	/

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.		
	Test mode	Description	
	Mode 1	Charging +TX	

2.3 Description of Support Units

Equipment	Model	S/N	Manufacturer
Adapter	HW-050200CH0	/	HUAWEI
Load	/	/	/

2.4 Deviation from Standards

None.

2.5 Abnormalities from Standard Conditions

None.

2.6 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064

2.7 Test Location

All tests were performed at:	
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86 755 85259392
Fax:	+86 755 27219460

2.8 Additional Instructions

Test Software	/
Power level setup	Default

3 Test Instruments list

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	Exposure level Tester	Narda	ELT-400	N-0231	2021.6.26	2022.6.25
2	Magnetic field probe	Narda	ELT Probe 100cm2	M0675	2021.6.26	2022.6.25
3	Isotropic electric field probe	Narda	EP-601	611WX70332	2021.6.26	2022.6.25

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

4 Maximum permissible exposure

4.1 Limit

Frequency range(MHz)	Electric field strength(V/m)	Magnetic field strength(A/m)	Power density(mW/cm ²)	Averaging time(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0 6	6
300-1500			f/300	6
1500-100000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100000			1	30
f = frequency in MHz				
* = Plane-wave equivalent power density				

4.2 Requirements


Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting and RF exposure evaluation.

- (1) Power transfer frequency is less than 1 MHz
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.

4.3 Measure Procedures

E and H-field measurements should be made with the center of the probe at a distance of 15 cm surrounding the device and 20 cm above the top surface of the primary/client pair.

4.4 Measure setup




4.5 Measurement data

Maximum permissible Exposure				
Frequency range	Test sides	Separation (cm)	E –field(V/m)	H–field(A/m)
0.11-0.205MHz	Top	20	0.854	0.212
	Bottom	15	0.821	0.210
	Left	15	0.824	0.214
	Right	15	0.823	0.208
	Front	15	0.819	0.205
	Back	15	0.810	0.216
Limit			614	1.63
Margin Limit (%)			0.139%	13.25%

The test under empty load, half load and full load mode. All modes were tested. Only the worse-case (full load) was recorded in the report.

5 Test Setup Photo



-----End-----