
 C US	II 1 GD IECEx SIR 17.0060X MFG: YYYY IP 66 I M1 SIRA 17ATEX2237X Tamb -30°C to +105°C SN: NNNNNNNN Ex ia I Ma Ex ia IIC 150°C (T3) Ga Ex ia IIIC T146°C Da Model: DSV1 FCC ID: 2A6IE-DSV1 IC:28778-DSV1 CSAE 21UKEX2441X CSA 23CA80157383X CI I, Zn 0, AEx ia IIC 150°C Ga CI I, Div.1, Grps ABCD MC 302539 CI II, Zn 20, AEx ia IIIC T146°C Da CI II, Div 1, Grps EFG CI III, Div 1	 0843 	Dodge Industrial, Inc. 1061 Holland Rd. Simpsonville, SC 29681  0539
--	---	---	--

- NOTE(S):
- 1) LAYOUT OF INFORMATION MAY VARY, PROVIDED CONTENT IS IDENTICAL
 - 2) CE, HEX, EX, CSA AND UKCA MARKS TO BE 5MM HIGH MINIMUM
 - 3) MARKING TO BE ETCHED TO STAINLESS STEEL COMPONENT IDENTIFIED IN 750000
 - 4) REPLACE "YYYY" AFTER "MFG:" WITH CURRENT YEAR OF MANUFACTURING.
 - 5) WEEE WHEELIE BIN 7MM HIGH MINIMUM

	TDR: 200003482	MAT'L PART NO:	DIMENSION TOLERANCE, ETC. UNLESS OTHERWISE SPECIFIED: MACHINE TOLERANCE PER S022 FABRICATION TOLERANCE PER S356 CASTING TOLERANCE PER S249 BREAK ALL SHARP EDGES .005-.015 SURFACE FINISH: 125 µin	SHEET NUMBER: 1 OF 1	
	BY: USMIKUN1	TREATMENT:		MODEL NO: 750000	
	TIME & DATE: 03/06/2023	WEIGHT:		VERSION: 06	
	MAT'L DESC:			PAPER SIZE: A REV: F	
REV. DESC: UPDATED LABEL INFO & NOTES			DRAWING NO: 750000-3		
DESCRIPTION: DODGE OPTIFY SENSOR - FULL MARKING					