

FCC ID: 2A6IP-CPE350S

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Test Result of RF Exposure Evaluation

	Maximum peak output power (dBm)	Output Power to antenna (mW)	Antenna Gain (numeric) =10log(dBi)	Power Density (S) (mW/ cm2)	Total Power Density (S) (mW/ cm2)	Limit of Power Density (S) (mW/ cm2)	Result
802.11 a ANT1	17.06	50.82	15.85 (12.00dBi)	0.16022	/	1	Pass
802.11 a ANT2	16.53	44.98	15.85 (12.00dBi)	0.14182	/	1	Pass
802.11 ac 20 ANT1	15.98	39.63	15.85 (12.00dBi)	0.12495	0.24904	1	Pass
802.11 ac 20 ANT2	15.95	39.36	15.85 (12.00dBi)	0.12409			
802.11 ac 40 ANT1	13.79	23.93	15.85 (12.00dBi)	0.07546	0.15233	1	Pass
802.11 ac 40 ANT2	13.87	24.38	15.85 (12.00dBi)	0.07687			
802.11 n20 ANT1	13.61	22.96	15.85 (12.00dBi)	0.07240	0.19535	1	Pass
802.11 n20 ANT2	15.91	38.99	15.85 (12.00dBi)	0.12295			
802.11 n40 ANT2	14.00	25.12	15.85 (12.00dBi)	0.07920	0.18629	1	Pass
802.11 n40 ANT2	15.31	33.96	15.85 (12.00dBi)	0.10709			