



SPECIFICATION FOR APPROVAL

1.MECHANICAL DIMENSION (UNIT:mm)



2. SCHEMATICS:



备注： 加背胶
Note: Add back glue

A	B	C	D2	E	H	I			I
43.5±0.5	16±0.5	0.8±0.05	50±3	4±2	2.2MAX	5±1			

3.WINDING:

1.1

STEP	START-FINISH	WIRE TYPE	TURNS	TAPE	REMARK
N1	S-F	Silk-covered wire $\varnothing 0.08 \times 105\text{mm}$ 2UEW	11TS (Ref)		

4.ELECTRICAL

ITEM	L	DCR	Temperature		HI-POT
TEST COND	Coil and diskette	S-F	At normal temperature		
	100KHz,0.25V	AT 25°C			
SPEC	6.3uH±10%	70mΩ Max	0-80°C		

5.BILF OF MATERIAL :

NO.	ITEM	MATERIAL SPECIFICATION	MANUFACTURER	SGS NO.
1	Silk covered thread 0.08*105 strands	Acetone silk-covered wire 0.08*105 strands	NANJINGJINNINGCO,LTD	
2	Lead-free tin strip	Lead-free tin strip	QIAODO	
3	Magnetic sheet	$\varnothing 43.5 \times 0.8$ manganese zinc hard disk with L slot	TAIYI CO.,LTD	
4	glue	Yellow gum 9999	LIANCHENG CO.,LTD	
5	High-temperature adhesive paper	8mm wide high temperature adhesive paper	CUDAK CO.,LTD	
6	Rubber backing	$\varnothing 41.5 \times 0.1$	CUDAK CO.,LTD	

Company : HRSW ELECTRONICS CO.,LTD
Address : Building 46, Zone 5, Huaide Cuigang Industrial Park, Fuyong Street, Bao'an District, Shenzhen

PART NO

TITLE

G43.5/0.8 thick 11 rings inner diameter 16MM 50 long

DRAWN BY

CHECKED BY

APPROVED BY

He Weihua

Wei Hong

Wei Hong