## RF EXPOSURE EVALUATION

FCC ID: 2A6K7-08X

Anbotek Product Safety

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b):

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

 $[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f_{(GHz)}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $\leq$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Max Tune Up Power (dBm)	Distance (mm)	Calculation results	Limit Anbot	Operating Mode
2402	2.8	3.00	5	0.618	× 3 pm	Anbotek Anbotek Anbotek
2440	2.4	3.00	5 Anbo	0.623	otek 3	
2480	1.66	3.00 pm	oten 5 Ar	0.628	3	
2412	9.27	9.80	inbore 5	2.966	An3otek	Anborn
2437	9.27	9.80	AntoSter	2.982	3 noote	802.11b
2462	9.16	9.80	50 <sup>0101</sup>	2.997	6 3 port	
2412	9.46	9.80	5 Anbot	2.966	Net 3	Inbotek P
2437	9.40	9.80	otek 5 An	2.982		802.11g
2462	9.31	9.80	nbotek5	2.997	3.04	Anbotek
2412	9.11	9.80	nb 5 <sup>K</sup>	2.966	3	Anbotel
2437	9.44	9.80	5 otek	2.982	3	802.11n20
2462	8.93	9.80	5 nbote	2.997	3	obotek p
2422	9.05	9.80	rek 5 prit	2.972	3	nbotek
2437	bote <sup>k</sup> 9.71 Mills	9.80	botek 5	2.982	3	802.11n40
2452	9.66	9.80	5	2.991	And 3 tel	

The BLE and WiFi 2.4G cannot simultaneous transmission.

Result: No Standalone SAR test is required.

## Shenzhen Anbotek Compliance Laboratory Limited

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China. Tel:(86) 0755–26066440 Fax:(86) 0755–26014772 Email:service@anbotek.com Hotline 400-003-0500 www.anbotek.com.cn

