

TEST REPORT

Reference No...... : WTD23D02031234W003
FCC ID : 2A6P4-KEY-PHONE-LLC
Applicant..... : KEY PHONE LLC
Address..... : 816 Myrtle Ave, Brooklyn, NY US
Manufacturer : ShenZhen SongMing Communication Technology Co. Ltd
Address..... : 2 sets of No.3 Building, Geshan Road, Tangxiachong Community,
Yanlou Street Bao'an District, Shenzhen, China
Product..... : KeyPhone
Model(s) : KP523
Brand..... : KeyPhone
Standards..... : FCC 47CFR Part 15.247
Date of Receipt sample : 2023-02-27
Date of Test : 2023-02-27 to 2023-03-22
Date of Issue..... : 2023-04-18
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

James Cheng

James Cheng / Project Engineer

Approved by:



Deval Qin

Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 REVISION HISTORY.....	4
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.....	5
4.2 DETAILS OF E.U.T.....	5
4.3 CHANNEL LIST.....	6
4.4 TEST MODE	7
4.5 TEST FACILITY	8
5 TEST SUMMARY.....	9
6 EQUIPMENT USED DURING TEST.....	10
6.1 EQUIPMENTS LIST	10
6.2 DESCRIPTION OF SUPPORT UNITS.....	11
6.3 MEASUREMENT UNCERTAINTY	11
7 CONDUCTED EMISSION.....	12
7.1 E.U.T. OPERATION.....	12
7.2 EUT SETUP	12
7.3 MEASUREMENT DESCRIPTION	12
7.4 CONDUCTED EMISSION TEST RESULT	13
8 RADIATED EMISSIONS.....	17
8.1 EUT OPERATION.....	17
8.2 TEST SETUP	18
8.3 SPECTRUM ANALYZER SETUP	19
8.4 TEST PROCEDURE.....	20
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	20
8.6 SUMMARY OF TEST RESULTS.....	21
9 DUTY CYCLE.....	37
10 CONDUCTED SPURIOUS EMISSIONS.....	41
10.1 TEST PROCEDURE	41
10.2 TEST RESULT	42
11 BAND EDGE MEASUREMENT.....	58
11.1 TEST PROCEDURE	58
11.2 TEST RESULT	59
12 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT.....	64
12.1 TEST PROCEDURE:	64
12.2 TEST RESULT:	64
14 MAXIMUM PEAK CONDUCTED OUTPUT POWER	81
14.1 TEST PROCEDURE:	81
14.2 TEST RESULT:	82
15 POWER SPECTRAL DENSITY	91
15.1 TEST PROCEDURE:	91
15.2 TEST RESULT:	91
16 ANTENNA REQUIREMENT	100

17 RF EXPOSURE100

18 PHOTOGRAPHS OF TEST SETUP AND EUT.....100

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD23D02031234W003	2023-02-27	2023-02-27 to 2023-03-22	2023-04-18	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	KeyPhone
Model(s):	KP523
Model Description:	N/A
GSM Band(s):	GSM 850/1900MHz
GPRS Class:	12
WCDMA Band(s):	FDD Band II/IV/V
LTE Band(s):	FDD Band 2/4/5/12/17/66
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/ n(HT20/40)/ac(HT20/40/80)
Bluetooth Version:	Bluetooth v5.0 with BLE
GPS:	Support
Hardware Version:	Q102_MB_V1.1
Software Version:	keyphone_pk523_Q102_232_v1.0_20230109
Highest frequency (Exclude Radio):	1.3GHz
Storage Location:	Internal Storage

4.2 Details of E.U.T.

Operation Frequency:	Wi-Fi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz BLE:2402-2480MHz
Max. RF output power:	Wi-Fi(2.4G): 19.70dBm BLE: -4.636dBm
Type of Modulation:	Wi-Fi: CCK, OFDM BLE:GFSK
Antenna installation:	WiFi: internal permanent antenna BLE: internal permanent antenna
Antenna Gain:	Wi-Fi(2.4G): 2.18dBi BLE: 2.18dBi
Ratings:	Battery DC 3.8V, 2500mAh DC 5V, 1000mA, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.2A)
Adapter:	Manufacturer: SHENZHEN FUSHIGANG TECHNOLOGY CO., LTD. Model No.: AS0601A-0501000USU

4.3 Channel List

Wi-Fi

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

4.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

4.5 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

Note: All test were performed that the device transmit continue of the 100% duty cycle.

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2022-08-01	2023-07-31
2.	LISN	R&S	ENV216	100115	2022-08-01	2023-07-31
3.	Cable	Top	TYPE16(3.5M)	-	2022-08-01	2023-07-31
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2022-04-28	2023-04-27
2	Amplifier	Agilent	8447D	2944A10178	2022-08-01	2023-07-31
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2022-08-07	2023-08-06
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2022-04-28	2023-04-27
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2022-04-28	2023-04-27
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2022-07-29	2023-07-28
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2022-08-08	2023-08-07
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2022-04-28	2023-04-27
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2022-04-28	2023-04-27
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2022-10-30	2023-10-29
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2022-05-02	2023-05-01
4	Amplifier	ANRITSU	MH648A	M43381	2022-04-28	2023-04-27
5	Cable	HUBER+SUHNER	CBL2	525178	2022-04-28	2023-04-27
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSP40	100501	2022-08-01	2023-07-31
2.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2022-04-28	2023-04-27

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7 **Conducted Emission**

Test Requirement: FCC 47CFR Part 15 Section 15.207
Test Method: ANSI C63.10:2013
Test Result: PASS
Frequency Range: 150kHz to 30MHz
Class/Severity: Class B
Limit:

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 o 30	60	50


7.1 **E.U.T. Operation**

Operating Environment :
Temperature: 23.8 °C
Humidity: 35.0 % RH
Atmospheric Pressure: 101.2kPa
EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

7.2 **EUT Setup**

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



7.3 **Measurement Description**


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: Wi-Fi mode (802.11b mode low channel)

Live line:




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1500	36.97	10.33	47.30	65.99	-18.69	QP	
2	0.1500	19.04	10.33	29.37	55.99	-26.62	AVG	
3	0.2740	30.32	10.26	40.58	60.99	-20.41	QP	
4	0.2740	13.60	10.26	23.86	50.99	-27.13	AVG	
5	0.4660	26.74	10.26	37.00	56.58	-19.58	QP	
6	0.4660	20.90	10.26	31.16	46.58	-15.42	AVG	
7	0.5060	29.82	10.26	40.08	56.00	-15.92	QP	
8	0.5060	18.55	10.26	28.81	46.00	-17.19	AVG	
9	1.5060	20.32	10.36	30.68	56.00	-25.32	QP	
10	1.5060	10.14	10.36	20.50	46.00	-25.50	AVG	
11	4.8580	18.34	10.52	28.86	56.00	-27.14	QP	
12	4.8580	5.88	10.52	16.40	46.00	-29.60	AVG	

Neutral line:




Worst Mode: BLE mode (low channel)

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1580	36.01	10.32	46.33	65.56	-19.23	QP	
2	0.1580	23.78	10.32	34.10	55.56	-21.46	AVG	
3	0.2700	29.25	10.26	39.51	61.12	-21.61	QP	
4	0.2700	18.38	10.26	28.64	51.12	-22.48	AVG	
5	0.3899	27.60	10.25	37.85	58.06	-20.21	QP	
6	0.3899	18.10	10.25	28.35	48.06	-19.71	AVG	
7	0.4620	23.30	10.26	33.56	56.66	-23.10	QP	
8	0.4620	20.21	10.26	30.47	46.66	-16.19	AVG	
9	0.4940	28.26	10.26	38.52	56.10	-17.58	QP	
10	0.4940	18.38	10.26	28.64	46.10	-17.46	AVG	
11	0.6980	20.59	10.35	30.94	56.00	-25.06	QP	
12	0.6980	13.80	10.35	24.15	46.00	-21.85	AVG	

Neutral line:



8 Radiated Emissions

Test Requirement: FCC 47CFR Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Wi-Fi:

Test Frequency: 9KHz~30MHz

Remark: only the worst data (802.11b/g/n Low channel mode) were recorded.

Frequency	Measurement results dB μ V @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dB μ V/m @30m	Limits dB μ V/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b							
6.397	24.97	QP	21.84	40.00	6.81	29.54	-22.73
15.633	26.19	QP	21.35	40.00	7.54	29.54	-22.00
26.649	24.39	QP	20.67	40.00	5.06	29.54	-24.48
802.11g							
6.702	23.41	QP	21.84	40.00	5.25	29.54	-24.29
16.510	26.10	QP	21.35	40.00	7.45	29.54	-22.09
26.134	25.22	QP	20.67	40.00	5.89	29.54	-23.65
802.11n(HT20)							
7.162	24.75	QP	21.84	40.00	6.59	29.54	-22.95
15.680	26.14	QP	21.35	40.00	7.49	29.54	-22.05
26.715	24.47	QP	20.67	40.00	5.14	29.54	-24.40
802.11n(HT40)							
7.111	25.66	QP	21.84	40.00	7.50	29.54	-22.04
16.286	25.72	QP	21.35	40.00	7.07	29.54	-22.47
26.576	25.19	QP	20.67	40.00	5.86	29.54	-23.68

Test Frequency : 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
256.31	40.83	QP	301	1.1	H	-12.36	28.47	46.00	-17.53
256.31	44.19	QP	57	1.9	V	-12.36	31.83	46.00	-14.17
4824.00	52.38	PK	312	1.0	V	-1.06	51.32	74.00	-22.68
4824.00	43.11	Ave	312	1.0	V	-1.06	42.05	54.00	-11.95
7236.00	50.61	PK	334	1.3	H	1.33	51.94	74.00	-22.06
7236.00	38.41	Ave	334	1.3	H	1.33	39.74	54.00	-14.26
2324.75	46.96	PK	191	1.1	V	-13.19	33.77	74.00	-40.23
2324.75	38.55	Ave	191	1.1	V	-13.19	25.36	54.00	-28.64
2380.78	42.23	PK	110	1.8	H	-13.14	29.09	74.00	-44.91
2380.78	37.03	Ave	110	1.8	H	-13.14	23.89	54.00	-30.11
2487.65	44.96	PK	66	1.9	V	-13.08	31.88	74.00	-42.12
2487.65	37.35	Ave	66	1.9	V	-13.08	24.27	54.00	-29.73

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
256.31	40.21	QP	218	1.4	H	-12.36	27.85	46.00	-18.15
256.31	45.40	QP	79	1.3	V	-12.36	33.04	46.00	-12.96
4874.00	52.14	PK	8	1.7	V	-0.62	51.52	74.00	-22.48
4874.00	41.70	Ave	8	1.7	V	-0.62	41.08	54.00	-12.92
7311.00	50.06	PK	130	1.6	H	2.21	52.27	74.00	-21.73
7311.00	39.22	Ave	130	1.6	H	2.21	41.43	54.00	-12.57
2316.32	46.75	PK	149	1.5	V	-13.19	33.56	74.00	-40.44
2316.32	39.23	Ave	149	1.5	V	-13.19	26.04	54.00	-27.96
2374.29	42.84	PK	360	1.2	H	-13.14	29.70	74.00	-44.30
2374.29	36.75	Ave	360	1.2	H	-13.14	23.61	54.00	-30.39
2484.95	44.33	PK	339	1.8	V	-13.08	31.25	74.00	-42.75
2484.95	37.70	Ave	339	1.8	V	-13.08	24.62	54.00	-29.38

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
256.31	41.36	QP	133	1.3	H	-12.36	29.00	46.00	-17.00
256.31	46.26	QP	28	1.8	V	-12.36	33.90	46.00	-12.10
4924.00	52.69	PK	26	1.7	V	-0.24	52.45	74.00	-21.55
4924.00	41.32	Ave	26	1.7	V	-0.24	41.08	54.00	-12.92
7386.00	49.97	PK	256	1.2	H	2.84	52.81	74.00	-21.19
7386.00	38.53	Ave	256	1.2	H	2.84	41.37	54.00	-12.63
2340.79	46.47	PK	203	1.9	V	-13.19	33.28	74.00	-40.72
2340.79	38.19	Ave	203	1.9	V	-13.19	25.00	54.00	-29.00
2389.72	43.88	PK	249	1.7	H	-13.14	30.74	74.00	-43.26
2389.72	36.17	Ave	249	1.7	H	-13.14	23.03	54.00	-30.97
2494.18	43.24	PK	330	2.0	V	-13.08	30.16	74.00	-43.84
2494.18	38.57	Ave	330	2.0	V	-13.08	25.49	54.00	-28.51

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
256.31	41.24	QP	346	1.6	H	-12.36	28.88	46.00	-17.12
256.31	46.03	QP	182	1.6	V	-12.36	33.67	46.00	-12.33
4824.00	53.40	PK	114	1.5	V	-1.06	52.34	74.00	-21.66
4824.00	42.08	Ave	114	1.5	V	-1.06	41.02	54.00	-12.98
7236.00	49.94	PK	151	1.7	H	1.33	51.27	74.00	-22.73
7236.00	39.11	Ave	151	1.7	H	1.33	40.44	54.00	-13.56
2335.45	45.95	PK	113	1.6	V	-13.19	32.76	74.00	-41.24
2335.45	39.76	Ave	113	1.6	V	-13.19	26.57	54.00	-27.43
2368.22	42.63	PK	228	1.1	H	-13.14	29.49	74.00	-44.51
2368.22	36.47	Ave	228	1.1	H	-13.14	23.33	54.00	-30.67
2488.39	43.33	PK	230	2.0	V	-13.08	30.25	74.00	-43.75
2488.39	38.85	Ave	230	2.0	V	-13.08	25.77	54.00	-28.23

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
256.31	40.02	QP	341	1.7	H	-12.36	27.66	46.00	-18.34
256.31	45.92	QP	27	1.1	V	-12.36	33.56	46.00	-12.44
4874.00	52.36	PK	230	1.9	V	-0.62	51.74	74.00	-22.26
4874.00	43.34	Ave	230	1.9	V	-0.62	42.72	54.00	-11.28
7311.00	48.96	PK	266	1.4	H	2.21	51.17	74.00	-22.83
7311.00	38.70	Ave	266	1.4	H	2.21	40.91	54.00	-13.09
2312.68	46.29	PK	49	1.5	V	-13.19	33.10	74.00	-40.90
2312.68	39.98	Ave	49	1.5	V	-13.19	26.79	54.00	-27.21
2377.70	44.79	PK	57	1.3	H	-13.14	31.65	74.00	-42.35
2377.70	37.59	Ave	57	1.3	H	-13.14	24.45	54.00	-29.55
2495.09	42.07	PK	65	1.5	V	-13.08	28.99	74.00	-45.01
2495.09	36.16	Ave	65	1.5	V	-13.08	23.08	54.00	-30.92

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
256.31	39.08	QP	331	1.1	H	-12.36	26.72	46.00	-19.28
256.31	45.85	QP	12	1.8	V	-12.36	33.49	46.00	-12.51
4924.00	52.93	PK	141	1.6	V	-0.24	52.69	74.00	-21.31
4924.00	43.32	Ave	141	1.6	V	-0.24	43.08	54.00	-10.92
7386.00	49.29	PK	41	1.9	H	2.84	52.13	74.00	-21.87
7386.00	39.89	Ave	41	1.9	H	2.84	42.73	54.00	-11.27
2349.08	45.83	PK	276	1.6	V	-13.19	32.64	74.00	-41.36
2349.08	39.85	Ave	276	1.6	V	-13.19	26.66	54.00	-27.34
2355.66	42.85	PK	261	1.1	H	-13.14	29.71	74.00	-44.29
2355.66	37.48	Ave	261	1.1	H	-13.14	24.34	54.00	-29.66
2487.07	43.46	PK	339	1.7	V	-13.08	30.38	74.00	-43.62
2487.07	38.22	Ave	339	1.7	V	-13.08	25.14	54.00	-28.86

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Low Channel 2412MHz									
256.31	39.71	QP	217	1.0	H	-12.36	27.35	46.00	-18.65
256.31	47.08	QP	332	1.8	V	-12.36	34.72	46.00	-11.28
4824.00	52.61	PK	55	1.3	V	-1.06	51.55	74.00	-22.45
4824.00	44.03	Ave	55	1.3	V	-1.06	42.97	54.00	-11.03
7236.00	49.20	PK	104	1.7	H	1.33	50.53	74.00	-23.47
7236.00	40.51	Ave	104	1.7	H	1.33	41.84	54.00	-12.16
2323.77	46.25	PK	172	1.1	V	-13.19	33.06	74.00	-40.94
2323.77	39.94	Ave	172	1.1	V	-13.19	26.75	54.00	-27.25
2352.96	44.60	PK	211	2.0	H	-13.14	31.46	74.00	-42.54
2352.96	37.53	Ave	211	2.0	H	-13.14	24.39	54.00	-29.61
2496.87	42.67	PK	272	1.6	V	-13.08	29.59	74.00	-44.41
2496.87	38.82	Ave	272	1.6	V	-13.08	25.74	54.00	-28.26

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Middle Channel 2437MHz									
256.31	39.89	QP	33	1.1	H	-12.36	27.53	46.00	-18.47
256.31	47.81	QP	291	1.5	V	-12.36	35.45	46.00	-10.55
4874.00	51.11	PK	235	1.6	V	-0.62	50.49	74.00	-23.51
4874.00	44.64	Ave	235	1.6	V	-0.62	44.02	54.00	-9.98
7311.00	50.17	PK	33	1.5	H	2.21	52.38	74.00	-21.62
7311.00	39.91	Ave	33	1.5	H	2.21	42.12	54.00	-11.88
2313.98	45.80	PK	33	1.8	V	-13.19	32.61	74.00	-41.39
2313.98	39.26	Ave	33	1.8	V	-13.19	26.07	54.00	-27.93
2360.37	42.69	PK	252	1.3	H	-13.14	29.55	74.00	-44.45
2360.37	38.77	Ave	252	1.3	H	-13.14	25.63	54.00	-28.37
2486.02	42.61	PK	339	1.2	V	-13.08	29.53	74.00	-44.47
2486.02	37.83	Ave	339	1.2	V	-13.08	24.75	54.00	-29.25

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: High Channel 2462MHz									
256.31	39.98	QP	87	1.5	H	-12.36	27.62	46.00	-18.38
256.31	47.12	QP	234	1.1	V	-12.36	34.76	46.00	-11.24
4924.00	49.61	PK	184	1.7	V	-0.24	49.37	74.00	-24.63
4924.00	43.40	Ave	184	1.7	V	-0.24	43.16	54.00	-10.84
7386.00	50.71	PK	351	1.9	H	2.84	53.55	74.00	-20.45
7386.00	40.51	Ave	351	1.9	H	2.84	43.35	54.00	-10.65
2311.59	45.01	PK	195	1.4	V	-13.19	31.82	74.00	-42.18
2311.59	38.35	Ave	195	1.4	V	-13.19	25.16	54.00	-28.84
2365.63	44.77	PK	288	1.3	H	-13.14	31.63	74.00	-42.37
2365.63	38.81	Ave	288	1.3	H	-13.14	25.67	54.00	-28.33
2490.78	42.61	PK	254	1.6	V	-13.08	29.53	74.00	-44.47
2490.78	38.94	Ave	254	1.6	V	-13.08	25.86	54.00	-28.14

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Low Channel 2422MHz									
256.31	40.89	QP	101	1.3	H	-12.36	28.53	46.00	-17.47
256.31	48.24	QP	284	1.2	V	-12.36	35.88	46.00	-10.12
4844.00	47.34	PK	17	1.1	V	-1.06	46.28	74.00	-27.72
4844.00	41.07	Ave	17	1.1	V	-1.06	40.01	54.00	-13.99
7266.00	47.94	PK	326	1.7	H	1.33	49.27	74.00	-24.73
7266.00	39.14	Ave	326	1.7	H	1.33	40.47	54.00	-13.53
2325.11	46.12	PK	98	1.2	V	-13.19	32.93	74.00	-41.07
2325.11	39.17	Ave	98	1.2	V	-13.19	25.98	54.00	-28.02
2367.08	44.84	PK	311	1.2	H	-13.14	31.70	74.00	-42.30
2367.08	38.33	Ave	311	1.2	H	-13.14	25.19	54.00	-28.81
2496.31	44.91	PK	228	1.9	V	-13.08	31.83	74.00	-42.17
2496.31	38.98	Ave	228	1.9	V	-13.08	25.90	54.00	-28.10

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Middle Channel 2437MHz									
256.31	41.71	QP	116	1.1	H	-12.36	29.35	46.00	-16.65
256.31	48.50	QP	257	1.2	V	-12.36	36.14	46.00	-9.86
4874.00	47.77	PK	325	1.5	V	-0.62	47.15	74.00	-26.85
4874.00	41.27	Ave	325	1.5	V	-0.62	40.65	54.00	-13.35
7311.00	47.11	PK	348	1.7	H	2.21	49.32	74.00	-24.68
7311.00	38.26	Ave	348	1.7	H	2.21	40.47	54.00	-13.53
2320.41	46.91	PK	20	1.9	V	-13.19	33.72	74.00	-40.28
2320.41	38.11	Ave	20	1.9	V	-13.19	24.92	54.00	-29.08
2369.66	42.50	PK	175	1.1	H	-13.14	29.36	74.00	-44.64
2369.66	37.33	Ave	175	1.1	H	-13.14	24.19	54.00	-29.81
2492.71	44.84	PK	80	2.0	V	-13.08	31.76	74.00	-42.24
2492.71	38.53	Ave	80	2.0	V	-13.08	25.45	54.00	-28.55

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: High Channel 2452MHz									
256.31	41.02	QP	287	1.1	H	-12.36	28.66	46.00	-17.34
256.31	48.93	QP	340	1.3	V	-12.36	36.57	46.00	-9.43
4904.00	47.94	PK	197	1.8	V	-0.24	47.70	74.00	-26.30
4904.00	40.85	Ave	197	1.8	V	-0.24	40.61	54.00	-13.39
7356.00	46.37	PK	236	1.8	H	2.84	49.21	74.00	-24.79
7356.00	39.05	Ave	236	1.8	H	2.84	41.89	54.00	-12.11
2315.40	45.75	PK	108	1.4	V	-13.19	32.56	74.00	-41.44
2315.40	37.42	Ave	108	1.4	V	-13.19	24.23	54.00	-29.77
2389.49	44.80	PK	157	1.2	H	-13.14	31.66	74.00	-42.34
2389.49	38.95	Ave	157	1.2	H	-13.14	25.81	54.00	-28.19
2494.21	44.38	PK	51	1.9	V	-13.08	31.30	74.00	-42.70
2494.21	36.35	Ave	51	1.9	V	-13.08	23.27	54.00	-30.73

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:**Test Frequency: 9KHz~26MHz**

Remark: only the worst data (GFSK modulation Low channel mode) were recorded.

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
6.573	24.88	QP	21.84	40.00	6.72	29.54	-22.82
15.650	25.88	QP	21.35	40.00	7.23	29.54	-22.31
26.389	25.38	QP	20.67	40.00	6.05	29.54	-23.49

Test Frequency : 26MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2402MHz									
275.62	35.05	QP	151	1.4	H	-13.35	21.70	46.00	-24.30
275.62	40.92	QP	200	1.9	V	-13.35	27.57	46.00	-18.43
4804.00	49.17	PK	43	1.6	V	-1.06	48.11	74.00	-25.89
4804.00	42.09	Ave	43	1.6	V	-1.06	41.03	54.00	-12.97
7206.00	46.11	PK	203	1.2	H	1.33	47.44	74.00	-26.56
7206.00	36.85	Ave	203	1.2	H	1.33	38.18	54.00	-15.82
2320.83	45.35	PK	301	1.9	V	-13.19	32.16	74.00	-41.84
2320.83	39.53	Ave	301	1.9	V	-13.19	26.34	54.00	-27.66
2359.00	43.41	PK	253	1.3	H	-13.14	30.27	74.00	-43.73
2359.00	36.20	Ave	253	1.3	H	-13.14	23.06	54.00	-30.94
2484.04	44.16	PK	93	1.7	V	-13.08	31.08	74.00	-42.92
2484.04	37.14	Ave	93	1.7	V	-13.08	24.06	54.00	-29.94

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
GFSK Middle Channel 2440MHz									
275.62	35.27	QP	100	1.8	H	-13.35	21.92	46.00	-24.08
275.62	39.97	QP	138	1.6	V	-13.35	26.62	46.00	-19.38
4880.00	43.46	PK	37	1.0	V	-0.62	42.84	74.00	-31.16
4880.00	43.56	Ave	37	1.0	V	-0.62	42.94	54.00	-11.06
7320.00	45.13	PK	44	1.1	H	2.21	47.34	74.00	-26.66
7320.00	35.94	Ave	44	1.1	H	2.21	38.15	54.00	-15.85
2343.91	45.90	PK	67	1.9	V	-13.19	32.71	74.00	-41.29
2343.91	37.40	Ave	67	1.9	V	-13.19	24.21	54.00	-29.79
2374.67	45.00	PK	248	1.8	H	-13.14	31.86	74.00	-42.14
2374.67	36.31	Ave	248	1.8	H	-13.14	23.17	54.00	-30.83
2498.85	43.35	PK	236	1.9	V	-13.08	30.27	74.00	-43.73
2498.85	38.25	Ave	236	1.9	V	-13.08	25.17	54.00	-28.83

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
GFSK High Channel 2480MHz									
275.62	35.98	QP	288	1.4	H	-13.35	22.63	46.00	-23.37
275.62	38.46	QP	59	1.5	V	-13.35	25.11	46.00	-20.89
4960.00	43.97	PK	123	1.4	V	-0.24	43.73	74.00	-30.27
4960.00	44.08	Ave	123	1.4	V	-0.24	43.84	54.00	-10.16
7440.00	44.61	PK	120	2.0	H	2.84	47.45	74.00	-26.55
7440.00	36.29	Ave	120	2.0	H	2.84	39.13	54.00	-14.87
2319.52	45.58	PK	347	1.9	V	-13.19	32.39	74.00	-41.61
2319.52	39.45	Ave	347	1.9	V	-13.19	26.26	54.00	-27.74
2388.34	44.07	PK	219	1.4	H	-13.14	30.93	74.00	-43.07
2388.34	38.73	Ave	219	1.4	H	-13.14	25.59	54.00	-28.41
2494.52	42.52	PK	97	1.0	V	-13.08	29.44	74.00	-44.56
2494.52	38.69	Ave	97	1.0	V	-13.08	25.61	54.00	-28.39

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

9 Duty Cycle


Modulation	On time(ms)	Period(ms)	Duty Cycle(%)	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	8.38	8.46	99.05	0.04	-0.08
802.11g	1.38	1.44	95.83	0.18	-0.37
802.11n20	1.296	1.356	95.58	0.20	-0.39
802.11n40	0.648	0.700	92.57	0.34	-0.67
BLE	0.284	0.632	44.9	-16.52	33.04

Remark:

- 1) Duty Cycle=On Time/Period
- 2) Duty Cycle Factor= $10 \cdot \log(1/\text{Duty cycle})$
- 3) Average Factor= $20 \log_{10} \text{Duty Cycle}$


Test Plot

802.11b




Date: 9.MAR.2023 10:40:23


802.11g




Date: 9.MAR.2023 10:39:06



Date: 9.MAR.2023 10:37:42



Date: 9.MAR.2023 10:36:24



Date: 18.APR.2023 14:39:28

10 Conducted Spurious Emissions

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to _ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW _ [3 × RBW].
 - e) Detector = peak.
 - f) Sweep time = auto couple.
 - g) Trace mode = max hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.


Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

10.2 Test Result

9KHz – 30MHz


802.11b

Low Channel




Date: 9.MAR.2023 11:11:31


Middle Channel




Date: 9.MAR.2023 11:15:24




Date: 9.MAR.2023 11:16:50



Date: 9.MAR.2023 11:19:21




Date: 9.MAR.2023 11:20:51



Date: 9.MAR.2023 11:22:05


802.11n HT20

Low Channel




Date: 9.MAR.2023 11:25:16

Middle Channel




Date: 9.MAR.2023 11:27:58




Date: 9.MAR.2023 11:29:48


802.11n HT40



Date: 9.MAR.2023 11:31:13




Date: 9.MAR.2023 11:34:34



Date: 9.MAR.2023 11:35:43


BLE

Low Channel




Date: 8.MAR.2023 09:22:01

Middle Channel



Date: 8.MAR.2023 09:31:44




Date: 8.MAR.2023 09:34:16

Above 30MHz

802.11b

Low Channel


Fundamental



Date: 9.MAR.2023 11:14:50

Middle Channel


Fundamental



Date: 9.MAR.2023 11:16:12

High Channel

Fundamental




Date: 9.MAR.2023 11:17:37



802.11g

Low Channel

Fundamental




Date: 9.MAR.2023 11:20:11




802.11n HT20

Low Channel



Date: 9.MAR.2023 11:27:25


Middle Channel



Date: 9.MAR.2023 11:29:24

High Channel

Fundamental




Date: 9.MAR.2023 11:30:37



802.11n HT40

Low Channel

Fundamental




Date: 9.MAR.2023 11:34:02




BLE

Fundamental




Date: 8.MAR.2023 09:24:24

Fundamental



Date: 8.MAR.2023 09:33:41



Date: 8.MAR.2023 09:37:15

11 Band Edge Measurement

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

Test Limit: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


Test Mode: Transmitting

11.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result

Test result plots shown as follows:




Date: 9.MAR.2023 10:12:54




Date: 9.MAR.2023 10:14:57

TX 11g: Band edge-left side




Date: 9.MAR.2023 10:17:23


TX 11g: Band edge-right side




Date: 9.MAR.2023 10:20:07




Date: 9.MAR.2023 10:24:41




Date: 9.MAR.2023 10:29:52




Date: 9.MAR.2023 10:34:23



Date: 9.MAR.2023 10:32:36



Date: 8.MAR.2023 09:16:53



Date: 8.MAR.2023 09:19:33

12 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

12.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. 6dB Bandwidth Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz
99% Bandwidth Set the spectrum analyzer : RBW = 1~5% DTS OBW, VBW = 3 RBW


12.2 Test Result:

13	Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b		Channel 1	7.555	12.226
		Channel 6	8.560	13.686
		Channel 11	7.076	12.026
TX 11g		Channel 1	13.80	16.198
		Channel 6	16.02	16.820
		Channel 11	12.60	16.100
TX 11n HT20		Channel 1	13.80	17.330
		Channel 6	16.86	17.917
		Channel 11	12.61	17.225
TX 11n HT40		Channel 3	22.59	35.973
		Channel 6	36.10	36.898
		Channel 9	23.79	35.456
BLE		Channel 0	0.678	1.038
		Channel 19	0.678	1.044
		Channel 39	0.678	1.044


Test result plot:

6dB Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9






Date: 8.MAR.2023 08:46:53




Date: 8.MAR.2023 08:52:30




Date: 8.MAR.2023 08:54:01

99% Bandwidth


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9






Date: 8.MAR.2023 08:43:27



Date: 8.MAR.2023 08:41:43



Date: 8.MAR.2023 08:40:41

14 Maximum Peak conducted Output Power

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013

14.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019

section 8.3.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq DTS$ bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set span $\geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 8.3.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1\%$ to 5% of the OBW, not to exceed 1 MHz..
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the span $\geq 1.5 \times OBW$.
- d) Detector = RMS.
- e) Sweep time = auto couple.
- f) trigger = free run..
- g) Number of points in sweep $\geq [2 \times \text{span} / RBW]$. (This gives bin-to-bin spacing $\leq RBW / 2$, so that narrowband signals are not lost between frequency bins.)
- h) Trace average at least 100 traces in power averaging (rms) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum..

14.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	17.59	1W/30dBm
	Middle-2437	17.23	1W/30dBm
	High-2462	17.45	1W/30dBm
TX 11g	Low-2412	19.70	1W/30dBm
	Middle-2437	19.24	1W/30dBm
	High-2462	19.57	1W/30dBm
TX 11n HT20	Low-2412	19.44	1W/30dBm
	Middle-2437	19.04	1W/30dBm
	High-2462	19.36	1W/30dBm
TX 11n HT40	Low-2422	18.82	1W/30dBm
	Middle-2437	18.46	1W/30dBm
	High-2452	18.52	1W/30dBm
BLE	Low-2402	-4.636	1W/30dBm
	Middle-2440	-5.925	1W/30dBm
	High-2480	-5.623	1W/30dBm

Test Plot


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19



BLE: channel 39



15 Power Spectral density

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019;
ANSI C63.10:2013


15.1 Test Procedure:

KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019 section 10.2


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

15.2 Test Result:


Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-13.35	8dBm per 3kHz
	Middle-2437	-14.51	8dBm per 3kHz
	High-2462	-12.66	8dBm per 3kHz
TX 11g	Low-2412	-18.10	8dBm per 3kHz
	Middle-2437	-19.22	8dBm per 3kHz
	High-2462	-17.93	8dBm per 3kHz
TX 11n HT20	Low-2412	-18.49	8dBm per 3kHz
	Middle-2437	-20.15	8dBm per 3kHz
	High-2462	-18.31	8dBm per 3kHz
TX 11n HT40	Low-2422	-22.77	8dBm per 3kHz
	Middle-2437	-24.23	8dBm per 3kHz
	High-2452	-22.21	8dBm per 3kHz
BLE	Low-2402	-21.96	8dBm per 3kHz
	Middle-2440	-23.24	8dBm per 3kHz
	High-2480	-22.43	8dBm per 3kHz




Date: 9.MAR.2023 10:41:48




Date: 9.MAR.2023 10:42:34




Date: 9.MAR.2023 10:43:21



Date: 9.MAR.2023 11:01:04




Date: 9.MAR.2023 11:03:03




Date: 9.MAR.2023 11:03:53

Mode: TX 11n HT20 channel 1




Date: 9.MAR.2023 11:07:22


Mode: TX 11n HT20 channel 6




Date: 9.MAR.2023 11:06:12




Date: 9.MAR.2023 11:06:46




Date: 9.MAR.2023 11:08:19




Date: 9.MAR.2023 11:09:27




Date: 9.MAR.2023 11:10:04



Date: 8.MAR.2023 09:08:38



Date: 8.MAR.2023 09:13:01



Date: 8.MAR.2023 09:13:45

16 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

17 RF Exposure

Remark: refer to SAR test report: WTD23X02031284W.

18 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-KP523-Photos.

=====End of Report=====