

RF Exposure Evaluation Report

FCC ID : 2A6PM-UA2-TMM-V2
Equipment : TrioMobil UA Module
Brand Name : TRIO MOBIL
Model Name : UA2-TMM-V2
Applicant : TRIO MOBIL INC
1401 PENNSYLVANIA AVE STE 105
WILMINGTON DELAWARE United States 19806
Manufacturer : TRIO MOBIL INC
1401 PENNSYLVANIA AVE STE 105
WILMINGTON DELAWARE United States 19806
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Mar. 28, 2022, and testing was started from May 21, 2022 and completed on Jul. 20, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB 447498 D04 Interim General RF Exposure Guidance v01 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

Table of Contents

1. General Description.....	4
1.1. EUT General Information	4
1.2. Antenna Information.....	4
1.3. Table for Permissive Change	4
1.4. Testing Location Information	4
2. RF Exposure Evaluation	5
2.1. Applicable Standard.....	5
2.2. RF Exposure Exempt Measurement.....	5
2.3. Multiple RF Sources Exposure	6
2.4. SAR evaluation	6

Photographs of EUT V01



History of This Test Report

Reviewed by: Sam Tsai

Report Producer: Jenny Yang

1. General Description

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Ultra Wide Band	3100-10600	3494.4 3993.6	BPSK

1.2. Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	Taiyo Yuden	AH086M555003-T	Multilayer Monopole	Surface Mount

Ant.	Port	Gain (dBi)	
		3494.4MHz	3993.6MHz
1	1	2.3	2.6

For UWB function:

Ant. 1 (port 1) could transmit/receive.

1.3. Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA212662
 Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Add host (Brand: TRIO MOBIL, Model: UA2-PSC-V2)	
Add bat charger(U5), accelerometer (U4) ,vibration motor driver circuit (Q6) and SOS button circuit components	Photographs of EUT was updated

1.4. Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	
Test site Designation No. TW3785 with FCC.		
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	TEL: 886-3-327-0973
Test site Designation No. TW0008 with FCC.		

2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10}\left(\frac{60}{ERP_{20cm} \sqrt{f}}\right) \text{ and f is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83 R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2 R^2 \end{cases}$ <p>f is in MHz; R is in m; $R > \lambda / 2\pi$</p>

2.3. Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P, including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP_j = the ERP of fixed, mobile, or portable RF source j.</p> <p>$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>$Evaluated Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>

2.4. SAR evaluation

1. Per KDB 447498 D04 Interim General RF Exposure Guidance v01,
Option (A): 1.1307(b)(3)(ii)(A): Available maximum time-averaged power is no more than 1 mW.
RF exposure evaluation is not required.

Mode	EIRP (dBm)	Gain (dBi)	Power (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL Pth (dBm)	TL Ratio
UWB;Ch1	-13.99	2.30	-16.29	0.50	-13.49	0.50	0.01425	1.00	A	0.00	0.0264
UWB;Ch2	-13.14	2.60	-15.74	0.50	-12.64	0.50	0.01732	1.00	A	0.00	0.0299

Note: EIRP = PSD-AV * OBW

THE END