

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 1 of 54

Applicant : PETKIT Network Technology (Shanghai) Co., Ltd.
Address of Applicant : Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai

Product Name : PETKIT PUROBOT MAX PRO WITH CAMERA
SELF-CLEANING CAT LITTER BOX

Brand Name : PETKIT

Model Name : P9904

Sample Acquisition Method : Sent by Client

Sample No. : E24080036-01#13
E24080036-01#14

FCC ID : 2A72N-P9904

Standards : FCC CFR47 Part 15.407, Subpart E

Date of Receipt : 2024-09-03

Date of Test : 2024-09-04~ 2024-09-26

Date of Issue : 2024-09-27

Remark:

This report details the results of the testing carried out on one sample, the results contained in this report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

Prepared by: Erik Yang
(Erik Yang)

Reviewed by: Jennifer Zhou
(Jennifer Zhou)

Approved by: Echo Mu
(Authorized signatory: Echo Mu)

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 2 of 54

Contents

1	GENERAL INFORMATION	3
1.1	TESTING LABORATORY	3
1.2	DETAILS OF APPLICATION	3
1.3	DETAILS OF EUT	3
1.4	TEST METHODOLOGY	4
1.5	TEST SUMMARY	5
2	TEST CONDITION	6
2.1	ENVIRONMENTAL CONDITIONS	6
2.2	EQUIPMENT LIST	6
2.3	MEASUREMENT UNCERTAINTY	7
3	TEST SET-UP AND OPERATION MODES	8
3.1	DETAILS OF TEST MODE	8
3.2	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
3.3	SUPPORT SOFTWARE	9
3.4	TEST SETUP DIAGRAM	9
4	TEST RESULTS	11
4.1	TRANSMITTER REQUIREMENT & TEST SUITES	11
4.1.1	<i>Antenna Requirement</i>	11
4.1.2	<i>Maximum Conducted Output Power</i>	12
4.1.3	<i>26dB Bandwidth and 99% Bandwidth</i>	13
4.1.4	<i>6dB Bandwidth and 99% Bandwidth</i>	17
4.1.5	<i>Maximum Conducted Output Power Spectral Density</i>	24
4.1.6	<i>Conducted Spurious Emission</i>	25
4.1.7	<i>Radiated Emission</i>	26
4.1.8	<i>Band Edge (Restricted-band band-edge)</i>	27
4.1.9	<i>Frequency Stability</i>	28
4.2	MAINS EMISSIONS	30
4.2.1	<i>Conducted Emission on AC Mains</i>	30
5	APPENDIXES	33
5.1	PHOTOGRAPHS OF THE SAMPLE	33
5.2	ANTENNA POSITION SET-UP FOR CONDUCTED EMISSIONS	53
5.3	SET-UP FOR CONDUCTED RF TEST AT ANTENNA PORT	53
5.4	SET-UP FOR SPURIOUS EMISSIONS BELOW 1GHZ	54
5.5	SET-UP FOR SPURIOUS EMISSIONS ABOVE 1GHZ	54

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 3 of 54

1 General Information

1.1 Testing Laboratory

Company Name	ICAS Testing Technology Service (Shanghai) Co., Ltd
Address	No.1298, Pingan Road, Minhang District, Shanghai, China
Telephone	0086 21-51682999
Fax	0086 21-54711112
Homepage	www.icasiso.com

1.2 Details of Application

Applicant Company Name	PETKIT Network Technology (Shanghai) Co., Ltd.
Address	Room 4139, Building 2, 588 Zixing Road, Minhang District, Shanghai
Contact Person	TingHe
Telephone	+86 13916991059
Email	ting.he@petkit.com
Manufacturer Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.
Factory Company Name	Dongguan Zhihang Electronic Technology Co., LTD.
Address	Room 701, Building 15, No.1, Pushi Road I, Qiaotou Town, Dongguan City,Guangdong Province, China.

1.3 Details of EUT

Product Name	PETKIT PUROBOT MAX PRO WITH CAMERA SELF-CLEANING CAT LITTER BOX
Brand Name	PETKIT
Test Model Name	P9904
FCC ID	2A72N-P9904
Mode of Operation	WLAN 802.11a/n(HT20)
Operation Frequency	Band I:5150MHz~5250MHz; Band IV: 5725MHz ~ 5850MHz
Modulation Type	OFDM(BPSK/QPSK/16-QAM/64-QAM)
Number of Channels	8
Channel Bandwidth	802.11a: 20MHz 802.11n: 20MHz
Antenna Type	Internal Antenna
Antenna Gain	3.90dBi
Extreme Temperature Range	0°C~ +40°C
Test Voltage	AC 120V 60Hz

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 4 of 54

Extreme Voltage	Low Voltage: AC 100V High Voltage: AC 240V
Product Type	Mobile for FCC standard
Wi-Fi Hardware Version	V4.0
Software Version	2.49
RF power setting in TEST SW	Band I: SecureCRT Version 7.0.4 and rtwpriv command Power setting patha=86 Band IV: SecureCRT Version 7.0.4 and rtwpriv command Power setting patha=72

Note:

1. The above information was declared by the manufacture.
2. The EUT is designed as master device.
3. The EUT do not support TPC.
4. For more details, please refer to the User's manual of the EUT.

Channel List

Frequency Band	Channel Number	Frequency
Band I: 5150MHz ~ 5250MHz	36	5180 MHz
	40	5200 MHz
	44	5220 MHz
	48	5240 MHz
Band IV: 5725MHz ~ 5850MHz	149	5745 MHz
	153	5765 MHz
	157	5785 MHz
	165	5825 MHz

Note: For 20MHz bandwidth system use Channel 36,44,48,149,157,165

1.4 Test Methodology

47 CFR Part 15, Subpart E	Subpart E—Unlicensed National Information Infrastructure Devices
KDB Publication 789033 D02 v02r01	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E
ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Note(s):

All test items were verified and recorded according to the standards and without any addition/deviation/exclusion during the test

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 5 of 54

1.5 Test Summary

Test Item	FCC Rules	Result
Antenna Requirement	FCC Part 15.407(a), 15.203	PASS
Maximum Conducted Output Power	FCC Part 15.407(a)	PASS
26dB Bandwidth and 99% Bandwidth	FCC Part 15.407(a)	PASS
6dB Bandwidth	FCC Part 15.407(e)	PASS
Maximum Conducted Output Power Spectral Density	FCC Part 15.407(a)	PASS
Conducted Spurious Emission	FCC Part 15.407(b), 15.209	PASS
Radiated Emission	FCC Part 15.407(b), 15.209, 15.205	PASS
Band Edge (Restricted-band band-edge)	FCC Part 15.407(b), 15.205, 15.209	PASS
Frequency Stability	FCC Part 15.407(g)	PASS
Conducted Emission on AC Mains	FCC Part 15.207(a)	PASS

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 6 of 54

2 Test Condition

2.1 Environmental conditions

Temperature (°C)	18-25
Humidity (%RH)	40-65
Barometric Pressure (mbar)	960-1060

2.2 Equipment List

Name of Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020B	MY59260184	2024-06-26	2025-06-25
Spectrum Analyzer	Rohde & Schwarz	FSV40N	101450	2024-06-04	2025-06-03
Signal Generator	Rohde & Schwarz	SMR27	100184	2024-06-26	2025-06-25
EMI Test Receiver	Rohde & Schwarz	ESPI3	100173	2024-06-05	2025-06-04
EMI Test Receiver	Rohde & Schwarz	ESR 7	101911	2024-06-04	2025-06-03
V-network	SCHWARZBECK	NSLK 8127	8127-902	2024-06-05	2025-06-04
Attenuator	SCHWARZBECK	VTSD 9561-FN	/	2024-06-05	2025-06-04
Broadband Antenna	SCHWARZBECK	VULB9163	9163-1037	2023-03-22	2025-03-21
Horn Antenna-18G	SCHWARZBECK	BBHA9120D	9120D-1775	2023-06-13	2025-06-12
Loop Antenna	SCHWARZBECK	FMZB 1513	/	2023-06-09	2025-06-08
Horn Antenna-40G	YINGLIAN	LB-180400-KF	N/A	2023-06-18	2025-06-17
Broadband Preamplifier	SCHWARZBECK	BBV 9718	346	2024-06-04	2025-06-03
Temperature Box	ESPEC	ECT-2	055239A	2023-11-09	2024-11-08
DC Power Supply	ITECH	IT6952A	N/A	2024-06-27	2026-06-26
EMC chamber 9*6*6(L*W*H)	CHANGNING	966	N/A	2023-06-09	2025-06-08
Shielded Enclosure 8*5*4(L*W*H)	CHANGNING	854	N/A	2023-06-09	2025-06-08
Test Software	BL	BL410_E	Version:2.1.1.436	N/A	N/A
Test Software	BL	BL410_R	Version:2.1.1.409	N/A	N/A

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 7 of 54

2.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by CISPR and ANSI. The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95.45%.

Parameter		Uncertainty
Antenna Port Conducted Emission		$\pm 1.04\text{dB}$
Radiated Emission	< 1GHz	$\pm 5.00\text{dB}$
	> 1GHz	$\pm 5.46\text{dB}$
Conducted Emission on AC Mains	150KHz-30MHz	$\pm 3.36\text{dB}$
Occupied Channel Bandwidth		$\pm 39.26\text{KHz}$
Maximum Conducted Output Power		$\pm 1.06\text{dB}$
Maximum Conducted Output Power Spectral Density		$\pm 1.12\text{dB}$
Frequency Stability		$\pm 0.38\text{ppm}$

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 8 of 54

3 Test Set-up and Operation Modes

3.1 Details of Test Mode

Using test software was control EUT work in continuous transmitter and receiver mode. Select test channel as below:
For 802.11a/n(HT20)

Band I (5150 – 5250 MHz)		Band IV (5725 – 5850 MHz)	
Channel	Frequency	Channel	Frequency
The lowest channel(CH36)	5180MHz	The lowest channel(CH149)	5745MHz
The middle channel(CH44)	5220MHz	The middle channel(CH157)	5785MHz
The highest channel(CH48)	5240MHz	The highest channel(CH165)	5825MHz

Through Pre-scan under all rate at lowest channel, the data rate as below table described is the worst case, so we choose these data rate for test.

Type	Data rate
802.11a	54Mbps
802.11n(HT20)	MCS7

The basic operation modes are:

- A. On
 - 1. WLAN mode
 - a. Transmitting
 - b. Receiving
- B. Standby
- C. Off

3.2 Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model Name	Serial No.
AC ADAPTER	N/A	GQ24-120200-AX	Input: AC 100-240V 50/60Hz 1.0A Max; Output: DC 12V 2A
Laptop 1	HP	HP ZHAN 66 Pro G1	5CD7438R1J
Laptop 2	Lenovo	TP00083A	PF-0PRDGN
USB Cable	N/A	N/A	1.00m Unshielded

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 9 of 54

3.3 Support Software

Description	Manufacturer	Software Name
Software	N/A	SecureCRT Version 7.0.4 and rtwpriv command


3.4 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Configuration for Conduction Test



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 10 of 54

Diagram of Measurement Configuration for Transmitter Test





Diagram of Measurement Equipment Configuration for conducted output power setup



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 11 of 54

4 Test Results

4.1 Transmitter Requirement & Test Suites

4.1.1 Antenna Requirement

RESULT:

PASS

Test standard : FCC Part 15.407(a), 15.203
Requirement : An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. In addition, If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 3.90dBi. The antenna is an Internal antenna with no possibility of replacement with a non-approved antenna by the end-user.

Therefore, the EUT is considered to comply with this provision.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 12 of 54

4.1.2 Maximum Conducted Output Power

RESULT:

PASS

Test standard : FCC Part 15.407(a)
 Requirement : ANSI C63.10-2013 clause 12.3.3.1, KDB 789033
 Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
 Operation Mode : A.1.a
 Ambient temperature : 24.8°C
 Relative humidity : 43%

Table 1: Maximum Conducted Output Power for Band I (5150MHz~5250MHz)

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum Conducted Output Power		Applicable Limit
			(dBm)	(mW)	
802.11a	66.68	5180	14.23	26.49	250mW (23.98dBm)
		5220	14.24	26.55	
		5240	14.27	26.73	
802.11n(HT20)	63.39	5180	14.13	25.88	
		5220	14.27	26.73	
		5240	14.18	26.18	

Table 2: Maximum Conducted Output Power for Band IV (5725MHz~5850MHz)

Test Mode	Duty Cycle (%)	Test Channel (MHz)	Maximum Conducted Output Power		Applicable Limit
			(dBm)	(mW)	
802.11a	52.98	5745	15.35	34.28	1W(30dBm)
		5785	14.07	25.53	
		5825	13.82	24.10	
802.11n(HT20)	64.75	5745	14.72	29.65	
		5785	13.62	23.01	
		5825	12.93	19.63	

Notes: Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 13 of 54

4.1.3 26dB Bandwidth and 99% Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.407(a)
Requirement : ANSI C63.10-2013 clause 12.4, KDB 789033
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 24.8°C
Relative humidity : 43%

Table 3: 26dB Bandwidth and 99% Bandwidth for Band I (5150MHz~5250 MHz)

Test Mode	Test Channel (MHz)	26dB Bandwidth (MHz)	99% Bandwidth (MHz)
802.11a	5180	19.81	16.310
	5220	19.49	16.275
	5240	19.57	16.277
802.11n(HT20)	5180	20.17	17.412
	5220	20.22	17.383
	5240	20.28	17.407

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 14 of 54


Figure 1: 802.11a, 5180MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



Figure 2: 802.11a, 5220MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 15 of 54


Figure 3: 802.11a, 5240MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



Figure 4: 802.11n(HT20), 5180MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 16 of 54


Figure 5: 802.11n(HT20), 5220MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



Figure 6: 802.11n(HT20), 5240MHz

Test Plot of -26dB Bandwidth and 99% Bandwidth



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 17 of 54

4.1.4 6dB Bandwidth and 99% Bandwidth

RESULT:

PASS

Test standard : FCC Part 15.407(e)
Requirement : ANSI C63.10-2013 clause 12.4, KDB 789033
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 24.8°C
Relative humidity : 43%

Table 4: 6dB Bandwidth and 99% Occupied Bandwidth

Test Mode	Test Channel (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	6dB Bandwidth Applicable Limit (MHz)
802.11a	5745	16.38	16.482	>0.5
	5785	16.32	16.416	
	5825	16.14	16.437	
802.11n(HT20)	5745	16.60	17.552	
	5785	17.22	17.639	
	5825	17.50	17.536	

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 18 of 54

Figure 7: 802.11a, 5745MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 19 of 54

Figure 8: 802.11a, 5785MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 20 of 54

Figure 9: 802.11a, 5825MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 21 of 54

Figure 10: 802.11n(HT20), 5745MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 22 of 54

Figure 11: The plots of 6dB Bandwidth, 802.11n(HT20), 5785MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27


Page 23 of 54

Figure 12: The plots of 6dB Bandwidth, 802.11n(HT20), 5825MHz

Test Plot of -6dB Bandwidth



Test Plot of 99% Occupied Bandwidth



TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 24 of 54

4.1.5 Maximum Conducted Output Power Spectral Density

RESULT:

PASS

Test standard : FCC Part 15.407(a)
 Requirement : ANSI C63.10-2013 clause 12.5(SA-2), KDB 789033
 Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
 Operation Mode : A.1.a
 Ambient temperature : 24.8°C
 Relative humidity : 43%

Notes:

Test plots please refer to the annex document "SHE24080036-02DE DATA WIFI5GHz- Maximum Conducted Output Power Spectral Density EXHIBIT A"

Table 5: Maximum Conducted Output Power Spectral Density for Band I (5150MHz~5250MHz)

Test Mode	Duty Cycle	Test Channel (MHz)	Maximum PSD (dBm/MHz)	Applicable Limit (dBm/MHz)
802.11a	66.68	5180	5.75	11
		5220	6.30	
		5240	5.73	
802.11n(HT20)	55.07	5180	6.43	
		5220	6.18	
		5240	5.48	

Table 6: Maximum Conducted Output Power Spectral Density for Band IV (5725MHz~5850MHz)

Test Mode	Duty Cycle	Test Channel (MHz)	Maximum PSD (dBm/500kHz)	Applicable Limit (dBm/500kHz)
802.11a	63.59	5745	3.83	30
		5785	2.44	
		5825	2.38	
802.11n(HT20)	60.32	5745	4.92	
		5785	4.05	
		5825	3.21	

Notes: Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 25 of 54

4.1.6 Conducted Spurious Emission

RESULT:

PASS

Test standard : FCC Part 15.407(b), 15.209,
Requirement : ANSI C63.10-2013 clause 12.7.4, KDB 789033
Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 24.8°C
Relative humidity : 43%

Notes:

Test plots please refer to the annex document "SHE24080036-02DE DATA WLAN 5GHz-TX CSE EXHIBIT A".

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 26 of 54

4.1.7 Radiated Emission

RESULT:

PASS

Test standard : FCC Part 15.407(b), 15.209, 15.205
Requirement : ANSI C63.10-2013 clause 12.7.4, KDB 789033
Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/Middle/High
Operation Mode : A.1.a
Ambient temperature : 23.6°C
Relative humidity : 44%

Notes:

Test plots please refer to the annex document "SHE24080036-02DE DATA WIFI5GHZ-TX EXHIBIT A"

1. For 9 kHz ~ 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported.
2. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.
3. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.
4. Factor = Antenna Factor + Cable loss - Amplifier gain, Margin= Results-Limit.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 27 of 54

4.1.8 Band Edge (Restricted-band band-edge)

RESULT:

PASS

Test standard : FCC Part 15.407(b)
Requirement : ANSI C63.10-2013 clause 12.7.4.4, KDB 789033
Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/High
Operation Mode : A.1.a
Ambient temperature : 23.6°C
Relative humidity : 44%

Notes:

Test plots please refer to the annex document "SHE24080036-02DE DATA WIFI5GHz-TX EXHIBIT A"

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.
2. Factor = Antenna Factor + Cable loss - Amplifier gain, Margin= Results-Limit.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 28 of 54

4.1.9 Frequency Stability

RESULT:

PASS

Test standard : FCC Part 15.407(g)

Kind of test site : Shielded room

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1.a

Ambient temperature : 24.8°C

Relative humidity : 43%

Table 7: Frequency Stability

Band I (5150MHz – 5250MHz):

Voltage vs. Frequency Stability (5180MHz)

Test Conditions		Frequency (MHz)	Max. Deviation (ppm)	Limit (ppm)
Temp (°C)	Voltage (V)			
25	AC 100V	5179.990400	1.85	±20
	AC 120V	5179.990425	1.85	
	AC 240V	5179.990550	1.82	

Temperature vs. Frequency Stability (5180MHz)

Test Conditions		Frequency (MHz)	Max. Deviation (ppm)	Limit (ppm)
Voltage (V)	Temp (°C)			
AC 120V	0	5179.990575	1.82	±20
	10	5179.990625	1.81	
	20	5179.990675	1.80	
	30	5179.990775	1.78	
	40	5179.990750	1.79	

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 29 of 54

Band IV (5725MHz – 5850MHz):

Voltage vs. Frequency Stability (5745MHz)

Test Conditions		Frequency (MHz)	Max. Deviation (ppm)	Limit (ppm)
Temp (°C)	Voltage (V)			
25	AC 100V	5744.989425	1.84	±20
	AC 120V	5744.989550	1.82	
	AC 240V	5744.989675	1.80	

Temperature vs. Frequency Stability (5745MHz)

Test Conditions		Frequency (MHz)	Max. Deviation (ppm)	Limit (ppm)
Voltage (V)	Temp (°C)			
AC 120V	0	5744.989925	1.75	±20
	10	5744.990050	1.73	
	20	5744.990200	1.71	
	30	5744.990475	1.66	
	40	5744.990525	1.65	

Note: The all configurations were tested respectively, but only the worst channel shown here.

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 30 of 54

4.2 Mains Emissions

4.2.1 Conducted Emission on AC Mains

RESULT:

PASS

Test standard : FCC Part 15.207
Requirement : ANSI C63.10-2013 clause 6.2
Kind of test site : Shielded room

Test setup

Input Voltage : DC 12V supply by AC adapter (which received AC 120V, 60Hz)
Operation Mode : A.1.a
Earthing : Not Connected
Ambient temperature : 22.9°C
Relative humidity : 53%

For details refer to following test plot.

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 31 of 54

Note: The all configurations were tested respectively, but only the worst configuration shown here.

Figure 13: Conducted Emission on AC Mains, L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.164	53.37	9.85	65.26	11.89	Peak	L	Pass
1*	0.164	39.59	9.85	65.26	25.67	QP	L	Pass
1**	0.164	30.16	9.85	55.26	25.10	AV	L	Pass
2	0.374	43.48	9.88	58.41	14.93	Peak	L	Pass
2*	0.374	39.59	9.88	58.41	18.82	QP	L	Pass
2**	0.374	31.57	9.88	48.41	16.84	AV	L	Pass
3	0.738	43.25	9.90	56.00	12.75	Peak	L	Pass
3*	0.738	29.96	9.90	56.00	26.04	QP	L	Pass
3**	0.738	25.99	9.90	46.00	20.01	AV	L	Pass
4	1.752	38.28	9.76	56.00	17.72	Peak	L	Pass
4*	1.752	26.26	9.76	56.00	29.74	QP	L	Pass
4**	1.752	29.38	9.76	46.00	16.62	AV	L	Pass
5	3.918	31.74	9.77	56.00	24.26	Peak	L	Pass
5*	3.918	19.27	9.77	56.00	36.73	QP	L	Pass
5**	3.918	20.28	9.77	46.00	25.72	AV	L	Pass
6	7.956	31.88	9.69	60.00	28.12	Peak	L	Pass
6*	7.956	23.52	9.69	60.00	36.48	QP	L	Pass
6**	7.956	20.30	9.69	50.00	29.70	AV	L	Pass


TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 32 of 54

Figure 14: Conducted Emission on AC Mains, N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.154	54.66	9.98	65.78	11.12	Peak	N	Pass
1*	0.154	40.96	9.98	65.78	24.82	QP	N	Pass
1**	0.154	30.23	9.98	55.78	25.55	AV	N	Pass
2	0.368	43.26	9.99	58.55	15.29	Peak	N	Pass
2*	0.368	37.42	9.99	58.55	21.13	QP	N	Pass
2**	0.368	32.29	9.99	48.55	16.26	AV	N	Pass
3	0.910	39.03	10.02	56.00	16.97	Peak	N	Pass
3*	0.910	30.39	10.02	56.00	25.61	QP	N	Pass
3**	0.910	26.83	10.02	46.00	19.17	AV	N	Pass
4	1.350	44.94	9.91	56.00	11.06	Peak	N	Pass
4*	1.350	30.98	9.91	56.00	25.02	QP	N	Pass
4**	1.350	27.98	9.91	46.00	18.02	AV	N	Pass
5	4.476	36.63	9.78	56.00	19.37	Peak	N	Pass
5*	4.476	24.22	9.78	56.00	31.78	QP	N	Pass
5**	4.476	20.56	9.78	46.00	25.44	AV	N	Pass
6	7.304	38.00	9.80	60.00	22.00	Peak	N	Pass
6*	7.304	29.24	9.80	60.00	30.76	QP	N	Pass
6**	7.304	25.83	9.80	50.00	24.17	AV	N	Pass

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 33 of 54

5 Appendixes

5.1 Photographs of the Sample



All of the sample



Front of the sample

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 34 of 54



Rear of the sample



Left of the sample

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 35 of 54



Right of the sample




Top of the sample

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 36 of 54



Bottom of the sample




Open-1 of the sample

TEST REPORT

Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 37 of 54



Open-2 of the sample



Open-3 of the sample

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 38 of 54



Open-4 of the sample




Internal-1 of the sample

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 39 of 54



Internal-2 of the sample




Internal-3 of the sample

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 40 of 54



Internal-4 of the sample




Internal-5 of the sample

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 41 of 54



Internal-6 of the sample




Internal-7 of the sample

TEST REPORT


Report No.: SHE24080036-02DE

Date: 2024-09-27

Page 42 of 54



Internal-8 of the sample



Internal-9 of the sample