

Downloading the App



Scan the following QR code, download and install the App.

adapter or USB port on your computer.



Scan QR Code and Download

Charging and Active

To charge your device, plug the charging cable into the



The MAC address on the "Setting"-"About" page could help





you identify your device on the scanning list.





Use the Touch Screen






wear a bracelet



Close to the skin for testing

Smart Watch Features



Enter body temperature mode and The temperature was measured every day



Smart Watch Features



when using the call function, Make sure the connection

Smart Watch Features



















Smart Watch Features













Smart Watch Features







Smart Watch Features
















Getting to Know Your Device

.Using in Wet Conditions Your device is water-resistant, which means it is rain-proof and splash-proof and can stand up to even the sweatiest workout. on't hurt the device, wearing it 24/7 does not give your skin

With Quick View you can check the time or the message form

your wrist towards you and the time screen will appear for a

nance to breathe. Whenever you get your bracelet wet, dry

you bought the product.

Operating temperature: 14°F to 122°F (-10°C to 50°C) Non-operating temperature: -4°F to 140°F (-20°C to 60°C)

Fits a wrist between 5.5 and 7.7 inches in circumference.

waste and should be disposed of at your local electronic

General Info & Specifications

your phone on your Smart Bracelet without taping. Just turn

equipment collection facility. For more information, please contact your local electronic

household waste, the Smart Bracelet unit is considered electronic

Please kindly be aware that it is the consumer's responsibility to properly dispose and recycle Smart Bracelet and accompanying

equipment waste management authority or the retailer where



USER MANUAL

手表客户端下载

扫描下方二维码下载并安装手表客户端。



使用配备的磁吸充电器吸附到手表背面的金属触点,充电器 另一端接入USB充电头或者电脑USB接口即可。



手表充电与激活

切换至「设备」页面,点击「绑定设

接,在客户端数据页面下拉可以同步数据。


连接手表


打开手机客户端设置个人信息




在手表设置菜单—关于界面,将显示手表MAC地址,可以通过 设备列表中的MAC地址来确定你的设备;

手表绑定成功后,今后每次打开客户端,手表会自动与手机连











手表操作指导






手表功能简介





进行测试每天都测量温度

























手表功能简介






在使用通话功能时,在使用通话功能时,

需要确保手表与手机的连接状态稳定。







手表功能简介















手表功能简介





















手表功能简介













手表功能简介














血压数值为什么跟血压计有偏差?












(需要在手机设置中找到通知设置,开启微信、QQ、电话、短信、 分支流动;血管紧张感增加,将使上下血压测量值偏差会更大。 手机客户端的通知开关)



3.打开手环客户端的辅助功能设置 (在手机设置中找到辅助功能,打开手环客户端的辅助功能设置)

表将无法接收推送。

常见问题与解答



(需要在手机设置中找到通知设置,开启微信、QQ、电话、短信、

2.确认消息在手机通知栏都可以正常显示,手表消息推送是通

为什么不能佩戴手表洗热水澡?

降下来后又会重新凝结成液相的水滴,容易造成手表内部线路 短路,损伤手表电路板,进而损坏手表。

为什么手表接收不到消息推送? 手表和血压计测量数值出现的偏差是由多种因素决定的,血压 安卓手机设置: 计测量部位是在肱动脉,手表测量部位是在微动脉的两个主要 1.确认在手机客户端开启了消息推送的开关 支,正常情况下主动脉血压测量值和微动脉血压测量值会相 过读取手机通知栏消息进行推送;若手机通知栏没有消息,手





常见问题与解答









脉里流动的是离心方向的血液,血压计测量时绑带使你的肘正 中以下部位处于受压状态,暂时血液无法顺畅的向下面的动脉

差三到四十;如果你使用手表和血压计同时进行测量,由于动

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be u sed in portable exposure condition without restriction