



# FCC Part 15C Test Report

## FCC ID: 2A74I-TLL331441

Applicant: ABN SYSTEMS INTERNATIONAL S.A.

Address: Str. Marinariilor, nr. 31, Sector 1 Bucuresti,Romania

Manufacturer: Shenzhen Rti-Tek Co., Ltd.

Address: 4th Floor, Factory 10, Xiaweyuan Industrial Zone, Gushu Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, P.R.C.

EUT: Thermostat

Trade Mark: TELLUR

Model Number: TLL331441

Date of Receipt: Aug. 30, 2022

Test Date: Aug. 30, 2022 - Oct. 17, 2022

Date of Report: Oct. 17, 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.249  
ANSI C63.10: 2013

Test Result: Pass

Report Number: DL-20220925016E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*



<b>Table of Contents</b>	<b>Page</b>
<b>1. SUMMARY OF TEST RESULTS .....</b>	<b>4</b>
1.1 MEASUREMENT UNCERTAINTY .....	4
1.2 TEST FACILITY .....	4
<b>2. GENERAL INFORMATION .....</b>	<b>5</b>
2.1 GENERAL DESCRIPTION OF EUT .....	5
2.2 DESCRIPTION OF TEST MODES .....	5
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED .....	6
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) .....	6
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS .....	7
<b>3. EMC EMISSION TEST .....</b>	<b>8</b>
3.1 CONDUCTED EMISSION MEASUREMENT .....	8
3.1.1 POWER LINE CONDUCTED EMISSION Limits .....	8
3.1.2 TEST PROCEDURE .....	8
3.1.3 DEVIATION FROM TEST STANDARD .....	8
3.1.4 TEST SETUP .....	9
3.1.5 EUT OPERATING CONDITIONS .....	9
3.1.6 TEST RESULTS .....	9
3.2 RADIATED EMISSION MEASUREMENT .....	10
3.2.1 RADIATED EMISSION LIMITS .....	10
3.2.2 TEST PROCEDURE .....	11
3.2.3 DEVIATION FROM TEST STANDARD .....	11
3.2.4 TEST SETUP .....	11
3.2.5 EUT OPERATING CONDITIONS .....	12
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) .....	13
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) .....	14
3.2.8 TEST RESULTS (1GHZ~25GHZ) .....	16
3.3 RADIATED BAND EMISSION MEASUREMENT .....	17
3.3.1 TEST REQUIREMENT: .....	17
3.3.2 TEST PROCEDURE .....	17
3.3.3 DEVIATION FROM TEST STANDARD .....	17
3.3.4 TEST SETUP .....	18
3.3.5 EUT OPERATING CONDITIONS .....	18
<b>4. BANDWIDTH TEST .....</b>	<b>20</b>
4.1 APPLIED PROCEDURES / LIMIT .....	20
4.1.1 TEST PROCEDURE .....	20
4.1.2 DEVIATION FROM STANDARD .....	20
4.1.3 TEST SETUP .....	20



---

Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS .....	20
4.1.5 TEST RESULTS .....	21
<b>5. ANTENNA REQUIREMENT .....</b>	<b>23</b>
5.1 STANDARD REQUIREMENT .....	23
5.2 EUT ANTENNA .....	23
<b>6. TEST SEUUP PHOTO .....</b>	<b>24</b>



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.249(c)	Fundamental & Radiated Spurious Emission Measurement	PASS	
15.205	Band Edge Emission	PASS	
15.215	20dB Bandwidth	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

### 1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.42\text{dB}$
3	Spurious emissions, conducted	$\pm 2.76\text{dB}$
4	All emissions, radiated (<1G)	$\pm 3.65\text{dB}$
5	All emissions, radiated (>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

### 1.2 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.  
Add.: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone,  
Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456  
Designation Number: CN1307  
IC Registered No.: CN0118



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Thermostat
Trademark	TELLUR
Model No.:	TLL331441
Model Difference:	N/A
Sample No.:	DL-20220925016#
Operation Frequency:	2402~2480MHz
Channel numbers:	40 Channels
Channel separation:	2M
Modulation technology:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	4dBi
Power supply:	DC 4.5V from Battery (3x1 .5V LR6/AA)

Note:

- 1.For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual.
- 2.The EUT’s all information provided by client.

3.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	11	2424	23	2446
02	2404	12	2426	24	2448
~	~	~	~	~	~
9	2420	19	2440	39	2480
10	2422	20	2442		

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	
Mode 1	CH01	GFSK
Mode 2	CH19	
Mode 3	CH39	
Mode 4	Charging	


Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.



### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Spurious Emission Test

Note: The device is powered by DC, this item is not applicable

### 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
E-1	Thermostat	TLL331441	N/A	EUT
E-2	No	No	N/A	No

Item	Shielded Type	Ferrite Core	Length	Note
C1	No	No	No	No

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

**2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS**

## Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4408B	MY50140780	Nov. 06, 2021	Nov. 05, 2022
2	Test Receiver (9kHz-7GHz)	R&S	ESRP7	101393	Nov. 06, 2021	Nov. 05, 2022
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB9162	00306	Nov. 06, 2021	Nov. 05, 2022
4	Horn Antenna (1GHz-18GHz)	Schwarzbeck	BBHA9120D	02139	Nov. 06, 2021	Nov. 05, 2022
5	Horn Antenna (18GHz-40GHz)	A.H. Systems	SAS-574	588	Nov. 06, 2021	Nov. 05, 2022
6	Amplifier (9KHz-6GHz)	Schwarzbeck	BBV9743B	00153	Nov. 06, 2021	Nov. 05, 2022
7	Amplifier (1GHz-18GHz)	EMEC	EM01G8GA	00270	Nov. 06, 2021	Nov. 05, 2022
8	Amplifier (18GHz-40GHz)	Quanjuda	DLE-161	97	Nov. 06, 2021	Nov. 05, 2022
9	Loop Antenna (9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	Nov. 06, 2021	Nov. 05, 2022
10	RF cables1 (9kHz-1GHz)	ChengYu	966	004	Nov. 06, 2021	Nov. 05, 2022
11	RF cables2 (1GHz-40GHz)	ChengYu	966	003	Nov. 06, 2021	Nov. 05, 2022
12	Antenna connector	Florida RF Labs	N/A	RF 01#	Nov. 06, 2021	Nov. 05, 2022
13	Power probe	KEYSIGHT	U2021XA	MY55210018	Nov. 06, 2021	Nov. 05, 2022
14	Signal Analyzer 9kHz-26.5GHz	Agilent	N9020A	MY55370280	Nov. 06, 2021	Nov. 05, 2022
15	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	Nov. 06, 2021	Nov. 05, 2022
16	D.C. Power Supply	LongWei	PS-305D	010964729	Nov. 06, 2021	Nov. 05, 2022

## Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	843 Shielded Room	ChengYu	843 Room	843	Nov. 25, 2019	Nov. 24, 2022
2	EMI Receiver	R&S	ESR	101421	Nov. 06, 2021	Nov. 05, 2022
3	LISN	R&S	ENV216	102417	Nov. 06, 2021	Nov. 05, 2022
4	843 Cable 1#	ChengYu	CE Cable	001	Nov. 06, 2021	Nov. 05, 2022

## Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ_EMCC	EMC-CON 3A1.1
2	EMC radiation test system	FALA	EZ_EMCC	FA-03A2
3	RF test system	MAIWEI	MTS8310	2.0.0.0
4	RF communication test system	MAIWEI	MTS8200	2.0.0.0



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 3.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation



### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 3.1.6 TEST RESULTS

Note: The device is powered by DC, this item is not applicable



**3.2 RADIATED EMISSION MEASUREMENT**

**3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)**

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microrvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 - 928 MHz	50	500
2400 - 2483.5 MHz	50	500
5725 - 5875 MHz	50	500
24.0 - 24.25 GHz	250	2500

**LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)**

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

### 3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

Temperature:	24°C	Relative Humidity:	58%
Pressure:	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 4.5V		
Test Mode :	Mode 1		



No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	75.7113	31.30	-18.67	12.63	40.00	-27.37	QP
2	154.8204	29.80	-15.50	14.30	43.50	-29.20	QP
3	191.0738	33.69	-18.03	15.66	43.50	-27.84	QP
4	344.3855	30.52	-13.67	16.85	46.00	-29.15	QP
5	556.7743	32.41	-8.28	24.13	46.00	-21.87	QP
6 *	807.4290	31.16	-3.55	27.61	46.00	-18.39	QP


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



Temperature:	26°C	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 4.5V		
Test Mode :	Mode 1		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	33.7394	42.83	-15.62	27.21	40.00	-12.79	QP
2	40.2756	41.83	-14.69	27.14	40.00	-12.86	QP
3	68.8721	38.52	-17.23	21.29	40.00	-18.71	QP
4	87.8786	42.91	-19.88	23.03	40.00	-16.97	QP
5	193.7727	46.71	-17.86	28.85	43.50	-14.65	QP
6	400.4318	41.48	-12.13	29.35	46.00	-16.65	QP

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



**3.2.8 TEST RESULTS (1GHZ~25GHZ)**

2402MHz									
2402	96.58	26.36	2.76	51.45	74.25	94.00	-19.75	Average	Vertical
2402	122.35	26.36	2.76	51.45	100.02	114.00	-13.98	peak	Vertical
4804	66.87	27.41	3.08	52.16	45.20	54.00	-8.80	Average	Vertical
4804	74.19	27.41	3.08	52.16	52.52	74.00	-21.48	peak	Vertical
7206	66.38	31.25	4.33	51.74	50.22	54.00	-3.78	Average	Vertical
7206	75.49	31.25	4.33	51.74	59.33	74.00	-14.67	peak	Vertical
2402	105.36	26.67	2.76	51.45	83.34	94.00	-10.66	Average	Horizontal
2402	128.77	26.67	2.76	51.45	106.75	114.00	-7.25	peak	Horizontal
4804	54.19	27.41	3.08	52.16	32.52	54.00	-21.48	Average	Horizontal
4804	73.21	27.41	3.08	52.16	51.54	74.00	-22.46	peak	Horizontal
7206	61.28	31.25	4.33	51.74	45.12	54.00	-8.88	Average	Horizontal
7206	72.23	31.25	4.33	51.74	56.07	74.00	-17.93	peak	Horizontal
2440MHz									
2440	94.18	26.76	2.79	51.67	72.06	94.00	-21.94	Average	Vertical
2440	126.98	26.76	2.79	51.67	104.86	114.00	-9.14	peak	Vertical
4880	66.54	27.47	3.12	52.11	45.02	54.00	-8.98	Average	Vertical
4880	71.25	27.47	3.12	52.11	49.73	74.00	-24.27	peak	Vertical
7320	61.32	31.34	4.37	51.77	45.26	54.00	-8.74	Average	Vertical
7320	77.25	31.34	4.37	51.77	61.19	74.00	-12.81	peak	Vertical
2440	99.24	26.23	2.56	51.34	76.69	94.00	-17.31	Average	Horizontal
2440	110.12	26.23	2.56	51.34	87.57	114.00	-26.43	peak	Horizontal
4880	62.34	32.11	3.12	52.11	45.46	54.00	-8.54	Average	Horizontal
4880	74.19	32.11	3.12	52.11	57.31	74.00	-16.69	peak	Horizontal
7320	68.32	24.33	4.37	51.77	45.25	54.00	-8.75	Average	Horizontal
7320	75.64	24.33	4.37	51.77	52.57	74.00	-21.43	peak	Horizontal
2480MHz									
2480	105.26	26.95	2.83	51.98	83.06	94.00	-10.94	Average	Vertical
2480	120.36	26.95	2.83	51.98	98.16	114.00	-15.84	peak	Vertical
4960	59.26	27.44	3.34	52.23	37.81	54.00	-16.19	Average	Vertical
4960	74.36	27.44	3.34	52.23	52.91	74.00	-21.09	peak	Vertical
7440	60.12	31.39	4.57	51.69	44.39	54.00	-9.61	Average	Vertical
7440	74.25	31.39	4.57	51.69	58.52	74.00	-15.48	peak	Vertical
2480	94.56	26.95	2.83	51.98	72.36	94.00	-21.64	Average	Horizontal
2480	120.36	26.95	2.83	51.98	98.16	114.00	-15.84	peak	Horizontal
4960	62.34	27.44	3.34	52.23	40.89	54.00	-13.11	Average	Horizontal
4960	74.15	27.44	3.34	52.23	52.70	74.00	-21.30	peak	Horizontal
7440	62.35	31.39	4.57	51.69	46.62	54.00	-7.38	Average	Horizontal
7440	74.16	31.39	4.57	51.69	58.43	74.00	-15.57	peak	Horizontal

Note:  
 1. Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor.  
 2. Over Limit= Absolute Level - Limit.  
 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.  
 4. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)





3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



### 3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.3.6 TEST RESULT**

GFSK

Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
2402MHz									
2390	56.54	27.69	2.73	52.12	34.84	74	-39.16	Average	Vertical
2390	65.36	27.46	2.73	52.12	43.43	54	-10.57	peak	Vertical
2400	77.41	27.41	2.78	52.16	55.44	74	-18.56	Average	Vertical
2400	65.29	27.41	2.78	52.16	43.32	54	-10.68	peak	Vertical
2390	77.25	27.38	2.73	52.12	55.24	74	-18.76	Average	Horizontal
2390	65.89	27.38	2.73	52.12	43.88	54	-10.12	peak	Horizontal
2400	72.56	27.41	2.78	52.16	50.59	74	-23.41	Average	Horizontal
2400	63.25	27.41	2.78	52.16	41.28	54	-12.72	peak	Horizontal
2480MHz									
2483.5	55.36	27.44	2.86	52.23	33.43	54	-20.57	Average	Vertical
2483.5	73.35	27.44	2.86	52.23	51.42	74	-22.58	peak	Vertical
2500	58.23	27.49	2.88	52.26	36.34	54	-17.66	Average	Vertical
2500	78.36	27.49	2.88	52.26	56.47	74	-17.53	peak	Vertical
2483.5	60.78	27.44	2.86	52.23	38.85	54	-15.15	Average	Horizontal
2483.5	73.27	27.44	2.86	52.23	51.34	74	-22.66	peak	Horizontal
2500	63.37	27.49	2.88	52.26	41.48	54	-12.52	Average	Horizontal
2500	74.67	27.49	2.88	52.26	52.78	74	-21.22	peak	Horizontal

Note:

1. Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor.

2. Over Limit= Absolute Level - Limit.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.

4. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)



#### 4. BANDWIDTH TEST

##### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C	
Section	Test Item
15.249	Bandwidth

##### 4.1.1 TEST PROCEDURE

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW)  $\geq$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

##### 4.1.2 DEVIATION FROM STANDARD

No deviation.

##### 4.1.3 TEST SETUP



##### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS


	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	2402	1.193	Pass
	2440	1.203	Pass
	2480	1.191	Pass

2402MHz





2440MHz



2480MHz




## 5. ANTENNA REQUIREMENT

### 5.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



### 5.2 EUT ANTENNA

The EUT antenna is PCB Antenna ,. It comply with the standard requirement.



## 6. TEST SEUUP PHOTO

### Radiated Measurement Photos



※※※※※ END OF REPORT ※※※※※