

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

11 TROBOOT IN ORANIA CONTRACTOR		
Product Description	Bluetooth Headphone	
Test Model	TLL511271	
Series Model	TLL511441, TLL511281, TLL511371, TLL511471	
FCC ID	2A74I-TLL511271	

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

BR&EDR:

P_t=0.510dBm=1.12mW

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR= $(1.12\text{mW} / 5\text{mm}).[\sqrt{2.441\text{GHz}}]=0.349<3.0$ for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.