

# RF Exposure Evaluation Report

**FCC ID** : 2A753-BTHS20  
**Equipment** : Dragon BT Headset 2.0  
**Brand Name** : Nuance Communications  
**Model Name** : DragonBT2.0  
**Applicant** : Nuance Communications, Inc.  
1 Wayside Road, Burlington, Massachusetts  
01803, United States  
**Manufacturer** : Nuance Communications, Inc.  
1 Wayside Road, Burlington, Massachusetts  
01803, United States  
**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Oct. 14, 2021, and testing was started from Nov. 22, 2021 and completed on Dec. 09, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Jackson Tsai

Approved by: Jackson Tsai

***SPORTON INTERNATIONAL INC. Hsinhua Laboratory***

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

## Table of Contents

<b>1. General Description.....</b>	<b>4</b>
1.1.    EUT General Information .....	4
1.2.    Testing Location Information .....	4
<b>2. RF Exposure Evaluation .....</b>	<b>5</b>
2.1.    Applicable Standard.....	5
2.2.    SAR evaluation .....	5

### Photographs of EUT V01



## History of This Test Report

Reviewed by: Ben Tseng  
Report Producer: Jenny Yang

## 1. General Description

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

### 1.2. Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	<b>ADD:</b> No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	<b>TEL:</b> 886-3-327-3456	<b>FAX:</b> 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	<b>ADD:</b> No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	<b>TEL:</b> 886-3-318-0787	<b>FAX:</b> 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

## 2. RF Exposure Evaluation

### 2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

### 2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:  
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  
 $[\sqrt{f_{(GHz)}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR
  - $f_{(GHz)}$  is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation
  - The result is rounded to one decimal place for comparison

Max. Power (dBm)	Tolerance (dB)	Tune-up Max. Power (dBm)	Test Distance (mW)	Frequency (GHz)	Exclusion Thresholds
-1.33	0.5	-0.83	0.83	5	0.26

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is  $0.26 < 3$ , RF exposure evaluation is not required.

THE END