

TEST REPORT

Product Name : Bone Conduction Headphone
Model Number : G7, G7C, AI5006-BLK, AI5006-RED,
AI5006-YLW
FCC ID : 2A75N-G7C

Prepared for : SPRITE TECHNOLOGY LIMITED
Address : 4th Floor,A3 Building, Shenliang Industry Zone, NO.299 Gu
anping Road, Longhua District, Shenzhen, China 518110

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F.,Building 2, Zone A,Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2404220213E00202R
Date(s) of Tests : Apr 22, 2024 to May 07, 2024
Date of issue : May 08, 2024

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	6



1. TEST RESULT CERTIFICATION

Applicant : SPRITE TECHNOLOGY LIMITED
 Address : 4th Floor,A3 Building, Shenliang Industry Zone, NO.299 Guanping Road, Longhua District, Shenzhen, China 518110
 Manufacturer : SPRITE TECHNOLOGY LIMITED
 Address : 4th Floor,A3 Building, Shenliang Industry Zone, NO.299 Guanping Road, Longhua District, Shenzhen, China 518110
 Factory : SPRITE TECHNOLOGY LIMITED
 Address : 4th Floor,A3 Building, Shenliang Industry Zone, NO.299 Guanping Road, Longhua District, Shenzhen, China 518110
 EUT : Bone Conduction Headphone
 Model Name : G7, G7C, AI5006-BLK, AI5006-RED, AI5006-YLW
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Apr 22, 2024 to May 07, 2024

Prepared by : Warren Deng

Warren Deng /Editor

Reviewer : Tim Dong

Tim Dong /Supervisor

Approve & Authorized Signer : 

Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2404220213E00202R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Bone Conduction Headphone
Model Number:	G7, G7C, AI5006-BLK, AI5006-RED, AI5006-YLW All products are identical except the model number,color and LED function are different.G7 has LED function while the others without.G7C, AI5006-BLK, AI5006-RED,and AI5006-YLWare identical except model number and color.Here we selected G7 for all the test.
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	3.50 dBm(0.002239 W)
Antenna Gain:	2.67 dBi
Power supply:	DC 5V from USB DC 3.7V from battery
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 2.67 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK	2.39	2±1	3	0.6185	3
2441	GFSK	1.74	2±1	3	0.6235	3
2480	GFSK	0.14	0±1	1	0.3965	3
2402	Π/4-DQPSK	3.11	3±1	4	0.7786	3
2441	Π/4-DQPSK	2.46	2±1	3	0.6235	3
2480	Π/4-DQPSK	0.83	1±1	2	0.4992	3
2402	8DPSK	3.50	3±1	4	0.7786	3
2441	8DPSK	2.82	3±1	4	0.7849	3
2480	8DPSK	1.19	1±1	2	0.4992	3

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***