

FCC §15.247 (i), §2.1091 – RF Exposure

# FCC ID: 2A77XRS-200-1A

#### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

| Limits for Oc | cupational / Con | trolled Exposure |
|---------------|------------------|------------------|
|               |                  |                  |

| Frequency<br>Range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S)<br>(mW/ cm <sup>2</sup> ) | Averaging Time<br> E  <sup>2</sup> , H  <sup>2</sup> or S<br>(minutes) |  |
|--------------------------|---|---|---|--|--|
| 0.3-3.0                  | 614                                     | 1.63                                    | (100)*                                      | 6  |  |
| 3.0-30                   | 1842 / f                                | 4.89 / f                                | (900 / f)*                                  | 6  |  |
| 30-300                   | 61.4                                    | 0.163                                   | 1.0   | 6  |  |
| 300-1500                 |   |   | F/300                                       | 6  |  |
| 1500-100,000             |   |   | 5   | 6  |  |

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

| Frequency<br>Range (MHz) | Electric Field<br>Strength (E)<br>(V/m) | Magnetic Field<br>Strength (H)<br>(A/m) | Power Density (S)<br>(mW/ cm <sup>2</sup> ) | Averaging Time<br> E  <sup>2</sup> , H  <sup>2</sup> or S<br>(minutes) |
|--------------------------|---|---|---|--|
| 0.3-1.34                 | 614                                     | 1.63                                    | (100)*                                      | 30   |
| 1.34-30                  | 824/f                                   | 2.19/f                                  | (180/f)*                                    | 30   |
| 30-300                   | 27.5                                    | 0.073                                   | 0.2   | 30   |
| 300-1500                 |   |   | F/1500                                      | 30   |
| 1500-100,000             |   |   | 1.0   | 30   |

#### Limits for General Population / Uncontrolled Exposure

Note: f = frequency in MHz

\* = Plane-wave equivalent power density



### MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01  $S=PG/4\pi R^2$ 

Where: S = power density

P = power input to antenna

- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna, R=0.2m

## **TEST RESULTS**

|              | Tune up<br>Produce<br>power | Maximum<br>output<br>power<br>(dBm) | Output<br>power to<br>antenna<br>(mW) | Antenna<br>Gain<br>(numeric) | Power<br>Density<br>(S)<br>(mW/<br>cm2) | Limit<br>(mW<br>/ cm2<br>) | Result |
|--------------|-----------------------------|-------------------------------------|---------------------------------------|------------------------------|---|----------------------------|--------|
| 2.4G<br>WIFI | 13±1                        | 14                                  | 25.12                                 | 2.75(4.39dBi)                | 0.013747                                | 1                          | Pass   |
| 5.1G<br>WIFI | 12±1                        | 13                                  | 19.95                                 | 1.71(2.32dBi)                | 0.006789                                | 1                          | Pass   |
| 5.3G<br>WIFI | 11±1                        | 12                                  | 15.85                                 | 1.71(2.32dBi)                | 0.005394                                | 1                          | Pass   |
| 5.6G<br>WIFI | 9±1                         | 10                                  | 31.62                                 | 1.71(2.32dBi)                | 0.010760                                | 1                          | Pass   |
| 5.8G<br>WIFI | 9±1                         | 10                                  | 25.12                                 | 1.71(2.32dBi)                | 0.008548                                | 1                          | Pass   |
| BLE          | 6±1                         | 7                                   | 5.01                                  | 2.75(4.39dBi)                | 0.002742                                | 1                          | Pass   |

#### For the Max simultaneous transmission:

WIFI+BLE

Simultaneous transmitting =0.013747/1+0.002742/1=0.0165  $\leqslant$  1.0

For the max result : 0.0165  $\leq$  1.0, compliance with FCC's RF Exposure