



# FCC Test Report

APPLICANT : Ningbo Lingzhu Technology CO., Ltd.  
EQUIPMENT : Smart Control Panel L  
MODEL NAME : TPP05-Z(US)  
FCC ID : 2A789-TPP05  
STANDARD : 47 CFR Part 15 Subpart B  
CLASSIFICATION : Certification  
TEST DATE(S) : Aug. 10, 2023 ~ Aug. 11, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1. GENERAL DESCRIPTION ..... 5**

    1.1. Applicant..... 5

    1.2. Manufacturer ..... 5

    1.3. Product Feature of Equipment Under Test ..... 5

    1.4. Product Specification of Equipment Under Test ..... 5

    1.5. Modification of EUT ..... 6

    1.6. Test Location..... 6

    1.7. Test Software ..... 6

    1.8. Applicable Standards ..... 6

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 7**

    2.1. Test Mode ..... 7

    2.2. Connection Diagram of Test System ..... 8

    2.3. Support Unit used in test configuration and system..... 8

**3. TEST RESULT ..... 9**

    3.1. Test of AC Conducted Emission Measurement ..... 9

    3.2. Test of Radiated Emission Measurement ..... 13

**4. LIST OF MEASURING EQUIPMENT ..... 18**

**5. MEASUREMENT UNCERTAINTY ..... 19**

**APPENDIX A. SETUP PHOTOGRAPHS**





## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 8.63 dB at 0.524 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 1.96 dB at 87.23 MHz for Quasi-Peak

**Conformity Assessment Condition:**

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1. General Description

## 1.1. Applicant

Ningbo Lingzhu Technology CO., Ltd.

No.578,Building 7,No.535 Kangqiao South Road,Jiangbei District,Ningbo,PRC

## 1.2. Manufacturer

Ningbo Lingzhu Technology CO., Ltd.

No.578,Building 7,No.535 Kangqiao South Road,Jiangbei District,Ningbo,PRC

## 1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Control Panel L
Model Name	TPP05-Z(US)
FCC ID	2A789-TPP05
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 2.4GHz Zigbee
SN	RE/CE: NSZEE18MK00020 for sample 1 NSZEE18MK0005A for sample 2

**Remark:** There are two samples under test, they are only different for LCD panel. According to the difference, Sample 1 perform full test and Sample 2 verify the worst case.

## 1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz Zigbee: 2400 MHz ~ 2483.5 MHz
Rx Frequency	802.11b/g/n: 2400 MHz ~ 2483.5 MHz 802.11a/n: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz Zigbee: 2400 MHz ~ 2483.5 MHz
Antenna Type	WLAN/Zigbee : IPEX Antenna
Type of Modulation	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) Zigbee : O-QPSK



### 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH07-KS	CN1257	314309

### 1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	210616
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test


### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Zigbee Link + WLAN (2.4G) Idle + Microphone on + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 1
	Mode 2: WLAN (5G) Idle + Speaker + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 1
	Mode 3: WLAN (5G) Idle + Speaker + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 2
Radiated Emissions	Mode 1: Zigbee Link + WLAN (2.4G) Idle + Microphone on + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 1
	Mode 2: WLAN (5G) Idle + Speaker + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 1
	Mode 3: Zigbee Link + WLAN (2.4G) Idle + Microphone on + LAN link (RJ45) + L1+L2 light link + RS485 Link + AC Power + Sample 2
<b>Remark:</b>	
1. The worst case of AC is mode 3; only the test data of this mode is reported.	
2. The worst case of RE is mode 1; only the test data of this mode is reported.	

## 2.2. Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Light	N/A	N/A	N/A	N/A	N/A
4.	AC Power	N/A	N/A	N/A	N/A	N/A





### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup




AMN = Artificial mains network (LISN)  
AE = Associated equipment  
EUT = Equipment under test  
ISN = Impedance stabilization network



### 3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS  
 Condition : FCC IC-QP LISN-060105-L 2023 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.150	47.08	-18.92	66.00	36.60	0.05	10.43	QP
2	0.150	34.98	-21.02	56.00	24.50	0.05	10.43	Average
3	0.165	43.97	-21.24	65.21	33.50	0.04	10.43	QP
4	0.165	31.67	-23.54	55.21	21.20	0.04	10.43	Average
5	0.189	40.66	-23.40	64.06	30.21	0.03	10.42	QP
6	0.189	28.66	-25.40	54.06	18.21	0.03	10.42	Average
7	0.486	42.39	-13.84	56.23	32.20	-0.03	10.22	QP
8	0.486	32.09	-14.14	46.23	21.90	-0.03	10.22	Average
9	0.524	43.27	-12.73	56.00	33.11	-0.04	10.20	QP
10 *	0.524	37.37	-8.63	46.00	27.21	-0.04	10.20	Average
11	4.478	32.73	-23.27	56.00	22.80	-0.13	10.06	QP
12	4.478	23.23	-22.77	46.00	13.30	-0.13	10.06	Average



Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS  
 Condition : FCC IC-QP LISN-060105-N 2023 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.156	43.67	-22.02	65.69	33.20	0.04	10.43	QP
2	0.156	31.67	-24.02	55.69	21.20	0.04	10.43	Average
3	0.192	38.67	-25.26	63.93	28.20	0.05	10.42	QP
4	0.192	28.27	-25.66	53.93	17.80	0.05	10.42	Average
5	0.454	38.78	-18.02	56.80	28.59	-0.06	10.25	QP
6	0.454	31.38	-15.42	46.80	21.19	-0.06	10.25	Average
7	0.479	44.46	-11.90	56.36	34.30	-0.07	10.23	QP
8 *	0.479	36.96	-9.40	46.36	26.80	-0.07	10.23	Average
9	0.516	42.84	-13.16	56.00	32.70	-0.07	10.21	QP
10	0.516	35.94	-10.06	46.00	25.80	-0.07	10.21	Average
11	4.874	32.53	-23.47	56.00	22.60	-0.13	10.06	QP
12	4.874	25.13	-20.87	46.00	15.20	-0.13	10.06	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



### 3.2. Test of Radiated Emission Measurement

#### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





### 3.2.5. Test Result of Radiated Emission

Test Engineer :	Levi zhuo	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m 3117 SN00240138 HORIZONTAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 q	87.23	38.04	-1.96	40.00	54.53	14.27	1.28	32.04	100	124 QP
2	112.45	37.69	-5.81	43.50	51.20	16.99	1.54	32.04	100	124 QP
3	250.19	35.52	-10.48	46.00	46.76	18.45	2.30	31.99	---	---
4 p	350.10	38.97	-7.03	46.00	47.96	20.31	2.73	32.03	---	---
5	599.39	36.01	-9.99	46.00	38.93	25.79	3.57	32.28	---	---
6	925.31	37.89	-8.11	46.00	35.01	29.63	4.43	31.18	---	---
7	4094.00	37.42	-36.58	74.00	59.01	33.47	9.58	64.64	---	---
8	6967.00	41.47	-32.53	74.00	56.95	35.59	12.57	63.64	---	---
9	8395.00	41.71	-32.29	74.00	56.00	35.80	13.86	63.95	---	---
10	10248.00	43.10	-30.90	74.00	53.37	37.25	15.50	63.02	---	---
11	12441.00	44.10	-29.90	74.00	50.98	38.98	16.77	62.63	---	---
12	16623.00	45.67	-28.33	74.00	50.37	41.58	19.44	65.72	---	---





Test Engineer :	Levi zhuo	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH07-KS  
 Condition : FCC CLASS-B 3m 3117 SN00240138 VERTICAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	33.88	28.59	-11.41	40.00	36.97	23.13	0.55	32.06	100	124 QP	
2	q 87.23	37.50	-2.50	40.00	53.99	14.27	1.28	32.04	100	124 QP	
3	p 137.67	38.38	-5.12	43.50	51.30	17.41	1.69	32.02	---	---	Peak
4	462.62	37.33	-8.67	46.00	43.13	23.15	3.13	32.08	---	---	Peak
5	575.14	39.79	-6.21	46.00	42.62	25.91	3.49	32.23	---	---	Peak
6	774.96	37.60	-8.40	46.00	37.37	28.15	4.05	31.97	---	---	Peak
7	4060.00	36.86	-37.14	74.00	58.49	33.45	9.56	64.64	---	---	Peak
8	6848.00	39.98	-34.02	74.00	55.75	35.54	12.55	63.86	---	---	Peak
9	9381.00	43.19	-30.81	74.00	55.68	36.48	14.50	63.47	---	---	Peak
10	11710.00	43.46	-30.54	74.00	50.97	38.45	16.26	62.22	---	---	Peak
11	13920.00	43.88	-30.12	74.00	51.03	38.72	17.94	63.81	---	---	Peak
12	15773.00	44.53	-29.47	74.00	50.55	40.44	18.89	65.35	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



### 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 12, 2022	Aug. 10, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 12, 2022	Aug. 10, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 12, 2023	Aug. 10, 2023	Aug. 11, 2024	Radiation (03CH07-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Aug. 10, 2023	Apr. 05, 2024	Radiation (03CH07-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 17, 2022	Aug. 10, 2023	Oct. 16, 2023	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2023	Aug. 10, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 12, 2022	Aug. 10, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
Amplifier	EM	EM18G40GGA	060851	18~40GHz	Jan. 05, 2023	Aug. 10, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Aug. 10, 2023	NCR	Radiation (03CH07-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Aug. 10, 2023	NCR	Radiation (03CH07-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Aug. 10, 2023	NCR	Radiation (03CH07-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 16, 2023	Aug. 11, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Aug. 11, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Aug. 11, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Aug. 11, 2023	Oct. 11, 2023	Conduction (CO01-KS)
Transient limiter	COM-POWER	LIT-153	531040	150kHz~30MHz	Sep. 15, 2022	Aug. 11, 2023	Sep. 14, 2023	Conduction (CO01-KS)
Power bar	SP101EA	CN02	-	150kHz~30MHz	May 16, 2023	Aug. 11, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN	R&S	ENV216	100334	9kHz~30MHz	Oct. 13, 2022	Aug. 11, 2023	Oct. 12, 2023	Conduction (CO01-KS)

NCR: No Calibration Required



## 5. Measurement Uncertainty

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.94 dB
---	---------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	6.20 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.86 dB
---	---------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.24 dB
---	---------