

RF Exposure Evaluation Report

APPLICANT : Ningbo Lingzhu Technology CO., Ltd.
EQUIPMENT : Smart Battery Doorbell
MODEL NAME : SC060-WCB2,SC060-WCB2A,
SC060-WCB2B,SC060-WCB2C,
SC060-WCB3,SC060-WCB3A,
SC060-WCB3B,SC060-WCB3C,
SC060-WCB4,SC060-WCB4A,
SC060-WCB4B,SC060-WCB4C
FCC ID : 2A789SC060
STANDARD : 47 CFR Part 2.1091

The product evaluation date was started from Jul. 14, 2023 and completed on Jul. 14, 2023. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA342506	Rev. 01	Initial issue of report.	Jul. 31, 2023



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Ningbo Lingzhu Technology CO., Ltd.
Address	No.578, Building 7, No.535 Kangqiao South Road, Jiangbei District, Ningbo, Zhejiang, PRC

Manufacturer	
Company Name	Ningbo Lingzhu Technology CO., Ltd.
Address	No.578, Building 7, No.535 Kangqiao South Road, Jiangbei District, Ningbo, Zhejiang, PRC



2. Description of Equipment Under Test (EUT)

Table with 2 columns: Feature Name, Specification. Rows include EUT Type (Smart Battery Doorbell), Model Name (SC060-WCB2, SC060-WCB2A, etc.), FCC ID (2A789SC060), Wireless Technology and Frequency Range (WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz, 433MHz), Mode (WLAN 2.4GHz 802.11b/g/n HT20, 433MHz: ASK), Antenna Gain (WLAN 2.4GHz: 3.79 dBi, 433MHz: -10.36 dBi), Antenna Type (WLAN: FPC Antenna, 433MHz: Spring Antenna), EUT Stage (Identical Prototype).

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations: 1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. 2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF average output tune up power among production units

<2.4GHz WLAN >

Mode		Maximum Average Power (dBm)
2.4GHz	802.11b	14.00
	802.11g	13.00
	802.11n-HT20	12.00

<433MHz >

Mode	Maximum Average Power (dBm)
433MHz	7.00



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
433MHz	433.0	-10.36	7.00	-3.360	0.461	0.000	0.289
WLAN2.4GHz	2412.0	3.79	14.00	17.790	60.117	0.012	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WLAN2.4GHz and 433MHz cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----