

## 5. RF EXPOSURE EVALUATION

### 5.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .

### 5.2 Measurement Result

Operation Modes	Frequency (MHz)	$\lambda/2\pi$ (mm)	Distance (mm)	Exemption ERP		Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	MPE-Based Exemption
				(mW)	(dBm)					
WLAN 2.4G	2412-2462	19.80	200	768	28.85	16	4	17.85	61	Compliant
433M	433.595	110	200	222	23.46	/	/	-16.97	0.02	Compliant

Note:

433M:

$$E \text{ (dBuV/m)} = \text{EIRP (dBm)} + 104.8 - 20\log(d)$$

Peak Filed strength is 80.38 dBuV/m = -14.82 dBm EIRP (ERP = -16.97dBm)

WLAN 2.4G can transmit simultaneously with 433M:

$$\sum_{i=1}^a \left( \frac{P_i}{P_{th_i}} \right) + \sum_{j=1}^b \left( \frac{ERP_j}{ERP_{th_j}} \right) + \sum_{k=1}^c \left( \frac{Evaluated_k}{Exposure Limit_k} \right)$$

$$= ERP_{2.4G}/ERP_{limit-2.4G} + ERP_{433M}/ERP_{limit-433M}$$

$$= 61/768 + 0.02/222$$

$$= 0.08$$

**Result: The device compliant the MPE-Based Exemption at 20cm distances.**

**===== END OF REPORT =====**