

TEST REPORT

Product Name : Laser engraving machine
JL3 Pro, A6, A6 Pro, A6 Plus, A6 Max, L2, L2
Model Number : Pro, L2 Plus, L2 Max, X1, X1 Pro, X1 Plus, X1
Max, JL9, JL9 Pro, JL9 Plus, JL9 Max, JL3
FCC ID : 2A79Y-X1

Prepared for : Dongguan Xinjia Laser Technology Co.,Ltd.
Address : Room 602, No.419, Jinxing Road, Liaobu Town, Dongguan
City, Guangdong Province

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2406250151E00102R
Date(s) of Tests : june 25, 2024 to july 08, 2024
Date of issue : july 08, 2024

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Dongguan Xinjia Laser Technology Co.,Ltd.
Address : Room 602, No.419, Jinxing Road, Liaobu Town, Dongguan City, Guangdong Province
Manufacturer : Dongguan Xinjia Laser Technology Co.,Ltd.
Address : Room 602, No.419, Jinxing Road, Liaobu Town, Dongguan City, Guangdong Province
Factory : Dongguan Xinjia Laser Technology Co.,Ltd.
Address : Room 602, No.419, Jinxing Road, Liaobu Town, Dongguan City, Guangdong Province
EUT : Laser engraving machine
Model Name : JL3 Pro, A6, A6 Pro, A6 Plus, A6 Max, L2, L2 Pro, L2 Plus, L2 Max, X1, X1 Pro, X1 Plus, X1 Max, JL9, JL9 Pro, JL9 Plus, JL9 Max, JL3
Trademark : WAINLUX

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : june 25, 2024 to july 08, 2024


Prepared by : Warren Deng

Warren Deng /Editor

Reviewer : Tim Dong

Tim Dong /Supervisor

Approve & Authorized Signer : Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2406250151E00102R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Laser engraving machine
Model Number:	JL3 Pro, A6, A6 Pro, A6 Plus, A6 Max, L2, L2 Pro, L2 Plus, L2 Max, X1, X1 Pro, X1 Plus, X1 Max, JL9, JL9 Pro, JL9 Plus, JL9 Max, JL3 Note: All models are the same, except the model name. Select model JL3 Pro here to complete all the tests.
Sample:	2#
Device Type:	2.4G WIFI
Data Rate:	802.11b 802.11g 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range(s) :	2412-2462MHz for 802.11b/g/n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels:	11 channels for 802.11b/g/n(HT20); 7 Channels for 802.11n(HT40);
Transmit Power Max:	14.53dBm(0.028379 W)
Antenna Gain:	3.05 dBi
Power supply:	AC 100-240V, 50/60Hz
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{24} \text{ where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain:
2.4G: 3.05 dBi

802.11b: Antenna A

Channel	Channel Freq. (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm ²)	Power density Limits (mW/cm ²)
1	2412	14.53	17.58	17±1	18	63.10	0.025335	1
6	2437	13.75	16.80	16±1	17	50.12	0.020125	1
11	2462	14.26	17.31	17±1	18	63.10	0.025335	1

802.11g: Antenna A

Channel	Channel Freq. (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm ²)	Power density Limits (mW/cm ²)
1	2412	11.7	14.75	14±1	15	31.62	0.012698	1
6	2437	12.34	15.39	15±1	16	39.81	0.015986	1
11	2462	10.97	14.02	14±1	15	31.62	0.012698	1

802.11n HT20: Antenna A

Channel	Channel Freq. (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm ²)	Power density Limits (mW/cm ²)
1	2412	11.54	14.59	14±1	15	31.62	0.012698	1
6	2437	10.56	13.61	13±1	14	25.12	0.010086	1
11	2462	10.75	13.80	13±1	14	25.12	0.010086	1

802.11n HT40: Antenna A

Channel	Channel Freq. (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power(dBm) tolerance	Max tuneup power(mW) tolerance	Power Density at R=20cm (mW/cm ²)	Power density Limits (mW/cm ²)
3	2422	10.58	13.63	13±1	14	25.12	0.010086	1
6	2437	10.12	13.17	13±1	14	25.12	0.010086	1
9	2452	10.21	13.26	13±1	14	25.12	0.010086	1

According to KDB 447498, no stand-alone required for WIFI antenna, and no simultaneous SAR measurement is required.

*** End of Report ***