

**RF Exposure Evaluation**

According to KDB447498D01 General RF Exposure Guidance v06 4.3.1. Standalone SAR test exclusion considerations Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

**Limits**

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

**Test Result of RF Exposure Evaluation**

2.4G-WIFI ANT: 1.5dBi;

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

2.4GWIFI:

Test channel	Antenna Output Power (dBm)	Tune up tolerance (dBm)	Max Tune up tolerance (dBm)
802.11b -2412MHz	14.71	15±1	16
802.11b -2412MHz	15.099	15±1	16
802.11b -2412MHz	14.913	15±1	16
802.11g -2412MHz	13.678	14±1	15
802.11g -2412MHz	13.704	14±1	15
802.11g -2412MHz	13.295	14±1	15
802.11n -2412MHz	13.349	14±1	15
802.11n -2412MHz	13.303	14±1	15
802.11n -2412MHz	13.932	14±1	15
802.11n40 -2412MHz	11.628	12±1	13
802.11n40 -2412MHz	11.463	12±1	13
802.11n40 -2412MHz	11.512	12±1	13

Test worst case

Maximum tune-up Power (dBm)	Maximum tune-up Power (mW)	Calculated value (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
16	50.119	0.0112	1.0

Remark:

1)The Max Conducted Peak Output Power data refer to report Report No.: ZKT-220530L3632

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (50.119 * 1.413) / (4 * 3.1415 * 20^2) = 0.0112$ ,  $G = 10^{gain/10} = 1.413$

3) EUT wifi-2.4G module is more than 20cm away from the human body.

conclusion :

The MPE(2.4GWIFI ) is less than the limit value of 1.0, so there is no sar requirement