

TEST REPORT

Reference No..... : WTX22X08157744W001
FCC ID : 2A7CJ-DS16V2US
Applicant : JETI model s.r.o.
Address..... : Lomena 1530, Pribor, 74258 Czech Republic
Manufacturer : The same as Applicant
Address..... : The same as Applicant
Product Name : Transmitter Duplex
Model No..... : DS-16 II
Standards : FCC Part 15.247
Date of Receipt sample : 2022-08-02
Date of Test..... : 2022-08-02 to 2022-10-11
Date of Issue : 2022-10-11
Test Report Form No. : WTX_Part 15_247W
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:


Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Mike Shi

Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS.....	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 EUT SETUP AND TEST MODE	7
1.6 MEASUREMENT UNCERTAINTY	8
1.7 TEST EQUIPMENT LIST AND DETAILS	9
2. SUMMARY OF TEST RESULTS	12
3 ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....	14
5. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION	16
5.1 STANDARD APPLICABLE	16
5.2 TEST SETUP BLOCK DIAGRAM	16
5.3 TEST PROCEDURE	16
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
6. DWELL TIME OF HOPPING CHANNEL	18
6.1 STANDARD APPLICABLE	18
6.2 TEST SETUP BLOCK DIAGRAM	18
6.3 TEST PROCEDURE	18
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	19
7. 20DB BANDWIDTH	20
7.1 STANDARD APPLICABLE	20
7.2 TEST SETUP BLOCK DIAGRAM	20
7.3 TEST PROCEDURE	20
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	21
8. RF OUTPUT POWER	22
8.1 STANDARD APPLICABLE	22
8.2 TEST SETUP BLOCK DIAGRAM	22
8.3 TEST PROCEDURE	22
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	22
9. FIELD STRENGTH OF SPURIOUS EMISSIONS	23
9.1 STANDARD APPLICABLE	23
9.2 TEST PROCEDURE	23
9.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	25
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	25
10. OUT OF BAND EMISSIONS.....	32
10.1 STANDARD APPLICABLE	32
10.2 TEST PROCEDURE	32
10.3 SUMMARY OF TEST RESULTS/PLOTS	33
11. CONDUCTED EMISSIONS	38
11.1 TEST PROCEDURE	38
11.2 BASIC TEST SETUP BLOCK DIAGRAM	38
11.3 TEST RECEIVER SETUP.....	38
11.4 SUMMARY OF TEST RESULTS/PLOTS	38
APPENDIX SUMMARY	39
APPENDIX A.....	40

APPENDIX B.....44

APPENDIX C.....49

APPENDIX D.....52

APPENDIX E.....55

APPENDIX PHOTOGRAPHS.....60

Report version

Version No.	Date of issue	Description
Rev.00	2022-10-11	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Transmitter Duplex
Trade Name:	/
Model No.:	DS-16 II
Adding Model(s):	/
Rated Voltage:	Charging Port:DC12V Battery:DC3.6V
Battery Capacity:	6.2Ah
Power Adapter:	MODEL:SYS1541-2412 INPUT:AC100-240V~,1.0A MAX 50/60Hz OUTPUT:DC12V,2A
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Frequency Range:	AP1: 2405-2475MHz AP2: 2405-2480MHz
RF Output Power:	AP1: 8.39dBm (Conducted) AP2: 4.80dBm (Conducted)
Modulation:	GFSK
Quantity of Channels:	AP1: 15 AP2: 16
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	AP1: 1.35dBi AP2: 4.12dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest

possible emissions level, more detailed description as follows:

Test Mode List for AP1		
Test Mode	Description	Remark
TM1	Low Channel	2405MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2475MHz
TM4	Hopping	2405-2475MHz

Test Mode List for AP2		
Test Mode	Description	Remark
TM1	Low Channel	2405MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2480MHz
TM4	Hopping	2405-2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SMET-1313	Spectrum Analyzer	Agilent	N9020A	MY54320548	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
☒ Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2022-01-07	2023-01-06
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-19
☒ Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21

SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-22	2023-03-21
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1216	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2022-03-25	2023-03-24
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
☐ Chamber B:Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-22	2023-03-21
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-22	2023-03-21
☐ Chamber C:Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-22	2023-03-21
☒ Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-22	2023-03-21
☐ Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-22	2023-03-21
SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-22	2023-03-21

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.209(a)	Radiated Spurious Emissions	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)	Channel Separation	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§15.247(a)	20dB Bandwidth	Compliant
§15.247(b)(1)	RF Power Output	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§15.247(a)(1)	Frequency Hopping Sequence	Compliant
§15.247(g), (h)	Frequency Hopping System	Compliant

N/A: Not applicable.

3 Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has a monopole antenna and a sleeve dipole antenna, fulfill the requirement of this section.

4. Frequency Hopping System Requirements

4.1 Standard Applicable

According to FCC Part 15.247(a)(1), the system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

4.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses transmitter radio which operates in 2400-2483.5MHz band. It uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 15 bands (5MHz each; centred from 2405 to 2475MHz) in the range 2,400-2,483.5MHz.

This device was tested with a system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for 558074 D01 15.247 Meas Guidance v05r02 and FCC Part 15.247 rule.

4.3 EUT Pseudorandom Frequency Hopping Sequence

For AP1:

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 4, 10, 14, 15,, 14, 11, 15, 6, 8, 4, 1, 3, 13, 14,, 6, 14, 7, 11, 6, 13, 12, 2, 11, 5, 3, 11, 12, 13, 7, 5, 2, 7, 6, 13, 14, 8, 10, 14, 15, 4, 1, 11, 10, 11, 6, 11, 1, 4, 5, 11, 12, 15, 2, 13, 9, 10, 15, 5, 1, 12, 1, 6 etc.

For AP2:

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 4, 10, 14, 15,, 14, 11, 15, 6, 8, 4, 1, 3, 13, 14,, 6, 14, 7, 11, 6, 13, 12, 2, 11, 5, 3, 11, 12, 13, 7, 5, 2, 7, 6, 13, 14, 8, 10, 14, 15, 4, 1, 11, 10, 11, 6, 11, 1, 4, 5, 11, 12, 15, 2, 13, 9, 10, 15, 5, 1, 12, 1, 6 etc.


The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

5. Quantity of Hopping Channels and Channel Separation

5.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

- Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- VBW $\geq$ RBW.
- Sweep: Auto.
- Detector function: Peak.
- Trace: Max hold.
- Allow the trace to stabilize.

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

- Span: Wide enough to capture the peaks of two adjacent channels.
- RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- Video (or average) bandwidth (VBW) $\geq$ RBW.
- Sweep: Auto.

Reference No.: WTX22X08157744W001

e) Detector function: Peak.

f) Trace: Max hold.

g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.4 Summary of Test Results/Plots


Please refer to Appendix A

6. Dwell Time of Hopping Channel

6.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} & \text{(Number of hops in the period specified in the requirements)} = \\ & \text{(number of hops on spectrum analyzer)} \times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops

Reference No.: WTX22X08157744W001

in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

6.4 Summary of Test Results/Plots


Please refer to Appendix B

7. 20dB Bandwidth

7.1 Standard Applicable

According to 15.247(a) and 15.215(c), 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

7.2 Test Setup Block Diagram



7.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- Steps a) through c) might require iteration to adjust within the specified tolerances.
- The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- Set detection mode to peak and trace mode to max hold.
- Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to

stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down

amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Summary of Test Results/Plots


Please refer to Appendix C

8. RF Output Power

8.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5MHz band: 0.125 watts.

8.2 Test Setup Block Diagram



8.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20dB bandwidth, centered on a hopping channel.
- 2) RBW > 20dB bandwidth of the emission being measured.
- 3) VBW $\geq$ RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.

e) A plot of the test results and setup description shall be included in the test report.

8.4 Summary of Test Results/Plots

Please refer to Appendix D

9. Field Strength of Spurious Emissions

9.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

9.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz
RBW=10KHz,
VBW =30KHz
Sweep time= Auto
Trace = max hold
Detector function = peak

Frequency :30MHz-1GHz
RBW=120KHz,
VBW=300KHz
Sweep time= Auto
Trace = max hold
Detector function = peak, QP

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold
Detector function = peak, AV

9.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\begin{aligned}\text{Corr. Ampl.} &= \text{Indicated Reading} + \text{Correct} \\ \text{Correct} &= \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}\end{aligned}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

9.4 Summary of Test Results/Plots


Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case (GFSK) is recorded in this report.

For AP1:


➤ Spurious Emissions Below 1GHz

Test Channel	2.4G Hopping	Polarity:	Horizontal
--------------	--------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.8430	26.65	-8.28	18.37	40.00	-21.63	-	-	QP
2	96.7749	27.75	-9.53	18.22	43.50	-25.28	-	-	QP
3	263.8190	35.63	-6.61	29.02	46.00	-16.98	-	-	QP
4	394.8545	44.43	-3.72	40.71	46.00	-5.29	-	-	QP
5	449.5558	44.90	-2.99	41.91	46.00	-4.09	-	-	QP
6	900.1474	32.43	3.90	36.33	46.00	-9.67	-	-	QP

Test Channel	2.4G Hopping	Polarity:	Vertical
--------------	--------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	46.9948	27.66	-7.90	19.76	40.00	-20.24	-	-	QP
2	168.4138	36.68	-11.18	25.50	43.50	-18.00	-	-	QP
3	365.5391	42.72	-4.21	38.51	46.00	-7.49	-	-	QP
4	420.5803	45.35	-3.36	41.99	46.00	-4.01	-	-	QP
5	533.8321	44.10	-1.70	42.40	46.00	-3.60	-	-	QP
6	590.9737	43.31	-0.51	42.80	46.00	-3.20	-	-	QP

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz


Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2405MHz							
4810	52.22	-2.85	49.37	74	-24.63	H	PK
4810	47.06	-2.85	44.21	54	-9.79	H	AV
7215	50.76	2.76	53.52	74	-20.48	H	PK
7215	41.53	2.76	44.29	54	-9.71	H	AV
4810	51.58	-2.85	48.73	74	-25.27	V	PK
4810	44.59	-2.85	41.74	54	-12.26	V	AV
7215	49.15	2.76	51.91	74	-22.09	V	PK
7215	38.38	2.76	41.14	54	-12.86	V	AV
Middle Channel-2440MHz							
4880	49.87	-2.85	47.02	74	-26.98	H	PK
4880	46.05	-2.85	43.20	54	-10.80	H	AV
7320	52.14	2.76	54.90	74	-19.10	H	PK
7320	45.24	2.76	48.00	54	-6.00	H	AV
4880	50.90	-2.85	48.05	74	-25.95	V	PK
4880	45.63	-2.85	42.78	54	-11.22	V	AV
7320	51.97	2.76	54.73	74	-19.27	V	PK
7320	40.01	2.76	42.77	54	-11.23	V	AV
High Channel-2475MHz							
4950	50.56	-2.85	47.71	74	-26.29	H	PK
4950	45.48	-2.85	42.63	54	-11.37	H	AV
7425	50.96	2.76	53.72	74	-20.28	H	PK
7425	43.02	2.76	45.78	54	-8.22	H	AV
4950	49.78	-2.85	46.93	74	-27.07	V	PK
4950	44.78	-2.85	41.93	54	-12.07	V	AV
7425	47.63	2.76	50.39	74	-23.61	V	PK
7425	41.12	2.76	43.88	54	-10.12	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

For AP2:


➤ Spurious Emissions Below 1GHz

Test Channel	2.4G Hopping	Polarity:	Horizontal
--------------	--------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.0066	28.23	-7.81	20.42	40.00	-19.58	-	-	QP
2	102.0014	28.14	-8.64	19.50	43.50	-24.00	-	-	QP
3	295.1469	35.47	-5.52	29.95	46.00	-16.05	-	-	QP
4	394.8545	44.43	-3.72	40.71	46.00	-5.29	-	-	QP
5	449.5558	45.23	-2.99	42.24	46.00	-3.76	-	-	QP
6	929.0082	33.38	4.11	37.49	46.00	-8.51	-	-	QP

Test Channel	2.4G Hopping	Polarity:	Vertical
--------------	--------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.7434	27.66	-7.86	19.80	40.00	-20.20	-	-	QP
2	168.4138	36.92	-11.18	25.74	43.50	-17.76	-	-	QP
3	422.0577	44.27	-3.36	40.91	46.00	-5.09	-	-	QP
4	447.9822	44.15	-3.01	41.14	46.00	-4.86	-	-	QP
5	533.8321	44.11	-1.70	42.41	46.00	-3.59	-	-	QP
6	590.9737	43.25	-0.51	42.74	46.00	-3.26	-	-	QP

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2405MHz							
4810	51.58	-2.85	48.73	74	-25.27	H	PK
4810	47.42	-2.85	44.57	54	-9.43	H	AV
7215	50.62	2.76	53.38	74	-20.62	H	PK
7215	41.53	2.76	44.29	54	-9.71	H	AV
4810	51.33	-2.85	48.48	74	-25.52	V	PK
4810	44.52	-2.85	41.67	54	-12.33	V	AV
7215	49.46	2.76	52.22	74	-21.78	V	PK
7215	37.71	2.76	40.47	54	-13.53	V	AV
Middle Channel-2440MHz							
4880	49.09	-2.85	46.24	74	-27.76	H	PK
4880	46.62	-2.85	43.77	54	-10.23	H	AV
7320	52.37	2.76	55.13	74	-18.87	H	PK
7320	46.17	2.76	48.93	54	-5.07	H	AV
4880	50.64	-2.85	47.79	74	-26.21	V	PK
4880	46.02	-2.85	43.17	54	-10.83	V	AV
7320	52.48	2.76	55.24	74	-18.76	V	PK
7320	39.48	2.76	42.24	54	-11.76	V	AV
High Channel-2480MHz							
4960	50.11	-2.56	47.55	74	-26.45	H	PK
4960	46.77	-2.56	44.21	54	-9.79	H	AV
7440	53.12	3.54	56.66	74	-17.34	H	PK
7440	45.34	3.54	48.88	54	-5.12	H	AV
4960	49.99	-2.56	47.43	74	-26.57	V	PK
4960	46.11	-2.56	43.55	54	-10.45	V	AV
7440	51.67	3.54	55.21	74	-18.79	V	PK
7440	39.99	3.54	43.53	54	-10.47	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

10. Out of Band Emissions

10.1 Standard Applicable

According to §15.247 (d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

10.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100kHz.
 - 6) Video bandwidth: 300kHz.
 - 7) Detector: Peak.
 - 8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes

to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.

g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.

According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span


30MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100kHz, video bandwidth of 300kHz, and a coupled sweep time with a peak detector. The band 30MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

10.3 Summary of Test Results/Plots

Note: All test modes are performed, only the worst case is recorded in this report.


For AP1:

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency	Reading	Correct	Duty Cycle Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	61.93	-8.78	N/A	53.15	74.00	-20.85	peak
/	/	/	/	-38.06	15.09	54.00	-38.91	ave
2	2390.000	78.17	-8.48	N/A	69.69	74.00	-4.31	peak
/	/	/	/	-38.06	31.63	54.00	-22.37	ave
3	2405.445	117.53	-8.42	N/A	109.11	/	/	peak

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------




No.	Frequency	Reading	Correct	Duty Cycle Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2474.350	115.77	-8.17	N/A	107.60	/	/	peak
2	2483.500	80.09	-8.14	N/A	71.95	74.00	-2.05	peak
	/	/	/	-38.06	33.89	54.00	-20.11	ave
3	2500.000	68.92	-8.08	N/A	60.84	74.00	-13.16	peak
	/	/	/	-38.06	22.78	54.00	-31.22	ave

Duty Cycle Correction:
Duty Cycle Correction = 20*log (0.92/23.2) =-38.06dB


For AP2:

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency	Reading	Correct	Duty Cycle Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	53.75	-8.78	N/A	44.97	74.00	-29.03	peak
/	/	/	/	-38.06	6.91	54.00	-47.09	ave
2	2390.000	70.93	-8.48	N/A	62.45	74.00	-11.55	peak
/	/	/	/	-38.06	24.39	54.00	-29.61	ave
3	2405.445	107.96	-8.43	N/A	99.53	/	/	peak

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency	Reading	Correct	Duty Cycle Correction	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2474.350	107.17	-8.15	N/A	99.02	/	/	peak
2	2483.500	80.50	-8.14	N/A	72.36	74.00	-1.64	peak
	/	/	/	-38.06	34.30	54.00	-19.70	ave
3	2500.000	63.31	-8.08	N/A	55.23	74.00	-18.77	peak
	/	/	/	-38.06	17.17	54.00	-36.83	ave

Duty Cycle Correction:
Duty Cycle Correction = $20 \times \log(0.92/23.2) = -38.06\text{dB}$


11. Conducted Emissions

11.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

11.2 Basic Test Setup Block Diagram



11.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal

11.4 Summary of Test Results/Plots

Not applicable



APPENDIX SUMMARY

Project No.	WTX22X08157744W	Test Engineer	Baidi Zhong
Start date	2022/09/27	Finish date	2022/09/28
Temperature	23℃	Humidity	45%
RF specifications	2.4GHz-FHSS		

APPENDIX	Description of Test Item	Result
A	Hopping Channels and Channel Separation	Compliant
B	Dwell Time of Hopping Channel	Compliant
C	20dB Bandwidth	Compliant
D	RF Output Power	Compliant
E	Conducted Out of Band Emissions	Compliant

APPENDIX A


Hopping Channels Number				
Ant.	Mode	Test Result	Limit	Result
AP1	FHSS	15	≥15	Pass
AP2	FHSS	16	≥15	Pass

AP1	 Date: 28.SEP.2022 14:21:54
AP2	 Date: 28.SEP.2022 11:38:52

Channel Separation				
Ant.	Mode	Channel	Carrier Frequencies Separation (MHz)	Result
AP1	FHSS	Low	5.01	Pass
		Middle	5.01	Pass
		High	5.01	Pass
AP2	FHSS	Low	5.01	Pass
		Middle	5.01	Pass
		High	5.01	Pass


AP1

Low




Date: 28.SEP.2022 10:08:31

Middle



Date: 28.SEP.2022 10:10:07


High



Date: 28.SEP.2022 10:12:19


AP2

Low




Date: 28.SEP.2022 11:39:30

Middle



Date: 28.SEP.2022 11:40:16

High




Date: 28.SEP.2022 11:41:37

APPENDIX B


Ant.	Mode	Test Channel	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
AP1	FHSS	Low	0.93	241.80	400
		Middle	0.97	252.20	400
		High	0.88	228.80	400
AP2	FHSS	Low	0.91	254.80	400
		Middle	0.88	246.40	400
		High	0.88	246.40	400

AP1

Low




Date: 28.SEP.2022 11:27:27




Date: 28.SEP.2022 11:28:15


Middle



Date: 28.SEP.2022 11:06:49




Date: 28.SEP.2022 11:28:28







Date: 28.SEP.2022 11:10:42

High



Date: 28.SEP.2022 11:28:37

AP2	 Date: 28.SEP.2022 11:44:44
Low	 Date: 28.SEP.2022 11:47:40
Middle	 Date: 28.SEP.2022 11:46:07




APPENDIX C

20 dB Bandwidth				
Ant.	Test Mode	Test Channel MHz	20 dB Bandwidth MHz	Result
AP1	FHSS	2405	2.57	Pass
		2440	2.59	Pass
		2475	2.61	Pass
AP2	FHSS	2405	2.79	Pass
		2440	2.87	Pass
		2480	2.85	Pass


AP1

Low




Date: 28.SEP.2022 10:02:39

Middle



Date: 28.SEP.2022 10:01:55


High



Date: 28.SEP.2022 10:01:27


AP2

Low




Date: 28.SEP.2022 11:37:35

Middle



Date: 28.SEP.2022 11:36:22




High



Date: 28.SEP.2022 11:35:49


APPENDIX D

RF Output Power					
Ant.	Channel	Output power (dBm)	Output power (mW)	Limit (mW)	Result
AP1	Low	8.04	6.37	125	Pass
	Middle	8.37	6.87	125	Pass
	High	8.39	6.90	125	Pass
AP2	Low	4.80	2.56	125	Pass
	Middle	4.58	2.87	125	Pass
	High	4.07	2.55	125	Pass

AP1	
Low	 Ref: 30 dBm Att: 40 dB RBW 1 MHz VSW 3 MHz SWT 2.5 ms Marker 1 [T1] 8.04 dBm 2.40535000 GHz 30 Offset 1 dB Center: 2.405 GHz 500 kHz/ Span: 5 MHz Date: 28.SEP.2022 09:37:14
Middle	 Ref: 30 dBm Att: 40 dB RBW 1 MHz VSW 3 MHz SWT 2.5 ms Marker 1 [T1] 8.37 dBm 2.440410000 GHz 30 Offset 1 dB Center: 2.44 GHz 500 kHz/ Span: 5 MHz Date: 28.SEP.2022 09:38:00
High	 Ref: 30 dBm Att: 40 dB RBW 1 MHz VSW 3 MHz SWT 2.5 ms Marker 1 [T1] 8.39 dBm 2.474420000 GHz 30 Offset 1 dB Center: 2.475 GHz 500 kHz/ Span: 5 MHz Date: 28.SEP.2022 09:38:53


AP2

Low




Date: 28.SEP.2022 11:34:32

Middle



Date: 28.SEP.2022 11:34:56

High





Date: 28.SEP.2022 11:35:08



APPENDIX E

AP1
Conducted Out of Band Emissions


Low




Middle




High








AP2
Conducted Out of Band Emissions




Middle



High





APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****