


RF Exposure Evaluation Report

| | | |
|--|---|---|
| Report Reference No. | MTWG2206104-H | |
| FCC ID | 2A7D4-PROX999 | |
| Compiled by (position+printed name+signature)..: | File administrators Alisa Luo |  |
| Supervised by (position+printed name+signature)..: | Test Engineer Sunny Deng |  |
| Approved by (position+printed name+signature)..: | Manager Yvette Zhou |  |
| Date of issue..... | July 01, 2022 | |
| Representative Laboratory Name. : Shenzhen Most Technology Service Co., Ltd. | | |
| Address..... | No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China. | |
| Applicant's name..... : shenzhen beeforeo technology Co.,LTD | | |
| Address..... | 1003, No. 57, Chilingtouxinercun Gaofeng Community, Dalang Street, Longhua New District Shenzhen Guangdong 518000 CN | |
| Test specification/ Standard | 47 CFR Part 1.1307 47 CFR Part 2.1093 | |
| TRF Originator..... | Shenzhen Most Technology Service Co., Ltd. | |
| Shenzhen Most Technology Service Co., Ltd. All rights reserved. | | |
| This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. | | |
| Test item description | TWS | |
| Trade Mark..... | SQRMINI | |
| Model/Type reference..... | Pro X999 | |
| Listed Models | N/A | |
| Modulation Type..... | GFSK, π/4DQPSK, 8DPSK | |
| Operation Frequency..... | From 2402MHz to 2480MHz | |
| Hardware Version..... | X999-V2.2 | |
| Software Version..... | X999-20220520002 | |
| Rating..... | DC 3.7V(by battery) DC 5V(by USB) | |
| Result..... | PASS | |

TEST REPORT

Equipment under Test : TWS

Model /Type : Pro X999

Listed Models : N/A

Remark : N/A

Applicant : **shenzhen beeforo technology Co.,LTD**

Address : 1003, No. 57, Chilingtouxinercun Gaofeng Community,
Dalang Street, Longhua New District Shenzhen Guangdong
518000 CN

Manufacturer : **shenzhen beeforo technology Co.,LTD**

Address : 1003, No. 57, Chilingtouxinercun Gaofeng Community,
Dalang Street, Longhua New District Shenzhen Guangdong
518000 CN

| | |
|---------------------|-------------|
| Test Result: | PASS |
|---------------------|-------------|

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

1. Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|------------|---------------|------------|
| 00 | 2022.07.01 | Initial Issue | Alisa Luo |
| | | | |
| | | | |

2. SAR Evaluation

2.1 RF Exposure Compliance Requirement

2.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

2.1.3 EUT RF Exposure

Measurement Data

BT classic

| GFSK | | | |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
| | | | (dBm) |
| Lowest(2402MHz) | -3.210 | -3.210 ± 1 | -2.210 |
| Middle(2440MHz) | -2.963 | -2.963 ± 1 | -1.863 |
| Highest(2480MHz) | -1.908 | -1.908 ± 1 | -0.908 |

| π /4DQPSK | | | |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
| | | | (dBm) |
| Lowest(2402MHz) | -1.103 | -1.103 ± 1 | -0.103 |
| Middle(2440MHz) | -0.346 | -0.346 ± 1 | 0.654 |
| Highest(2480MHz) | 0.389 | 0.389 ± 1 | 1.389 |

| 8DPSK | | | |
|------------------|-------------------------|-------------------------|-----------------------|
| Test channel | Peak Output Power (dBm) | Tune up tolerance (dBm) | Maximum tune-up Power |
| | | | (dBm) |
| Lowest(2402MHz) | -0.701 | -0.701 ± 1 | 0.299 |
| Middle(2440MHz) | 0.048 | 0.048 ± 1 | 1.048 |
| Highest(2480MHz) | 0.946 | 0.946 ± 1 | 1.946 |

| Worst case: 8DPSK | | | | | | |
|-------------------|---|-----------------------|------|------------------|---------------------|--------------------|
| Channel | Maximum Peak Conducted Output Power (dBm) | Maximum tune-up Power | | Calculated value | Exclusion threshold | SAR Test Exclusion |
| | | (dBm) | (mW) | | | |
| Middle(2480MHz) | 0.946 | 1.946 | 1.57 | 0.493 | 3.0 | Yes |

.....THE END OF REPORT.....