## FCC ID: 2A7DR-BM111V5

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)		Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-1.47	0.71	-1±1	0	1.00	<5	0.30997	3.00	YES
	2.441	-1.98	0.63	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	-1.83	0.66	-1±1	0	1.00	<5	0.31496	3.00	YES
π/4- DQPSK	2.402	-0.74	0.84	-1±1	0	1.00	<5	0.30997	3.00	YES
	2.441	-1.26	0.75	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	-1.16	0.77	-1±1	0	1.00	<5	0.31496	3.00	YES
8-DQPSK	2.402	-2.25	0.60	-2±1	-1	0.79	<5	0.24622	3.00	YES
	2.441	-1.43	0.72	-1±1	0	1.00	<5	0.31247	3.00	YES
	2.480	-2.83	0.52	-2±1	-1	0.79	<5	0.25018	3.00	YES

## Conclusion:

For the max result: 0.31496≤ 3.0 for 1g SAR, SAR is not required.

**Signature: Date:** 2023-03-09

NAME AND TITLE (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.