



# Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

## FCC PART 15 SUBPART C TEST REPORT FCC PART 15.407

Report Reference No. .... : CTA22052700704

FCC ID. .... : 2A7IC-DUODUOGO

Compiled by

( position+printed name+signature) : File administrators Kevin Liu

Supervised by

( position+printed name+signature) : Project Engineer Kevin Liu

Approved by

( position+printed name+signature) : RF Manager Eric Wang

Date of issue ..... : Jun. 14, 2022

Testing Laboratory Name ..... : Shenzhen CTA Testing Technology Co., Ltd.

Address ..... : Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name ..... : MaFengWo dianzishangwupingtaiyouxiangongsi

Address ..... : 3rd Floor, Building 3, Jiaanda Technology Industrial Park, Huafan Road, Dalang Street, Longhua District, Shenzhen, Guangdong, China

Test specification..... :

Standard ..... : FCC Part 15.407: UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : Tablet

Trade Mark..... : DUODUOGO

Manufacturer..... : MaFengWo dianzishangwupingtaiyouxiangongsi

Model/Type reference ..... : DUODUOGO

Listed Models ..... : AOYODKG, OUZRS, Firmast

Modulation Type ..... : DSSS,OFDM

Operation Frequency ..... : From 5180MHz to 5240MHz, 5260MHz to 5320MHz, 5500MHz to 5700MHz, 5745MHz to 5825MHz

Rating..... : DC 3.7V From Battery and DC 5.0V From external circuit

Result..... : PASS



Eric Wang

## TEST REPORT

Equipment under Test : Tablet

Model /Type : DUODUOGO

Listed Models : AOYODKG, OUZRS, Firmast

Applicant : MaFengWo dianzishangwupingtaiyouxiangongsi

Address : 3rd Floor, Building 3, Jiaanda Technology Industrial Park, Huafan Road, Dalang Street, Longhua District, Shenzhen, Guangdong, China

Manufacturer : MaFengWo dianzishangwupingtaiyouxiangongsi

Address : 3rd Floor, Building 3, Jiaanda Technology Industrial Park, Huafan Road, Dalang Street, Longhua District, Shenzhen, Guangdong, China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

<u>1.</u>	<u>TEST STANDARDS .....</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY .....</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment Under Test	6
2.4.	Short description of the Equipment under Test (EUT)	6
2.5.	EUT operation mode	6
2.6.	Block Diagram of Test Setup	7
2.7.	Related Submittal(s) / Grant (s)	7
2.8.	Modifications	7
<u>3.</u>	<u>TEST ENVIRONMENT .....</u>	<u>8</u>
3.1.	Address of the test laboratory	8
3.2.	Test Facility	8
3.3.	Environmental conditions	8
3.4.	Test Description	8
3.5.	Statement of the measurement uncertainty	9
3.6.	Equipments Used during the Test	10
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS.....</u>	<u>11</u>
4.1.	AC Power Conducted Emission	11
4.2.	Radiated Emission	14
4.3.	Duty Cycle	22
4.4.	Maximum Average Output Power	23
4.5.	Power Spectral Density	26
4.6.	6dB Bandwidth	27
4.7.	26dB Bandwidth	28
4.8.	Antenna Requirement	29
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT .....</u>	<u>30</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</u>	<u>30</u>

## 1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE DEVICES.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E

## 2. SUMMARY

### 2.1. General Remarks

Date of receipt of test sample	:	May 20, 2022
Testing commenced on	:	May 25, 2022
Testing concluded on	:	Jun. 14, 2022

### 2.2. Product Description

Product Name:	Tablet
Model/Type reference:	DUODUOGO
List Model:	N/A
Power supply:	DC 3.7V From Battery and DC 5.0V From external circuit
Adapter information : (Auxiliary test supplied by testing Lab)	Model: EP-TA20CBC Input:AC 100-240V 50/60Hz Output:DC 5V 2A
testing sample ID:	CTA220527007-1# (Engineer sample), CTA220527007-2# (Normal sample)
Hardware version:	V1.0
Software version:	V1.0
<b>WIFI</b>	
WLAN	Supported 802.11 a//n/ac
Modulation Type	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac20/40/80: OFDM(64QAM, 16QAM, QPSK, BPSK)
Operation frequency	IEEE 802.11a: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz IEEE 802.11n HT20: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz IEEE 802.11n HT40: 5190-5230MHz, 5270-5310MHz, 5510-5670MHz, 5755-5795MHz IEEE 802.11ac20: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz IEEE 802.11ac40: 5190-5230MHz, 5270-5310MHz, 5510-5670MHz, 5755-5795MHz IEEE 802.11ac80: 5210MHz, 5290MHz, 5530MHz, 5775MHz
Channel number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 1 Channels for 80MHz bandwidth(5530Hz) 1 channels for 80MHz bandwidth(5775MHz)
Antenna type:	PIFA antenna
Antenna gain:	0.00dBi

## 2.3. Equipment Under Test

### Power supply system utilised

Power supply voltage	:	<input type="radio"/>	230V / 50 Hz	<input type="radio"/>	120V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 3.7V From Battery and DC 5.0V From external circuit

## 2.4. Short description of the Equipment under Test (EUT)

This is a Tablet.

For more details, refer to the user's manual of the EUT.

### 2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

IEEE 802.11a/ac20/ac40/ac80/n20/n40:


U-NI-1		U-NI-1		U-NI-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

U-NI-2A		U-NI-2A		U-NI-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

U-NI-2C		U-NI-2C		U-NI-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550		
108	5540	118	5590		
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				

U-NI-3		U-NI-3		U-NI-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

## 2.6. Block Diagram of Test Setup



## 2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2A7IC-DUODUOGO** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## 2.8. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST ENVIRONMENT

#### 3.1. Address of the test laboratory

##### Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

#### 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 517856 Designation Number: CN1318**

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6534.01**

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### 3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

#### 3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.203	Antenna gain	802.11ac	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11ac	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Power spectral density	802.11a/ac20/ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Spectrum bandwidth – 26 dB bandwidth	802.11a/ac20/ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(e)	Spectrum bandwidth – 6 dB bandwidth	802.11a/ac20/ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	Maximum output power	802.11a/ac20/ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(b)	Band edge compliance conducted	802.11a/ac20/ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(b)	Band edge	802.11a/ac20/	<input checked="" type="checkbox"/> Lowest	802.11a/ac20/a	<input checked="" type="checkbox"/> Lowest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

	compliance radiated	ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Highest	c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Highest					
§15.407(a)	TX spurious emissions conducted	-/-	-/-	-/-	-/-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(a)	TX spurious emissions radiated	802.11a/ac20/ ac40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11a/ac20/a c40/ac80 802.11n HT20/40	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.407(g)	Frequency Stability	-/-	-/-	-/-	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11a/ac20/ ac40/ac80 802.11n HT20/40	-/-	802.11ac	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

## Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

### 3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2021/08/06	2022/08/05
LISN	R&S	ENV216	CTA-314	2021/08/06	2022/08/05
EMI Test Receiver	R&S	ESPI	CTA-307	2021/08/06	2022/08/05
EMI Test Receiver	R&S	ESCI	CTA-306	2021/08/06	2022/08/05
Spectrum Analyzer	Agilent	N9020A	CTA-301	2021/08/06	2022/08/05
Spectrum Analyzer	R&S	FSP	CTA-337	2021/08/06	2022/08/05
Vector Signal generator	Agilent	N5182A	CTA-305	2021/08/06	2022/08/05
Analog Signal Generator	R&S	SML03	CTA-304	2021/08/06	2022/08/05
Universal Radio Communication	CMW500	R&S	CTA-302	2021/08/06	2022/08/05
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2021/08/06	2022/08/05
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2021/08/07	2022/08/06
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2021/08/07	2022/08/06
Loop Antenna	Zhinan	ZN30900C	CTA-311	2021/08/07	2022/08/06
Horn Antenna	Beijing Hangwei Dayang	OBH100400	CTA-336	2021/08/06	2022/08/05
Amplifier	Schwarzbeck	BBV 9745	CTA-312	2021/08/06	2022/08/05
Amplifier	Taiwan chengyi	EMC051845B	CTA-313	2021/08/06	2022/08/05
Directional coupler	NARDA	4226-10	CTA-303	2021/08/06	2022/08/05
High-Pass Filter	XingBo	XBLBQ-GTA18	CTA-402	2021/08/06	2022/08/05
High-Pass Filter	XingBo	XBLBQ-GTA27	CTA-403	2021/08/06	2022/08/05
Automated filter bank	Tonscend	JS0806-F	CTA-404	2021/08/06	2022/08/05
Power Sensor	Agilent	U2021XA	CTA-405	2021/08/06	2022/08/05
Amplifier	Schwarzbeck	BBV9719	CTA-406	2021/08/06	2022/08/05

Note: The Cal.Interval was one year.

## 4. TEST CONDITIONS AND RESULTS

### 4.1. AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .





## 4.2. Radiated Emission

### Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

### **Undesirable emission limits**

Requirement	Limit(EIRP)	Limit (Field strength at 3m) <small>Note1</small>
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dB $\mu$ V/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m}, \text{ where } P \text{ is the eirp (Watts)}$$

(5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209


(6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

### **Radiated emission limits**


Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

**TEST CONFIGURATION**


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



### Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak


### TEST RESULTS

#### Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
1. All 802.11a / 802.11n/ac (HT20) /802.11n/ac (HT40)/ 802.11ac (HT80) modes have been tested for above 1GHz test, for below 1GHz test, only the worst case 802.11a low channel of U-NII 1 band was recorded.
2. All 802.11a / 802.11n/ac (HT20) /802.11n/ac (HT40)/ 802.11ac (HT80) modes have been tested for above 1GHz test, for above 1GHz test, only the worst case 802.11a was recorded.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

## For 30MHz-1GHz


## Horizontal



## Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	48.915	27.25	11.11	-16.14	40.00	28.89	100	334	Horizontal
2	66.7388	33.99	13.98	-20.01	40.00	26.02	100	0	Horizontal
3	167.012	38.96	17.75	-21.21	43.50	25.75	100	229	Horizontal
4	255.161	41.58	23.72	-17.86	46.00	22.28	100	197	Horizontal
5	536.946	29.05	15.26	-13.79	46.00	30.74	100	83	Horizontal
6	939.86	29.50	20.58	-8.92	46.00	25.42	100	293	Horizontal

## Vertical



## Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	43.3375	31.58	14.90	-16.68	40.00	25.10	100	59	Vertical
2	57.7662	37.25	19.52	-17.73	40.00	20.48	100	196	Vertical
3	136.821	48.74	27.10	-21.64	43.50	16.40	100	18	Vertical
4	294.931	38.08	20.66	-17.42	46.00	25.34	100	3	Vertical
5	554.042	29.00	15.46	-13.54	46.00	30.54	100	294	Vertical
6	970.051	28.58	19.82	-8.76	54.00	34.18	100	360	Vertical

For 1GHz to 40GHz

Note: All 802.11a / 802.11n/ac (HT20) /802.11n/ac (HT40)/ 802.11ac (HT80) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.

**5150-5250MHz:****U-NII 1 & 802.11a Mode (above 1GHz)**

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 5180MHz	5150.00	56.31	PK	H	68.20	11.89	59.74	33.04	5.45	41.92	-3.43
	5150.00	47.32	AV	H	54.00	6.68	50.75	33.04	5.45	41.92	-3.43
	10360.00	51.42	PK	H	68.20	16.78	38.83	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
40.00 5200MHz	10400.00	52.68	PK	H	68.20	15.52	49.00	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
	5350.50	57.43	PK	H	68.20	10.77	60.70	32.84	5.97	42.08	-3.27
48.00 5240MHz	5350.50	48.00	AV	H	54.00	6.00	51.27	32.84	5.97	42.08	-3.27
	10480.00	51.89	PK	H	68.20	16.31	48.15	38.89	10.19	45.34	3.74

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
36.00 5180MHz	5150.00	54.84	PK	V	68.20	13.36	58.27	33.04	5.45	41.92	-3.43
	5150.00	46.53	AV	V	54.00	7.47	49.96	33.04	5.45	41.92	-3.43
	10360.00	51.59	PK	V	68.20	16.61	47.92	38.83	10.12	45.28	3.67
	--	--	--	--	--	--	--	--	--	--	--
40.00 5200MHz	10400.00	51.59	PK	V	68.20	16.61	47.91	38.85	10.13	45.3	3.68
	--	--	--	--	--	--	--	--	--	--	--
	5350.50	57.42	PK	V	68.20	10.78	60.69	32.84	5.97	42.08	-3.27
48.00 5240MHz	5350.50	48.42	AV	V	54.00	5.58	51.69	32.84	5.97	42.08	-3.27
	10480.00	51.59	PK	V	68.20	16.61	47.85	38.89	10.19	45.34	3.74

**5260-5320MHz:****U-NII 1 & 802.11a Mode (above 1GHz)**

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
52.00 5260MHz	5150.00	48.98	PK	H	68.20	19.22	52.41	33.04	5.45	41.92	-3.43
	5150.00	40.12	AV	H	54.00	13.88	43.55	33.04	5.45	41.92	-3.43
	10520.00	51.52	PK	H	68.20	16.68	38.83	38.91	10.2	45.35	3.76
	--	--	--	--	--	--	--	--	--	--	--
56.00 5280MHz	10560.00	52.54	PK	H	68.20	15.66	48.79	38.92	10.21	45.38	3.75
	--	--	--	--	--	--	--	--	--	--	--
64.00 5320MHz	5350.50	45.21	PK	H	68.20	22.99	48.48	32.84	5.97	42.08	-3.27
	5350.50	39.65	AV	H	54.00	14.35	42.92	32.84	5.97	42.08	-3.27
	10480.00	52.54	PK	H	68.20	15.66	48.78	38.94	10.23	45.41	3.76

Channel	(MHz)	Level (dBuV/m)	Mode	Pol	(dBuV/m)	(dB)	Value (dBuV)	Factor (dB/m)	Factor (dB)	amplifier (dB)	Factor (dB/m)	
52.00 5260MHz	5150.00	48.32	PK	H	68.20	19.88	51.75	33.04	5.45	41.92	-3.43	
	5150.00	41.43	AV	H	54.00	12.57	44.86	33.04	5.45	41.92	-3.43	
	10520.00	52.67	PK	H	68.20	15.53	38.83	38.91	10.2	45.35	3.76	
	--	--	--	--	--	--	--	--	--	--	--	
56.00 5280MHz	10560.00	51.54	PK	H	68.20	16.66	47.79	38.92	10.21	45.38	3.75	
	--	--	--	--	--	--	--	--	--	--	--	
	64.00 5320MHz	5350.50	46.32	PK	H	68.20	21.88	49.59	32.84	5.97	42.08	-3.27
	5350.50	38.64	AV	H	54.00	15.36	41.91	32.84	5.97	42.08	-3.27	
	10480.00	51.48	PK	H	68.20	16.72	47.72	38.94	10.23	45.41	3.76	

**5500-5700MHz:**

Tested	Frequency	Emission	Detector	ANT	Limit	Margin	Raw	Antenna	Cable	Pre	Correction
Channel	(MHz)	Level	Mode	Pol	(dBuV/m)	(dB)	(dBuV)	Factor	Factor	amplifier	Factor
		(dBuV/m)						(dB/m)	(dB)	(dB)	(dB/m)
	5460.00	56.32	PK	V	68.20	11.88	59.14	33.39	6.01	42.22	-2.82
100.00	5460.00	46.79	AV	V	54.00	7.21	49.61	33.39	6.01	42.22	-2.82
5500MHz	11000.00	51.95	PK	V	68.20	16.25	47.52	39.12	10.85	45.54	4.43
--	--	--	--	--	--	--	--	--	--	--	--
120.00	11160.00	52.79	PK	V	68.20	15.41	48.33	39.07	10.87	45.48	4.46
5580MHz	--	--	--	--	--	--	--	--	--	--	--
140.00	5855.00	53.71	PK	V	68.20	14.49	55.90	33.91	6.17	42.27	-2.19
5700MHz	5855.00	44.21	AV	V	54.00	9.79	46.40	33.91	6.17	42.27	-2.19
	11400.00	51.89	PK	V	68.20	16.31	47.41	39.05	10.9	45.47	4.48

Tested	Frequency	Emission	Detector	ANT	Limit	Margin	Raw	Antenna	Cable	Pre	Correction
Channel	(MHz)	Level	Mode	Pol	(dBuV/m)	(dB)	(dBuV)	Factor	Factor	amplifier	Factor
		(dBuV/m)						(dB/m)	(dB)	(dB)	(dB/m)
	5460.00	55.76	PK	V	68.20	12.44	58.58	33.39	6.01	42.22	-2.82
100.00	5460.00	46.63	AV	V	54.00	7.37	49.45	33.39	6.01	42.22	-2.82
5500MHz	11000.00	52.18	PK	V	68.20	16.02	47.75	39.12	10.85	45.54	4.43
--	--	--	--	--	--	--	--	--	--	--	--
120.00	11160.00	51.39	PK	V	68.20	16.81	46.93	39.07	10.87	45.48	4.46
5580MHz	--	--	--	--	--	--	--	--	--	--	--
140.00	5855.00	52.56	PK	V	68.20	15.64	54.75	33.91	6.17	42.27	-2.19
5700MHz	5855.00	43.57	AV	V	54.00	10.43	45.76	33.91	6.17	42.27	-2.19
	11400.00	52.74	PK	V	68.20	15.46	48.26	39.05	10.9	45.47	4.48

**5725-5850MHz:**

Tested	Frequency	Emission	Detector	ANT	Limit	Margin	Raw	Antenna	Cable	Pre	Correction
Channel	(MHz)	Level	Mode	Pol	(dBuV/m)	(dB)	(dBuV)	Factor	Factor	amplifier	Factor
		(dBuV/m)						(dB/m)	(dB)	(dB)	(dB/m)
	5720.00	56.42	PK	H	68.20	11.78	59.20	33.42	6.04	42.24	-2.78
149.00	5720.00	48.12	AV	H	54.00	5.88	50.90	33.42	6.04	42.24	-2.78
5745MHz	11490.00	50.28	PK	H	68.20	17.92	45.80	39.02	10.91	45.45	4.48
--	--	--	--	--	--	--	--	--	--	--	--
157.00	11570.00	51.95	PK	H	68.20	16.25	47.50	38.93	10.95	45.43	4.45
5785MHz	--	--	--	--	--	--	--	--	--	--	--
48.00	5855.00	55.75	PK	H	68.20	12.45	57.94	33.91	6.17	42.27	-2.19
5825MHz	5855.00	47.21	AV	H	54.00	6.79	49.40	33.91	6.17	42.27	-2.19
	11650.00	51.88	PK	H	68.20	16.32	47.30	38.83	11.16	45.41	4.58

Tested Channel	Frequency (MHz)	Emission Level (dBuV/m)	Detector Mode	ANT Pol	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre amplifier (dB)	Correction Factor (dB/m)
	5720.00	57.31	PK	V	68.20	10.89	60.09	33.42	6.04	42.24	-2.78
149.00	5720.00	48.32	AV	V	54.00	5.68	51.10	33.42	6.04	42.24	-2.78
5745MHz	11490.00	52.64	PK	V	68.20	15.56	48.16	39.02	10.91	45.45	4.48
	--	--	--	--	--	--	--	--	--	--	--
157.00	11570.00	53.11	PK	V	68.20	15.09	48.66	38.93	10.95	45.43	4.45
5785MHz	--	--	--	--	--	--	--	--	--	--	--
48.00	5855.00	56.83	PK	V	68.20	11.37	59.02	33.91	6.17	42.27	-2.19
5825MHz	5855.00	48.19	AV	V	54.00	#VALUE!	#VALUE!	33.91	6.17	42.27	-2.19
	11650.00	52.68	PK	V	68.20	15.52	48.10	38.83	11.16	45.41	4.58

**REMARKS:**

1. Emission level (dB<sub>u</sub>V/m) = Raw Value (dB<sub>u</sub>V) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. Worst case data at 6Mbps at IEEE 802.11a; MCS0 at IEEE 802.11n HT20, IEEE 802.11n HT40, IEEE 802.11ac VHT20, IEEE 802.11ac VHT40 and IEEE 802.11ac VHT80;

**For Conducted Band edge Measurement**

The test results have included the antenna gain

*Please refer to Appendix C and Appendix D.*

### 4.3. Duty Cycle

#### TEST CONFIGURATION



#### TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 B Duty Cycle (x), Transmission Duration (T):

- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- b. The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW  $\geq$  EBW if possible; otherwise, set RBW to the largest available value. Set VBW  $\geq$  RBW. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are  $> 50/T$ , where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)


#### TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.

#### 4.4. Maximum Average Output Power

##### TEST CONFIGURATION



##### TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 Section E3 Measurement using a Power Meter (PM):

- Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
  - The EUT is configured to transmit continuously or to transmit with a constant duty cycle
  - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
  - The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B
- Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding  $10 \log(1/x)$  where x is the duty cycle (e.g.,  $10 \log(1/0.25)$  if the duty cycle is 25 percent).

##### LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed:1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)

Note: The maximum e.i.r.p at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)

##### TEST RESULTS

## 5150-5250MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
36	5180	5.96	0.50	6.46	24.00	PASS
44	5220	6.76	0.36	7.12	24.00	PASS
48	5240	6.32	0.56	6.88	24.00	PASS
802.11n20						
36	5180	6.21	0.53	6.74	24.00	PASS
44	5220	6.34	0.41	6.75	24.00	PASS
48	5240	6.18	0.59	6.77	24.00	PASS
802.11ac20						
36	5180	6.31	0.44	6.75	24.00	PASS
44	5220	6.28	0.56	6.84	24.00	PASS
48	5240	6.29	0.47	6.76	24.00	PASS
802.11n40						
38	5190	6.18	1.11	7.29	24.00	PASS
46	5230	6.02	1.06	7.08	24.00	PASS
802.11ac40						
38	5190	5.89	1.06	6.95	24.00	PASS
46	5230	5.61	0.85	6.46	24.00	PASS
802.11ac80						
42	5210	4.97	2.02	6.99	24.00	PASS

## 5260-5320MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
52	5260	6.43	0.53	6.96	24.00	PASS
60	5300	6.47	0.53	7.00	24.00	PASS
64	5320	6.37	0.53	6.90	24.00	PASS
802.11n20						
52	5260	6.68	0.59	7.27	24.00	PASS
60	5300	6.42	0.38	6.80	24.00	PASS
64	5320	6.39	0.56	6.95	24.00	PASS
802.11ac20						
52	5260	6.29	0.59	6.88	24.00	PASS
60	5300	6.48	0.44	6.92	24.00	PASS
64	5320	6.51	0.50	7.01	24.00	PASS
802.11n40						
54	5270	6.39	1.06	7.45	24.00	PASS
62	5310	6.68	1.02	7.70	24.00	PASS
802.11ac40						
54	5270	6.28	1.11	7.39	24.00	PASS
62	5310	6.37	1.01	7.38	24.00	PASS
802.11ac80						
58	5290	5.12	1.85	6.97	24.00	PASS

## 5500-5700MHz:


Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
100	5500	6.75	0.53	7.28	24.00	PASS
120	5580	6.52	0.50	7.02	24.00	PASS
140	5700	6.68	0.42	7.1	24.00	PASS
802.11n20						
100	5500	6.71	0.47	7.18	24.00	PASS
120	5580	6.62	0.53	7.15	24.00	PASS
140	5700	6.69	0.53	7.22	24.00	PASS
802.11ac20						
100	5500	6.71	0.47	7.18	24.00	PASS
120	5580	6.85	0.59	7.44	24.00	PASS
140	5700	6.78	0.47	7.25	24.00	PASS
802.11n40						
102	5510	6.32	1.02	7.34	24.00	PASS
110	5550	6.45	0.90	7.35	24.00	PASS
134	5670	6.28	1.11	7.39	24.00	PASS
802.11ac40						
102	5510	6.68	1.01	7.69	24.00	PASS
110	5550	6.51	0.96	7.47	24.00	PASS
134	5670	6.72	0.79	7.51	24.00	PASS
802.11ac80						
106	5530	5.45	2.02	7.47	24.00	PASS

## 5725-5850MHz:

Channel	Frequency (MHz)	Output Power AV (dBm)	Duty factor (dB)	Output Power AV + Duty factor (dBm)	Limits (dBm)	Verdict
802.11a						
149	5745	6.58	0.42	7.00	30.00	PASS
157	5785	6.47	0.47	6.94	30.00	PASS
165	5825	6.39	0.47	6.86	30.00	PASS
802.11n20						
149	5745	5.71	0.56	6.27	30.00	PASS
157	5785	5.84	0.50	6.34	30.00	PASS
165	5825	5.75	0.59	6.34	30.00	PASS
802.11ac20						
149	5745	5.83	0.59	6.42	30.00	PASS
157	5785	5.90	0.56	6.46	30.00	PASS
165	5825	5.78	0.53	6.31	30.00	PASS
802.11n40						
151	5755	5.56	0.74	6.30	30.00	PASS
159	5795	5.51	1.01	6.52	30.00	PASS
802.11ac40						
151	5755	5.69	0.90	6.59	30.00	PASS
159	5795	5.74	1.08	6.82	30.00	PASS
802.11ac80						
155	5775	5.49	1.94	7.43	30.00	PASS

## 4.5. Power Spectral Density

### TEST CONFIGURATION



### TEST PROCEDURE

According to KDB 789033 D02 General UNII Test Procedures New Rules v01 F: The rules requires "maximum power spectral density" measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- c. Make the following adjustments to the peak value of the spectrum, if applicable:
  1. If Method SA-2 or SA-2 Alternative was used, add  $10 \log(1/x)$ , where x is the duty cycle, to the peak of the spectrum.
  2. If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d. The result is the Maximum PSD over 1 MHz reference bandwidth.
- e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:
  1. Set RBW  $\geq 1/T$ , where T is defined in section II.B.I.a).
  2. Set VBW  $\geq 3$  RBW.
  3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log(500\text{kHz}/\text{RBW})$  to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
  4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10 \log(1\text{MHz}/\text{RBW})$  to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
  5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.
- f. Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHz is available on nearly all spectrum analyzers.

- f. Adjust the measurement in dBm by adding  $10 \log(1/x)$  where x is the duty cycle (e.g.,  $10 \log(1/0.25)$  if the duty cycle is 25 percent).

### LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:


Frequency Range (MHz)	Limit
5150-5250	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz

### TEST RESULTS

Please refer to Appendix B.

#### 4.6. 6dB Bandwidth

##### TEST CONFIGURATION



##### TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a. Set RBW = 100 kHz.
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

##### LIMIT

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz

##### TEST RESULTS

*Please refer to Appendix A3.*

## 4.7. 26dB Bandwidth

### TEST CONFIGURATION



### TEST PROCEDURE

According to KDB789033 D02 General UNII Test Procedures New Rules v01 for one of the following procedures may be used for Emission Bandwidth (EBW) measurement:

- a. Set RBW = 300 kHz (approximately 1% of the emission bandwidth).
- b. Set the video bandwidth (VBW) = 1000 KHz (VBW > RBW)
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize

g. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

### LIMIT

No Limits for 26dBc Bandwidth

### TEST RESULTS

*Please refer to Appendix A1.*

## 4.8. Antenna Requirement

### Standard Applicable



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **Antenna Information**

The maximum gain of antenna was 0.00 dBi, PIFA antenna, It meets the requirements of 15.203.

## 5. Test Setup Photos of the EUT



## 6. External and Internal Photos of the EUT

Reference to the test report No. CTA2205270070401

.....End of Report.....