

FCC TEST REPORT

FCC ID: 2A7IR-I9SPRO

Report Number. : ZKT-220614L4027

Date of Test : May 23, 2022 -- Jun. 11, 2022

Date of issue : Jun. 11, 2022

Total number of pages : 66

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial
Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Shenzhen Baker Chengrui Technology Co., LTD

Address : 6th Floor, Building 63, Longwangmiao Industrial Zone, Baishixia
East District, Fuyong Town, Baoan District, Shenzhen

Manufacturer's name : Shenzhen Baker Chengrui Technology Co., LTD

Address : 6th Floor, Building 63, Longwangmiao Industrial Zone, Baishixia
East District, Fuyong Town, Baoan District, Shenzhen

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013
KDB558074 D0115.247 Meas Guidance v 05r02

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-112_V0

Test Report Form(s) Originator..... : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : Bluetooth headset

Trademark : N/A

Model/Type reference..... : See page 8 General Description of EUT

Ratings..... : DC 3.7V from internal battery
DC3.7V from charging-base

Testing procedure and testing location:

Testing Laboratory: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature): Alen He



Reviewer (name + signature): Joe Liu



Approved (name + signature).....: Lake Xie



Table of Contents

	Page
1. VERSION	5
2. TEST SUMMARY	6
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	9
3.3 Support Equipment	9
3.4 Test Mode	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	12
4.1 Conducted emissions	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 Test Result	13
4.2 Radiated emissions	15
4.2.1 Radiated Emission Limits	15
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
4.2.6 TEST RESULTS	18
5. RADIATED BAND EMISSION MEASUREMENT	27
5.1 Test Requirement:	27
5.2 TEST PROCEDURE	27
5.3 DEVIATION FROM TEST STANDARD	28
5.4 TEST SETUP	28
5.5 EUT OPERATING CONDITIONS	28
5.6 TEST RESULT	29
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	31
6.1 Limit	31
6.2 Test Setup	31
6.3 Test procedure	31
6.4 DEVIATION FROM STANDARD	31
6.5 Test Result	31
7. 20DB BANDWIDTH	47
7.1 Test Setup	47
7.2 Limit	47
7.3 Test procedure	47
7.4 DEVIATION FROM STANDARD	47
7.5 Test Result	47
8. MAXIMUM PEAK OUTPUT POWER	51
8.1 Block Diagram Of Test Setup	51
8.2 Limit	51

8.3 Test procedure	51
8.4 DEVIATION FROM STANDARD	51
8.5 Test Result	51
9.1 Test Setup	52
9.2 Test procedure	52
9.3 DEVIATION FROM STANDARD	52
9.4 Test Result	52
10.NUMBER OF HOPPING FREQUENCY.....	56
10.1 Test Setup	56
10.2 Test procedure	56
10.3 DEVIATION FROM STANDARD	56
10.4 Test Result	57
11. DWELL TIME.....	58
11.1 Test Setup	58
11.2 Test procedure	58
11.3 DEVIATION FROM STANDARD	58
11.4 Test Result	59
12. ANTENNA REQUIREMENT	63
13. TEST SETUP PHOTO	64
14. EUT CONSTRUCTIONAL DETAILS	66

1. VERSION

Report No.	Version	Description	Approved
ZKT-220614L4027	Rev.01	Initial issue of report	Jun. 11, 2022

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission	PASS	
15.247(d)	Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Bluetooth headset
Model No.:	I9S PRO
Model Different.:	There are many models of this product, Their electrical circuit design, layout, components used and internal wiring are identical, Only the name and color will be different .
Serial No.:	M8, M6TWS, PROB, PROC, PROD, PROE, PROE, PROF, PROG, PROH, A01, A02, A03A, A03B, A03C, A03D, A03E, A03F, I7SA, I7SB, I7SC, I7SD, I7SE, A06, A06A, A06B, A06C, A06D, A07, A07A, A08, A08A, A09, A09A, A09B, A09C, A11, A11A, A11B, A11C, A11D, 12, 12A, I12, I12A, I12B, I12C, I12PRO, I12PROA, I12PROB, I12PROC, PRO3S, I4PROS, I4PROSA, I3PRO, I3PROS, A20, A21, Q30, A22, W12twS, I7S, W12twSA, J9, V9, I7mini, I7miniA, I7miniB, I7miniC, I7miniD, R3, W12, W12D, I7SA, M1, LB-8, LB-8B, G3, B3, W2C, W2F, T9, T9A, T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T11, T12, T13, T14, T15, T16, T17, T18, T19, T20, G1, G3, G4, G5, G6, G7, G8, G9, G10, G11, G12, G13, G14, G15, G16, G17, G18, G19, G20, R3, R4, R5, R6, R7, R8, R9, R10, R11, AB2, AB3, AB4, AB5, AB6, AG2, AG3, AG4, AG5, AC2, AC3, AC4, AC5, AC6, AV7, AV8, AV9, AVB1, AVB2, AVB3, AVB4, AC201, AC202, AC203, AC204, AC205, AC206, AC207, AC208, AC209, AC210
Hardware Version:	V2.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi
Power supply:	DC 3.7V from internal battery DC3.7V from charging-base

Note: The EUT is divided into two parts, left and right. After comparison, the circuits of the left and right parts are the same. The test result of this report is to test the left part.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz

12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration

Conducted Emission

DC Line	EUT
---------	-----

Radiated Emission

DC Line	EUT
---------	-----

Conducted Spurious

DC Line	EUT
---------	-----

3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	adapter	HUAWEI	HW-100400C01	/	Provid by lab


Item	Shielded Type	Ferrite Core	Length	Note
------	---------------	--------------	--------	------

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	
Power level setup	<10dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 21, 2021	Sep. 22, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 21, 2021	Sep. 22, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Sep. 21, 2021	Sep. 22, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 21, 2021	Sep. 22, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 21, 2021	Sep. 22, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 21, 2021	Sep. 22, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 21, 2021	Sep. 22, 2022
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Sep. 21, 2021	Sep. 22, 2022
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 21, 2021	Sep. 22, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 21, 2021	Sep. 22, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 21, 2021	Sep. 22, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 21, 2021	Sep. 22, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 21, 2021	Sep. 22, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 21, 2021	Sep. 22, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Sep. 21, 2021	Sep. 22, 2022
3	Test Cable	N/A	C01	N/A	Sep. 21, 2021	Sep. 22, 2022
4	Test Cable	N/A	C02	N/A	Sep. 21, 2021	Sep. 22, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 21, 2021	Sep. 22, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 21, 2021	Sep. 22, 2022

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperatur:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test mode:	




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1580	26.34	9.75	36.09	65.56	-29.47	QP	
2	0.1580	12.71	9.75	22.46	55.56	-33.10	AVG	
3	0.4900	26.20	9.85	36.05	56.17	-20.12	QP	
4 *	0.5020	20.01	9.85	29.86	46.00	-16.14	AVG	
5	0.9620	18.80	9.77	28.57	56.00	-27.43	QP	
6	1.0660	8.97	9.75	18.72	46.00	-27.28	AVG	
7	1.5660	6.68	9.68	16.36	46.00	-29.64	AVG	
8	1.6019	17.19	9.68	26.87	56.00	-29.13	QP	
9	3.4100	5.39	9.69	15.08	46.00	-30.92	AVG	
10	3.8460	15.49	9.68	25.17	56.00	-30.83	QP	
11	12.4340	-0.41	9.75	9.34	50.00	-40.66	AVG	
12	15.0740	10.80	9.66	20.46	60.00	-39.54	QP	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperatur:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test mode:	



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1901	28.21	9.75	37.96	64.03	-26.07	QP	
2	0.2381	10.66	9.77	20.43	52.16	-31.73	AVG	
3	0.4941	29.41	9.85	39.26	56.10	-16.84	QP	
4 *	0.5021	20.93	9.85	30.78	46.00	-15.22	AVG	
5	0.9741	21.51	9.77	31.28	56.00	-24.72	QP	
6	1.1461	12.15	9.74	21.89	46.00	-24.11	AVG	
7	1.4581	21.37	9.70	31.07	56.00	-24.93	QP	
8	1.5701	12.06	9.68	21.74	46.00	-24.26	AVG	
9	2.0061	10.74	9.65	20.39	46.00	-25.61	AVG	
10	2.4541	21.69	9.68	31.37	56.00	-24.63	QP	
11	6.1061	21.51	9.64	31.15	60.00	-28.85	QP	
12	6.1461	10.60	9.64	20.24	50.00	-29.76	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. when charging, BT can not transmit

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	DC 5.0V	Test mode	Charging




Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 5.0V	Test mode	Charging




Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. when charging, BT can not transmit

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V	Test mode	BT



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3.7V	Test mode	BT



Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. when charging ,BT can not transmit

1GHz~25GHz

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	53.94	30.55	5.77	24.66	53.82	74.00	-20.18	Pk
V	4804	44.44	30.55	5.77	24.66	44.32	54.00	-9.68	AV
V	7206	57.15	30.33	6.32	24.55	57.69	74.00	-16.31	Pk
V	7206	45.93	30.33	6.32	24.55	46.47	54.00	-7.53	AV
V	9608	43.82	30.85	7.45	24.69	45.11	74.00	-28.89	Pk
V	9608	43.79	30.85	7.45	24.69	45.08	54.00	-8.92	AV
H	4804	45.32	31.02	8.99	25.57	48.86	74.00	-25.14	Pk
H	4804	46.21	31.02	8.99	25.57	49.75	54.00	-4.25	AV
H	7206	45.47	30.55	5.77	24.66	45.35	74.00	-28.65	Pk
H	7206	45.16	30.55	5.77	24.66	45.04	54.00	-8.96	AV
H	9608	45.76	30.33	6.32	24.55	46.30	74.00	-27.70	Pk
H	9608	45.33	30.33	6.32	24.55	45.87	54.00	-8.13	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	56.87	30.55	5.77	24.66	56.75	74.00	-17.25	Pk
V	4882	44.28	30.55	5.77	24.66	44.16	54.00	-9.84	AV
V	7323	56.59	30.33	6.32	24.55	57.13	74.00	-16.87	Pk
V	7323	47.23	30.33	6.32	24.55	47.77	54.00	-6.23	AV
V	9764	44.15	30.85	7.45	24.69	45.44	74.00	-28.56	Pk
V	9764	45.22	30.85	7.45	24.69	46.51	54.00	-7.49	AV
H	4882	44.64	31.02	8.99	25.57	48.18	74.00	-25.82	Pk
H	4882	44.67	31.02	8.99	25.57	48.21	54.00	-5.79	AV
H	7323	44.45	30.55	5.77	24.66	44.33	74.00	-29.67	Pk
H	7323	44.10	30.55	5.77	24.66	43.98	54.00	-10.02	AV
H	9764	44.76	30.33	6.32	24.55	45.30	74.00	-28.70	Pk
H	9764	43.75	30.33	6.32	24.55	44.29	54.00	-9.71	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960	55.68	30.55	5.77	24.66	55.56	74.00	-18.44	Pk
V	4960	44.40	30.55	5.77	24.66	44.28	54.00	-9.72	AV
V	7440	54.70	30.33	6.32	24.55	55.24	74.00	-18.76	Pk
V	7440	47.06	30.33	6.32	24.55	47.60	54.00	-6.40	AV
V	9920	45.49	30.85	7.45	24.69	46.78	74.00	-27.22	Pk
V	9920	45.59	30.85	7.45	24.69	46.88	54.00	-7.12	AV
H	4960	44.12	31.02	8.99	25.57	47.66	74.00	-26.34	Pk
H	4960	45.87	31.02	8.99	25.57	49.41	54.00	-4.59	AV
H	7440	44.93	30.55	5.77	24.66	44.81	74.00	-29.19	Pk
H	7440	43.88	30.55	5.77	24.66	43.76	54.00	-10.24	AV
H	9920	46.34	30.33	6.32	24.55	46.88	74.00	-27.12	Pk
H	9920	44.11	30.33	6.32	24.55	44.65	54.00	-9.35	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

$\pi/4$ -DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804	55.55	30.55	5.77	24.66	55.43	74.00	-18.57	Pk
V	4804	45.22	30.55	5.77	24.66	45.10	54.00	-8.90	AV
V	7206	54.70	30.33	6.32	24.55	55.24	74.00	-18.76	Pk
V	7206	45.68	30.33	6.32	24.55	46.22	54.00	-7.78	AV
V	9608	46.39	30.85	7.45	24.69	47.68	74.00	-26.32	Pk
V	9608	45.41	30.85	7.45	24.69	46.70	54.00	-7.30	AV
H	4804	43.65	31.02	8.99	25.57	47.19	74.00	-26.81	Pk
H	4804	44.84	31.02	8.99	25.57	48.38	54.00	-5.62	AV
H	7206	46.34	30.55	5.77	24.66	46.22	74.00	-27.78	Pk
H	7206	44.48	30.55	5.77	24.66	44.36	54.00	-9.64	AV
H	9608	44.02	30.33	6.32	24.55	44.56	74.00	-29.44	Pk
H	9608	43.78	30.33	6.32	24.55	44.32	54.00	-9.68	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	57.29	30.55	5.77	24.66	57.17	74.00	-16.83	Pk
V	4882	43.69	30.55	5.77	24.66	43.57	54.00	-10.43	AV
V	7323	56.23	30.33	6.32	24.55	56.77	74.00	-17.23	Pk
V	7323	46.48	30.33	6.32	24.55	47.02	54.00	-6.98	AV
V	9764	44.92	30.85	7.45	24.69	46.21	74.00	-27.79	Pk
V	9764	43.95	30.85	7.45	24.69	45.24	54.00	-8.76	AV
H	4882	44.23	31.02	8.99	25.57	47.77	74.00	-26.23	Pk
H	4882	43.86	31.02	8.99	25.57	47.40	54.00	-6.60	AV
H	7323	44.68	30.55	5.77	24.66	44.56	74.00	-29.44	Pk
H	7323	43.72	30.55	5.77	24.66	43.60	54.00	-10.40	AV
H	9764	44.20	30.33	6.32	24.55	44.74	74.00	-29.26	Pk
H	9764	44.18	30.33	6.32	24.55	44.72	54.00	-9.28	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960	55.67	30.55	5.77	24.66	55.55	74.00	-18.45	Pk
V	4960	44.52	30.55	5.77	24.66	44.40	54.00	-9.60	AV
V	7440	57.56	30.33	6.32	24.55	58.10	74.00	-15.90	Pk
V	7440	46.35	30.33	6.32	24.55	46.89	54.00	-7.11	AV
V	9920	45.02	30.85	7.45	24.69	46.31	74.00	-27.69	Pk
V	9920	45.82	30.85	7.45	24.69	47.11	54.00	-6.89	AV
H	4960	46.28	31.02	8.99	25.57	49.82	74.00	-24.18	Pk
H	4960	45.12	31.02	8.99	25.57	48.66	54.00	-5.34	AV
H	7440	45.03	30.55	5.77	24.66	44.91	74.00	-29.09	Pk
H	7440	43.71	30.55	5.77	24.66	43.59	54.00	-10.41	AV
H	9920	46.29	30.33	6.32	24.55	46.83	74.00	-27.17	Pk
H	9920	45.46	30.33	6.32	24.55	46.00	54.00	-8.00	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8-DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804	54.31	30.55	5.77	24.66	54.19	74.00	-19.81	Pk
V	4804	44.40	30.55	5.77	24.66	44.28	54.00	-9.72	AV
V	7206	54.68	30.33	6.32	24.55	55.22	74.00	-18.78	Pk
V	7206	46.78	30.33	6.32	24.55	47.32	54.00	-6.68	AV
V	9608	44.23	30.85	7.45	24.69	45.52	74.00	-28.48	Pk
V	9608	43.73	30.85	7.45	24.69	45.02	54.00	-8.98	AV
H	4804	46.30	31.02	8.99	25.57	49.84	74.00	-24.16	Pk
H	4804	44.17	31.02	8.99	25.57	47.71	54.00	-6.29	AV
H	7206	45.38	30.55	5.77	24.66	45.26	74.00	-28.74	Pk
H	7206	46.43	30.55	5.77	24.66	46.31	54.00	-7.69	AV
H	9608	45.57	30.33	6.32	24.55	46.11	74.00	-27.89	Pk
H	9608	46.49	30.33	6.32	24.55	47.03	54.00	-6.97	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882	57.07	30.55	5.77	24.66	56.95	74.00	-17.05	Pk
V	4882	45.44	30.55	5.77	24.66	45.32	54.00	-8.68	AV
V	7323	55.19	30.33	6.32	24.55	55.73	74.00	-18.27	Pk
V	7323	45.31	30.33	6.32	24.55	45.85	54.00	-8.15	AV
V	9764	44.70	30.85	7.45	24.69	45.99	74.00	-28.01	Pk
V	9764	44.97	30.85	7.45	24.69	46.26	54.00	-7.74	AV
H	4882	46.16	31.02	8.99	25.57	49.70	74.00	-24.30	Pk
H	4882	43.71	31.02	8.99	25.57	47.25	54.00	-6.75	AV
H	7323	45.28	30.55	5.77	24.66	45.16	74.00	-28.84	Pk
H	7323	44.65	30.55	5.77	24.66	44.53	54.00	-9.47	AV
H	9764	46.57	30.33	6.32	24.55	47.11	74.00	-26.89	Pk
H	9764	44.24	30.33	6.32	24.55	44.78	54.00	-9.22	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960	52.39	30.55	5.77	24.66	52.27	74.00	-21.73	Pk
V	4960	44.13	30.55	5.77	24.66	44.01	54.00	-9.99	AV
V	7440	55.90	30.33	6.32	24.55	56.44	74.00	-17.56	Pk
V	7440	45.26	30.33	6.32	24.55	45.80	54.00	-8.20	AV
V	9920	46.59	30.85	7.45	24.69	47.88	74.00	-26.12	Pk
V	9920	45.76	30.85	7.45	24.69	47.05	54.00	-6.95	AV
H	4960	45.41	31.02	8.99	25.57	48.95	74.00	-25.05	Pk
H	4960	43.66	31.02	8.99	25.57	47.20	54.00	-6.80	AV
H	7440	44.60	30.55	5.77	24.66	44.48	74.00	-29.52	Pk
H	7440	44.46	30.55	5.77	24.66	44.34	54.00	-9.66	AV
H	9920	45.51	30.33	6.32	24.55	46.05	74.00	-27.95	Pk
H	9920	45.40	30.33	6.32	24.55	45.94	54.00	-8.06	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- The limit for radiated test was performed according to FCC PART 15C.
- The tighter limit applies at the band edges.
- Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequenc y (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV /m)	Detec tor Type	Resul t
GFSK	Low Channel: 2402MHz									
	H	2390.00	56.74	30.22	4.85	23.98	55.35	74.00	PK	PASS
	H	2390.00	42.89	30.22	4.85	23.98	41.50	54.00	AV	PASS
	H	2400.00	56.26	30.22	4.85	23.98	54.87	74.00	PK	PASS
	H	2400.00	47.39	30.22	4.85	23.98	46.00	54.00	AV	PASS
	V	2390.00	56.52	30.22	4.85	23.98	55.13	74.00	PK	PASS
	V	2390.00	45.60	30.22	4.85	23.98	44.21	54.00	AV	PASS
	V	2400.00	56.28	30.22	4.85	23.98	54.89	74.00	PK	PASS
	V	2400.00	46.19	30.22	4.85	23.98	44.80	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	57.66	30.22	4.85	23.98	56.27	74.00	PK	PASS
	H	2485.50	44.89	30.22	4.85	23.98	43.50	54.00	AV	PASS
	H	2483.50	56.79	30.22	4.85	23.98	55.40	74.00	PK	PASS
	H	2485.50	45.89	30.22	4.85	23.98	44.50	54.00	AV	PASS
	V	2483.50	57.03	30.22	4.85	23.98	55.64	74.00	PK	PASS
	V	2485.50	43.96	30.22	4.85	23.98	42.57	54.00	AV	PASS
	V	2483.50	56.09	30.22	4.85	23.98	54.70	74.00	PK	PASS
	V	2485.50	45.96	30.22	4.85	23.98	44.57	54.00	AV	PASS
$\pi/4$ -DQPSK	Low Channel: 2402MHz									
	H	2390.00	56.19	30.22	4.85	23.98	54.80	74.00	PK	PASS
	H	2390.00	44.57	30.22	4.85	23.98	43.18	54.00	AV	PASS
	H	2400.00	55.13	30.22	4.85	23.98	53.74	74.00	PK	PASS
	H	2400.00	44.87	30.22	4.85	23.98	43.48	54.00	AV	PASS
	V	2390.00	56.29	30.22	4.85	23.98	54.90	74.00	PK	PASS
	V	2390.00	43.57	30.22	4.85	23.98	42.18	54.00	AV	PASS
	V	2400.00	56.85	30.22	4.85	23.98	55.46	74.00	PK	PASS
	V	2400.00	47.23	30.22	4.85	23.98	45.84	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	54.13	30.22	4.85	23.98	52.74	74.00	PK	PASS
	H	2485.50	45.38	30.22	4.85	23.98	43.99	54.00	AV	PASS
	H	2483.50	56.39	30.22	4.85	23.98	55.00	74.00	PK	PASS
	H	2485.50	45.85	30.22	4.85	23.98	44.46	54.00	AV	PASS
	V	2483.50	52.28	30.22	4.85	23.98	50.89	74.00	PK	PASS
	V	2485.50	43.55	30.22	4.85	23.98	42.16	54.00	AV	PASS
	V	2483.50	57.01	30.22	4.85	23.98	55.62	74.00	PK	PASS
	V	2485.50	45.51	30.22	4.85	23.98	44.12	54.00	AV	PASS

8-DPSK	Low Channel: 2402MHz									
	H	2390.00	54.23	30.22	4.85	23.98	52.84	74.00	PK	PASS
	H	2390.00	44.06	30.22	4.85	23.98	42.67	54.00	AV	PASS
	H	2400.00	56.69	30.22	4.85	23.98	55.30	74.00	PK	PASS
	H	2400.00	45.66	30.22	4.85	23.98	44.27	54.00	AV	PASS
	V	2390.00	53.41	30.22	4.85	23.98	52.02	74.00	PK	PASS
	V	2390.00	44.43	30.22	4.85	23.98	43.04	54.00	AV	PASS
	V	2400.00	55.32	30.22	4.85	23.98	53.93	74.00	PK	PASS
	V	2400.00	46.86	30.22	4.85	23.98	45.47	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	54.77	30.22	4.85	23.98	53.38	74.00	PK	PASS
	H	2485.50	45.52	30.22	4.85	23.98	44.13	54.00	AV	PASS
	H	2483.50	57.07	30.22	4.85	23.98	55.68	74.00	PK	PASS
	H	2485.50	47.52	30.22	4.85	23.98	46.13	54.00	AV	PASS
	V	2483.50	57.69	30.22	4.85	23.98	56.30	74.00	PK	PASS
	V	2485.50	43.06	30.22	4.85	23.98	41.67	54.00	AV	PASS
	V	2483.50	56.37	30.22	4.85	23.98	54.98	74.00	PK	PASS
	V	2485.50	44.94	30.22	4.85	23.98	43.55	54.00	AV	PASS
Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.


6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result

GFSK mode:

Test channel:	Lowest channel
---------------	----------------




Test channel:

Middle channel




Test channel:	Highest channel
---------------	-----------------




$\pi/4$ -DQPSK mode:

Test channel:	Lowest channel
---------------	----------------




Test channel:

Middle channel



Test channel:


Highest channel



8-DPSK mode:


Test channel:

Lowest channel




Test channel:

Middle channel




Test channel:


Highest channel




GFSK No-hopping Band edge-left side




GFSK Hopping Band edge-left side




GFSK No-hopping Band edge-right side




GFSK Hopping Band edge-right side




$\pi/4$ -DQPSK No-hopping Band edge-left side




$\pi/4$ -DQPSK Hopping Band edge-left side




$\pi/4$ -DQPSK No-hopping Band edge-right side




$\pi/4$ -DQPSK Hopping Band edge-right side




8-DPSK No-hopping Band edge-left side




8-DPSK Hopping Band edge-left side



8-DPSK No-hopping Band edge-right side




8-DPSK Hopping Band edge-right side



7. 20DB BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 20 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.8976	Pass
	Middle	0.9269	
	Highest	0.8846	
$\pi/4$ -DQPSK	Lowest	1.206	Pass
	Middle	1.214	
	Highest	1.217	
8-DPSK	Lowest	1.261	Pass
	Middle	1.288	
	Highest	1.254	

Test plots

GFSK Low Channel




GFSK Middle Channel




GFSK High Channel




$\pi/4$ -DQPSK Low Channel




$\pi/4$ -DQPSK Middle Channel




$\pi/4$ -DQPSK High Channel



8-DPSK Low Channel



8-DPSK Middle Channel




8-DPSK High Channel



8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Limit:	21

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

8.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD

No deviation.


8.5 Test Result

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	2.528	21	Pass
	Middle	1.623		
	Highest	0.926		
$\pi/4$ -DQPSK	Lowest	3.126	21	Pass
	Middle	2.345		
	Highest	1.654		
8-DPSK	Lowest	3.81	21	Pass
	Middle	2.916		
	Highest	2.169		

9. Hopping Channel Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


9.3 DEVIATION FROM STANDARD

No deviation.


9.4 Test Result

Modulation	Test Channel	Separation (MHz)	Limit(MHz)	Result
GFSK	Low	0.999	0.8976	PASS
GFSK	Middle	1.001	0.9269	PASS
GFSK	High	0.997	0.8846	PASS
$\pi/4$ -DQPSK	Low	0.996	0.804	PASS
$\pi/4$ -DQPSK	Middle	1.001	0.809	PASS
$\pi/4$ -DQPSK	High	0.997	0.811	PASS
8-DPSK	Low	0.996	0.841	PASS
8-DPSK	Middle	1.003	0.859	PASS
8-DPSK	High	0.997	0.836	PASS

Test plots GFSK Low Channel




GFSK Middle Channel




GFSK High Channel




$\pi/4$ -DQPSK Low Channel



$\pi/4$ -DQPSK Middle Channel




$\pi/4$ -DQPSK High Channel




8-DPSK Low Channel



8-DPSK Middle Channel



8-DPSK High Channel



10.NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD


No deviation.

10.4 Test Result


Test Plots: 79 Channels in total GFSK



$\pi/4$ -DQPSK



8-DPSK



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

11.3 DEVIATION FROM STANDARD

No deviation.

11.4 Test Result


Frequency	Packet	Burst Width [ms/hop/ch]	Dwell time(ms)	Limit(ms)	Result
2441MHz	DH1	0.3988	127.616	400	Pass
2441MHz	DH3	1.654	264.640	400	Pass
2441MHz	DH5	2.903	309.653	400	Pass
2441MHz	2DH1	0.4081	130.592	400	Pass
2441MHz	2DH3	1.661	265.760	400	Pass
2441MHz	2DH5	2.910	310.400	400	Pass
2441MHz	3DH1	0.4101	131.232	400	Pass
2441MHz	3DH3	1.660	265.600	400	Pass
2441MHz	3DH5	2.911	310.507	400	Pass

Remarks:


The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
Test channel: 2402MHz as blow
DH1 2DH1 3DH1 time slot= $\text{Burst Width(ms)} \times (1600 / (2 \times 79)) \times 31.6$
DH3 2DH3 3DH3 time slot= $\text{Burst Width(ms)} \times (1600 / (4 \times 79)) \times 31.6$
DH5 2DH5 3DH5 time slot= $\text{Burst Width(ms)} \times (1600 / (6 \times 79)) \times 31.6$

Test Plots


GFSK DH1 2441MHZ




GFSK DH3 2441MHZ




GFSK DH5 2441MHZ




$\pi/4$ -DQPSK 2DH1 2441MHZ




$\pi/4$ -DQPSK 2DH3 2441MHZ




$\pi/4$ -DQPSK 2DH5 2441MHZ




8-DPSK 3DH1 2441MHZ




8-DPSK 3DH3 2441MHZ



8-DPSK 3DH5 2441MHZ



12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, the best case gain of the antennas are 0dBi, reference to the below photo for details ANT for BT 	

13. Test Setup Photo





14. EUT Constructional Details

Reference to the External photos file and internal photos file for details.

******* END OF REPORT *******