

Sainlogic SA7 Weather Station User Manual

Content

1. Introduction	3
2. Warning and Cautions	3
3. Quick Start Guide	3
4. Assembly of sensor arrays	4
4.1. Parts List	4
4.2. Recommended tools	5
4.3. Remove/Install the Wind Vane	6
4.4. Remove/Install the Wind Cup	7
4.5. Remove/ Install the rain collector	7
4.6. Installation of coil filters	8
4.7. Install Battery	9
5. Installation of the Sensor Array	11
5.1. Pre-installation Check	11
5.2. Site Survey	11
5.3. Adjusting the Sensor Mounting Direction	11
5.3.1. Northern Hemisphere Reference	12
5.3.2. Southern Hemisphere Reference	13
5.4. Securing the Mounting Pole	14
5.4.1. Horizontal mounting and fixing sensors	14
5.4.2. Vertical mounting and fixing sensors	15
5.4.3. Best Practices for Wireless Communication	16
6. Install the gateway	17
6.1. Button Operation	17
7. Display connected to WiFi	19
7.1. Real-time Network Monitoring	19
7.2. APP Download	19
7.3. APP Account Register and Login	19
7.3.1. Registering Process	19
7.3.2. Login process	20
7.4. Connecting Steps	21
7.4.1. Bluetooth Distribution Network Mode	21
7.4.2. Wifi Distribution Network Mode	24
7.4.3. Web page distribution network mode	28
7.5. Firmware Upgrade	32
7.6. Sign up on Wunderground.com	33
8. Time Zone	36
9. Data Discussion	38
10. Feels Like Temperatures	40
11. Glossary of Terms	41

12.Specifications	42
12.1. Wireless specifications	42
12.2. Measurement Specifications	42
12.3. Power Consumption	43
13. Maintenance	44
14. Troubleshooting Guide	44
15.Disclaimer	47
16. Warranty Information	47
17. FCC Statement	48

1. Introduction

Thank you for purchasing the Sainlogic Professional WiFi Wireless Weather Station. The following user guide provides detailed instructions on installation, operation and troubleshooting. This product is constantly changing and improving, especially the online services and associated applications.

To download the latest manuals and other help, please contact Customer Support.

Customer Support Email: info@sainlogic.com

Website: www.sainlogic.com

Customer Support Phone (Skype): +1 508 758 0493 (Mon-Sat 10 a.m. - 2 p.m, Eastern Standard Time)

2. Warning and Cautions

⚠ WARNING: Lightning strikes can be caused by any metal object, including your weather station mounting pole. Mounting your weather station during a storm is prohibited.

⚠ WARNING: Installing a weather station in an elevated location may result in injury or death, so perform as many preliminary checks and operations as possible on the ground and inside a building or house.

⚠ WARNING: Install the weather station on a clear, dry day.

3. Quick Start Guide

The following Quick Start Guide provides the necessary steps to install and operate the weather station.

1	Assembling and activating the outdoor sensor array	4-5
2	Gateway button definition	6
3	Connecting the device to Wi-Fi	7
4	Data Definition and Discussion	8-11
5	Specification	12
6	Troubleshooting	14

4. Assembly of sensor arrays








Figure 1

NO	Description	NO	Description
1	Wind Cup	7	Reset Button/LED Indicator
2	Solar Panel	8	Battery Door
3	Wind Vane	9	Mounting Pole Socket
4	Bubble Level		
5	Thermometer-Hygrometer Sensor		
6	Rain Collector		

4.1. Parts List


The weather station consists of the following parts.

QTY	Item	image
1	Gateway: Frame Dimensions: 3.1x3.1x3.6inch (78x78*91mm)	
1	Integrated Outdoor Transmitter Dimensions: Transmitter Dimensions: 12.9x4x9.8inch (327*101*249mm)	

1	Foot Mounting (with pole insert) Dimensions: 4.25x4.1x1.75inch (107x104x44.5mm)	
1	Mounting Bracket Back Plate (polemount) Dimensions: 4x3.25x1inch (101x82x25mm)	
1	Mounting Pole Dimensions: 12.8x1.3x0.9inch (325x33x22mm)	
2	Pole mounting nuts (M3) / bolts Ø3	
4	Pole mounting nuts (M5) / bolts (Ø5)	
4	Tapping screws	
1	Manual	
1	Power Adapter	

4.2. Recommended tools

We recommend using the following tools to assist in the installation of the weather station.

1	Precision screwdriver (for small Phillips screws)	
---	---	--

2	Compass or GPS (for wind direction calibration)	
3	Adjustable wrench	

4.3. Remove/Install the Wind Vane

Remove the wind vane: (refer to Figure 2)

- Locate the black waterproof silicone plug in the center of the round cap at the top of the wind vane and pick it out with a tool.
- Use a precision screwdriver to loosen the set screw in the round hole until the wind vane can be easily removed.




Figure 2

Install the Wind Vane:

- Put the round hole at the bottom of the wind vane against the wind vane shaft and tighten the fixing screws with a precision screwdriver to make sure the wind vane can rotate freely.
- Insert the black waterproof silicone plug into the round hole at the top of the wind vane and make sure it fits into the round hole to achieve waterproof effect.

 **Note:** The wind vane axis cannot rotate freely like the wind cup, which is specially designed by us.

4.4.Remove/Install the Wind Cup

Remove the wind cup: (refer to Figure 3)

- (a) Locate the black waterproof silicone plug in the center of the round cap at the top of the wind cup and pick it out with a tool.
- (b) Use a precision screwdriver to loosen the set screw in the round hole until the wind cup can be easily removed.




Figure 3

Install the wind cup:

- (a) Place the round hole at the bottom of the wind cup against the wind vane axis and tighten the fixing screw with a precision screwdriver to ensure that the wind cup can rotate freely.
- (b) Insert the black waterproof silicone plug into the round hole at the top of the wind cup and make sure it fits the hole to achieve waterproof effect.

4.5.Remove/ Install the rain collector

Remove the rain collector: (refer to Figure 4)

- (a) With your hand flat on top of the rain collector, grasp the entire rain collector and rotate it clockwise.
- (b) Remove the rain collector vertically upwards when a click is heard.




Figure 4

Remove the rain collector: (refer to Figure 5)

- Align the snap on the bottom edge of the rain collector with the snap notch on the transmitter so that the two fit perfectly, then press the rain collector down vertically.
- After placing the rain collector into the groove, rotate it counterclockwise and it will be installed successfully when you hear a click.




Figure 5

4.6. Installation of coil filters

- Place the coil vertically into the rain collector (hook facing downward) so that the coil fits snugly against the bottom of the rain collector.
- Gently press the coil so that it hooks into the hole at the bottom of the rain collector and locks into place. The tension of the spring will keep the filter tightly fitted to the rain collector.




Figure 6

4.7. Install Battery

Find the battery door at the bottom of the transmitter, as shown in Figure 7.




Figure 7

 **Note: Do not install the batteries backwards.** You can permanently damage the outdoor sensors. The solar panel does not charge the batteries, so rechargeable batteries are not recommended.

Remove the battery door on the back of the sensor by removing the set screw, as show in Figure 8.



Figure 8

Insert 3 new AA batteries and close the battery door as shown. Before closing the battery door and tightening the set screws, make sure the washers (around the inside perimeter of the battery door) are properly secured in their tracks.



Figure 9

 **Note:** We recommend installing AA lithium batteries for the Outdoor Sensor in cold weather environments.

When the battery is installed, the Integrated Outdoor Sensor LED indicator will illuminate for 3 seconds and then blink every 16 seconds. The sensor is transmitting data each time it blinks.




Figure 10

 **NOTE:** If the sensor LED does not flash after inserting the batteries, press the reset button on the bottom of the sensor as shown in Figure 10.

5. Installation of the Sensor Array

5.1. Pre-installation Check

Before installing the weather station at a permanent location, we recommend running it at a temporary, easily accessible location for one week. This allows you to check all functions in advance, ensure they are operating correctly, and familiarize yourself with the weather station and calibration procedures.

5.2. Site Survey


Before installing the weather station, consider the following points during the site survey:

1. The rain gauge must be cleaned every 3 months and the battery should be replaced every 3 months.
2. Avoid heat radiation transfer from buildings and structures. Generally, the sensor array should be installed at least 5 feet (1.5 meters) away from any buildings, structures, ground, or roofs.
3. Avoid influencing wind speed and rainfall measurements. The installation distance of the sensor array should be at least four times the height of the highest obstacle. For example, if a building is 20 feet (6 meters) high and the installation pole is 6 feet (2 meters) high, the installation distance should be $4 \times (20 - 6) = 56$ feet (17 meters). If the weather station is installed close to tall buildings, wind speed and rainfall measurements will be inaccurate.
4. Radio signal range. Assuming no interference from buildings, trees, vehicles, high-voltage lines, etc., the radio communication distance between the display console and the transmitter can reach up to 330 feet (100 meters). In most cases, due to interference from buildings and walls, most wireless applications can only reach up to 100 feet (30 meters). Radio signals cannot penetrate metal buildings.
5. In the worst-case scenario, radio interference from personal computers, radios, or televisions can completely cut off radio communication. Therefore, consider this when selecting the display console or installation location.

5.3. Adjusting the Sensor Mounting Direction

This professional weather station can be used in both the Northern and Southern Hemispheres. To ensure the accuracy of the wind direction display, please secure the direction of the integrated outdoor sensor before installation.

 **Note:** Wind direction is indicated by the letters N, E, S, and W. (N is north, E is east, S is south, W is west)



Southern Hemisphere

Figure 11

5.3.1. Northern Hemisphere Reference

The body of the outdoor sensor is embossed with the four cardinal directions: N, E, S, W, which are applicable only in the Northern Hemisphere.

Step 1: As shown in the diagram, there is an "S" indicator on the wind vane representing south.

Using a compass, check the direction and adjust the orientation of the entire sensor to ensure the "S" mark on the sensor aligns with the south.




Figure 12

Step 2: On the display console, set the location region to the Northern Hemisphere (NOR will appear in the time zone).
(For detailed steps on setting the location region, see Step 18 in section 9.2).

5.3.2. Southern Hemisphere Reference

For installing the integrated outdoor sensor in the Southern Hemisphere, disregard the four directions (N, E, S, W) marked on the sensor body. When installing, adjust the orientation of the entire outdoor sensor to ensure the solar panel faces north (and is positioned to receive maximum sunlight), as shown in the diagram.

Step 1: Install the Integrated Outdoor Sensor
Ensure the solar panel is facing north.



Figure 13

Step 2: Set the Location Region on the Display Console
Set the location region to the Southern Hemisphere (SOU will appear in the time zone).
(For detailed steps on setting the location region, please refer to Step 18 in section 9.2).

 **Note:** The location region (NOR or SOU) on the display console and the direction of the sensor must be adjusted according to your actual location.
If the integrated outdoor sensor is not positioned correctly during installation, it will result in permanent wind direction errors.

5.4.Securing the Mounting Pole

Observe the bubble level next to the rain gauge to ensure the bubble is stable within the circle, keeping the sensor array completely level. If the sensor array is not level, the rain gauge will not measure accurately.




Figure 14

 **NOTE:** If the bubble level cannot be read due to mounting limitations, a horizontal line or level can be placed across the top of the rain gauge for easier viewing.

5.4.1.Horizontal mounting and fixing sensors

Fasten the integrated outdoor sensor to the mounting bar bracket with two mounting bolts ($\varnothing 4$)/nuts (M3). Then, tighten the mounting bar to your existing mounting bar with four bolts ($\varnothing 5$) and nuts (M5) or secure it to a flat surface with four self-tapping screws as shown. (Figure 15)




Figure 15

5.4.2. Vertical mounting and fixing sensors

Fasten the integrated outdoor sensor to the mounting bar bracket with two mounting bolts ($\varnothing 4$)/nuts (M3). Then, tighten the mounting bar to your existing mounting bar with four bolts ($\varnothing 5$) and nuts (M5) or secure it to a flat surface with four self-tapping screws as shown.(Figure 16)




Figure 16

5.4.3.Best Practices for Wireless Communication

Wireless communication is susceptible to interference, distance, walls, and metal barriers. We recommend the following best practices for trouble-free wireless communication.

1. **Electro-Magnetic Interference (EMI):** Keep the console several feet away from computer monitors and TVs.
2. **Radio Frequency Interference (RFI):** If you have other 433 MHz devices and communication is intermittent, try turning off these other devices for troubleshooting purposes. You may need to relocate the transmitters or receivers to avoid intermittent communication.
3. **Line of Sight Rating:** This device is rated at 300 feet line of sight (no interference, barriers, or walls), but typically you will get 100 feet maximum. [This is under most real-world installations, which include passing through barriers or walls].
4. **Metal Barriers:** Radio frequency will not pass through metal barriers, such as aluminum siding. If you have metal siding, align the remote and console through a window to get a clear line of sight.

The following is a table of reception loss, versus the transmission medium. Each “wall” or obstruction decreases the transmission range by the factor shown below:

Medium	Radio Frequency (RF) signal strength reduction
Glass (untreated)	5-15%
Plastic	10-15%
Wood	10-40%
Brick	10-40%
Concrete	40-80%
Metal	90-100%

6. Install the gateway



Figure 17

1. Please plug in the display console with the power adapter.
2. Please press and hold the fourth button for 3 seconds to enter the pairing mode, the indicator light (red) flashes fast, the indicator light (red, green) will flash alternately after successful pairing.
3. If the gateway is in pairing status, one click to exit pairing mode

6.1. Button Operation



Figure 18

The gateway has the following 4 buttons for setting the display function by short press, long press or double tap.

Key	Description
-----	-------------

1-Reset Button	<p>Reset: Please press and hold the “Reset” button for 3 seconds, the gateway will disconnect the pairing with the transmitter.</p>
2-Rain Reset Button	<p>Rain Reset: Please press and hold the “Rain Reset” button for 3 seconds, all rain values will be cleared to zero (current hour, 24 hours, week, month).</p>
3-Internet Button	<p>WiFi connection(3 modes):</p> <p>Bluetooth Distribution Network Mode: Please press and hold the “Internet” button for 3 seconds, the device will enter the network mode. By default, the first network mode is “Bluetooth distribution network” mode, the indicator light (green) blinks about 0.5s kind of blinking once.</p> <p>WiFi Distribution Network Mode Please press and hold the “Internet” button, the device will enter “Bluetooth distribution network” mode. Then please long press the button again for at least 3 seconds, the device will enter “WiFi distribution network” mode, the indicator light (green) will blink once in 1s.</p> <p>Web page distribution Network Mode Please press and hold the “Internet” button to enter the distribution network mode, the device will enter “Bluetooth distribution network” mode. Then please long press the button again for at least 3s, the device will enter “WiFi distribution network” mode. In “WiFi distribution network” mode, press and hold again for 3s to enter “Web page network distribution” mode, the indicator light (green) will blink once in 2s.</p>
4-Paring Button	<p>Paring: Please press and hold the “Paring” button for 3 seconds to enter the pairing mode, the indicator light (red) flashes fast, the indicator light (red, green) will flash alternately after successful pairing.</p> <p>One click to exit pairing mode.</p>

7. Display connected to WiFi

7.1. Real-time Network Monitoring

The weather station can upload data to the following two platforms:

Application Services	Website	Description
Weatherseed APP	Wunderground.com	Our weather stations feature the most user-friendly design to monitor data across different platforms. Use our animated expandable modules to quickly view the details you want.
		

*Weather station use the WiFi connection to send data to the Internet.

* Please **DO NOT** fill in any credit card information on WU website. If a pop-up window appears when you open the Weather Underground website, please be careful and not to click it!

7.2.APP Download

Please search "Weatherseed " APP in Google Play or IOS App Store.

After downloading, you can follow the steps of WiFi connection to connect the weather station to WiFi and then view the data on the APP!

7.3.APP Account Register and Login

After successfully downloading "Weatherseed" APP, please open the APP, the first time you open the APP, the login or registration screen will appear. If you don't have an account for the first time, you need to register your own account to log in later; if you have already registered a Weatherseed account, you can log in directly without registering again.


7.3.1. Registering Process

You can follow the steps and pictures below to register your Weatherseed account:

- (1) Fill in your e-mail address;
- (2) Send the verification code to the e-mail address;
- (3) Go to the e-mail address to check the verification code and enter it;
- (4) Set a password;

- (5) Confirm the password (must be consistent with the set password);
- (6) Check the user agreement and proof of age;
- (7) Register an account.


 **Note:** Your account will be automatically logged in the APP directly after the registration is completed.



7.3.2. Login process

You can follow the steps and picture instructions below to log in to your Weatherseed account:

- (1) Enter your registered Weatherseed account (email address);
- (2) Enter the password you have set;
- (3) Check the User Privacy Agreement;
- (4) Log in to your account.



7.4. Connecting Steps

 **Note:** The weather station only supports 2.4 GHz signals. If you have a dual-band router (2.4 GHz and 5.0 GHz), please make sure that the router's 2.4 GHz band is turned on and can be distinguished from the 5.0 GHz channel's SSID for accurate connection to the 2.4 GHz channel.

 **Note:** The power adapter needs to be plugged into connect to WiFi. Battery power cannot connect to WiFi.

 **Note:** Please don't choose the wrong type and model, if you choose the wrong one, you can't match the network successfully.

7.4.1 Bluetooth Distribution Network Mode

Please press and hold the “Internet” button, the device will enter “Bluetooth distribution network” mode. After the gateway enters the “Bluetooth distribution network” mode, please open the APP to start networking:

Select the second icon  on the lower left to enter the networking interface to start networking, the specific steps and picture instructions are as follows:

(1) Enter the networking interface, click "Add Device" to start connecting the wifi ;

16:49  




There is no device at present!

 Add Device




(2) Add the device in the app, select the device type and model, and set a weather


station name, enter your location.



(3) Enter the network configuration interface and click “**Next**” to complete the three steps of network configuration. Then need to scan the QR code (Mac address) of the device.



(4) Select “Bluetooth distribution network” mode to automatically search for Bluetooth signals and pairing.
 After successful pairing, jump to WiFi interface. Please select 2.4Ghz WiFi and enter the password.



7.4.2. Wifi Distribution Network Mode

Please press and hold the “**Internet**” button, the device will enter “Bluetooth distribution network” mode. Then please long press the button again for at least 3 seconds, the device will enter “WiFi distribution network” mode, the indicator light (green) will blink once in 1s.

After the gateway enters the “WiFi distribution network” mode, please open the APP to start networking:

(1)Enter the networking interface, click "Add Device" to start connecting the wifi ;




There is no device at present!

Add Device



(2) Add the device in the app, select the device type and model, and set a weather station name, enter your location.



16:50



Give your device a name


Ex: My Weather Station


Where is your device located?

Please enter your address


Next

(3) Enter the network configuration interface and click “Next” to complete the three steps of network configuration. Then need to scan the QR code (Mac address) of the device.







(4) Select the distribution network mode: “WiFi distribution network”.
 Select your own WiFi (2.4Ghz), enter the correct password and connect the device.
 After the connection is successful, you will go back to Device page.



Current Device



My Device





7.4.3. Web page distribution network mode

Please press and hold the third button to enter the distribution network mode, the device will enter “Bluetooth distribution network” mode. Then please long press the button again for at least 3s, the device will enter “WiFi distribution network” mode.


In “WiFi distribution network” mode, press and hold again for 3s to enter “Web page distribution network” mode, the indicator light (green) will blink once in 2s.

After the gateway enters the “Web page distribution” mode, please open the APP to start networking.

(1) Add device in the dashboard interface. Select device type and model, and set a weather station name, enter your location. Enter the network configuration interface and click Next to complete the three steps of network configuration.



(2) Enter the network configuration interface and click “Next” to complete the three steps of network configuration. Scan the QR code.



(3)Select the “Web page distribution network” mode , Click Go to connect WiFi. Then will automatically jump to the WiFi list screen, click Connect “weatherseed” WiFi.




1. Please switch the device to Web page Network Connection.
2. Please connect to the device's Wi-Fi. The Wi-Fi name is [Weatherseed](#).

Next

Go to connect to Wi-Fi

Confirm that the device has switched to 'Web page Network Connection' mode and that the phone's Wi-Fi is connected to [Weatherseed](#).

Next



Return to the app, click the confirmation dot and click "Next". Please select 2.4Ghz WiFi, enter the password and click "Connect".




16:16

Current Device




My Device



 **NOTE:** Android system can select WiFi. IOS system needs to manually enter the WiFi name.

7.5. Firmware Upgrade

When your app receives a firmware upgrade notification, follow the steps below to remotely upgrade the firmware.



7.6. Sign up on Wunderground.com

1. Visit the "<https://www.wunderground.com>" website, and click "Join" button, input the Email and password, and select "Sign up for free" button to create your own account.



Member Account

Join Weather Underground

- Choose adding your webcam or personal weather station.
- You can delete your account at any time from your member settings.

The Weather Company needs your email to create your Weather Underground account.

Email
 ✓

Password (5-30 characters)
 [Show](#) ✓


Confirm New Password:

I agree to the [Terms of Use](#)

[Sign up for free](#)

[Already have an account? Sign in](#)

2. Click “Sign in” button to login, and switch to **Member Settings** page.



WEATHER UNDERGROUND | Sensor Network | Maps & Radar | Severe Weather | News & Blogs | Mobile Apps | More | Search Locations | Log in | Join

Popular Cities: San Francisco, CA (56°F Fair), Manhattan, NY (84°F Mostly Cloudy), Schiller Park, IL (60176) (67°F Cloudy), Boston, MA (75°F Clear), Houston, TX (84°F Fair), St James's, England, United Kingdom (WC2H 7DE) (64°F Clear)

Member Account

Sign in to Weather Underground!

Email
 ✓

Password
 [Forgot your password?](#) ✓

[Sign in](#)

[Don't have an account? Sign up](#)

[Terms of Use](#) | [Privacy Policy](#)
Please read these terms carefully. By using Weather Underground or signing up for an account, you're agreeing to these terms.

3. Select **My Devices** tab and click “Add New Devices”.

Note: in “Add New Devices” page, set the “**TYPE**”, “**LOCATION**”, “**DETAILS**” and “**DONE**” page step by step until 100% completion.

Member Settings

EMAIL & PASSWORD HOME & FAVORITE **MY DEVICES** API KEYS

Manage Devices

0 DEVICES TOTAL

No devices to show

Weather Underground is a global community of people connecting data from environmental sensors like weather stations and air quality monitors so we can provide the rich, hyperlocal data you need to power your passions. The future of weather is personal, hyperlocal, and smarter than you think. Join our global community and contribute to the future of forecasting.

[Learn More](#)

Add New Device

4. In **TYPE** Page, click “**Personal Weather Station**” drop down list to select “**Other**”.

Add a New Device

TYPE LOCATION DETAILS DONE

Select a Device Type

25%

Personal Weather Station

Outdoor Webcam

5. In **LOCATION** Page, Select “**Address**” or “**Manual**” Option, find and input your local position and press “**Next**”.

Add a New PWS

TYPE LOCATION DETAILS DONE

Set Device Name & Location

50%

Device Location:
 Address Manual

Your Location has been verified and added!
 Elevation: 915 ft.
 Lat, Lon: 45.114, -93.191
 Neighborhood: Mounds View
 Time Zone: America/Chicago

<img alt="Map showing the location of Mounds View, Minnesota, with a blue pin marking the spot. The map includes labels for Anoka County, Blaine Airport, Lexington, and various roads like 10, 61, 32, 44, 48, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 5810, 5811, 5812, 5813, 5814, 5815, 5816, 5817, 5818, 5819, 5820, 5821, 5822, 5823, 5824, 5825, 5826, 5827, 5828, 5829, 5830, 5831, 5832, 5833, 5834, 5835, 5836, 5837, 5838, 5839, 58310, 58311, 58312, 58313, 58314, 58315, 58316, 58317, 58318, 58319, 58320, 58321, 58322, 58323, 58324, 58325, 58326, 58327, 58328, 58329, 58330, 58331, 58332, 58333, 58334, 58335, 58336, 58337, 58338, 58339, 583310, 583311, 583312, 583313, 583314, 583315, 583316, 583317, 583318, 583319, 583320, 583321, 583322, 583323, 583324, 583325, 583326, 583327, 583328, 583329, 583330, 583331, 583332, 583333, 583334, 583335, 583336, 583337, 583338, 583339, 5833310, 5833311, 5833312, 5833313, 5833314, 5833315, 5833316, 5833317, 5833318, 5833319, 5833320, 5833321, 5833322, 5833323, 5833324, 5833325, 5833326, 5833327, 5833328, 5833329, 5833330, 5833331, 5833332, 5833333, 5833334, 5833335, 5833336, 5833337, 5833338, 5833339, 58333310, 58333311, 58333312, 58333313, 58333314, 58333315, 58333316, 58333317, 58333318, 58333319, 58333320, 58333321, 58333322, 58333323, 58333324, 58333325, 58333326, 58333327, 58333328, 58333329, 58333330, 58333331, 58333332, 58333333, 58333334, 58333335, 58333336, 58333337, 58333338, 58333339, 583333310, 583333311, 583333312, 583333313, 583333314, 583333315, 583333316, 583333317, 583333318, 583333319, 583333320, 583333321, 583333322, 583333323, 583333324, 583333325, 583333326, 583333327, 583333328, 583333329, 583333330, 583333331, 583333332, 583333333, 583333334, 583333335, 583333336, 583333337, 583333338, 583333339, 5833333310, 5833333311, 5833333312, 5833333313, 5833333314, 5833333315, 5833333316, 5833333317, 5833333318, 5833333319, 5833333320, 5833333321, 5833333322, 5833333323, 5833333324, 5833333325, 5833333326, 5833333327, 5833333328, 5833333329, 5833333330, 5833333331, 5833333332, 5833333333, 5833333334, 5833333335, 5833333336, 5833333337, 5833333338, 5833333339, 58333333310, 58333333311, 58333333312, 58333333313, 58333333314, 58333333315, 58333333316, 58333333317, 58333333318, 58333333319, 58333333320, 58333333321, 58333333322, 58333333323, 58333333324, 58333333325, 58333333326, 58333333327, 58333333328, 58333333329, 58333333330, 58333333331, 58333333332, 58333333333, 58333333334, 58333333335, 58333333336, 58333333337, 58333333338, 58333333339, 583333333310, 583333333311, 583333333312, 583333333313, 583333333314, 583333333315, 583333333316, 583333333317, 583333333318, 583333333319, 583333333320, 583333333321, 583333333322, 583333333323, 583333333324, 583333333325, 583333333326, 583333333327, 583333333328, 583333333329, 583333333330, 583333333331, 583333333332, 583333333333, 583333333334, 583333333335, 583333333336, 583333333337, 583333333338, 583333333339, 5833333333310, 5833333333311, 5833333333312, 5833333333313, 5833333333314, 5833333333315, 5833333333316, 5833333333317, 5833333333318, 5833333333319, 5833333333320, 5833333333321, 5833333333322, 5833333333323, 5833333333324, 5833333333325, 5833333333326, 5833333333327, 5833333333328, 5833333333329, 5833333333330, 5833333333331, 5833333333332, 5833333333333, 5833333333334, 5833333333335, 5833333333336, 5833333333337, 5833333333338, 5833333333339, 58333333333310, 58333333333311, 58333333333312, 58333333333313, 58333333333314, 58333333333315, 58333333333316, 58333333333317, 58333333333318, 58333333333319, 58333333333320, 58333333333321, 58333333333322, 58333333333323, 58333333333324, 58333333333325, 58333333333326, 58333333333327, 58333333333328, 58333333333329, 58333333333330, 58333333333331, 58333333333332, 58333333333333, 58333333333334, 58333333333335, 58333333333336, 58333333333337, 58333333333338, 58333333333339, 583333333333310, 583333333333311, 583333333333312, 583333333333313, 583333333333314, 583333333333315, 583333333333316, 583333333333317, 583333333333318, 583333333333319, 583333333333320, 583333333333321, 583333333333322, 583333333333323, 583333333333324, 583333333333325, 583333333333326, 583333333333327, 583333333333328, 583333333333329, 583333333333330, 583333333333331, 583333333333332, 583333333333333, 583333333333334, 583333333333335, 583333333333336, 583333333333337, 583333333333338, 583333333333339, 5833333333333310, 5833333333333311, 5833333333333312, 5833333333333313, 5833333333333314, 5833333333333315, 5833333333333316, 5833333333333317, 5833333333333318, 5833333333333319, 5833333333333320, 5833333333333321, 5833333333333322, 5833333333333323, 5833333333333324, 5833333333333325, 5833333333333326, 5833333333333327, 5833333333333328, 5833333333333329, 5833333333333330, 5833333333333331, 5833333333333332, 5833333333333333, 5833333333333334, 5833333333333335, 5833333333333336, 5833333333333337, 5833333333333338, 5833333333333339, 58333333333333310, 58333333333333311, 58333333333333312, 58333333333333313, 58333333333333314, 58333333333333315, 58333333333333316, 58333333333333317, 58333333333333318, 58333333333333319, 58333333333333320, 58333333333333321, 58333333333333322, 58333333333333323, 58333333333333324, 58333333333333325, 58333333333333326, 58333333333333327, 58333333333333328, 58333333333333329, 58333333333333330, 58333333333333331, 58333333333333332, 58333333333333333, 58333333333333334, 58333333333333335, 58333333333333336, 58333333333333337, 58333333333333338, 58333333333333339, 583333333333333310, 583333333333333311, 583333333333333312, 583333333333333313, 583333333333333314, 583333333333333315, 583333333333333316, 583333333333333317, 583333333333333318, 583333333333333319, 583333333333333320, 583333333333333321, 583333333333333322, 583333333333333323, 583333333333333324, 583333333333333325, 583333333333333326, 583333333333333327, 583333333333333328, 583333333333333329, 583333333333333330, 583333333333333331, 583333333333333332, 583333333333333333, 583333333333333334, 583333333333333335, 583333333333333336, 583333333333333337, 583333333333333338, 583333333333333339, 5833333333333333310, 5833333333333333311, 5833333333333333312, 5833333333333333313, 5833333333333333314, 5833333333333333315, 5833333333333333316, 5833333333333333317, 5833333333333333318, 5833333333333333319, 5833333333333333320, 5833333333333333321, 5833333333333333322, 5833333333333333323, 5833333333333333324, 5833333333333333325, 5833333333333333326, 5833333333333333327, 5833333333333333328, 5833333333333333329, 5833333333333333330, 5833333333333333331, 5833333333333333332, 5833333333333333333, 5833333333333333334, 5833333333333333335, 5833333333333333336, 5833333333333333337, 5833333333333333338, 5833333333333333339, 58333333333333333310, 58333333333333333311, 58333333333333333312, 58333333333333333313, 58333333333333333314, 58333333333333333315, 58333333333333333316, 58333333333333333317, 58333333333333333318, 58333333333333333319, 58333333333333333320, 58333333333333333321, 58333333333333333322, 58333333333333333323, 58333333333333333324, 58333333333333333325, 58333333333333333326, 58333333333333333327, 58333333333333333328, 58333333333333333329, 58333333333333333330, 58333333333333333331, 58333333333333333332, 58333333333333333333, 58333333333333333334, 58333333333333333335, 58333333333333333336, 58333333333333333337, 58333333333333333338, 58333333333333333339, 583333333333333333310, 583333333333333333311, 583333333333333333312, 583333333333333333313, 583333333333333333314, 583333333333333333315, 583333333333333333316, 583333333333333333317, 583333333333333333318, 583333333333333333319, 583333333333333333320, 583333333333333333321, 583333333333333333322, 583333333333333333323, 583333333333333333324, 583333333333333333325, 583333333333333333326, 583333333333333333327, 583333333333333333328, 583333333333333333329, 583333333333333333330, 583333333333333333331, 583333333333333333332, 583333333333333333333, 583333333333333333334, 583333333333333333335, 583333333333333333336, 583333333333333333337, 583333333333333333338,

Add a New PWS

TYPE LOCATION DETAILS **DETAILS** DONE

Tell Us More About Your Device

75%

Name:(Required) **Surface Type:**

Elevation:(Required) **Associate Webcam:**

Device Hardware:(Required)

Height Above Ground:

You Make Our Forecasts More Accurate, We Respect Your Privacy
 Contribute to the Weather Underground community by sharing some information about yourself and your sensor. We use this information to manage your account and to improve the experience from the Weather Underground community. We may also share certain data for commercial purposes, such as your sensor location.
[Learn more about how we take your privacy seriously](#)

I Accept I Deny

Email Preferences:
 I would like to receive PWS notifications.

Back **Next**

7. In **DONE** Page, the device “**Station ID**” and “**Station Key**” are shown, copy and record the information for late use.

WEATHER UNDERGROUND Sensor Network Maps & Radar Severe Weather News & Blogs Mobile Apps More My Profile

Recent Cities Manhattan, NY

Add a New PWS

TYPE LOCATION DETAILS **DONE**

Registration Complete!

100%

Congratulations! Your personal weather station is now registered with Weather Underground.

Enter the information below to your weather station software.

Your PWS

Station ID: Station Key:

Copy credentials

Configure Your Software

View Devices

8. Time Zone

The following table summarizes time zones around the world:

Hours from GMT	Time zone	Cities
-12	IDLW: International Date Line West	---
-11	NT: Nome	Nome, AK, USA
-10	AHST: Alaska-Hawaii Standard CAT: Central Alaska HST: Hawaii Standard	Honolulu, HI, USA
-9	YST: Yukon Standard	Yukon Territory
-8	PST: Pacific Standard	Los Angeles, CA, USA
-7	MST: Mountain Standard	Denver, CO, USA
-6	CST: Central Standard	Chicago, IL, USA
-5	EST: Eastern Standard	New York, NY, USA
-4	AST: Atlantic Standard	Caracas, Venezuela
-3.5	Newfoundland Time (NT)	Newfoundland, Canada
-3	---	São Paulo, Brazil
-2	AT: Azores	Azores, Cape Verde Islands
-1	WAT: West Africa	---
0	GMT: Greenwich Mean WET: Western European	London, England
1	CET: Central European	Paris, France
2	EET: Eastern European	Athens, Greece
3	BT: Baghdad	Moscow, Russia
3.5	Iran Standard Time (IRST)	Tehran, Iran
4	---	Abu Dhabi, UAE
5	---	Tashkent, Uzbekistan
5.45	Nepal Standard Time	Nepal
5.5	Indian Standard Time (IST)	India
6	---	Astana, Kazakhstan
7	---	Bangkok, Thailand
8	CCT: China Coast	Beijing, China
9	JST: Japan Standard	Tokyo, Japan
9.5	Australian Central Standard Time (ACST)	Adelaide, Australia
10	GST: Guam Standard	Sydney, Australia
11	---	Magadan, Russia
12	IDLE: International Date Line East NZST: New Zealand Standard	Wellington, New Zealand

9. Data Discussion

(1)

Temperature errors can occur when a sensor is placed too close to a heat source (such as a building/structure, the ground, or trees).

To calibrate temperature, we recommend a mercury or red spirit (fluid) thermometer. Bi-metal (dial) and digital thermometers (from other weather stations) are not a good source and have their own margin of error.

Using a local weather station in your area is also a poor source due to changes in location and timing (airport weather stations are only updated once per hour).

Place the sensor in a shaded, controlled environment next to the fluid thermometer and allow the sensor to stabilize for 48 hours.

(2)

Humidity is a difficult parameter to measure electronically and drifts over time due to contamination. In addition, location has an adverse effect on humidity readings (installation over dirt vs. a lawn, for example).

Official stations recalibrate or replace humidity sensors on a yearly basis. Due to manufacturing tolerances, the humidity is accurate to $\pm 5\%$. To improve this accuracy, the indoor and outdoor humidity can be calibrated using an accurate source, such as a sling psychrometer.

 **NOTE:** The measured humidity range is between 10% and 99%. Humidity cannot be measured accurately outside of this range. Therefore, it is not possible to calibrate humidity below 10% or above 99%.

(3)

The app shows two different pressures: absolute pressure (measured value) and relative pressure (corrected for sea level).

In order to compare air pressure conditions at different locations, meteorologists correct air pressure to sea level pressure. Because barometric pressure decreases with elevation, the sea level corrected pressure (the pressure at your location if you are at sea level) is usually higher than your measured pressure.

Thus, at an elevation of 1,000 feet (305 meters), the absolute barometric pressure may be 28.62 inHg (969 mb), but the relative barometric pressure is 30.00 inHg (1016 mb).

The standard sea level pressure is 29.92 inHg (1013 mb). This is the average sea level pressure for the entire world. A relative pressure measurement greater than 29.92 inHg (1013 mb) is considered high pressure, and a relative pressure measurement

less than 29.92 inHg is considered low pressure.

To determine the relative barometric pressure at your location, look for an official reporting station near you (the Internet is the best source for real-time barometric conditions, such as the Weather.com or Wunderground.com websites) and set your weather station to match the official reporting station.

(4)

Wind speed is the most sensitive to installation constraints. The guideline for properly installing a wind speed sensor is 4 x the distance of the tallest obstruction. For example, if your house is 20' tall and you mount the sensor on a 5' pole:

$$\text{Distance} = 4 \times (20 - 5)' = 60'.$$

Many installations are not perfect, and installing the weather station on a roof can be difficult. Thus, you can calibrate for this error with a wind speed multiplier.

In addition to the installation challenges, wind cup bearings (moving parts) wear over time.

(5)

The rain collector is calibrated to the funnel diameter at the factory. The internal unit of the rain collector records 0.01 inches of rainfall (called resolution) for each pour. Accumulated rainfall can be compared to a sight glass rain gauge with an aperture of at least 4 inches.

The rain cycle view is calculated as follows:

View Period	Description	Example
1H	One hour delay from current time	If the current time is 08:25, the 1-hour rainfall refers to the rainfall from 08:25 to 09:25.
24H	Same time from current time to the day after	If the date is October 20 and the time is 08:25, the 24-hour rainfall is the amount of rainfall from 08:25 (10.20) to 08:25 (10.21).
Week	From the beginning of the week to the current time	If the current time is 08:25 on Thursday, the weekly rainfall refers to the rainfall from 00:00 on this Sunday to 08:25 on this Thursday.
Month	From the beginning of the month to the current time	If the current time is 08:25 on October 20, the monthly rainfall refers to the rainfall from 00:00 on October 1 to 08:25 on October 20.
Total	Total rainfall since the most recent start	If the start time is now October 20, 2024, then the total rainfall is

	October 20, 2024 to October 20, 2025.
--	---------------------------------------

 **NOTE:** Debris and insects can collect in the dump unit (they can form spider nests), so carefully remove the rain collector and check for debris in the dump unit before calibrating.

10. Feels Like Temperatures

The Feels Like Temperature is a combination of the Heat Index and the Wind Chill Index.

(1) When the air temperature is below 4.4°C (40°F), the Wind Chill Index is displayed, as shown in the following National Weather Service Wind Chill Index table:




Figure 19

(2) When the temperature is above 26.7°C (80°F), the heat index is displayed, as shown in the following National Weather Service heat index chart:




Figure 20

 **Note: Both the Wind Chill and Heat Index are displayed uniformly as it feels like.**

11. Glossary of Terms

Terms	Definition
Absolute pressure	Absolute pressure is the measured atmospheric pressure and is a function of altitude and, to a lesser extent, changes in weather conditions. Absolute air pressure is not corrected for sea level conditions. See relative air pressure for details.
Relative pressure	The measured air pressure relative to your location or environmental conditions.
HectoPascals (hPa)	A unit of pressure measured in the SI (International System of Units). Same as the millibar (1 hPa = 1 mbar).
Inches of Mercury (inHg)	Pressure expressed in imperial units. (1 inHg = 33.86 mbar).
Dew point	Dew point refers to the temperature at which water vapor condenses into water after cooling in air of a certain humidity under constant air pressure. The condensed water is called dew, and the dew point is a saturation temperature. Dew point is related to relative humidity. A high relative humidity means the dew point is closer to the current air temperature. A relative humidity of 100% means the dew point is equal to the current temperature and the water in the air

	reaches maximum saturation. When the dew point remains constant and the temperature rises, the relative humidity decreases
Rain gauge	<p>A rain gauge is a device that measures liquid precipitation (rain) over a period of time, rather than solid precipitation (snow, hail, or ice).</p> <p>All digital rain gauges are self-emptying or self-dumping (also called dumping rain gauges). The accuracy of a rain gauge depends on the amount of rain that falls during each emptying cycle.</p>
Accuracy	Precision is defined as the ability of a measurement to match the actual value of the quantity being measured.
Range	Range is defined as the number and interval of measurable values.
Resolution	Resolution is defined as the number of significant digits (decimal digits) that can be reliably measured.
Wind vane	Wind direction refers to the direction the wind is blowing from. For example, if the display shows the wind direction as south, it means the wind is blowing from the south.

12.Specifications

12.1. Wireless specifications

Wireless transmission	Specifications
Line of sight wireless sensor array RF transmission (open air)	330 ft, 100 ft in most cases
Line of sight Wi-Fi RF transmission (open air)	80 ft
Outdoor sensor update frequency	16 sec
Sensor array RF frequency	433 MHz
Wi-Fi console RF frequency	2.4 GHz

12.2. Measurement Specifications

The table below provides the specifications of the measured parameters.

Measurement	Range	Accuracy	Resolution
Indoor Temperature	0 to 60 °C (32 to 140°F)	± 1 °C (± 2°F)	0.1 °C(°F)
Outdoor Temperature	-40 to 60 °C (-40 to 140°F)	± 1 °C (± 2°F)	0.1 °C(°F)
Indoor humidity	10 to 99 %	± 5% (only)	1%

		guaranteed between 20 to 90%)	
Outdoor Humidity	10 to 99 %	± 5% (only guaranteed between 20 to 90%)	1%
Rainfall	0 to 9999mm	<15mm: ±1 mm, 15mm to 9999mm: ±7%	<1000mm (0.3mm) >1000mm (1mm)
Wind direction	0 - 360°	± 10° (16 point compass)	± 1° (16 point compass)
Wind Speed	0 to 50 m/s	2 m/s ~10 m/s: ±0.3m/s, 10m/s ~50 m/s: ±10% (whichever is greater)	0.1 m/s
Barometric Pressure	300 to 1100 hpa	± 3 hpa	0.1 hpa

12.3. Power Consumption

Gateway	Power adapter plugged in to use
Integrated Outdoor Sensor:	3xAA alkaline or lithium batteries (not included) provide backup power when solar power is limited.  Note: The solar panel does not charge the battery, it is an auxiliary power source.
Power Adapter	5V-1000mA (Included)
Battery Life	If the base station signal reception is good, the transmitter battery can last at least 3 months. If the base station reception signal is intermittent, the transmitter battery life may be reduced. We recommend using lithium batteries for the transmitter in cold climates below -20°C (-4°F).

13. Maintenance

(1) We recommend cleaning the rain gauge once every 3 months. Twist the funnel clockwise and lift it vertically to expose the rain gauge assembly (see the image below). Then wipe the internal rain gauge assembly with a damp cloth to remove any dirt, debris, or insects. If insect infestation is a concern, you can lightly spray the array with an insecticide.




Figure 21

(2) Clean the solar panel with a damp cloth every 3 months.

Replace the battery every 3 months. If left for too long, the battery may leak due to environmental factors. In harsh environments, check the battery every 3 months (when cleaning the solar panel).

(3) When replacing the battery, apply anti-corrosion compound to the battery terminals, which is available on Amazon and most hardware stores.

(4) In snowy conditions, spray the top of the weather station with anti-icing silicone spray to prevent snow accumulation.

(5) Over time, the smoothness of the rain gauge funnel surface will degrade due to dirt, debris. Therefore, we recommend spraying Teflon spray on the rain gauge funnel and coil filter to reduce the surface tension of the water.

14. Troubleshooting Guide

If your question is not answered here, you can contact us by Customer Support Email, Customer Support Phone and Website:

- (1) Customer Support Email: info@sainlogic.com
- (2) Website: <https://www.sainlogic.com/>
- (3) Customer Support Phone (Skype) : +1(508)758-0493 (10 a.m.–2 p.m. EST)

Problem	Solution
Outdoor/Indoor data is not shown in the APP	<p>Make sure the device is showing offline.</p> <p>If the device is online, but the data still not be displayed on the app.</p> <p>Please follow the instructions below to troubleshoot.</p> <ol style="list-style-type: none"> 1. Please press and hold the first button for 3 seconds, the gateway will disconnect the pairing with the transmitter. 2. Then please reset the transmitter. <p>After the transmitter is powered on, if the indicator light blinks every 16 seconds it means the outdoor unit is working properly.</p> <p>After the transmitter is powered on and working properly, the display has to be re-plugged in to re-receive the transmitter signal. It usually takes 1-3 minutes to receive the data, do not operate the keys or power off until the transmitter data is received.</p> <p>Install a new set of batteries for the remote sensor. In cold weather environments, install lithium batteries.</p> <ol style="list-style-type: none"> 3. Plug in the device with the power adapter. <p>Please press and hold the fourth button for 3 seconds to enter the pairing mode, the indicator light (red) flashes fast, the indicator light (red, green) will flash alternately after successful pairing.</p> <ol style="list-style-type: none"> 4. If the device shows offline on the app, you need to reconnect to WiFi.
Rainfall display is incorrect/zero	Please check and verify the following points when you find you rainfall is not working or inaccurate:

1. Make sure that the level bubble is seated in the small black circle in the installation. Sloping installation might cause incorrect reading or even not working.

2. Shake the sensor array back and forth. After hearing the click sound inside the sensor array, observe whether the rainfall reading in the console changes.

3. Check whether the funnel in the rain collector was blocked by tree leaves or debris. Remove the rain collector to check whether the rain tip was blocked by insects or debris.

4. Check whether different rainfall histories are correct. Check the Quick Mode part in the instruction manual to know how to get rainfall histories in different periods.

5. An example on how rainfall histories for different periods are calculated.

Presume that the current time is 08:42 22rd Sept. 2023

Rainfall Hour: 08:42-09:42

Rainfall Day: 08:42 on September 22 to 08:42 on September 23

Rainfall Week: 00:00 Sunday to 08:42 today

Rainfall Month: 00:00 1st Sept. to 08:42 today

Rainfall Total: Total rainfall amount from the latest powering on

6. How to verify the rainfall accuracy

A: Use a bottle containing 500g or 500ml of water.

B: Drip water slowly into the rain collector. DO NOT POUR WATER QUICKLY.

C. Observe the rainfall reading of the console after the water is completely dripped out. It should be 5.46cm +/-5%. (5.46cm=54.6mm)

7. The rain gauge could not measure rainfall below 0.3mm due to limited resolution.

 **Note: One transmitter can connect to multiple gateway of the same model, but one gateway cannot be connected to multiple transmitters at the same time.**

 **Note: Please carefully check whether the model is consistent before purchasing. If you have any questions, please consult after-sales service in advance.**

15. Disclaimer

Please protect the environment by returning used batteries to an authorized recycling station. Electrical and electronic waste contains hazardous substances. Disposal of e-waste in the natural environment and/or in unauthorized locations can damage the environment.

Reading the user manual is strongly recommended and the manufacturer and supplier cannot be held responsible for any incorrect readings or consequences resulting from failure to read the manual carefully.

This product is intended for home use only and is not intended for medical purposes or public safety information. This product is not a toy and should be kept out of the reach of children.

We assume no liability for accidental, consequential, punitive or other similar damages related to operation or malfunction.

16. Warranty Information

Sainlogic provides a 1-year limited warranty against manufacturing defects in materials and workmanship on this product.

This limited warranty begins on the date of original purchase and is valid only for the product purchased and only for the original purchaser of this product. To obtain warranty service, the purchaser must contact Sainlogic to determine the problem and service procedure.

Warranty service can only be performed by Sainlogic. The original dated bill of sale must be presented to Sainlogic upon request as proof of purchase.

Sainlogic's warranty covers all defects in materials and workmanship except:

- (1) Damage caused by accident, unreasonable use or neglect (lack of reasonable and necessary maintenance);
- (2) Damage caused by failure to follow the instructions in the user's manual;
- (3) Damage caused by self-repair or alteration;

- (4) Equipment not intended for personal use;
- (5) Applications and uses of this product that do not correspond to the intended use;
- (6) The product is unable to receive signals due to any source of interference or metal obstruction;

If you need to register or apply for a warranty, please contact us by Customer Support.

Customer Support Email: info@sainlogic.com

Website: <https://www.sainlogic.com/>

Customer Support Phone (Skype) : +1(508)758-0493 (10 a.m.–2 p.m. EST)

17. FCC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 0cm between the radiator and your body.