

FCC ID: 2A7S7A0020220822C

1. RF EXPOSURE EVALUATION

According to FCC 1.1310 and FCC KDB 447498 D01 v06: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in 20cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2. TEST PROCEDURE

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

3. EUT TECHNICAL DESCRIPTION

Characteristics	Description
Product	Thermostat
Model Number	ET-72GW, ET-7AW, ET-92GW (Note: The only difference in models is the model's name, all other information is the same. The main test model applied for this report is ET-72GW)
Modulation	GFSK
Operating Frequency Range	2402-2480MHz
Number of Channels	40 Channels

IEEE 802.11 WLAN Mode Supported	<input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20MHz channel bandwidth)
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n
Operating Frequency Range	2412-2462MHz for 802.11b/g/n(HT20)
Number of Channels	11 channels for 802.11b/g/n(HT20)

Antenna Type	PCB Antenna
Antenna Gain	2.5 dBi
Temperature Range	5°C ~ 45°C

4. Measurement Result

Mode	Max Measured power (dBm)	Antenna gain (dBi)	Antenna Gain Numeric	R (cm)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
BLE	3.32	2.5	1.78	20	0.001	1
2.4G WIFI	19.39	2.5	1.78	20	0.031	1

----- The End -----