

FCC Test Report

Applicant : **Shenzhen Qianyan Technology LTD**

Address : **No.3301,Block C,Section 1,Chuangzhi
Yuncheng, Building,Liuxian Avenue,Xili
Community, Xili Street, Nanshan District,
Shenzhen, 518000, China**

Product Name : **Gaming Sync Box**

Report Date : **Jul. 05, 2023**

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Configuration	6
1.5. Description Of Test Setup	7
1.6. Test Equipment List	8
1.7. Measurement Uncertainty	9
1.8. Description of Test Facility	9
2. Summary of Test Results	10
3. Conducted Emission Test	11
3.1. Test Standard and Limit	11
3.2. Test Setup	11
3.3. Test Procedure	11
3.4. Test Data	11
4. Radiation Spurious Emission and Band Edge	16
4.1. Test Standard and Limit	16
4.2. Test Setup	16
4.3. Test Procedure	17
4.4. Test Data	18
5. Maximum Peak Output Power Test	26
5.1. Test Standard and Limit	26
5.2. Test Setup	26
5.3. Test Procedure	26
5.4. Test Data	26
6. Antenna Requirement	27
6.1. Test Standard and Requirement	27
6.2. Antenna Connected Construction	27
APPENDIX I -- TEST SETUP PHOTOGRAPH	28
APPENDIX II -- EXTERNAL PHOTOGRAPH	28
APPENDIX III -- INTERNAL PHOTOGRAPH	28



TEST REPORT

Applicant : Shenzhen Qianyan Technology LTD

Manufacturer : Shenzhen Qianyan Technology LTD

Product Name : Gaming Sync Box

Model No. : H6602

Trade Mark : Govee

Rating(s) : Input: 12V $\overline{=}$

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Apr. 24, 2023

Date of Test

Apr. 24 ~ Jun. 06, 2023

Prepared by

Nian Xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 05, 2023

Note 1:

This is a Class II application which was based on the original report 18220WC20240402. The difference between the original device and current one described as following:

1. Add Adapter*lights: BI36G-120300-AdU*1.8m lights, BI72G-120500-E2*5m lights.
2. Change the Product Name to "Gaming Sync Box".
3. Change the Model Number to "H6602".
4. Change the EUT appearance and update EUT Photograph.

The changes are not related with the other RF parameters, only Conducted Emission and Radiated Emission were tested.



1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng, Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qianyan Technology LTD
Address	:	No.3301,Block C,Section 1,Chuangzhi Yuncheng, Building,Liuxian Avenue,Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Gaming Sync Box
Model No.	:	H6602
Trade Mark	:	Govee
Test Power Supply	:	AC 120V, 60Hz for adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter 1 for 3.6m LED Strip Light	:	Model: BI48G-120400-AdU Input: 100-240V~50/60Hz 1.4A Output: 12V= 4A
Adapter 2 for 1.8m LED Strip Light	:	Model: BI36GL-120300-AdU Input: 100-240V~50/60Hz 1.0A Output: 12V= 3A
Adapter 3 for 5m LED Strip Light	:	Model: BI72G-120500-E2 Input: 100-240V~50/60Hz 1.8A Output: 12V= 5A

RF Specification

Operation Mode	:	<input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(HT20) <input type="checkbox"/> 802.11n(HT40)
Operation Frequency	:	2412~2462MHz
Number of Channel	:	11 Channel for 20MHz bandwidth (2412~2462MHz)
Modulation Type	:	<input checked="" type="checkbox"/> 802.11b: DSSS (CCK, DQPSK, DBPSK) <input checked="" type="checkbox"/> 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) <input checked="" type="checkbox"/> 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	:	PCB Antenna
Antenna Gain(Peak)	:	4.58dBi (Provided by customer)

Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. For 802.11b, 802.11g, and 802.11n(HT20) modes were test with channel 1, 6, 11.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 23, 2022	1 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year



1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
5MHz~30MHz	60	50	

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.

AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

For Adapter: BI36GL-120300-AdU


Test Site: 1# Shielded Room

Operating Condition: 802.11b 2412MHz

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Temp.(°C)/Hum.(%RH): 28°C/51%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	46.80	9.83	56.63	65.56	-8.93	QP	
2	0.1620	32.39	9.83	42.22	55.36	-13.14	AVG	
3	0.5340	33.93	9.85	43.78	56.00	-12.22	QP	
4	0.5380	24.65	9.85	34.50	46.00	-11.50	AVG	
5	0.5660	21.28	9.86	31.14	46.00	-14.86	AVG	
6	3.4340	27.39	9.84	37.23	56.00	-18.77	QP	
7	3.8580	18.55	9.85	28.40	46.00	-17.60	AVG	
8	6.5899	20.53	9.86	30.39	50.00	-19.61	AVG	
9	6.6939	28.68	9.86	38.54	60.00	-21.46	QP	
10	18.2099	26.82	10.26	37.08	60.00	-22.92	QP	
11	20.8420	36.30	10.43	46.73	60.00	-13.27	QP	
12	21.2780	31.74	10.51	42.25	50.00	-7.75	AVG	



Conducted Emission Test Data

For Adapter: BI36GL-120300-AdU

Test Site: 1# Shielded Room
 Operating Condition: 802.11b 2412MHz
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 28°C/51%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	46.88	9.83	56.71	65.36	-8.65	QP	
2	0.1620	33.37	9.83	43.20	55.36	-12.16	AVG	
3	0.2819	35.90	9.83	45.73	60.76	-15.03	QP	
4	0.5420	34.07	9.85	43.92	56.00	-12.08	QP	
5	0.5420	25.21	9.85	35.06	46.00	-10.94	AVG	
6	1.8540	16.62	9.83	26.45	46.00	-19.55	AVG	
7	2.3140	27.31	9.83	37.14	56.00	-18.86	QP	
8	3.6420	27.53	9.85	37.38	56.00	-18.62	QP	
9	6.7659	20.88	9.86	30.74	50.00	-19.26	AVG	
10	15.3459	16.69	10.19	26.88	50.00	-23.12	AVG	
11	20.8299	33.95	10.44	44.39	50.00	-5.61	AVG	
12	20.8300	36.33	10.44	46.77	60.00	-13.23	QP	



Conducted Emission Test Data

For Adapter: BI72G-120500-E2


Test Site: 1# Shielded Room

Operating Condition: 802.11b 2412MHz

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Temp.(°C)/Hum.(%RH): 28°C/51%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	48.65	9.83	58.48	65.56	-7.08	QP	
2	0.1819	46.87	9.83	56.70	64.39	-7.69	QP	
3	0.1819	31.00	9.83	40.83	54.39	-13.56	AVG	
4	0.2340	25.16	9.83	34.99	52.30	-17.31	AVG	
5	0.3100	33.61	9.83	43.44	59.97	-16.53	QP	
6	0.4100	18.38	9.81	28.19	47.65	-19.46	AVG	
7	0.4940	30.90	9.85	40.75	56.10	-15.35	QP	
8	1.6460	13.48	9.84	23.32	46.00	-22.68	AVG	
9	3.8500	10.62	9.85	20.47	46.00	-25.53	AVG	
10	19.3020	32.47	10.29	42.76	50.00	-7.24	AVG	
11	19.7380	37.35	10.30	47.65	60.00	-12.35	QP	
12	21.9340	32.15	10.62	42.77	60.00	-17.23	QP	



Conducted Emission Test Data

For Adapter: BI72G-120500-E2


Test Site: 1# Shielded Room

Operating Condition: 802.11b 2412MHz

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Temp.(°C)/Hum.(%RH): 28°C/51%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	50.01	9.82	59.83	65.99	-6.16	QP	
2	0.1580	48.93	9.83	58.76	65.56	-6.80	QP	
3	0.1740	45.78	9.83	55.61	64.76	-9.15	QP	
4	0.2340	42.73	9.83	52.56	62.30	-9.74	QP	
5	0.3420	32.47	9.82	42.29	59.15	-16.86	QP	
6	19.7180	37.02	10.29	47.31	60.00	-12.69	QP	
7	0.1580	28.65	9.83	38.48	55.56	-17.08	AVG	
8	0.2700	19.82	9.83	29.65	51.12	-21.47	AVG	
9	0.5020	15.81	9.85	25.66	46.00	-20.34	AVG	
10	1.4380	13.95	9.84	23.79	46.00	-22.21	AVG	
11	3.7740	10.45	9.85	20.30	46.00	-25.70	AVG	
12	19.4980	32.07	10.29	42.36	50.00	-7.64	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
-		74.0	Peak	3	

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9kHz, VBW = 30kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector = Peak, Trace mode = Max hold, Sweep = auto couple.

For average measurement:

-VBW = 10Hz, When duty cycle is no less than 98 percent

-VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.


During the test, pre-scan all modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

For Adapter: BI36GL-120300-AdU

Test Mode: 802.11b 2412MHz
 Power Source: AC 120V, 60Hz for adapter
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.6°C/54%RH




No.	Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.0000	43.78	-20.26	23.52	40.00	-16.48	QP			
2	383.9318	48.06	-16.10	31.96	46.00	-14.04	QP			
3	432.5457	52.41	-15.71	36.70	46.00	-9.30	QP			
4	480.5276	44.24	-14.43	29.81	46.00	-16.19	QP			
5	528.2458	43.67	-12.64	31.03	46.00	-14.97	QP			
6	576.6443	43.22	-11.10	32.12	46.00	-13.88	QP			



Test Results (30~1000MHz)

For Adapter: BI36GL-120300-AdU

Test Mode: 802.11b 2412MHz
 Power Source: AC 120V, 60Hz for adapter
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.6°C/54%RH




No.	Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	53.5052	45.22	-17.07	28.15	40.00	-11.85	QP			
2	132.2205	46.98	-21.63	25.35	43.50	-18.15	QP			
3	154.8204	50.41	-21.88	28.53	43.50	-14.97	QP			
4	171.3925	45.54	-21.05	24.49	43.50	-19.01	QP			
5	480.5276	49.62	-12.79	36.83	46.00	-9.17	QP			
6	528.2458	42.80	-11.97	30.83	46.00	-15.17	QP			



Test Results (30~1000MHz)

For Adapter: BI72G-120500-E2

Test Mode: 802.11b 2412MHz
 Power Source: AC 120V, 60Hz for adapter
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.6°C/54%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.2110	52.50	-20.19	32.31	40.00	-7.69	QP			
2	36.7661	42.95	-17.59	25.36	40.00	-14.64	QP			
3	60.0690	42.03	-17.51	24.52	40.00	-15.48	QP			
4	150.0107	47.15	-22.85	24.30	43.50	-19.20	QP			
5	432.5457	45.60	-15.71	29.89	46.00	-16.11	QP			
6	480.5276	51.59	-14.43	37.16	46.00	-8.84	QP			



Test Results (30~1000MHz)

For Adapter: BI72G-120500-E2

Test Mode: 802.11b 2412MHz
 Power Source: AC 120V, 60Hz for adapter
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.6°C/54%RH



No.	Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.1054	43.90	-17.94	25.96	40.00	-14.04	QP			
2	36.8953	44.59	-16.16	28.43	40.00	-11.57	QP			
3	46.9948	43.08	-15.34	27.74	40.00	-12.26	QP			
4	60.2801	42.55	-17.59	24.96	40.00	-15.04	QP			
5	139.8508	51.03	-22.17	28.86	43.50	-14.64	QP			
6	480.5276	46.40	-12.79	33.61	46.00	-12.39	QP			



Test Results (Above 1000MHz)

Test Mode: 802.11b Mode			Test channel: Lowest			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.26	15.31	43.57	74.00	-30.43	Vertical
7236.00	29.81	18.06	47.87	74.00	-26.13	Vertical
9648.00	29.71	23.77	53.48	74.00	-20.52	Vertical
12060.00	*			74.00		Vertical
14472.00	*			74.00		Vertical
4824.00	27.70	15.31	43.01	74.00	-30.99	Horizontal
7236.00	30.01	18.06	48.07	74.00	-25.93	Horizontal
9648.00	28.11	23.77	51.88	74.00	-22.12	Horizontal
12060.00	*			74.00		Horizontal
14472.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	20.28	15.31	35.59	54.00	-18.41	Vertical
7236.00	21.59	18.06	39.65	54.00	-14.35	Vertical
9648.00	21.61	23.77	45.38	54.00	-8.62	Vertical
12060.00	*			54.00		Vertical
14472.00	*			54.00		Vertical
4824.00	20.21	15.31	35.52	54.00	-18.48	Horizontal
7236.00	22.58	18.06	40.64	54.00	-13.36	Horizontal
9648.00	19.85	23.77	43.62	54.00	-10.38	Horizontal
12060.00	*			54.00		Horizontal
14472.00	*			54.00		Horizontal



Test Results (Above 1000MHz)

Test Mode: 802.11b Mode				Test channel: Middle		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	28.21	15.41	43.62	74.00	-30.38	Vertical
7311.00	28.16	18.01	46.17	74.00	-27.83	Vertical
9748.00	29.65	23.79	53.44	74.00	-20.56	Vertical
12185.00	*			74.00		Vertical
14622.00	*			74.00		Vertical
4874.00	27.50	15.41	42.91	74.00	-31.09	Horizontal
7311.00	28.93	18.01	46.94	74.00	-27.06	Horizontal
9748.00	28.41	23.79	52.20	74.00	-21.80	Horizontal
12185.00	*			74.00		Horizontal
14622.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	19.03	15.41	34.44	54.00	-19.56	Vertical
7311.00	19.06	18.01	37.07	54.00	-16.93	Vertical
9748.00	19.90	23.79	43.69	54.00	-10.31	Vertical
12185.00	*			54.00		Vertical
14622.00	*			54.00		Vertical
4874.00	18.60	15.41	34.01	54.00	-19.99	Horizontal
7311.00	19.01	18.01	37.02	54.00	-16.98	Horizontal
9748.00	19.12	23.79	42.91	54.00	-11.09	Horizontal
12185.00	*			54.00		Horizontal
14622.00	*			54.00		Horizontal



Test Results (Above 1000MHz)

Test Mode: 802.11b Mode				Test channel: Highest		
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	28.07	15.51	43.58	74.00	-30.42	Vertical
7386.00	28.10	17.97	46.07	74.00	-27.93	Vertical
9848.00	29.09	23.82	52.91	74.00	-21.09	Vertical
12310.00	*			74.00		Vertical
14772.00	*			74.00		Vertical
4924.00	28.16	15.51	43.67	74.00	-30.33	Horizontal
7386.00	29.28	17.97	47.25	74.00	-26.75	Horizontal
9848.00	28.91	23.82	52.73	74.00	-21.27	Horizontal
12310.00	*			74.00		Horizontal
14772.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	18.86	15.51	34.37	54.00	-19.63	Vertical
7386.00	18.50	17.97	36.47	54.00	-17.53	Vertical
9848.00	20.34	23.82	44.16	54.00	-9.84	Vertical
12310.00	*			54.00		Vertical
14772.00	*			54.00		Vertical
4924.00	18.41	15.51	33.92	54.00	-20.08	Horizontal
7386.00	19.39	17.97	37.36	54.00	-16.64	Horizontal
9848.00	19.35	23.82	43.17	54.00	-10.83	Horizontal
12310.00	*			54.00		Horizontal
14772.00	*			54.00		Horizontal

Remark:

1. During the test, pre-scan the 802.11b,g,n(HT20) mode, and found the 802.11b mode is worse case , the report only record this mode.
2. Result=Reading + Factor
3. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.
4. During the test, pre-scan the all adapter, and found the adapter 3(model: BI72G-120500-E2) is worse case, the report only record this mode.




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

1. The Transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the power value.
3. Repeat above procedures on all channels needed to be tested.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.4. Test Data

Test Item	: Max. peak output power	Test Mode	: 802.11b/g/n(HT20)
Test Voltage	: AC 120V, 60Hz for adapter	Temperature	: 23.6°C
Test Result	: PASS	Humidity	: 45 %

Test Mode	Antenna	Frequency[MHz]	Peak Power[dBm]	Conducted Limit[dBm]
11B	Ant1	2412	18.90	≤30.00
		2437	18.68	≤30.00
		2462	18.18	≤30.00
11G	Ant1	2412	18.79	≤30.00
		2437	18.57	≤30.00
		2462	17.83	≤30.00
11N20	Ant1	2412	18.80	≤30.00
		2437	18.57	≤30.00
		2462	17.84	≤30.00

Note: The original data is referenced.



6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

6.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 4.58dBi It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

