

FCC Test Report

Report No.: AGC11322220701FE03

FCC ID : 2A7VE-BJD001

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Remote Control Car

BRAND NAME : Cusocue

MODEL NAME : Please see page 4

APPLICANT: NANCHANGSHI ZHAOQIANGKEJIYOUXIANGONGSI

DATE OF ISSUE : Jul. 22, 2022

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Subpart C Section 15.227

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 19

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jul. 22, 2022	Valid	Initial release







TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES	7
5. SYSTEM TEST CONFIGURATION	7
5.1. CONFIGURATION OF EUT SYSTEM	7
5.2. EQUIPMENT USED IN EUT SYSTEM	7
5.3. SUMMARY OF TEST RESULTS	7
6. TEST FACILITY	8
7. TEST EQUIPMENT LIST	8
8. RADIATED EMISSION	9
8.1 TEST LIMIT	9
8.2. MEASUREMENT PROCEDURE	9
8.2. TEST SETUP	11
8.3. TEST RESULT	12
9. BANDWIDTH	17
9.1. MEASUREMENT PROCEDURE	17
9.2. TEST SETUP	17
9.3. TEST RESULT	18
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	19
APPENDIX B: PHOTOGRAPHS OF EUT	19





1. VERIFICATION OF CONFORMITY

Applicant	NANCHANGSHI ZHAOQIANGKEJIYOUXIANGONGSI		
Address	DONGSHENGDADAO555HAO1HAOLOU613SHI, QINGSHANHUQUCHANGDONGGONGYEYUAN, NANCHANG, JIANGXI, CHINA		
Manufacturer	NANCHANGSHI ZHAOQIANGKEJIYOUXIANGONGSI		
Address	DONGSHENGDADAO555HAO1HAOLOU613SHI, QINGSHANHUQUCHANGDONGGONGYEYUAN, NANCHANG, JIANGXI, CHINA		
Factory	NANCHANGSHI ZHAOQIANGKEJIYOUXIANGONGSI		
Address	DONGSHENGDADAO555HAO1HAOLOU613SHI, QINGSHANHUQUCHANGDONGGONGYEYUAN, NANCHANG, JIANGXI, CHINA		
Product Designation	Remote Control Car		
Brand Name	Cusocue		
Test Model	BJD001		
Series Model	Please see page 5		
Difference description	All the series models are the same as the test model except for the model names and the color of appearance.		
Date of test	Jul. 13, 2022 to Jul. 22, 2022		
Deviation	None		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.227. The test results of this report relate only to the tested sample identified in this report.

Prepared By

Alan Duan
(Project Engineer)

Calvin Liu
(Reviewer)

Approved By

Max Zhang
(Authorized Officer)

Jul. 22, 2022

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 5 of 19

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Attriajor tecrinical description of Learns described as following			
Operation Frequency	27.145MHz		
Field Strength(3m)	55.80dBuV/m(AV)@3m		
Modulation	FSK		
Number of channels	1		
Hardware Version	CS-283T-T		
Software Version	CS-283T-T		
Antenna Designation	Integral antenna		
Antenna Gain	1dBi		
Power Supply	DC 3V by battery		

	LB001, LB002, LB003, LB004, LB005, LB006, LB007, LB008, LB009,
	LB010, LB011, LB012, LB013, LB014, LB015, LB016, LB017, LB018,
	LB019, LB020, BJD002, BJD003, BJD004, BJD005, BJD006, BJD007,
	BJD008, BJD009, BJD010, BJD011, BJD012, BJD013, BJD014, BJD015,
	BJD016, BJD017, BJD018, BJD019, BJD020, RC01, RC02, RC03, RC04,
Series Model	RC05, RC06, RC07, RC08, RC09, RC10, RC11, RC12, RC13, RC14,
	RC15, RC16, RC17, RC18, RC19, RC20, LBC1, LBC2, LBC3, LBC4,
	LBC5, LBC6, LBC7, LBC8, LBC9, LBC10, LBC11, LBC12, LBC13, LBC14,
	LBC15, LBC16, LBC17, LBC18, LBC19, LBC20, YKC01, YKC02, YKC03,
	YKC04, YKC05, YKC06, YKC07, YKC08, YKC09, YKC10, YKC11, YKC12,
	YKC13, YKC14, YKC15, YKC16, YKC17, YKC18, YKC19, YKC20



Page 6 of 19

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB
- Uncertainty of Occupied Channel Bandwidth: Uc = ±2 %



Page 7 of 19

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION		
1	Wireless operate mode		
2	TX mode		

Note:

- 1. All the test modes can be supply by new battery, and only the data of the worst case recorded in the test report.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1:

EUT	

5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	Remote Control Car	Cusocue	BJD001	EUT

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.227&15.209	Radiated Emission	Compliant
§15.215	20dB bandwidth	Compliant
§15.207	Conducted Emission	Not applicable

The conducted emission tests at AC port are not required for devices which only employ battery power for operation



Page 8 of 19

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd	
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	
Designation Number CN1259		
FCC Test Firm Registration Number		
A2LA Cert. No.	5054.02	
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA	

7. TEST EQUIPMENT LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
Attenuator	Weinachel Corp	58-30-33	N/A	Jul. 09, 2022	Jul. 08, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
ANTENNA	SCHWARZBECK	VULB9168	D69250	Jan. 08, 2021	Jan. 07, 2023



Page 9 of 19

8. RADIATED EMISSION

8.1 TEST LIMIT

Standard FCC 15.209


Frequency	Distance	Field	Strengths Limit	
(MHz)	Meters	μ V/m	dB(μV)/m	
0.009 ~ 0.490	300	2400/F(kHz)		
0.490 ~ 1.705	30	24000/F(kHz)		
1.705 ~ 30	30	30		
30 ~ 88	3	100	40.0	
88 ~ 216	3	150	43.5	
216 ~ 960	3	200	46.0	
960 ~ 1000	3	500	54.0	
Above 1000	3	Other:74.0 dB(µV)/m	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m	
		(Average)		

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed





at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RBW 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RBW 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RBW 120KHz for QP




8.2. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz





Page 12 of 19

8.3. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

EUT:	Remote Control Car	Model Name.:	BJD001
Temperature :	25 ℃	Relative Humidtity:	60%
Pressure :	1010 hPa	Test Voltage :	DC 3V
Test Mode :	Mode 1	Polarization :	

Frequency MHz	Polarization	Reading dB(uV) AV	Factor dB (1/m)	Level dB(uV/m) AV	Limit dB(uV/m) AV	Margin dB	Pass/Fail
27.145	Face	44.54	11.26	55.80	80.00	-24.20	Pass
27.145	Side	44.32	11.26	55.58	80.00	-24.42	Pass

Note: 1.The level of peak emission is less than the average limit, so the level of average emission need not to be tested. Other emissions from 9kHz to 30MHz are considered as ambient noise. No recording in the test report.


2: Level(dBuV/m)=Reading(dBuV)+Factor(dB/m)

 $Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ loss(dB) + Attenuation(dB) for\ Attenuator(dB/m) + Cable\ loss(dB/m) + Cable\ loss$

Margin=Level-Limit




RADIATED EMISSION BELOW 1GHZ-Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∀	dB	dBuV/m	dBuV/m	dB	Detector
1		39.7000	-1.32	14.92	13.60	40.00	-26.40	peak
2		67.1833	-0.62	16.93	16.31	40.00	-23.69	peak
3		139.9333	-0.60	17.64	17.04	43.50	-26.46	peak
4	:	290.2832	2.10	19.71	21.81	46.00	-24.19	peak
5	4	445.4832	1.17	20.83	22.00	46.00	-24.00	peak
6	*	670.2000	1.69	22.79	24.48	46.00	-21.52	peak



RADIATED EMISSION BELOW 1GHZ-Vertical




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBu∀	dB	dBuV/m	dBuV/m	dB	Detector
1		31.6167	2.53	12.22	14.75	40.00	-25.25	peak
2		72.0333	-0.31	16.67	16.36	40.00	-23.64	peak
3		128.6167	2.26	18.08	20.34	43.50	-23.16	peak
4		138.3167	2.62	18.21	20.83	43.50	-22.67	peak
5		257.9500	3.20	18.35	21.55	46.00	-24.45	peak
6	*	860.9667	2.00	27.55	29.55	46.00	-16.45	peak

RESULT: PASS



Radiated Emission above 1GHz Test at 3m Distance-Horizontal



PK Data List

NO	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1164.9165	64.51	-19.87	74.00	9.49	150	273	Horizontal
2	1646.0646	61.44	-18.79	74.00	12.56	150	209	Horizontal
3	1884.0884	59.57	-16.93	74.00	14.43	150	162	Horizontal
4	1989.499	65.79	-16.10	74.00	8.21	150	232	Horizontal
5	3126.9127	63.39	-10.84	74.00	10.61	150	37	Horizontal
6	3407.4407	63.29	-9.98	74.00	10.71	150	197	Horizontal

AV Final Data List


NO.	Freq. [MHz]	Factor [dB]	AV Value [dBµV/m]	AV Limit [dBµV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1165.2175	-19.87	29.46	54.00	24.54	100	359.3	Horizontal
2	1646.0456	-18.79	28.17	54.00	25.83	100	0	Horizontal
3	1884.3774	-16.93	29.42	54.00	24.58	100	0	Horizontal
4	1989.4200	-16.10	32.63	54.00	21.37	100	0	Horizontal
5	3127.2597	-10.84	37.88	54.00	16.12	100	0	Horizontal
6	3407.5537	-9.99	38.73	54.00	15.27	100	0	Horizontal

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Radiated Emission above 1GHz Test at 3m Distance-Vertical



PK Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1149.615	59.24	-19.87	74.00	14.76	150	241	Vertical
2	1219.3219	61.18	-19.88	74.00	12.82	150	312	Vertical
3	1649.4649	60.07	-18.76	74.00	13.93	150	289	Vertical
4	2108.5109	59.42	-15.39	74.00	14.58	150	300	Vertical
5	3344.5345	62.84	-10.18	74.00	11.16	150	141	Vertical
6	3592.7593	65.35	-9.40	74.00	8.65	150	194	Vertical

AV Final Data List

NO.	Freq. [MHz]	Factor [dB]	AV Value [dBµV/m]	AV Limit [dBµV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1149.8640	-19.87	29.07	54.00	24.93	100	0	Vertical
2	1219.4929	-19.88	29.42	54.00	24.58	100	0	Vertical
3	1649.7789	-18.76	30.17	54.00	23.83	100	0	Vertical
4	2108.7919	-15.39	31.95	54.00	22.05	100	0	Vertical
5	3344.0465	-10.18	39.33	54.00	14.67	100	0	Vertical
6	3592.4203	-9.40	39.89	54.00	14.11	100	0	Vertical

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Limit-Level.

2. The "Factor" value can be calculated automatically by software of measurement system.



Page 17 of 19

9. BANDWIDTH

9.1. MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below:

Centre frequency = Operation Frequency

RBW=300Hz


VBW=1KHz


Span: 30kHz

Sweep time: Auto

- 2. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 3. Record the plots and Reported.

9.2. TEST SETUP







9.3. TEST RESULT

TEST ITEM	20DB BANDWIDTH
TEST MODULATION	FSK

Test Data (kHz)	Criteria	
Operate Channel	120.8	PASS

TEST PLOT OF BANDWIDTH





Page 19 of 19

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC11322220701AP01

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC11322220701AP02

----END OF REPORT---



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.