



FCC&IC TEST REPORT

FCC ID: 2A7ZC-FC2

On Behalf of

GEOMATE POSITIONING PTE. LTD.

Handheld GNSS Data Collector

Model No.: FC2

Prepared for : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE
(200808)

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,
518103, Shenzhen, Guangdong, China

Report Number : A2312102-C01-R08
Date of Receipt : December 25, 2023
Date of Test : December 25, 2023 - June 20, 2024
Date of Report : June 20, 2024
Version Number : V0
Test Result : **Pass**

Contents

1. General Information	5
1.1. Description of Device (EUT)	5
1.2. Accessories of Device (EUT)	6
1.3. Ancillary Equipment Details	6
1.4. Test Lab Information	6
2. Summary of test	7
2.1. Summary of test result	7
2.2. Block Diagram	7
2.3. Test mode	7
2.4. Test Conditions	7
2.5. Measurement Uncertainty (95% confidence levels, k=2)	8
2.6. Test Equipment	9
3. Occupied bandwidth and 20dB Bandwidth	10
3.1. Limit	10
3.2. Test Procedure	10
3.3. Test Setup	10
3.4. Test Result	10
4. Radiated emissions	11
4.1. Limit	11
4.2. Block Diagram of Test setup	11
4.3. Test Procedure	12
4.4. Test Result	13
5. Frequency stability	19
5.1. Test limit	19
5.2. Test Procedure	19
5.3. Test Setup	19
5.4. Test Results	20
6. Power Line Conducted Emissions	21
6.1. Block Diagram of Test Setup	21
6.2. Limit	21
6.3. Test Procedure	21
6.4. Test Result	21
7. Antenna Requirements	24
7.1. Limit	24
7.2. Antenna Connected Construction	24
7.3. Results	24
8. Test setup photo	25

TEST REPORT DECLARATION

Applicant : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE (200808)
Manufacturer : GEOMATE POSITIONING PTE. LTD.
Address : 808 FRENCH ROAD #04-167 KITCHENER COMPLEX SINGAPORE (200808)
EUT Description : Handheld GNSS Data Collector
(A) Model No. : FC2

(B) Trademark : 

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.225

ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:

Yannis Wen
Project Engineer



Approved by (name + signature).....:

Jack Xu
Project Manager



Date of issue.....

June 20, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 20, 2024	Initial released Issue	Yannis Wen

1. General Information

1.1. Description of Device (EUT)

EUT : Handheld GNSS Data Collector

Model No. : FC2

DIFF : N/A

Power supply : DC 5V from adapter and DC 3.8V from battery.

NFC

Operation frequency : 13.56MHz

Channel No. : 1 Channel

Modulation : ASK

Antenna Type : Internal antenna, Antenna gain 1.5dBi.
Antenna information is provided by applicant.

Software version : V1.0

Hardware Version : V1.0

1.2. Accessories of Device (EUT)

Accessories	: AC Adapter
Manufacturer	: EDAC POWER Electronics Co., Ltd
Model	: EA1012AVRU-050
Ratings	: Input: 100-240Vac~50/60Hz 1.0A Output: 5.0V~2.4A

1.3. Ancillary Equipment Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	N/A	N/A	N/A	N/A	N/A

1.4. Test Lab Information

Shenzhen Alpha Product Testing Co., Ltd


Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

2. Summary of test

2.1. Summary of test result

Description of Test Item	Standard	Results
	FCC	
Conducted Emission	15.207	PASS
Radiated emissions	15.209	PASS
Fundamental field strength limit	15.225	PASS
Frequency stability	15.225	PASS
20dB Emission Bandwidth	15.225	PASS
Antenna Requirement	15.203	PASS

2.2. Block Diagram



2.3. Test mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
1	CH1	13.56
Note: According exploratory test, EUT will have maximum output power in those data rate. so those data rate were used for all test.		

2.4. Test Conditions

Temperature range	21-25°C
Humidity range	40-75%
Pressure range	86-106kPa

2.5. Measurement Uncertainty (95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V) 3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V) 3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V) 4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.6. Test Equipment

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2023.08.16	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2023.08.16	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2023.08.16	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	1Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	1Year
RF Cable	Resenberger	Cable 1	/	RE1	2023.08.16	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2023.08.16	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2023.08.16	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2023.08.16	1Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2023.07.25	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2023.08.16	1 Year

3. Occupied bandwidth and 20dB Bandwidth

3.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC part 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

3.2. Test Procedure

1. The transmitter output was directly connected to a spectrum analyzer with a 50Ω cable. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 3KHz RBW and 10kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.
2. The test receiver set RBW =1-5%BW, VBW≥3*RBW, Sweep time set auto, detail see the test plot for 99% Bandwidth.

3.3. Test Setup



3.4. Test Result

Mode	Freq (MHz)	20dB Bandwidth (KHz)	99% Bandwidth(KHz)	Limit (kHz)	Conclusion
Tx Mode	13.56	11.66	50.775	/	PASS



4. Radiated emissions

4.1. Limit

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Note:

a) The tighter limit applies at the band edges.

For example: F.S limit at 88MHz is 100uV/m

b) If measurement is made at 3m distance, then F.S Limit at 3m distance is adjusted by using the formula of $L_{d1} = L_{d2} * (d2/d1)^2$.

For example:

F.S Limit at 30m(d2) distance is 30uV/m(L_{d2}), then F.S Limit at 3m(d1) distance is

$$L_{d1} = 30\text{uV/m} * (30/3)^2 = 100 * 30\text{uV/m} = 69.54 \text{ dBuV/m}$$

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.


(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.


(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

4.2. Block Diagram of Test setup

In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



In 3m Anechoic Chamber Test Setup Diagram for frequency 30MHz-1GHz



4.3. Test Procedure

Procedure of Preliminary Test

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 4.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.

Mains cables, telephone lines or other connections to auxiliary equipment located outside the test are shall drape to the floor, be fitted with ferrite clamps or ferrite tubes placed on the floor at the point where the cable reaches the floor and then routed to the place where they leave the turntable. No extension cords shall be used to mains receptacle.

The antenna was placed at 3 meter away from the EUT as stated in ANSI C63.10:2013. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.

The Receiver quickly scanned from 9KHz to 30MHz and 30MHz to 1GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

The test mode(s) described in clause 2.4 were scanned during the preliminary test:

After the preliminary scan, we found the test mode producing the highest emission level. The EUT and cable configuration, antenna position, polarization and turntable position of the above highest emission level were recorded for the final test.

Procedure of Final Test

EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.

The Receiver scanned from 9KHz to 30MHz and 30MHz to 1GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.

Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and only Q.P. reading is presented.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 200Hz for 9 KHz to 150 KHz measure, 10 KHz for 150 KHz to 30MHz measure and 120 KHz for 30 MHz to 1GHz measure .


4.4. Test Result

PASS. (See below detailed test result)

Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS


Frequency Range	:	9KHz~30MHz
Test Mode	:	TX: 13.56MHz
Test Results	:	PASS
Note: 1. The test results are listed in next pages. 2. This mode is worst case mode, so this report only reflected the worst mode. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the quasi-peak detector need not be carried out.		

X

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	
							dB	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		0.0165	10.54	21.34	31.88	123.3	-91.48	peak
2		0.0256	10.37	21.11	31.48	119.5	-88.08	peak
3		0.0386	11.29	20.52	31.81	116.0	-84.19	peak
4		0.0468	11.95	20.07	32.02	114.3	-82.31	peak
5		0.0922	10.73	19.88	30.61	108.4	-77.85	peak
6	*	0.0995	11.72	19.80	31.52	107.8	-76.28	peak

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		0.2000	24.96	20.13	45.09	101.7	-56.69	peak
2		0.4465	23.56	19.78	43.34	94.81	-51.47	peak
3		0.7430	17.87	19.85	37.72	70.33	-32.61	peak
4		1.2177	12.77	20.05	32.82	65.97	-33.15	peak
5		1.8472	12.19	20.21	32.40	70.00	-37.60	peak
6	*	13.5173	46.72	20.63	67.35	70.00	-2.65	peak


Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Note: Mark 6 is the working frequency of the EUT.

From 30MHz to 1GHz: Conclusion: PASS


Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment		Limit	Margin	
					MHz	dBuV	dB	dBuV/m	dB
1	*	34.9272	16.13	13.74	29.87	40.00	-10.13	peak	
2		57.0712	16.40	13.41	29.81	40.00	-10.19	peak	
3		139.6875	14.70	14.29	28.99	43.50	-14.51	peak	
4		205.2428	19.94	10.99	30.93	43.50	-12.57	peak	
5		401.8855	11.61	16.29	27.90	46.00	-18.10	peak	
6		722.9924	12.65	22.06	34.71	46.00	-11.29	peak	

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
			Level	Factor	ment	dBuV/m	dB	Detector
		MHz	dBuV					
1		56.9779	11.59	13.41	25.00	40.00	-15.00	peak
2		147.7486	9.98	14.89	24.87	43.50	-18.63	peak
3	*	206.5665	21.41	11.01	32.42	43.50	-11.08	peak
4		239.3151	19.92	12.53	32.45	46.00	-13.55	peak
5		361.8830	14.78	15.47	30.25	46.00	-15.75	peak
6		720.6300	11.39	22.03	33.42	46.00	-12.58	peak

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Field Strength Emissions Result

Temperature		24°C			Relative Humidity		56%	
Pressure		960hPa			Distance		3m	
Test Mode		TX						
Freq. (MHz)	Position H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limits 3m (dBuV/m)	Margin (dBuV/m)	
13.560	H	Peak	81.11	-13.94	67.17	124	-56.83	
13.560	H	AV	78.85	-13.94	64.91	104	-39.09	
13.110	H	Peak	50.75	-13.94	36.81	80.5	-43.69	
13.410	H	Peak	51.42	-13.94	37.48	90.5	-53.02	
13.553	H	Peak	48.89	-13.94	34.95	90.5	-55.55	
13.567	H	Peak	45.79	-13.93	31.86	90.5	-58.64	
13.710	H	Peak	43.85	-13.93	29.92	80.5	-50.58	
14.010	H	Peak	45.23	-13.93	31.30	80.5	-49.20	
Freq. (MHz)	Position H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limits 3m (dBuV/m)	Margin (dBuV/m)	
13.560	V	Peak	80.55	-13.94	66.61	124	-57.39	
13.560	V	AV	77.33	-13.94	63.39	104	-40.61	
13.110	V	Peak	51.02	-13.94	37.08	80.5	-43.42	
13.410	V	Peak	50.51	-13.94	36.57	90.5	-53.93	
13.553	V	Peak	48.49	-13.94	34.55	90.5	-55.95	
13.567	V	Peak	46.35	-13.93	32.42	90.5	-58.08	
13.710	V	Peak	45.18	-13.93	31.25	80.5	-49.25	
14.010	V	Peak	43.64	-13.93	29.71	80.5	-50.79	

Note:

1: 30m to 3m correction factor calculation:

$$40 \times \log(30m/3m) = 40$$

2: --Means other frequency and mode comply with standard requirements and at least have 20dB margin.

3: Correct Factor = Cable Loss + Antenna Factor - Amplifier Gain

Measurement Result = Reading + Correct Factor

Margin = Measurement Result - Limit

5. Frequency stability

5.1. Test limit


Please refer section RSS 210 B.6 & 15.225e.

Regulation 15.225(e) The frequency tolerance of the carrier signal shall be maintained within +/-0.01% (± 100 ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.2. Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3. Test Setup



5.4. Test Results


PASS.

Detailed information please see the following page.

Assigned Frequency(MHz): 13.56MHz				
Voltage	Temperature	Measured Frequency (MHz)	Frequency stability	Limit
Low DC 4.37V	+20°C	13.560895	0.000895	$\pm 100 \text{ ppm}$ $\pm 0.001356 \text{ MHz}$
Normal DC 3.8V	-20°C	13.560642	0.000642	
	-10°C	13.560915	0.000915	
	0°C	13.560258	0.000258	
	+10°C	13.560285	0.000285	
	+20°C	13.560067	0.000067	
	+30°C	13.560744	0.000744	
	+40°C	13.559496	-0.000504	
	+50°C	13.560766	0.000766	
High DC 3.23V	+20°C	13.559818	-0.000182	

6. Power Line Conducted Emissions

6.1. Block Diagram of Test Setup



6.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(µV)	Average Level dB(µV)
	66 ~ 56*	56 ~ 46*
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.


6.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N1), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C64.10:2013 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

6.4. Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit


Line:

No.	Mk.	Reading		Correct Factor	Measure-ment	Limit	Margin	Comment
		Freq.	Level					
		MHz	dBuV	dB	dBuV	dB	Detector	Comment
1	0.1530	40.92	9.94	50.86	65.84	-14.98	peak	
2	0.2460	36.01	9.97	45.98	61.89	-15.91	peak	
3	0.4920	35.11	9.96	45.07	56.13	-11.06	QP	
4 *	0.4920	30.72	9.96	40.68	46.13	-5.45	AVG	
5	1.0740	34.82	9.91	44.73	56.00	-11.27	peak	
6	2.2770	30.23	9.90	40.13	56.00	-15.87	peak	
7	26.6100	23.94	10.51	34.45	60.00	-25.55	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dB			
1		0.1650	41.96	9.93	51.89	65.21	-13.32	peak	
2		0.4950	36.67	9.96	46.63	56.08	-9.45	QP	
3	*	0.4950	29.46	9.96	39.42	46.08	-6.66	AVG	
4		0.7200	35.70	9.93	45.63	56.00	-10.37	peak	
5		2.4690	31.04	9.91	40.95	56.00	-15.05	peak	
6		3.5640	27.33	9.96	37.29	56.00	-18.71	peak	
7		7.1370	24.43	10.12	34.55	60.00	-25.45	peak	

*:Maximum data x:Over limit !:over margin

<Reference Only>

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

7. Antenna Requirements

7.1. Limit

For intentional device, according to RSS-Gen Section 6.8 and FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.209, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.



7.2. Antenna Connected Construction

The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

7.3. Results

The EUT antenna is Internal Antenna. It complies with the standard requirement.

8. Test setup photo



-----END OF THE REPORT-----