



RF Exposure Evaluation

FCC ID: 2A7ZM-M7MICROPHONE

1. Client Information

Applicant	:	JBU GLOBAL LLC
Address	:	19416 NE 26th Ave, 114B, Miami, Florida 33180, United States
Manufacturer	:	New Tech Development Co,Ltd
Address	:	Room 301, Building 2000081, Shangwei IndustrialZone, Zhangkengjing Community, Guanhu Street, Longhua District, Shenzhen. China.

2. General Description of EUT

EUT Name	:	Ostinato M7 Microphone	
Model(s) No.	:	Ostinato M7 Microphone	
Model Different	:	----	
Brand Name	:	MASINGO	
Sample ID	:	202209-0054-1-1#& 202209-0054-1-2#	
Product Description	:	Operation Frequency:	565-604MHz
	:	Number of Channel:	3 Channels
	:	RF Output Power:	1.72dBi Internal antenna
	:	Antenna Gain:	Digital systems
Power Supply	:	1.5V AA*2 battery	
Software Version	:	V1.0	
Hardware Version	:	V2.0	
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.			

Note: More test information about the EUT please refer the RF Test Report.

The RF Exposure Evaluation for FCC:

SAR Test Exclusion Calculations

FCC: According to 447498 D04 Interim General RF Exposure Guidance v01.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169



Calculation:

Test separation: 5mm					
Wireless microphone					
Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mW)	Limit P _{th} (mW)
565	0.609	0±1	1	1.259	15
584	0.083	0±1	1	1.259	15
604	0.189	0±1	1	1.259	15

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D04, No SAR is required.

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 and the RSS-102§4 Table 4 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06, No SAR is required.

-----END OF REPORT-----

