



MPE Calculation

| | |
|-----------------------|------------------------------------------------|
| Applicant: | Visir Inc. |
| Address: | 39899 Balentine Drive STE 200 Newark, CA 94560 |
| Product: | RIX Laser RangeFinder |
| FCC ID: | 2A7ZZ-4D-ILR |
| Model No.: | LRF-01 |
| Reference RF report # | 709502308708-00B |

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1,500 | / | / | f/1500 | 30 |
| 1,500–100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);



Calculated Data for BLE

| | |
|------------------------------------------------------------------------------------------|--------|
| Maximum peak output power at antenna input terminal (dBm): | 3.94 |
| Maximum peak output power at antenna input terminal (mW): | 2.48 |
| Prediction distance (cm): | 20 |
| Antenna Gain, typical (dBi): | 2.47 |
| Maximum Antenna Gain (numeric): | 1.766 |
| The worst case is power density at predication frequency at 20 cm (mW/cm ²): | 0.0009 |
| MPE limit for general population exposure at prediction frequency (mW/cm ²): | 1.0 |

The max power density 0.0009 (mW/cm²) < 1 (mW/cm²)

Result: Compliant

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG

Jiayi XU

Guo Chengjie

EMC Section Manager

EMC Project Engineer

EMC Test Engineer

Date: 2023-12-12

Date: 2023-12-12

Date: 2023-12-12