

# FCC TEST REPORT

For

**Team Free**

**Model Number: TF100**

**FCC ID: 2A82ETF100**

**Report Number : WT228002407**

Test Laboratory : Shenzhen Academy of Metrology and Quality  
Inspection  
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan,  
Shenzhen, China  
Tel : 0086-755-86928965  
Fax : 0086-755-86009898-31396  
Web : [www.smq.com.cn](http://www.smq.com.cn)  
E-mail : [emcrf@smq.com.cn](mailto:emcrf@smq.com.cn)

## Revision History

No	Date	Remark
V1.0	2023.02.06	Initial issue

## TEST REPORT DECLARATION




Applicant : Shenzhen Jiancheng Yunshi Technology Co., Ltd  
Address : A2101, Building 9, Zone 2, No. 3609 Baishi Road, Nanshan District, Shenzhen  
Manufacturer : Shenzhen Jiancheng Yunshi Technology Co., Ltd  
Address : A2101, Building 9, Zone 2, No. 3609 Baishi Road, Nanshan District, Shenzhen  
EUT Description : Team Free  
Model No. : TF100  
Trade mark : TELE System  
Serial Number : /  
FCC ID : 2A82ETF100

Test Standards:

### FCC Part 15 Subpart B

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:	 _____ (Zhou Fangai 周芳媛)	Date:	Feb.06, 2023 _____
Checked by:	 _____ (Wan Xiaojing 万晓婧)	Date:	Feb.06, 2023 _____
Approved by:	 _____ (Lin Yixiang 林奕翔)	Date:	Feb.06, 2023 _____

## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION .....</b>	<b>3</b>
<b>1. TEST RESULTS SUMMARY .....</b>	<b>5</b>
<b>2. GENERAL INFORMATION.....</b>	<b>6</b>
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer .....	6
2.3. Measurement Uncertainty .....	6
<b>3. PRODUCT DESCRIPTION.....</b>	<b>8</b>
3.1. EUT Description.....	8
3.2. Block Diagram of EUT Configuration .....	8
3.3. Operating Condition of EUT .....	8
3.4. Support Equipment List .....	9
3.5. Test Conditions.....	9
3.6. Modifications .....	9
<b>4. TEST EQUIPMENT USED .....</b>	<b>10</b>
<b>5. CONDUCTED EMISSION TEST .....</b>	<b>11</b>
5.1. Test Standard and Limit .....	11
5.2. Test Procedure .....	11
5.3. Test Arrangement.....	11
5.4. Test Data .....	11
<b>6. RADIATION EMISSION TEST.....</b>	<b>14</b>
6.1. Test Standard and Limit .....	14
6.2. Test Procedure .....	14
6.3. Test Arrangement.....	15
6.4. Test Data .....	15

## 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
Conducted Emission	15.107	Pass
Radiation Emission	15.109	Pass

Remark: "N/A" means "Not applicable."

## **2. GENERAL INFORMATION**

### **2.1. Report information**

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

The lab will not be liable for any loss or damage resulting for false, inaccurate, inappropriate or incomplete product information provided by the applicant/manufacturer.

### **2.2. Laboratory Accreditation and Relationship to Customer**

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

The Laboratory is registered to perform emission tests with VCCI, and the registration number are C-20048, G20076, R-20077, R-20078 and T-20047.

The Laboratory is Accredited Testing Laboratory of American Association for Laboratory Accreditation (A2LA) and certificate number is 3292.01.

### **2.3. Measurement Uncertainty**

Conducted Emission

9 kHz~150 kHz  $U=3.7\text{dB}$   $k=2$   
150 kHz~30MHz  $U=3.3\text{dB}$   $k=2$

Radiated Emission

30MHz~1000MHz  $U=4.3\text{dB}$   $k=2$   
1GHz~6GHz  $U=4.6\text{ dB}$   $k=2$   
6GHz~40GHz  $U=5.1\text{dB}$   $k=2$

### 3. PRODUCT DESCRIPTION


NOTE: The extreme test conditions for temperature and antenna gain were declared by the manufacturer.

#### 3.1. EUT Description

Description	: Team Free
Manufacturer	: Shenzhen Jiancheng Yunshi Technology Co., Ltd
Model Number	: TF100
Test voltage	: AC 120V/60Hz
Software Version	: V1.1.34
Hardware Version	: V11
Frequency	: 2.4WiFi:2412MHz~2462MHz 5WiFi: U-NII 1(5180~5240 MHz) U-NII 3(5745~5825 MHz)
Type(s) of Modulation	: DSSS (DBPSK, DQPSK, CCK) for 802.11b OFDM (BPSK, QPSK, 16QAM, 64QAM) for 802.11a/g/n OFDM (BPSK, QPSK, 16QAM, 64QAM,256QAM) for 802.11ac
Antenna Type	: 2.4G WiFi: Loop Antenna -1.68dBi 5G WiFi: Loop Antenna U-NII 1(5180~5240 MHz) 1.47dBi U-NII 3(5745~5825 MHz) 4.24dBi

Remark: --

#### 3.2. Block Diagram of EUT Configuration



Test mode 1

#### 3.3. Operating Condition of EUT

Test mode 1: Full system executed

EUT has more than one typical operation, only the worst test mode will be recorded in this report.

The Radiated emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).



### 3.4. Support Equipment List

Table 2 Support Equipment List

Name	Model No.	S/N	Manufacturer
Adapter for EUT	GA-0361203000	---	Huizhou Guoatong Technology Co., Ltd
DomyBox	DM4036	---	Domy
Notebook	HP ProBook 440 G6	---	HP
LCD Monitor	P2421	---	DELL
LCD Monitor	24E1N56	--	FEISHENG
Mouse	MSU1465	---	HP

### 3.5. Test Conditions

Date of test : Oct.21, 2022- Feb.02, 2023

Date of EUT Receive : Oct.18, 2022

Temperature: 22°C-24°C

Relative Humidity: 45%-53%

### 3.6. Modifications

No modification was made.

#### 4. TEST EQUIPMENT USED

Table 3 Test Equipment List

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
<b>Conducted Emission</b>					
SB3319	Test Receiver	R&S	ESCS30	Nov.04,2021	1 Year
SB3319	Test Receiver	R&S	ESCS30	Nov.03,2022	1 Year
SB8501/06	AMN	R&S	ESH2-Z5	Jan.20,2022	1 Year
SB8501/06	AMN	R&S	ESH2-Z5	Jan.19,2023	1 Year
SB9548	Shielded Room	Albatross	SR	Sep.06,2022	1 Year
<b>Radiated Emission</b>					
SB15044/01	Test Receiver	R&S	ESW8	Sep.13,2022	1 Year
SB18856	Broadband Antenna	SCHWARZBE CK	VULB9163	Sep.07,2022	1 Year
SB9422/16	Horn Antenna	R&S	HF907	Apr.08,2022	1 Year
SB18844	Semi Anechoic Chamber	Albatross	9×6×6(m)	Mar.22,2022	1 Year
SB20321/02	Spectrum Analyzer	R&S	FSW43	Jan.13,2022	1 Year
SB20321/02	Spectrum Analyzer	R&S	FSW43	Jan.12,2023	1 Year
SB8501/11	Antenna	R&S	3160-09	Mar.09,2020	3 Years
SB8501/12	Antenna	R&S	3160-10	Mar.17,2020	3 Years
SB8501/16	Pre-Amplifier	R&S	SCU-26	Jan.20,2022	1 Year
SB8501/16	Pre-Amplifier	R&S	SCU-26	Jan.19,2023	1 Year
SB9059	Pre-Amplifier	R&S	SCU-40	Aug.23,2022	1 Year
SB18844	Semi Anechoic Chamber	Albatross	9×6×6(m)	Mar.22,2022	1 Year

## 5. CONDUCTED EMISSION TEST

### 5.1. Test Standard and Limit

#### 5.1.1. Test Standard

FCC Part 15: Section 15.107

#### 5.1.2. Test Limit

Table 4 Conducted Emission Test Limit (Class B)

Frequency	Power Port limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15MHz ~ 0.5MHz	66~56*	56~46*
0.5MHz ~ 5 MHz	56	46
5 MHz ~ 30MHz	60	50

\* Decreasing linearly with logarithm of the frequency

### 5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions from both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

### 5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 5.4. Test Data


The emissions don't show in below are too low against the limits. Refer to the test curves.

Table 5 Conducted Emission Test Data at mains Port


Test mode: 1								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.150	9.7	44.7	54.4	66	32.2	41.9	56
	0.190	9.7	40.2	49.9	64.0	30.1	39.8	54.0
	0.362	9.7	39.7	49.4	58.7	33.5	43.2	48.7
	0.490	9.7	32.7	42.4	56.2	26.5	36.2	46.2
	1.026	9.8	34.0	43.8	56	26.9	36.7	46
	1.290	9.8	33.7	43.5	56	26.4	36.2	46
Neutral	0.162	9.7	43.7	53.4	65.4	29.6	39.3	55.4
	0.198	9.7	40.1	49.8	63.7	29.9	39.6	53.7
	0.358	9.7	39.2	48.9	58.8	32.8	42.5	48.8
	0.506	9.8	31.4	41.2	56	24.8	34.6	46
	0.730	9.8	32.9	42.7	56	25.6	35.4	46
	1.882	9.8	33.6	43.4	56	26.6	36.4	46

- REMARKS: 1. Emission level (dBuV) =Read Value (dBuV) + Correction Factor (dB)  
 2. Correction Factor (dB) =LISN Factor (dB) + Cable Factor (dB) +Limiter Factor (dB)  
 3. The other emission levels were more than 20dB below the limits.

### Line



### Neutral



## 6. RADIATION EMISSION TEST

### 6.1. Test Standard and Limit

#### 6.1.1. Test Standard

FCC Part 15: Section 15.109

#### 6.1.2. Test Limit

Table 6 Radiation Emission Test Limit for FCC (Class B)

Frequency	Test distance	Limit dB( $\mu$ V/m)		
		Quasi-peak	Average	Peak
30MHz~88MHz	<b>3m</b>	40	/	/
88MHz~216MHz	<b>3m</b>	43.5		
216MHz~960MHz	<b>3m</b>	46		
960MHz~1000MHz	<b>3m</b>	54		
>1000MHz	<b>3m</b>		54	74
<b>Conditional testing procedure for above 1 GHz :</b>				
<b>Highest frequency generated or used in the device or on which the device operates or tunes (MHz)</b>		<b>Upper frequency of measurement range (MHz)</b>		
Below 1.705		30		
1.705~108		1000		
108~500		2000		
500~1000		5000		
Above 1000		5th harmonic of the highest frequency or 40 GHz, whichever is lower.		

\* The lower limit shall apply at the transition frequency.

\* The test distance is 3m.

### 6.2. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set **3 meters** away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

RBW = 100 kHz (less than or equal to 1 GHz); 1 MHz (above 1 GHz)

VBW  $\geq$  3 x RBW

Detector = Peak & Quasi-Peak (frequency range 30 MHz to 1 GHz);

Peak & Average (frequency range above 1 GHz);

Changing VBW to 10 Hz for average measurement

The use of a higher-than-specified video bandwidth produces a conservative measurement result.

### 6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 6.4. Test Data

The emissions don't show in below are too low against the limits. Refer to the test curves.

Table 7 Radiated Emission Test Data

Test mode: 1								
Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Reading (dBµV/m)	Level (dBµV/m)	Polarity (Horizontal/Vertical)	Limits (dBµV/m)	Margin (dB)	Note
171.013	1.5	9.0	28.4	38.9	Horizontal	43.5	4.6	QP
341.972	2.2	14.1	22.5	38.8	Horizontal	46	7.2	QP
399.933	2.4	14.6	26.6	43.6	Horizontal	46	2.4	QP
513.060	2.8	16.6	20.7	40.1	Horizontal	46	5.9	QP
800.050	3.6	20.1	14.5	38.2	Horizontal	46	7.8	QP
60.797	0.9	12.7	20.5	34.1	Vertical	40	5.9	QP
79.833	1.0	7.8	27.1	35.9	Vertical	40	4.1	QP
85.411	1.0	10.3	25.0	36.3	Vertical	40	3.7	QP
400.055	2.4	15.1	25.6	43.1	Vertical	46	2.9	QP
513.060	2.8	16.6	20.3	39.7	Vertical	46	6.3	QP
855.106	3.8	20.1	16.2	40.1	Vertical	46	5.9	QP
1025.500	-41.1	24.4	65.7	49.0	Vertical	74	25.0	PK
1282.200	-40.8	24.3	66.2	49.7	Vertical	74	24.3	PK
1482.800	-40.8	25.1	65.1	49.4	Vertical	74	24.6	PK
2224.000	-40.2	28.3	61.3	49.4	Vertical	74	24.6	PK
2564.000	-39.9	28.6	61.1	49.8	Vertical	74	24.2	PK
2966.900	-39.2	29.4	57.8	48.0	Vertical	74	26.0	PK
1037.400	-41.1	24.4	67.7	51.0	Horizontal	74	23.0	PK
1185.300	-41.0	24.4	67.7	51.1	Horizontal	74	22.9	PK
1334.900	-40.8	24.3	72.9	56.4	Horizontal	74	17.6	PK
2966.900	-39.2	29.4	60.4	50.6	Horizontal	74	23.4	PK
3560.200	-38.9	31.5	60.0	52.6	Horizontal	74	21.4	PK
3708.100	-39.0	32.0	57.3	50.3	Horizontal	74	23.7	PK
1025.500	-41.1	24.4	47.4	30.7	Vertical	54	23.3	AV
1282.200	-40.8	24.3	50.5	34.0	Vertical	54	20.0	AV
1482.800	-40.8	25.1	44.9	29.2	Vertical	54	24.8	AV
2224.000	-40.2	28.3	42.2	30.3	Vertical	54	23.7	AV
2564.000	-39.9	28.6	44.3	33.0	Vertical	54	21.0	AV
2966.900	-39.2	29.4	38.9	29.1	Vertical	54	24.9	AV


1037.400	-41.1	24.4	53.5	36.8	Horizontal	54	17.2	AV
1185.300	-41.0	24.4	52.9	36.3	Horizontal	54	17.7	AV
1334.900	-40.8	24.3	67.0	50.5	Horizontal	54	3.5	AV
2966.900	-39.2	29.4	40.4	30.6	Horizontal	54	23.4	AV
3560.200	-38.9	31.5	40.7	33.3	Horizontal	54	20.7	AV
3708.100	-39.0	32.0	41.5	34.5	Horizontal	54	19.5	AV
35063.050	-32.7	43.7	41.6	52.6	Vertical	74	21.4	PK
38596.000	-32.7	43.7	47.3	58.3	Vertical	74	15.7	PK
39554.500	-32.7	43.7	47.7	58.7	Vertical	74	15.3	PK
38151.850	-32.7	43.7	43.4	54.4	Horizontal	74	19.6	PK
38618.150	-32.7	43.7	46.2	57.2	Horizontal	74	16.8	PK
39761.150	-32.7	43.7	46.9	57.9	Horizontal	74	16.1	PK
35063.050	-32.7	43.7	33.3	44.3	Vertical	54	9.7	AV
38596.000	-32.7	43.7	35.8	46.8	Vertical	54	7.2	AV
39554.500	-32.7	43.7	36.1	47.1	Vertical	54	6.9	AV
38151.850	-32.7	43.7	34.2	45.2	Horizontal	54	8.8	AV
38618.150	-32.7	43.7	34.9	45.9	Horizontal	54	8.1	AV
39761.150	-32.7	43.7	34.6	45.6	Horizontal	54	8.4	AV

Emission level (dBuV)=Read Value(dBuV/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)




30MHz-1GHz

Horizontal




Vertical




1GHz-18GHz

Horizontal




Vertical




18GHz-26.5GHz

Horizontal




Vertical




26.5GHz-40GHz

Horizontal



Vertical



-----End of Report-----