



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20221001747E-03
Applicant: Acenew technology(Shenzhen) limited company
Address of Applicant: Room 706, 7th floor building G 2 , TCLInternational City E, No.1001, Zhongshanyuan Road, Xili Street, Nanshan District, Shenzhen
Equipment Under Test (EUT):
EUT Name: Neutron 1200 Portable Power Station
Model No.: AN12-10, AN12-20, AN12-30, AN12-40, AN12-50, AN12-60, AN12-70, AN12-80, AN12-90
Test Model No.: AN12-10
Brand Name: acenew
FCC ID: 2A84T-AN12-10
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2022-10-13
Date of Test: 2022-10-13 to 2022-11-21
Date of Issue: 2023-01-14
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20221001747E-03	Rev.01	Initial report	2023-01-14

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BLE	4
3.4 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	Acenew technology(Shenzhen) limited company
Address of Applicant:	Room 706, 7th floor building G 2 , TCLInternational City E, No.1001, Zhongshanyuan Road, Xili Street, Nanshan District, Shenzhen
Manufacturer:	Acenew technology(Shenzhen) limited company
Address of Manufacturer:	Room 706, 7th floor building G 2 , TCLInternational City E, No.1001, Zhongshanyuan Road, Xili Street, Nanshan District, Shenzhen
Factory:	Huizhou blueway electronics co., ltd
Address of Factory:	No.101, West Hechang 5th Road, Zhongkai High-Tech Development Zone, Huizhou, Guangdong, P.R.China

3.2 General Description of EUT

Product Name:	Neutron 1200 Portable Power Station
Model No.:	AN12-10, AN12-20, AN12-30, AN12-40, AN12-50, AN12-60, AN12-70, AN12-80, AN12-90
Test Model No.:	AN12-10
Trade Mark:	acenew
Software Version:	V1.0
Hardware Version:	V1.0
EUT Power Supply:	Power by AC 110V

3.3 General Description of BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Non Frequency Hopping Spread Spectrum(NFHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	Chip antenna
Antenna Gain:	1.8dBi

3.4 General Description of 2.4G WIFI Classic	
Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	Chip antenna
Antenna Gain:	1.8dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BLE Classic

Measurement Data

GFSK(1Mbps) mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	1.86	-0.29	-0.5±1	0.5	1.12
Middle(2440MHz)	1.9	-0.25	-0.5±1	0.5	1.12
Highest(2480MHz)	0.56	-1.59	-1.5±1	-0.5	0.89
GFSK(2Mbps) mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	1.93	-0.22	-0.5±1	0.5	1.12
Middle(2440MHz)	1.9	-0.25	-0.5±1	0.5	1.12
Highest(2480MHz)	0.57	-1.58	-1.5±1	-0.5	0.89

Note: 1) Refer to report No. CQASZ20221001747E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's Bluetooth module is more than 20cm away from the human body.

2) For 2.4G WIFI Classic

Measurement Data

11B mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	11.57	9.42	9.5±1	10.5	11.22
Middle(2437MHz)	11.36	9.21	9.5±1	10.5	11.22
Highest(2462MHz)	10.52	8.37	8.5±1	9.5	8.91
11G mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	8.68	6.53	6.5±1	7.5	5.62
Middle(2437MHz)	11.69	9.54	9.5±1	10.5	11.22
Highest(2462MHz)	11.48	9.33	9.5±1	10.5	11.22
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	11.38	9.23	9.5±1	10.5	11.22
Middle(2437MHz)	10.84	8.69	8.5±1	9.5	8.91
Highest(2462MHz)	11.21	9.06	9.0±1	10.0	10.00

Note: 1) Refer to report No. CQASZ20221001747E-02 for EUT test Max Conducted AV Output Power value.

2) EUT WIFI module is more than 20cm away from the human body.

*** END OF REPORT ***